

Lecture 12. Trigger

What is a Trigger?

- A trigger is a **database objects** that **automatically executes a function** when a specific event happens on a table
- Events: `INSERT` , `UPDATE` , `DELETE` , `TRUNCATE`
- The code that actually runs is a **trigger function** (usually written in PL/pgSQL).

Idea:

| "When something happens to this table, run this code."

Why Use Triggers?

- When DB is used by **many different applications**, you want some logic to live **inside the database**, not in every app.
 - Examples:
 - **Audit/history**: keep history of changes (e.g. old last names, changes log) on every `INSERT` / `UPDATE` .
 - **Automatic actions**: maintain summary tables, counters, etc.
 - Key point: triggers run **automatically** whenever the configured event occurs.
-

Trigger Types (Row vs Statement)

PostgreSQL supports **two main trigger types**:

1. Row-level trigger

- Defined with `FOR EACH ROW`.
- Fired **once per affected row**.
- Used when you need to inspect or modify individual rows.

2. Statement-level trigger

- Defined with `FOR EACH STATEMENT`.
- Fired **once per statement**, no matter how many rows are affected.
- Good for logging that “something happened” or doing bulk actions.

PostgreSQL-Specific Trigger Features vs SQL Standard

PostgreSQL has some specifics:

- Fires triggers also on `TRUNCATE` (not just INSERT/UPDATE/DELETE).
- Allows **statement-level triggers on views** (and `INSTEAD OF` triggers on views in general).
- Requires a **user-defined function** as the trigger action; SQL standard allows writing arbitrary SQL directly in the trigger body.

Trigger Function (Must Return `TRIGGER`)

Before you create a trigger, you must define a **trigger function**:

```
CREATE FUNCTION trigger_function()
RETURNS TRIGGER
LANGUAGE plpgsql
AS $$
BEGIN
    -- trigger logic
    RETURN NEW; -- or RETURN OLD, depending on BEFORE/AFTER and ev
```

```
ent  
END;  
$$;
```

Key points:

- Declared **with no arguments** and `RETURNS TRIGGER`.
- Written in `plpgsql` (most common), but can be other languages.
- When executed as a trigger, it has special variables: PostgreSQL
 - `NEW` – new row (for `INSERT` and `UPDATE` in row-level triggers).
 - `OLD` – old row (for `UPDATE` and `DELETE` in row-level triggers).
 - `TG_TABLE_NAME`, `TG_WHEN`, `TG_LEVEL`, etc. – meta info about trigger.

CREATE TRIGGER – Syntax & Meaning

Basic form:

```
CREATE TRIGGER trigger_name  
{ BEFORE | AFTER }  
{ event } -- INSERT | UPDATE | DELETE | TRUNCATE  
ON table_name  
[ FOR [EACH] { ROW | STATEMENT } ]  
EXECUTE PROCEDURE trigger_function();
```

Pieces:

- `trigger_name` – name of the trigger.
- `BEFORE` / `AFTER` – **when** it fires relative to the event:
 - `BEFORE` – before the row is changed (you can modify `NEW` or cancel).
 - `AFTER` – after the change is done (good for logging).
- `event` – `INSERT`, `UPDATE`, `DELETE`, `TRUNCATE` (or multiple with `OR` in full syntax).
- `FOR EACH ROW` – row-level; `FOR EACH STATEMENT` – statement-level.
- `EXECUTE PROCEDURE trigger_function()` – bind to the trigger function.

Example Idea from Slides (Employees Audit)

Slides show tables: `employees` and `employee_audits`

```
CREATE TABLE employees (  
  id      INT GENERATED ALWAYS AS IDENTITY,  
  first_name VARCHAR(40) NOT NULL,  
  last_name VARCHAR(40) NOT NULL,  
  PRIMARY KEY (id)  
);  
  
CREATE TABLE employee_audits (  
  id      INT GENERATED ALWAYS AS IDENTITY,  
  employee_id INT      NOT NULL,  
  last_name VARCHAR(40) NOT NULL,  
  changed_on TIMESTAMP(6) NOT NULL  
);
```

Typical trigger scenario (conceptually):

- Event: `UPDATE` of `employees.last_name`.
- Action: insert a row into `employee_audits` with:
 - `employee_id` = `OLD.id`
 - `last_name` = `OLD.last_name`
 - `changed_on` = `CURRENT_TIMESTAMP`

This is a **row-level AFTER UPDATE trigger** that logs each change.

When to Use Triggers

Use triggers when you need:

- **Cross-application logic** in one place (DB), not duplicated.

- **Automatic auditing:** history of data changes.
 - **Enforcing custom business rules** that are too complex for simple constraints.
 - Automatic side-effects when data changes.
-

DROP TRIGGER

```
DROP TRIGGER [IF EXISTS] trigger_name  
ON table_name  
[ CASCADE | RESTRICT ];
```

- **CASCADE** – also drop dependent objects.
 - **RESTRICT** – fail if dependencies exist (default).
-

ALTER TRIGGER

```
ALTER TRIGGER trigger_name  
ON table_name  
RENAME TO new_trigger_name;
```