

C Piscine

C 05

*Summary: this document is the subject for the C 05 module of the C Piscine @ 42.*

# Contents

I	Instructions	2
II	Foreword	4
III	Exercise 00 : ft_iterative_factorial	6
IV	Exercise 01 : ft_recursive_factorial	7
V	Exercise 02 : ft_iterative_power	8
VI	Exercise 03 : ft_recursive_power	9
VII	Exercise 04 : ft_fibonacci	10
VIII	Exercise 05 : ft_sqrt	11
IX	Exercise 06 : ft_is_prime	12
X	Exercise 07 : ft_find_next_prime	13
XI	Exercise 08 : The Ten Queens	14

8622(n5(doer)edures)]TJET126.03412511.797 497.179 cm[[]0 d 0 J 0.393-1168 m 114.395 0 l SQBT/

- Your reference guide is called `Google / man / the Internet / ....`
- Check out the "C Piscine" part of the forum on the intranet, or the slack Piscine.
- Examine the examples thoroughly. They could very well call for details that are not explicitly mentioned in the subject...
- By Odin, by Thor ! Use your brain !!!



Norminette must be launched with the `-R CheckForbiddenSourceHeader` flag. Moulinette will use it too.

# Chapter II

## Foreword

Here are some lyrics extract from the Harry Potter saga:

Oh you may not think me pretty,  
But don't judge on what you see,  
I'll eat myself if you can find  
A smarter hat than me.

You can keep your bowlers black,  
Your top hats sleek and tall,  
For I'm the Hogwarts Sorting Hat  
And I can cap them all.

The Sorting Hat, stored in the Headmaster's Office.  
There's nothing hidden in your head  
The Sorting Hat can't see,  
So try me on and I will tell you  
Where you ought to be.

You might belong in Gryffindor,  
Where dwell the brave at heart,  
Their daring, nerve, and chivalry  
Set Gryffindors apart;

You might belong in Hufflepuff,  
Where they are just and loyal,  
Those patient Hufflepuffs are true  
And unafraid of toil;

Or yet in wise old Ravenclaw,  
If you've a ready mind,  
Where those of wit and learning,  
Will always find their kind;

Or perhaps in Slytherin  
You'll make your real friends,  
Those cunning folks use any means


To achieve their ends.

So put me on! Don't be afraid!  
And don't get in a flap!  
You're in safe hands (though I have none)  
For I'm a Thinking Cap!

Unfortunately, this subject's got nothing to do with the Harry Potter saga, which is too bad, because your exercises won't be done by magic.

# Chapter III

## Exercise 00 : ft\_iterative\_factorial


	Exercise 00
ft_iterative_factorial	
Turn-in directory : <i>ex00/</i>	
Files to turn in : <b>ft_iterative_factorial.c</b>	
Allowed functions : <b>None</b>	

- Create an iterated function that returns a number. This number is the result of a factorial operation based on the number given as a parameter.
- If the argument is not valid the function should return 0.
- Overflows must not be handled, the function return will be undefined.
- Here's how it should be prototyped :

```
int ft_iterative_factorial (int nb);
```

# Chapter IV

## Exercise 01 : ft\_recursive\_factorial

	Exercise 01
ft_recursive_factorial	
Turn-in directory : <i>ex01/</i>	
Files to turn in : <b>ft_recursive_factorial.c</b>	
Allowed functions : <b>None</b>	


- Create a recursive function that returns the factorial of the number given as a parameter.
- If the argument is not valid the function should return 0.
- Overflows must not be handled, the function return will be undefined.
- Here's how it should be prototyped :

```
int ft_recursive_factorial(int nb);
```



# Chapter V

## Exercise 02 : ft\_iterative\_power


	Exercise 02
ft_iterative_power	
Turn-in directory : <i>ex02/</i>	
Files to turn in : <b>ft_iterative_power.c</b>	
Allowed functions : None	

- Create an iterated function that returns the value of a power applied to a number. An power lower than 0 returns 0. Overflows must not be handled.
- We've decided that 0 power 0 will returns 1
- Here's how it should be prototyped :

```
int ft_iterative_power(int nb, int power);
```

# Chapter VI

## Exercise 03 : ft\_recursive\_power


	Exercise 03
ft_recursive_power	
Turn-in directory : <i>ex03/</i>	
Files to turn in : <b>ft_recursive_power.c</b>	
Allowed functions : None	

- Create a recursive function that returns the value of a power applied to a number.
- Overflows must not be handled, the function return will be undefined.
- We've decided that 0 power 0 will returns 1
- Here's how it should be prototyped :

```
int ft_recursive_power(int nb, int power);
```

# Chapter VII

## Exercise 04 : ft\_fibonacci

	Exercise 04
	ft_fibonacci
Turn-in directory : <i>ex04/</i>	
Files to turn in : <b>ft_fibonacci.c</b>	
Allowed functions : <b>None</b>	


- Create a function `ft_fibonacci` that returns the `n`-th element of the Fibonacci sequence, the first element being at the 0 index. We'll consider that the Fibonacci sequence starts like this: 0, 1, 1, 2.
- Overflows must not be handled, the function return will be undefined.
- Here's how it should be prototyped :

```
int ft_fibonacci(int index);
```

- Obviously, `ft_fibonacci` has to be recursive.
- If the `index` is less than 0, the function should return -1.

# Chapter VIII

## Exercise 05 : ft\_sqrt


	Exercise 05
ft_sqrt	
Turn-in directory : <i>ex05/</i>	
Files to turn in : <b>ft_sqrt.c</b>	
Allowed functions : None	

- Create a function that returns the square root of a number (if it exists), or 0 if the square root is an irrational number.
- Here's how it should be prototyped :

```
int ft_sqrt(int nb);
```

# Chapter IX

## Exercise 06 : ft\_is\_prime

	Exercise 06
	ft_is_prime
Turn-in directory : <i>ex06/</i>	
Files to turn in : <b>ft_is_prime.c</b>	
Allowed functions : None	

- Create a function that returns 1 if the number given as a parameter is a prime number, and 0 if it isn't.
- Here's how it should be prototyped :


```
int ft_is_prime(int nb);
```



0 and 1 are not prime numbers.

# Chapter X

## Exercise 07 : ft\_find\_next\_prime


	Exercise 07
ft_find_next_prime	
Turn-in directory : <i>ex07/</i>	
Files to turn in : <code>ft_find_next_prime.c</code>	
Allowed functions : None	

- Create a function that returns the next prime number greater or equal to the number given as argument.
- Here's how it should be prototyped :

```
int ft_find_next_prime(int nb);
```

# Chapter XI

## Exercise 08 : The Ten Queens

	Exercise 08
The Ten Queens	
Turn-in directory : <i>ex08/</i>	
Files to turn in : <b>ft_ten_queens_puzzle.c</b>	
Allowed functions : <b>write</b>	

- Create a function that displays all possible placements of the ten queens on a chessboard which would contain ten columns and ten lines, without them being able to reach each other in a single move, and returns the number of possibilities.
- Recursivity is required to solve this problem.
- Here's how it should be prototyped :

```
int ft_ten_queens_puzzle(void);
```

- Here's how it'll be displayed :

```
$> ./a.out | cat -e
0257948136$
0258693147$
...
4605713829$
4609582731$
...
9742051863$
$>
```

- The sequence goes from left to right. The first digit represents the first Queen's position in the first column (the index starting from 0). The Nth digit represents the Nth Queen's position in the Nth column.
- The return value must be the total number of displayed solutions.