



AbstractResponse Class

Contains the normalized response fields from payment gateways that are common to all the other gateway responses.

Namespace

[CommercePayments](#)

Usage

You must specify the `CommercePayments` namespace when creating an instance of this class. The constructor of this class takes no arguments. For example:

```
CommercePayments.AbstractResponse abr = new CommercePayments.AbstractResponse();
```

This class can't be instantiated on its own. This class implements the `GatewayResponse` class. Other `GatewayResponse` classes extend this class to inherit common properties.

- [AbstractResponse Methods](#)

AbstractResponse Methods

The following are methods for `AbstractResponse`.

- [setGatewayAvsCode\(gatewayAvsCode\)](#)
Sets the AVS (address verification system) result code information that the gateway returned. Maximum length of 64 characters.
- [setGatewayDate\(gatewayDate\)](#)
Sets the date that the transaction occurred. Some gateways don't send this value.
- [setGatewayMessage\(gatewayMessage\)](#)
Sets error messages that the gateway returned for the payment request. Maximum length of 255 characters.
- [setGatewayResultCode\(gatewayResultCode\)](#)
Sets a gateway-specific result code. The code may be mapped to a Salesforce-specific result code. Maximum length of 64 characters.
- [setGatewayResultCodeDescription\(gatewayResultCodeDescription\)](#)
Sets a description of the gateway-specific result code that a payment gateway returned. Maximum length of 1000 characters.
- [setSalesforceResultCodeInfo\(salesforceResultCodeInfo\)](#)
Sets the Salesforce-specific result code information. Payment gateways have many response codes for payment calls. Salesforce uses the result code information to map payment gateway codes to a predefined set of standard Salesforce result codes.

setGatewayAvsCode(gatewayAvsCode)

Sets the AVS (address verification system) result code information that the gateway returned. Maximum length of 64 characters.

Signature

```
global void setGatewayAvsCode(String gatewayAvsCode)
```



Code sent by gateways that use an address verification system.

Return Value

Type: void

setGatewayDate(gatewayDate)

Sets the date that the transaction occurred. Some gateways don't send this value.

Signature

```
global void setGatewayDate(Datetime gatewayDate)
```

Parameters

gatewayDate

Type: [Datetime](#)

Date and time of the gateway communication.

Return Value

Type: void

setGatewayMessage(gatewayMessage)

Sets error messages that the gateway returned for the payment request. Maximum length of 255 characters.

Signature

```
global void setGatewayMessage(String gatewayMessage)
```

Parameters

gatewayMessage

Type: [String](#)

Information on error messages sent from the gateway.

Return Value

Type: void

setGatewayResultCode(gatewayResultCode)

Sets a gateway-specific result code. The code may be mapped to a Salesforce-specific result code. Maximum length of 64 characters.

Signature

```
global void setGatewayResultCode(String gatewayResultCode)
```

Parameters

gatewayResultCode

Type: [String](#)

Gateway-specific result code. Must be used to map a Salesforce-specific result code.

Return Value



Sets a description of the gateway-specific result code that a payment gateway returned. Maximum length of 1000 characters.

Signature

```
global void setGatewayResultCodeDescription(String gatewayResultCodeDescription)
```

Parameters

gatewayResultCodeDescription

Type: [String](#)

Description of the gateway's result code. Use this field to learn more about why the gateway returned a certain result code.

Return Value

Type: void

setSalesforceResultCodeInfo(salesforceResultCodeInfo)

Sets the Salesforce-specific result code information. Payment gateways have many response codes for payment calls. Salesforce uses the result code information to map payment gateway codes to a predefined set of standard Salesforce result codes.

Signature

```
global void setSalesforceResultCodeInfo(commercepayments.SalesforceResultCodeInfo  
salesforceResultCodeInfo)
```

Parameters

salesforceResultCodeInfo

Type: [commercepayments.SalesforceResultCodeInfo](#)

Description of the Salesforce result code value.

Return Value

Type: void

DID THIS ARTICLE SOLVE YOUR ISSUE?

Let us know so we can improve!

[Share your feedback](#)

DEVELOPER CENTERS

[Heroku](#)[MuleSoft](#)[Tableau](#)[Commerce Cloud](#)

POPULAR RESOURCES

[Documentation](#)[Component Library](#)[APIs](#)[Trailhead](#)

COMMUNITY

[Trailblazer Community](#)[Events and Calendar](#)[Partner Community](#)[Blog](#)



© Copyright 2025 Salesforce, Inc. [All rights reserved.](#) Various trademarks held by their respective owners. Salesforce, Inc. Salesforce Tower, 415 Mission Street, 3rd Floor, San Francisco, CA 94105, United States

[Privacy Information](#) [Terms of Service](#) [Legal](#) [Use of Cookies](#) [Trust](#) [Cookie Preferences](#)

 [Your Privacy Choices](#) [Responsible Disclosure](#) [Contact](#)