



StaticResourceCalloutMock Class

Utility class used to specify a fake response for testing HTTP callouts.

Namespace

System

Usage

Use the methods in this class to set the response properties for testing HTTP callouts.

- [StaticResourceCalloutMock Constructors](#)
- [StaticResourceCalloutMock Methods](#)

StaticResourceCalloutMock Constructors

The following are constructors for `StaticResourceCalloutMock`.

- [StaticResourceCalloutMock\(\)](#)
Creates a new instance of the `StaticResourceCalloutMock` class.

StaticResourceCalloutMock()

Creates a new instance of the `StaticResourceCalloutMock` class.

Signature

```
public StaticResourceCalloutMock()
```

StaticResourceCalloutMock Methods

The following are methods for `StaticResourceCalloutMock`. All are instance methods.

- [setHeader\(headerName, headerValue\)](#)
Sets the specified header name and value for the fake response.
- [setStaticResource\(resourceName\)](#)
Sets the specified static resource, which contains the response body.
- [setStatus\(httpStatus\)](#)
Sets the specified HTTP status for the response.
- [setStatusCode\(httpStatusCode\)](#)
Sets the specified HTTP status for the response.

setHeader(headerName, headerValue)

Sets the specified header name and value for the fake response.

Signature

```
public Void setHeader(String headerName, String headerValue)
```

***headerValue***Type: [String](#)**Return Value**

Type: Void

setStaticResource(resourceName)

Sets the specified static resource, which contains the response body.

Signature

```
public Void setStaticResource(String resourceName)
```

Parameters***resourceName***Type: [String](#)**Return Value**

Type: Void

setStatus(httpStatus)

Sets the specified HTTP status for the response.

Signature

```
public Void setStatus(String httpStatus)
```

Parameters***httpStatus***Type: [String](#)**Return Value**

Type: Void

setStatusCode(httpStatusCode)

Sets the specified HTTP status for the response.

Signature

```
public Void setStatusCode(Integer httpStatusCode)
```

Parameters***httpStatusCode***Type: [Integer](#)**Return Value**

Type: Void

DID THIS ARTICLE SOLVE YOUR ISSUE?

Let us know so we can improve!

[Share your feedback](#)



DEVELOPER CENTERS

- Heroku
- MuleSoft
- Tableau
- Commerce Cloud
- Lightning Design System
- Einstein
- Quip

POPULAR RESOURCES

- Documentation
- Component Library
- APIs
- Trailhead
- Sample Apps
- Podcasts
- AppExchange

COMMUNITY

- Trailblazer Communi
- Events and Calendar
- Partner Community
- Blog
- Salesforce Admins
- Salesforce Architects

© Copyright 2025 Salesforce, Inc. [All rights reserved](#). Various trademarks held by their respective owners. Salesforce, Inc. Salesforce Tower, 415 Mission Street, 3rd Floor, San Francisco, CA 94105, United States

[Privacy Information](#) [Terms of Service](#) [Legal](#) [Use of Cookies](#) [Trust](#) [Cookie Preferences](#)

[Your Privacy Choices](#) [Responsible Disclosure](#) [Contact](#)