



# Topics Class

Access information about topics, such as their descriptions, the number of people talking about them, related topics, and information about groups contributing to the topic. Update a topic's name or description, merge topics, and add and remove topics from records and feed items.

## Namespace

[ConnectApi](#)

## Topics Methods

These methods are for `Topics`. All methods are static.

These methods in this class require Chatter and are subject to the per user, per namespace, per hour rate limit.

- [getGroupsRecentlyTalkingAboutTopic\(\*communityId\*, \*topicId\*\)](#)
- [getRecentlyTalkingAboutTopicsForGroup\(\*communityId\*, \*groupId\*\)](#)
- [getRecentlyTalkingAboutTopicsForUser\(\*communityId\*, \*userId\*\)](#)

All other methods in this class count toward the [Salesforce Platform total API request allocations](#), which are per org and span a 24-hour period.

- [assignTopic\(\*communityId\*, \*recordId\*, \*topicId\*\)](#)  
Assign a topic to a record or feed item.
- [assignTopicByName\(\*communityId\*, \*recordId\*, \*topicName\*\)](#)  
Assign a topic to a record or feed item.
- [createTopic\(\*communityId\*, \*name\*, \*description\*\)](#)  
Create a topic.
- [createTopicDataCategoryRules\(\*communityId\*, \*dataCategoryGroup\*, \*dataCategory\*, \*topicNames\*\)](#)  
Create topic and article assignment rules by data category.
- [deleteTopic\(\*communityId\*, \*topicId\*\)](#)  
Delete a topic.
- [getGroupsRecentlyTalkingAboutTopic\(\*communityId\*, \*topicId\*\)](#)  
Get information about the five groups that most recently contributed to a topic.
- [getRecentlyTalkingAboutTopicsForGroup\(\*communityId\*, \*groupId\*\)](#)  
Get up to five topics most recently used in a group.
- [getRecentlyTalkingAboutTopicsForUser\(\*communityId\*, \*userId\*\)](#)  
Get up to five topics most recently used by a user.
- [getRelatedTopics\(\*communityId\*, \*topicId\*\)](#)  
Get up to five topics most closely related to a topic.
- [getTopic\(\*communityId\*, \*topicId\*\)](#)  
Get a topic.
- [getTopicDataCategoryRules\(\*communityId\*, \*dataCategoryGroup\*, \*dataCategory\*\)](#)  
Get topic and article assignment rules by data category.
- [getTopics\(\*communityId\*, \*recordId\*\)](#)  
Get the first page of topics assigned to a record or feed item.



- [`getTopics\(communityId, pageParam, pageSize\)`](#)  
Get a page of topics.
- [`getTopics\(communityId, pageParam, pageSize, sortParam\)`](#)  
Get a page of sorted topics.
- [`getTopics\(communityId, q, sortParam\)`](#)  
Get the sorted topics that match the search criteria.
- [`getTopics\(communityId, q, pageParam, pageSize\)`](#)  
Get a page of topics that match the search criteria.
- [`getTopics\(communityId, q, pageParam, pageSize, sortParam\)`](#)  
Get a page of sorted topics that match the search criteria.
- [`getTopics\(communityId, q, exactMatch\)`](#)  
Get the topic that matches the exact, case-insensitive name.
- [`getTopicsOrFallbackToRenamedTopics\(communityId, q, exactMatch, fallbackToRenamedTopics\)`](#)  
Get the most recent renamed topic match, if there isn't an exact match.
- [`getTopicSuggestions\(communityId, recordId, maxResults\)`](#)  
Get up to a specified number of suggested topics for a record or feed item.
- [`getTopicSuggestions\(communityId, recordId\)`](#)  
Get suggested topics for a record or feed item.
- [`getTopicSuggestionsForText\(communityId, text, maxResults\)`](#)  
Get up to a specified number of suggested topics for a string of text.
- [`getTopicSuggestionsForText\(communityId, text\)`](#)  
Get suggested topics for a string of text.
- [`getTrendingTopics\(communityId\)`](#)  
Get trending topics for the org or Experience Cloud site.
- [`getTrendingTopics\(communityId, maxResults\)`](#)  
Get up to a specified number of trending topics for the org or Experience Cloud site.
- [`mergeTopics\(communityId, topicId, idsToMerge\)`](#)  
Merge up to five secondary topics with a primary topic.
- [`reassignTopicDataCategoryRules\(communityId, dataCategoryGroup, dataCategory, topicNames\)`](#)  
Reassign topic and article assignment rules by data category by deleting the existing rules and creating new rules.
- [`reassignTopicsByName\(communityId, recordId, topicNames\)`](#)  
Reassign all the topics on a record or feed item, that is, remove all the assigned topics on a record or feed item and add topics. Optionally, provide a list of suggested topics to assign to a record or feed item to improve future topic suggestions.
- [`unassignTopic\(communityId, recordId, topicId\)`](#)  
Remove a topic from a record or feed item.
- [`updateTopic\(communityId, topicId, topic\)`](#)  
Update the description or name of a topic or merge up to five secondary topics with a primary topic.
- [`updateTopicsForArticlesInDataCategory\(communityId, dataCategoryGroup, dataCategory, articleTopicAssignmentJob\)`](#)  
Assign topics to articles and unassign topics from articles in a data category.

## **`assignTopic(communityId, recordId, topicId)`**

Assign a topic to a record or feed item.

### **API Version**

29.0



```
public static ConnectApi.Topic assignTopic(String communityId, String recordId, String topicId)
```

#### Parameters

##### *communityId*

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

##### *recordId*

Type: [String](#)

ID for a record or feed item.

##### *topicId*

Type: [String](#)

ID for a topic.

#### Return Value

Type: [ConnectApi.Topic](#)

#### Usage

Only users with the Assign Topics permission can add existing topics to records or feed items. Administrators must enable topics for objects before users can add topics to records of that object type.

## assignTopicByName(communityId, recordId, topicName)

Assign a topic to a record or feed item.

#### API Version

29.0

#### Requires Chatter

No

#### Signature

```
public static ConnectApi.Topic assignTopicByName(String communityId, String recordId, String topicName)
```

#### Parameters

##### *communityId*

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

##### *recordId*

Type: [String](#)

The ID of the record or feed item to which to assign the topic.

##### *topicName*

Type: [String](#)

The name of a new or existing topic.



Only users with the Assign Topics permission can add existing topics to records or feed items. Only users with the Create Topics permission can add new topics to records or feed items. Administrators must enable topics for objects before users can add topics to records of that object type.

## **createTopic(*communityId*, *name*, *description*)**

Create a topic.

### **API Version**

36.0

### **Requires Chatter**

No

### **Signature**

```
public static ConnectApi.Topic createTopic(String communityId, String name, String description)
```

### **Parameters**

#### ***communityId***

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

#### ***name***

Type: [String](#)

The name of the topic.

#### ***description***

Type: [String](#)

The description of the topic.

### **Return Value**

Type: [ConnectApi.Topic](#)

### **Usage**

Only users with the Create Topics permission can create a topic.

## **createTopicDataCategoryRules(*communityId*, *dataCategoryGroup*, *dataCategory*, *topicNames*)**

Create topic and article assignment rules by data category.

### **API Version**

40.0

### **Requires Chatter**

No

### **Signature**

***communityId***Type: [String](#)

ID for an Experience Cloud site, internal, or null.

***dataCategoryGroup***Type: [String](#)

The data category group used by articles.

***dataCategory***Type: [String](#)

The data category used by articles.

***topicNames***Type: [ConnectApi.TopicNamesInput](#)A [ConnectApi.TopicNamesInput](#) object with the names of topics to assign to articles in a data category.**Return Value**Type: [ConnectApi.TopicPage](#)**deleteTopic(*communityId*, *topicId*)**

Delete a topic.

**API Version**

29.0

**Requires Chatter**

No

**Signature**

```
public static Void deleteTopic(String communityId, String topicId)
```

**Parameters*****communityId***Type: [String](#),

ID for an Experience Cloud site, internal, or null.

***topicId***Type: [String](#)

ID for a topic.

**Return Value**

Type: Void

**Usage**

Only users with the Delete Topics or Modify All Data permission can delete topics.

Topic deletion is asynchronous. If a topic is requested before the deletion completes, the response is successful and the `isBeingDeleted` property of `ConnectApi.Topic` is `true` in version 33.0 and later. If a topic is requested after the deletion completes, the response is `ConnectApi.NotFoundException`.



29.0

**Available to Guest Users**

32.0

**Requires Chatter**

Yes

**Signature**

```
public static ConnectApi.ChatterGroupSummaryPage getGroupsRecentlyTalkingAboutTopic(String communityId, String topicId)
```

**Parameters*****communityId***Type: [String](#)

ID for an Experience Cloud site, internal, or null.

***topicId***Type: [String](#)

ID for a topic.

**Return Value**Type: [ConnectApi.ChatterGroupSummaryPage](#)**Usage**

To test code that uses this method, use the matching set test method (prefix the method name with `setTest`). Use the set test method with the same parameters or the code throws an exception.

**See Also**

- [setTestGetGroupsRecentlyTalkingAboutTopic\(communityId, topicId, result\)](#)
- [Apex Developer Guide: Testing ConnectApi Code](#)

**getRecentlyTalkingAboutTopicsForGroup(communityId, groupId)**

Get up to five topics most recently used in a group.

**API Version**

29.0

**Available to Guest Users**

32.0

**Requires Chatter**

Yes

**Signature**

```
public static ConnectApi.TopicPage getRecentlyTalkingAboutTopicsForGroup(String communityId, String groupId)
```



ID for an Experience Cloud site, `internal`, or `null`.

#### *groupId*

Type: [String](#)

ID for a group.

#### Return Value

Type: [ConnectApi.TopicPage](#)

#### Usage

To test code that uses this method, use the matching set test method (prefix the method name with `setTest`). Use the set test method with the same parameters or the code throws an exception.

#### See Also

- [setTestGetRecentlyTalkingAboutTopicsForGroup\(communityId, groupId, result\)](#)
- [Apex Developer Guide: Testing ConnectApi Code](#)

## getRecentlyTalkingAboutTopicsForUser(communityId, userId)

Get up to five topics most recently used by a user.

#### API Version

29.0

#### Available to Guest Users

32.0

#### Requires Chatter

Yes

#### Signature

```
public static ConnectApi.TopicPage getRecentlyTalkingAboutTopicsForUser(String communityId,  
String userId)
```

#### Parameters

##### *communityId*

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

##### *userId*

Type: [String](#)

ID for a user.

#### Return Value

Type: [ConnectApi.TopicPage](#)

#### Usage

To test code that uses this method, use the matching set test method (prefix the method name with `setTest`). Use the set test method with the same parameters or the code throws an exception.



## getRelatedTopics(*communityId*, *topicId*)

Get up to five topics most closely related to a topic.

Two topics that are assigned to the same feed item at least three times are related.

### API Version

29.0

### Available to Guest Users

32.0

### Requires Chatter

No

### Signature

```
public static ConnectApi.TopicPage getRelatedTopics(String communityId, String topicId)
```

### Parameters

#### *communityId*

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

#### *topicId*

Type: [String](#)

ID for a topic.

### Return Value

Type: [ConnectApi.TopicPage](#)

### Usage

To test code that uses this method, use the matching set test method (prefix the method name with `setTest`). Use the set test method with the same parameters or the code throws an exception.

### See Also

- [setTestGetRelatedTopics\(\*communityId\*, \*topicId\*, \*result\*\)](#)
- [Apex Developer Guide: Testing ConnectApi Code](#)

## getTopic(*communityId*, *topicId*)

Get a topic.

### API Version

29.0

### Available to Guest Users

32.0





```
public static ConnectApi.Topic getTopic(String communityId, String topicId)
```

#### Parameters

##### *communityId*

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

##### *topicId*

Type: [String](#)

ID for a topic.

#### Return Value

Type: [ConnectApi.Topic](#)

### **getTopicDataCategoryRules(communityId, dataCategoryGroup, dataCategory)**

Get topic and article assignment rules by data category.

#### API Version

40.0

#### Requires Chatter

No

#### Signature

```
public static ConnectApi.TopicPage getTopicDataCategoryRules(String communityId, String dataCategoryGroup, String dataCategory)
```

#### Parameters

##### *communityId*

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

##### *dataCategoryGroup*

Type: [String](#)

The data category group used by articles.

##### *dataCategory*

Type: [String](#)

The data category used by articles.

#### Return Value

Type: [ConnectApi.TopicPage](#)

### **getTopics(communityId, recordId)**

Get the first page of topics assigned to a record or feed item.

#### API Version



#### Requires Chatter

No

#### Signature

```
public static ConnectApi.TopicPage getTopics(String communityId, String recordId)
```

#### Parameters

##### *communityId*

Type: [String](#)

ID for an Experience Cloud site, internal, or null.

##### *recordId*

Type: [String](#)

ID for a record or feed item.

#### Return Value

Type: [ConnectApi.TopicPage](#)

#### Usage

Administrators must enable topics for objects before users can add topics to records of that object type.

## getTopics(communityId)

Get the first page of topics for the org or Experience Cloud site.

#### API Version

29.0

#### Available to Guest Users

32.0

#### Requires Chatter

No

#### Signature

```
public static ConnectApi.TopicPage getTopics(String communityId)
```

#### Parameters

##### *communityId*

Type: [String](#)

ID for an Experience Cloud site, internal, or null.

#### Return Value

Type: [ConnectApi.TopicPage](#)

## getTopics(communityId, sortParam)

Get the first page of sorted topics for the org or community.



32.0

**Requires Chatter**

No

**Signature**

```
public static ConnectApi.TopicPage getTopics(String communityId, ConnectApi.TopicSort
sortParam)
```

**Parameters*****communityId***Type: [String](#)ID for an Experience Cloud site, `internal`, or `null`.***sortParam***Type: `ConnectApi.TopicSort`

Values are:

- `popularDesc` –Sorts topics by popularity with the most popular first. This value is the default.
- `alphaAsc` –Sorts topics alphabetically.

**Return Value**Type: [ConnectApi.TopicPage](#)**getTopics(*communityId*, *pageParam*, *pageSize*)**

Get a page of topics.

**API Version**

29.0

**Available to Guest Users**

32.0

**Requires Chatter**

No

**Signature**

```
public static ConnectApi.TopicPage getTopics(String communityId, Integer pageParam, Integer
pageSize)
```

**Parameters*****communityId***Type: [String](#)ID for an Experience Cloud site, `internal`, or `null`.***pageParam***Type: [Integer](#)Number of the page you want returned. Starts at 0. If you pass in `null` or 0, the first page is returned.



the default size is 25.

#### Return Value

Type: [ConnectApi.TopicPage](#)

### getTopics(*communityId*, *pageParam*, *pageSize*, *sortParam*)

Get a page of sorted topics.

#### API Version

29.0

#### Available to Guest Users

32.0

#### Requires Chatter

No

#### Signature

```
public static ConnectApi.TopicPage getTopics(String communityId, Integer pageParam, Integer
pageSize, ConnectApi.TopicSort sortParam)
```

#### Parameters

##### *communityId*

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

##### *pageParam*

Type: [Integer](#)

Number of the page you want returned. Starts at 0. If you pass in `null` or 0, the first page is returned.

##### *pageSize*

Type: [Integer](#)

Specifies the number of items per page. Valid values are from 1 through 100. If you pass in `null`, the default size is 25.

##### *sortParam*

Type: [ConnectApi.TopicSort](#)

Values are:

- `popularDesc` –Sorts topics by popularity with the most popular first. This value is the default.
- `alphaAsc` –Sorts topics alphabetically.

#### Return Value

Type: [ConnectApi.TopicPage](#)

### getTopics(*communityId*, *q*, *sortParam*)

Get the sorted topics that match the search criteria.

#### API Version



#### Requires Chatter

No

#### Signature

```
public static ConnectApi.TopicPage getTopics(String communityId, String q, ConnectApi.TopicSort sortParam)
```

#### Parameters

##### *communityId*

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

##### *q*

Type: [String](#)

Specifies the string to search. The string must contain at least two characters, not including wildcards.

##### *sortParam*

Type: `ConnectApi.TopicSort`

Values are:

- `popularDesc` –Sorts topics by popularity with the most popular first. This value is the default.
- `alphaAsc` –Sorts topics alphabetically.

#### Return Value

Type: [ConnectApi.TopicPage](#)

### getTopics(*communityId*, *q*, *pageParam*, *pageSize*)

Get a page of topics that match the search criteria.

#### API Version

29.0

#### Available to Guest Users

32.0

#### Requires Chatter

No

#### Signature

```
public static ConnectApi.TopicPage getTopics(String communityId, String q, Integer pageParam, Integer pageSize)
```

#### Parameters

##### *communityId*

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

##### *q*

***pageParam***Type: [Integer](#)

Number of the page you want returned. Starts at 0. If you pass in `null` or 0, the first page is returned.

***pageSize***Type: [Integer](#)

Specifies the number of items per page. Valid values are from 1 through 100. If you pass in `null`, the default size is 25.

**Return Value**Type: [ConnectApi.TopicPage](#)**getTopics(*communityId*, *q*, *pageParam*, *pageSize*, *sortParam*)**

Get a page of sorted topics that match the search criteria.

**API Version**

29.0

**Available to Guest Users**

32.0

**Requires Chatter**

No

**Signature**

```
public static ConnectApi.TopicPage getTopics(String communityId, String q, Integer pageParam, Integer pageSize, ConnectApi.TopicSort sortParam)
```

**Parameters*****communityId***Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

***q***Type: [String](#)

Specifies the string to search. The string must contain at least two characters, not including wildcards.

***pageParam***Type: [Integer](#)

Number of the page you want returned. Starts at 0. If you pass in `null` or 0, the first page is returned.

***pageSize***Type: [Integer](#)

Specifies the number of items per page. Valid values are from 1 through 100. If you pass in `null`, the default size is 25.

***sortParam***



- `alphaAsc`—Sorts topics alphabetically.

### Return Value

Type: [ConnectApi.TopicPage](#)

## **getTopics(*communityId*, *q*, *exactMatch*)**

Get the topic that matches the exact, case-insensitive name.

### API Version

33.0

### Available to Guest Users

33.0

### Requires Chatter

No

### Signature

```
public static ConnectApi.TopicPage getTopics(String communityId, String q, Boolean exactMatch)
```

### Parameters

#### ***communityId***

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

#### ***q***

Type: [String](#)

Specifies the string to search. The string must contain at least two characters, not including wildcards.

#### ***exactMatch***

Type: [Boolean](#)

Specify `true` to find a topic by its exact, case-insensitive name.

### Return Value

Type: [ConnectApi.TopicPage](#)

## **getTopicsOrFallbackToRenamedTopics(*communityId*, *q*, *exactMatch*, *fallbackToRenamedTopics*)**

Get the most recent renamed topic match, if there isn't an exact match.

### API Version

35.0

### Available to Guest Users

35.0

### Requires Chatter



String q, Boolean exactMatch, Boolean fallBackToRenamedTopics)

#### Parameters

##### *communityId*

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

##### *q*

Type: [String](#)

Specifies the string to search. The string must contain at least two characters, not including wildcards.

##### *exactMatch*

Type: [Boolean](#)

Specify `true` to find a topic by its exact, case-insensitive name or to find the most recent renamed topic match if there isn't an exact match.

##### *fallBackToRenamedTopics*

Type: [Boolean](#)

Specify `true` and if there isn't an exact match, the most recent renamed topic match is returned. If there are multiple renamed topic matches, only the most recent is returned. If there are no renamed topic matches, an empty collection is returned.

#### Return Value

Type: [ConnectApi.TopicPage](#)

## getTopicSuggestions(*communityId*, *recordId*, *maxResults*)

Get up to a specified number of suggested topics for a record or feed item.

#### API Version

29.0

#### Requires Chatter

No

#### Signature

```
public static ConnectApi.TopicSuggestionPage getTopicSuggestions(String communityId, String recordId, Integer maxResults)
```

#### Parameters

##### *communityId*

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

##### *recordId*

Type: [String](#)

ID for a record or feed item.

##### *maxResults*

Type: [Integer](#)





Type: [ConnectApi.TopicSuggestionPage](#)

### Usage

Administrators must enable topics for objects before users can see suggested topics for records of that object type.

To test code that uses this method, use the matching set test method (prefix the method name with `setTest`). Use the set test method with the same parameters or the code throws an exception.

### See Also

- [setTestGetTopicSuggestions\(communityId, recordId, maxResults, result\)](#)
- [Apex Developer Guide: Testing ConnectApi Code](#)

## getTopicSuggestions(communityId, recordId)

Get suggested topics for a record or feed item.

### API Version

29.0

### Requires Chatter

No

### Signature

```
public static ConnectApi.TopicSuggestionPage getTopicSuggestions(String communityId, String recordId)
```

### Parameters

#### *communityId*

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

#### *recordId*

Type: [String](#)

ID for a record or feed item.

### Return Value

Type: [ConnectApi.TopicSuggestionPage](#)

### Usage

Administrators must enable topics for objects before users can see suggested topics for records of that object type.

To test code that uses this method, use the matching set test method (prefix the method name with `setTest`). Use the set test method with the same parameters or the code throws an exception.

### See Also

- [setTestGetTopicSuggestions\(communityId, recordId, result\)](#)
- [Apex Developer Guide: Testing ConnectApi Code](#)



29.0

**Requires Chatter**

No

**Signature**

```
public static ConnectApi.TopicSuggestionPage getTopicSuggestionsForText(String communityId,  
String text, Integer maxResults)
```

**Parameters*****communityId***Type: [String](#)

ID for an Experience Cloud site, internal, or null.

***text***Type: [String](#)

String of text.

***maxResults***Type: [Integer](#)

Maximum number of topic suggestions that get returned. The default is 5. Value must be greater than 0 and less than or equal to 25.

**Return Value**Type: [ConnectApi.TopicSuggestionPage](#)**Usage**

To test code that uses this method, use the matching set test method (prefix the method name with `setTest`). Use the set test method with the same parameters or the code throws an exception.

**See Also**

- [setTestGetTopicSuggestionsForText\(communityId, text, maxResults, result\)](#)
- [Apex Developer Guide: Testing ConnectApi Code](#)

**getTopicSuggestionsForText(communityId, text)**

Get suggested topics for a string of text.

**API Version**

29.0

**Requires Chatter**

No

**Signature**

```
public static ConnectApi.TopicSuggestionPage getTopicSuggestionsForText(String communityId,  
String text)
```



ID for an Experience Cloud site, `internal`, or `null`.

### *text*

Type: [String](#)

String of text.

### Return Value

Type: [ConnectApi.TopicSuggestionPage](#)

### Usage

To test code that uses this method, use the matching set test method (prefix the method name with `setTest`). Use the set test method with the same parameters or the code throws an exception.

### See Also

- [setTestGetTopicSuggestionsForText\(communityId, text, result\)](#)
- [Apex Developer Guide: Testing ConnectApi Code](#)

## getTrendingTopics(communityId)

Get trending topics for the org or Experience Cloud site.

### API Version

29.0

### Available to Guest Users

32.0

### Requires Chatter

No

### Signature

```
public static ConnectApi.TopicPage getTrendingTopics(String communityId)
```

### Parameters

#### *communityId*

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

### Return Value

Type: [ConnectApi.TopicPage](#)

### Usage

The more frequently people add a specific topic to their posts and comments and comment on or like posts with the same topic over a short period, the more likely it is to become a trending topic. For example, if your coworkers are attending the upcoming Dreamforce conference and have started discussing it in Chatter, you might see a trending topic for Dreamforce. A trending topic is not solely based on popularity and usually relates to a one-time or infrequent event that has a spike in activity, such as a conference or a project deadline.

To test code that uses this method, use the matching set test method (prefix the method name with `setTest`). Use the set test method with the same parameters or the code throws an exception.



## getTrendingTopics(*communityId*, *maxResults*)

Get up to a specified number of trending topics for the org or Experience Cloud site.

### API Version

29.0

### Available to Guest Users

32.0

### Requires Chatter

No

### Signature

```
public static ConnectApi.TopicPage getTrendingTopics(String communityId, Integer maxResults)
```

### Parameters

#### *communityId*

Type: [String](#)

ID for an Experience Cloud site, internal, or null.

#### *maxResults*

Type: [Integer](#)

Maximum number of topic suggestions that get returned. The default is 5. Value must be greater than 0 and less than or equal to 25.

### Return Value

Type: [ConnectApi.TopicPage](#)

### Usage

The more frequently people add a specific topic to their posts and comments and comment on or like posts with the same topic over a short period, the more likely it is to become a trending topic. For example, if your coworkers are attending the upcoming Dreamforce conference and have started discussing it in Chatter, you might see a trending topic for Dreamforce. A trending topic is not solely based on popularity and usually relates to a one-time or infrequent event that has a spike in activity, such as a conference or a project deadline.

To test code that uses this method, use the matching set test method (prefix the method name with `setTest`). Use the set test method with the same parameters or the code throws an exception.

### See Also

- [setTestGetTrendingTopics\(\*communityId\*, \*maxResults\*, \*result\*\)](#)
- [Apex Developer Guide: Testing ConnectApi Code](#)

## mergeTopics(*communityId*, *topicId*, *idsToMerge*)

Merge up to five secondary topics with a primary topic.

### API Version



### Signature

```
public static ConnectApi.Topic mergeTopics(String communityId, String topicId, List<String>
idsToMerge)
```

### Parameters

#### *communityId*

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

#### *topicId*

Type: [String](#)

The ID for the primary topic for the merge. If this topic is a managed topic, it retains its topic type, topic images, and children topics.

#### *idsToMerge*

Type: [List<String>](#)

A list of up to five comma-separated secondary topic IDs to merge with the primary topic. If any of the secondary topics are navigational or featured topics, they lose their topic type, topic images, and children topics. Their feed items are reassigned to the primary topic. If you merge a topic with a content topic, the content associations are preserved. If you merge a topic with an inactive endorsee, the endorsement isn't mapped to the primary topic.

### Return Value

Type: [ConnectApi.Topic](#)

### Usage

Only users with the Delete Topics or Modify All Data permission can merge topics.

## reassignTopicDataCategoryRules(communityId, dataCategoryGroup, dataCategory, topicNames)

Reassign topic and article assignment rules by data category by deleting the existing rules and creating new rules.

### API Version

40.0

### Requires Chatter

No

### Signature

```
public static ConnectApi.TopicPage reassignTopicDataCategoryRules(String communityId, String
dataCategoryGroup, String dataCategory, ConnectApi.TopicNamesInput topicNames)
```

### Parameters

#### *communityId*

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

#### *dataCategoryGroup*



Type: [String](#)

The data category used by articles.

#### *topicNames*

Type: [ConnectApi.TopicNamesInput](#)

A [ConnectApi.TopicNamesInput](#) object with the names of topics to reassign to articles in a data category.

#### Return Value

Type: [ConnectApi.TopicPage](#)

### reassignTopicsByName(*communityId*, *recordId*, *topicNames*)

Reassign all the topics on a record or feed item, that is, remove all the assigned topics on a record or feed item and add topics. Optionally, provide a list of suggested topics to assign to a record or feed item to improve future topic suggestions.

#### API Version

35.0

#### Requires Chatter

No

#### Signature

```
public static ConnectApi.TopicPage reassignTopicsByName(String communityId, String recordId,
ConnectApi.TopicNamesInput topicNames)
```

#### Parameters

##### *communityId*

Type: [String](#)

ID for an Experience Cloud site, internal, or null.

##### *recordId*

Type: [String](#)

The ID of the record or feed item to which to assign the topic.

##### *topicNames*

Type: [ConnectApi.TopicNamesInput](#)

A list of topics to replace the currently assigned topics. Optionally, a list of suggested topics to assign to improve future topic suggestions.

#### Return Value

Type: [ConnectApi.TopicPage](#)

#### Usage

Only users with the Assign Topics permission can remove topics from records or feed items and add existing topics to records or feed items. Only users with the Create Topics permission can add new topics to records or feed items. Administrators must enable topics for objects before users can add topics to records of that object type.



29.0

**Requires Chatter**

No

**Signature**

```
public static Void unassignTopic(String communityId, String recordId, String topicId)
```

**Parameters*****communityId***Type: [String](#)ID for an Experience Cloud site, `internal`, or `null`.***recordId***Type: [String](#)

ID for a record or feed item.

***topicId***Type: [String](#)

ID for a topic.

**Return Value**

Type: Void

**Usage**

Only users with the Assign Topics permission can remove topics from feed items or records. Administrators must enable topics for objects before users can add topics to records of that object type.

**updateTopic(communityId, topicId, topic)**

Update the description or name of a topic or merge up to five secondary topics with a primary topic.

**API Version**

29.0

**Requires Chatter**

No

**Signature**

```
public static ConnectApi.Topic updateTopic(String communityId, String topicId,
ConnectApi.TopicInput topic)
```

**Parameters*****communityId***Type: [String](#)ID for an Experience Cloud site, `internal`, or `null`.



### *topic*

Type: [ConnectApi.TopicInput](#)

A [ConnectApi.TopicInput](#) object containing the name and description of the topic or up to five comma-separated secondary topic IDs to merge with the primary topic.

### Return Value

Type: [ConnectApi.Topic](#)

### Usage

Only users with the Edit Topics or Modify All Data permission can update topic names and descriptions. Only users with the Delete Topics or Modify All Data permission can merge topics.

## updateTopicsForArticlesInDataCategory([communityId](#), [dataCategoryGroup](#), [dataCategory](#), [articleTopicAssignmentJob](#))

Assign topics to articles and unassign topics from articles in a data category.

### API Version

40.0

### Requires Chatter

No

### Signature

```
public static ConnectApi.TopicPage updateTopicsForArticlesInDataCategory(String communityId,  
String dataCategoryGroup, String dataCategory, ConnectApi.ArticleTopicAssignmentJobInput  
articleTopicAssignmentJob)
```

### Parameters

#### *communityId*

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

#### *dataCategoryGroup*

Type: [String](#)

The data category group used by articles.

#### *dataCategory*

Type: [String](#)

The data category used by articles.

#### *articleTopicAssignmentJob*

Type: [ConnectApi.ArticleTopicAssignmentJobInput](#)

A [ConnectApi.ArticleTopicAssignmentJobInput](#) object that indicates the operation to take on which topics.

### Return Value

Type: [ConnectApi.TopicPage](#)





Code.

## setTestGetGroupsRecentlyTalkingAboutTopic(*communityId*, *topicId*, *result*)

Register a `ConnectApi.ChatterGroupSummaryPage` object to be returned when the matching `ConnectApi.getGroupsRecentlyTalkingAboutTopic` method is called in a test context. Use the method with the same parameters or you receive an exception.

### API Version

29.0

### Signature

```
public static Void setTestGetGroupsRecentlyTalkingAboutTopic(String communityId, String
topicId, ConnectApi.ChatterGroupSummaryPage result)
```

### Parameters

#### *communityId*

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

#### *topicId*

Type: [String](#)

ID for a topic.

#### *result*

Type: [ConnectApi.ChatterGroupSummaryPage](#)

Object containing test data.

### Return Value

Type: `Void`

### See Also

- [getGroupsRecentlyTalkingAboutTopic\(\*communityId\*, \*topicId\*\)](#)
- [Apex Developer Guide: Testing ConnectApi Code](#)

## setTestGetRecentlyTalkingAboutTopicsForGroup(*communityId*, *groupId*, *result*)

Register a `ConnectApi.TopicPage` object to be returned when the matching `ConnectApi.getRecentlyTalkingAboutTopicsForGroup` method is called in a test context. Use the method with the same parameters or you receive an exception.

### API Version

29.0

### Signature

```
public static Void setTestGetRecentlyTalkingAboutTopicsForGroup(String communityId, String
groupId, ConnectApi.TopicPage result)
```



ID for an Experience Cloud site, `internal`, or `null`.

#### ***groupId***

Type: [String](#)

ID for a group.

#### ***result***

Type: [ConnectApi.TopicPage](#)

Object containing test data.

#### **Return Value**

Type: Void

#### **See Also**

- [getRecentlyTalkingAboutTopicsForGroup\(communityId, groupId\)](#)
- [Apex Developer Guide: Testing ConnectApi Code](#)

## **setTestGetRecentlyTalkingAboutTopicsForUser(communityId, userId, result)**

Register a [ConnectApi.TopicPage](#) object to be returned when the matching [ConnectApi.getRecentlyTalkingAboutTopicsForUser](#) method is called in a test context. Use the method with the same parameters or you receive an exception.

#### **API Version**

29.0

#### **Signature**

```
public static Void setTestGetRecentlyTalkingAboutTopicsForUser(String communityId, String
userId, ConnectApi.TopicPage result)
```

#### **Parameters**

##### ***communityId***

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

##### ***userId***

Type: [String](#)

ID for a user.

##### ***result***

Type: [ConnectApi.TopicPage](#)

Specify the test topics page.

#### **Return Value**

Type: Void

#### **See Also**

- [getRecentlyTalkingAboutTopicsForUser\(communityId, userId\)](#)



Register a `ConnectApi.TopicPage` object to be returned when the matching `ConnectApi.getRelatedTopics` method is called in a test context. Use the method with the same parameters or you receive an exception.

#### API Version

29.0

#### Signature

```
public static Void setTestGetRelatedTopics(String communityId, String topicId,
ConnectApi.TopicPage result)
```

#### Parameters

##### *communityId*

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

##### *topicId*

Type: [String](#)

ID for a topic.

##### *result*

Type: [ConnectApi.TopicPage](#)

Object containing test data.

#### Return Value

Type: `Void`

#### See Also

- [getRelatedTopics\(communityId, topicId\)](#)
- [Apex Developer Guide: Testing ConnectApi Code](#)

## setTestGetTopicSuggestions(communityId, recordId, maxResults, result)

Register a `ConnectApi.TopicSuggestionPage` object to be returned when the matching `ConnectApi.getTopicSuggestions` method is called in a test context. Use the method with the same parameters or you receive an exception.

#### API Version

29.0

#### Signature

```
public static Void setTestGetTopicSuggestions(String communityId, String recordId, Integer
maxResults, ConnectApi.TopicSuggestionPage result)
```

#### Parameters

##### *communityId*

Type: [String](#)



ID for a record or feed item.

#### ***maxResults***

Type: [Integer](#)

Maximum number of topic suggestions that get returned. The default is 5. Value must be greater than 0 and less than or equal to 25.

#### ***result***

Type: [ConnectApi.TopicSuggestionPage](#)

Specify the test topic suggestions page.

#### **Return Value**

Type: Void

#### **See Also**

- [getTopicSuggestions\(communityId, recordId, maxResults\)](#)
- [Apex Developer Guide: Testing ConnectApi Code](#)

## **setTestGetTopicSuggestions(communityId, recordId, result)**

Register a [ConnectApi.TopicSuggestionPage](#) object to be returned when the matching [ConnectApi.getTopicSuggestions](#) method is called in a test context. Use the method with the same parameters or you receive an exception.

#### **API Version**

29.0

#### **Signature**

```
public static Void setTestGetTopicSuggestions(String communityId, String recordId, ConnectApi.TopicSuggestionPage result)
```

#### **Parameters**

##### ***communityId***

Type: [String](#)

ID for an Experience Cloud site, internal, or null.

##### ***recordId***

Type: [String](#)

ID for a record or feed item.

##### ***result***

Type: [ConnectApi.TopicSuggestionPage](#)

Object containing test data.

#### **Return Value**

Type: Void

#### **See Also**

- [getTopicSuggestions\(communityId, recordId\)](#)



## maxResults, result)

Register a `ConnectApi.TopicSuggestionPage` object to be returned when the matching `ConnectApi.getTopicSuggestionsForText` method is called in a test context. Use the method with the same parameters or you receive an exception.

### API Version

29.0

### Signature

```
public static Void setTestGetTopicSuggestionsForText(String communityId, String text, Integer maxResults, ConnectApi.TopicSuggestionPage result)
```

### Parameters

#### *communityId*

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

#### *text*

Type: [String](#)

String of text.

#### *maxResults*

Type: [Integer](#)

Maximum number of topic suggestions that get returned. The default is 5. Value must be greater than 0 and less than or equal to 25.

#### *result*

Type: [ConnectApi.TopicSuggestionPage](#)

Object containing test data.

### Return Value

Type: Void

### See Also

- [getTopicSuggestionsForText\(communityId, text, maxResults\)](#)
- [Apex Developer Guide: Testing ConnectApi Code](#)

## setTestGetTopicSuggestionsForText(communityId, text, result)

Register a `ConnectApi.TopicSuggestionPage` object to be returned when the matching `ConnectApi.getTopicSuggestionsForText` method is called in a test context. Use the method with the same parameters or you receive an exception.

### API Version

29.0

### Signature

```
public static Void setTestGetTopicSuggestionsForText(String communityId, String text, ConnectApi.TopicSuggestionPage result)
```



ID for an Experience Cloud site, `internal`, or `null`.

#### ***text***

Type: [String](#)

String of text.

#### ***result***

Type: [ConnectApi.TopicSuggestionPage](#)

Object containing test data.

#### **Return Value**

Type: Void

#### **See Also**

- [getTopicSuggestionsForText\(`communityId`, `text`\)](#)
- [Apex Developer Guide: Testing ConnectApi Code](#)

## **setTestGetTrendingTopics(`communityId`, `result`)**

Register a `ConnectApi.TopicPage` object to be returned when the matching `ConnectApi.getTrendingTopics` method is called in a test context. Use the method with the same parameters or you receive an exception.

#### **API Version**

29.0

#### **Signature**

```
public static Void setTestGetTrendingTopics(String communityId, ConnectApi.TopicPage result)
```

#### **Parameters**

##### ***communityId***

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

##### ***result***

Type: [ConnectApi.TopicPage](#)

Object containing test data.

#### **Return Value**

Type: Void

#### **See Also**

- [getTrendingTopics\(`communityId`\)](#)
- [Apex Developer Guide: Testing ConnectApi Code](#)

## **setTestGetTrendingTopics(`communityId`, `maxResults`, `result`)**



29.0

**Signature**

```
public static Void setTestGetTrendingTopics(String communityId, Integer maxResults,  
ConnectApi.TopicPage result)
```

**Parameters*****communityId***Type: [String](#)ID for an Experience Cloud site, `internal`, or `null`.***maxResults***Type: [Integer](#)

Maximum number of topic suggestions that get returned. The default is 5. Value must be greater than 0 and less than or equal to 25.

***result***Type: [ConnectApi.TopicPage](#)

Object containing test data.

**Return Value**

Type: Void

**See Also**

- [getTrendingTopics\(communityId, maxResults\)](#)
- [Apex Developer Guide: Testing ConnectApi Code](#)

**DID THIS ARTICLE SOLVE YOUR ISSUE?**

Let us know so we can improve!

[Share your feedback](#)




MuleSoft  
Tableau  
Commerce Cloud  
Lightning Design System  
Einstein  
Quip

Component Library  
APIs  
Trailhead  
Sample Apps  
Podcasts  
AppExchange

Events and Calendar  
Partner Community  
Blog  
Salesforce Admins  
Salesforce Architects

© Copyright 2025 Salesforce, Inc. [All rights reserved.](#) Various trademarks held by their respective owners. Salesforce, Inc.  
Salesforce Tower, 415 Mission Street, 3rd Floor, San Francisco, CA 94105, United States

[Privacy Information](#) [Terms of Service](#) [Legal](#) [Use of Cookies](#) [Trust](#) [Cookie Preferences](#)  
 [Your Privacy Choices](#) [Responsible Disclosure](#) [Contact](#)