



# AuditParamsRequest

`AuditParamsRequest` is used for audit parameters in a transaction request. This is an abstract request class that is extended by the `BaseRequest` class.

## Namespace

[CommercePayments](#)

## Usage

`AuditParamsRequest` is an abstract class that holds attributes related to audit parameters such as email, IP address, MAC address, and phone number. This class can't be instantiated on its own. All `CommercePayments` request classes extend this class.

- [AuditParamsRequest Constructors](#)
- [AuditParamsRequest Properties](#)

## AuditParamsRequest Constructors

The following are constructors for `AuditParamsRequest`.

- [AuditParamsRequest\(email, macAddress, ipAddress, phone\)](#)  
This constructor is intended for test usage and throws an exception if used outside of the Apex test context.

### AuditParamsRequest(email, macAddress, ipAddress, phone)

This constructor is intended for test usage and throws an exception if used outside of the Apex test context.

#### Signature

```
AuditParamsRequest(String email, String macAddress, String ipAddress, String phone)
```

#### Parameters

##### *email*

Type: [String](#)

Email of the client that initiated the request.

##### *macAddress*

Type: [String](#)

Mac address of the customer's device. Gateways often use this data in risk checks.

##### *ipAddress*

Type: [String](#)

The customer's IP address. Gateways often use this data in risk checks.

##### *phone*



## AuditParamsRequest Properties

The following are properties for `AuditParamsRequest`.

- **email**  
Email of the client that initiated the request.
- **ipAddress**  
The customer's IP address. Gateways often use this data in risk checks.
- **macAddress**  
Mac address of the customer's device. Gateways often use this data in risk checks.
- **phone**  
Phone number of the client that initiated the request.

### email

Email of the client that initiated the request.

#### Property Value

Type: `String`

### ipAddress

The customer's IP address. Gateways often use this data in risk checks.

#### Property Value

Type: `String`

### macAddress

Mac address of the customer's device. Gateways often use this data in risk checks.

#### Property Value

Type: `String`

### phone

Phone number of the client that initiated the request.

#### Property Value

Type: `String`

#### DID THIS ARTICLE SOLVE YOUR ISSUE?

Let us know so we can improve!

[Share your feedback](#)



Commerce Cloud  
Lightning Design System  
Einstein  
Quip

Trailhead  
Sample Apps  
Podcasts  
AppExchange

Blog  
Salesforce Admins  
Salesforce Architects

© Copyright 2025 Salesforce, Inc. [All rights reserved.](#) Various trademarks held by their respective owners. Salesforce, Inc.  
Salesforce Tower, 415 Mission Street, 3rd Floor, San Francisco, CA 94105, United States

[Privacy Information](#) [Terms of Service](#) [Legal](#) [Use of Cookies](#) [Trust](#) [Cookie Preferences](#)

[Your Privacy Choices](#) [Responsible Disclosure](#) [Contact](#)