



AuthProviderCallbackState Class

Provides request HTTP headers, body, and query parameters to the `AuthProviderPlugin.handleCallback` method for user authentication. This class allows you to group the information passed in rather than passing headers, body, and query parameters individually.

Namespace

[Auth](#)

- [AuthProviderCallbackState Constructors](#)
- [AuthProviderCallbackState Properties](#)

See Also

- [handleCallback\(authProviderConfiguration, callbackState\)](#)

AuthProviderCallbackState Constructors

The following are constructors for `AuthProviderCallbackState`.

- [AuthProviderCallbackState\(headers, body, queryParameters\)](#)
Creates an instance of the `AuthProviderCallbackState` class using the specified HTTP headers, body, and query parameters of the authentication request.

AuthProviderCallbackState(headers, body, queryParameters)

Creates an instance of the `AuthProviderCallbackState` class using the specified HTTP headers, body and query parameters of the authentication request.

Signature

```
public AuthProviderCallbackState(Map<String,String> headers, String body, Map<String,String> queryParameters)
```

Parameters

headers

Type: [Map<String,String>](#)

The HTTP headers of the authentication request.

body

Type: [String](#)

The HTTP body of the authentication request.

queryParameters

Type: [Map<String,String>](#)

The HTTP query parameters of the authentication request.



The HTTP body of the authentication request.

- [headers](#)
The HTTP headers of the authentication request.
- [queryParameters](#)
The HTTP query parameters of the authentication request.

body

The HTTP body of the authentication request.

Signature

```
public String body {get; set;}
```

Property Value

Type: [String](#)

headers

The HTTP headers of the authentication request.

Signature

```
public Map<String,String> headers {get; set;}
```

Property Value

Type: [Map<String,String>](#)

queryParameters

The HTTP query parameters of the authentication request.

Signature

```
public Map<String,String> queryParameters {get; set;}
```

Property Value

Type: [Map<String,String>](#)

DID THIS ARTICLE SOLVE YOUR ISSUE?

Let us know so we can improve!

[Share your feedback](#)

DEVELOPER CENTERS
[Heroku](#)

POPULAR RESOURCES
[Documentation](#)

COMMUNITY
[Trailblazer Communit](#)



EinsteinPodcastsSalesforce Architects

QuipAppExchange

© Copyright 2025 Salesforce, Inc. [All rights reserved.](#) Various trademarks held by their respective owners. Salesforce, Inc. Salesforce Tower, 415 Mission Street, 3rd Floor, San Francisco, CA 94105, United States

[Privacy Information](#)[Terms of Service](#)[Legal](#)[Use of Cookies](#)[Trust](#)[Cookie Preferences](#)

[Your Privacy Choices](#)[Responsible Disclosure](#)[Contact](#)