RestContext Class

Contains the `RestRequest` and `RestResponse` objects.

Namespace

System

Usage

Use the `System.RestContext` class to access the `RestRequest` and `RestResponse` objects in your Apex REST methods.

Sample

The following example shows how to use `RestContext` to access the `RestRequest` and `RestResponse` objects in an Apex REST method.

```apex
@RestResource(urlMapping='/MyRestContextExample/*')
global with sharing class MyRestContextExample {

    @HttpGet
    global static Account doGet() {
        RestRequest req = RestContext.request;
        RestResponse res = RestContext.response;
        String accountId = req.requestURI.substring(req.requestURI.lastIndexOf('/')+1);
        Account result = [SELECT Id, Name, Phone, Website FROM Account WHERE Id = :account
        return result;
    }

}
```

RestContext Properties

The following are properties for `RestContext`.

- **request**
  Returns the `RestRequest` for your Apex REST method.
- **response**
  Returns the `RestResponse` for your Apex REST method.

request

Returns the `RestRequest` for your Apex REST method.

Signature

```apex
public RestRequest request {get; set;}
```

Property Value

Returns the `RestResponse` for your Apex REST method.

Signature

```
public RestResponse response {get; set;}
```

Property Value

Type: System.RestResponse

DID THIS ARTICLE SOLVE YOUR ISSUE?
Let us know so we can improve!

Share your feedback

DEVELOPER CENTERS

Heroku

MuleSoft

Tableau

Commerce Cloud

Lightning Design System

Einstein

Quip

POPULAR RESOURCES

Documentation

Component Library

APIs

Trailhead

Sample Apps

Podcasts

AppExchange

COMMUNITY

Trailblazer Community

Events and Calendar

Partner Community

Blog

Salesforce Admins

Salesforce Architects

Privacy Information   Terms of Service   Legal   Use of Cookies   Trust   Cookie Preferences

Your Privacy Choices   Responsible Disclosure   Contact