



CommerceWishlist Class

Get, create, update, and delete wishlists. Add wishlists to carts. Get wishlist items, add items to wishlists, and delete wishlist items.

Namespace

[ConnectApi](#)

CommerceWishlist Methods

These methods are for `CommerceWishlist`. All methods are static.

- [addItemToWishlist\(webstoreId, wishlistId, wishlistItemInput\)](#)
Add an item to a wishlist for the context user.
- [addItemToWishlist\(webstoreId, effectiveAccountId, wishlistId, wishlistItemInput\)](#)
Add an item to a wishlist.
- [addWishlistToCart\(webstoreId, wishlistId\)](#)
Add a wishlist to the active cart for the context user.
- [addWishlistToCart\(webstoreId, wishlistId, effectiveAccountId\)](#)
Add a wishlist to the active cart.
- [addWishlistToCartWithCartId\(webstoreId, wishlistId, cartId\)](#)
Add a wishlist to a cart.
- [addWishlistToCartWithCartId\(webstoreId, wishlistId, cartId, effectiveAccountId\)](#)
Add a wishlist to a cart.
- [createWishlist\(webstoreId, wishlistInput\)](#)
Create a wishlist for the context user.
- [createWishlist\(webstoreId, effectiveAccountId, wishlistInput\)](#)
Create a wishlist.
- [deleteWishlist\(webstoreId, wishlistId\)](#)
Delete a wishlist for the context user.
- [deleteWishlist\(webstoreId, effectiveAccountId, wishlistId\)](#)
Delete a wishlist.
- [getWishlist\(webstoreId, effectiveAccountId, wishlistId, productFields, sortItemsBy\)](#)
Get a wishlist with product fields sorted by items.
- [getWishlist\(webstoreId, effectiveAccountId, wishlistId, productFields, pageSize, sortItemsBy\)](#)
Get a wishlist with product fields sorted by items with a specified number of items per page.
- [getWishlistItems\(webstoreId, effectiveAccountId, wishlistId, productFields, pageParam, sortItemsBy\)](#)
Get a page of sorted wishlist items with product fields.
- [getWishlistItems\(webstoreId, effectiveAccountId, wishlistId, productFields, pageParam, pageSize, sortItemsBy\)](#)
Get a page of specified size of sorted wishlist items with product fields.
- [getWishlistSummaries\(webstoreId, effectiveAccountId, includeDisplayedList\)](#)
Get wishlist summaries.

**productFields, pageSize, sortItemsBy)**

Get wishlist summaries with product fields sorted by items with a specified number of items per page.

- **removeWishlistItem(webstoreId, effectiveAccountId, wishlistId, wishlistItemId)**
Remove an item from a wishlist.
- **updateWishlist(webstoreId, wishlistId, wishlistUpdateInput)**
Update the name of a wishlist for the context user.
- **updateWishlist(webstoreId, effectiveAccountId, wishlistId, wishlistUpdateInput)**
Update the name of a wishlist.

addItemToWishlist(webstoreId, wishlistId, wishlistItemInput)

Add an item to a wishlist for the context user.

API Version

49.0

Requires Chatter

No

Signature

```
public static ConnectApi.WishlistItem addItemToWishlist(String webstoreId, String wishlistId,
ConnectApi.WishlistItemInput wishlistItemInput)
```

Parameters***webstoreId***

Type: [String](#)

ID of the webstore.

wishlistId

Type: [String](#)

ID of the wishlist.

wishlistItemInput

Type: [ConnectApi.WishlistItemInput](#)

A [ConnectApi.WishlistItemInput](#) body with the item to add to the wishlist.

Return Value

Type: [ConnectApi.WishlistItem](#)

Usage

This method respects buyer View Product entitlements and only users entitled to view product data can access it.

addItemToWishlist(webstoreId, effectiveAccountId, wishlistId, wishlistItemInput)

Add an item to a wishlist.

API Version

49.0



```
public static ConnectApi.WishlistItem addItemToWishlist(String webstoreId, String
effectiveAccountId, String wishlistId, ConnectApi.WishlistItemInput wishlistItemInput)
```

Parameters

webstoreId

Type: [String](#)

ID of the webstore.

effectiveAccountId

Type: [String](#)

ID of the account for which the request is made. If `null`, defaults to the account ID for the context user.

wishlistId

Type: [String](#)

ID of the wishlist.

wishlistItemInput

Type: [ConnectApi.WishlistItemInput](#)

A `ConnectApi.WishlistItemInput` body with the item to add to the wishlist.

Return Value

Type: [ConnectApi.WishlistItem](#)

Usage

This method respects buyer View Product entitlements and only users entitled to view product data can access it.

addWishlistToCart(webstoreId, wishlistId)

Add a wishlist to the active cart for the context user.

API Version

49.0

Requires Chatter

No

Signature

```
public static ConnectApi.WishlistToCartResult addWishlistToCart(String webstoreId, String
wishlistId)
```

Parameters

webstoreId

Type: [String](#)

ID of the webstore.

wishlistId

Type: [String](#)

ID of the wishlist.



This method respects buyer View Product entitlements and only users entitled to view product data can access it.

addWishlistToCart(webstoreId, wishlistId, effectiveAccountId)

Add a wishlist to the active cart.

API Version

49.0

Requires Chatter

No

Signature

```
public static ConnectApi.WishlistToCartResult addWishlistToCart(String webstoreId, String wishlistId, String effectiveAccountId)
```

Parameters

webstoreId

Type: [String](#)

ID of the webstore.

wishlistId

Type: [String](#)

ID of the wishlist.

effectiveAccountId

Type: [String](#)

ID of the account for which the request is made. If `null`, defaults to the account ID for the context user.

Return Value

Type: [ConnectApi.WishlistToCartResult](#)

Usage

This method respects buyer View Product entitlements and only users entitled to view product data can access it.

addWishlistToCartWithCartId(webstoreId, wishlistId, cartId)

Add a wishlist to a cart.

API Version

49.0

Requires Chatter

No

Signature

***webstoreId***Type: [String](#)

ID of the webstore.

wishlistIdType: [String](#)

ID of the wishlist.

cartIdType: [String](#)

ID of the cart. If null, wishlist items are added to the active cart.

Return ValueType: [ConnectApi.WishlistToCartResult](#)**Usage**

This method respects buyer View Product entitlements and only users entitled to view product data can access it.

addWishlistToCartWithCartId(webstoreId, wishlistId, cartId, effectiveAccountId)

Add a wishlist to a cart.

API Version

49.0

Requires Chatter

No

Signature

```
public static ConnectApi.WishlistToCartResult addWishlistToCartWithCartId(String webstoreId,
String wishlistId, String cartId, String effectiveAccountId)
```

Parameters***webstoreId***Type: [String](#)

ID of the webstore.

wishlistIdType: [String](#)

ID of the wishlist.

cartIdType: [String](#)

ID of the cart. If null, wishlist items are added to the active cart.

effectiveAccountIdType: [String](#)



Type: [ConnectApi.WishlistToCartResult](#)

Usage

This method respects buyer View Product entitlements and only users entitled to view product data can access it.

createWishlist(webstoreId, wishlistInput)

Create a wishlist for the context user.

API Version

49.0

Requires Chatter

No

Signature

```
public static ConnectApi.Wishlist createWishlist(String webstoreId, ConnectApi.WishlistInput wishlistInput)
```

Parameters

webstoreId

Type: [String](#)

ID of the webstore.

wishlistInput

Type: [ConnectApi.WishlistInput](#)

A [ConnectApi.WishlistInput](#) body that includes the wishlist name and items.

Return Value

Type: [ConnectApi.Wishlist](#)

createWishlist(webstoreId, effectiveAccountId, wishlistInput)

Create a wishlist.

API Version

49.0

Requires Chatter

No

Signature

```
public static ConnectApi.Wishlist createWishlist(String webstoreId, String effectiveAccountId, ConnectApi.WishlistInput wishlistInput)
```

Parameters

webstoreId

Type: [String](#)

ID of the webstore.



Context user.

wishlistInput

Type: [ConnectApi.WishlistInput](#)

A [ConnectApi.WishlistInput](#) body that includes the wishlist name and items.

Return Value

Type: [ConnectApi.Wishlist](#)

deleteWishlist(webstoreId, wishlistId)

Delete a wishlist for the context user.

API Version

49.0

Requires Chatter

No

Signature

```
public static Void deleteWishlist(String webstoreId, String wishlistId)
```

Parameters

webstoreId

Type: [String](#)

ID of the webstore.

wishlistId

Type: [String](#)

ID of the wishlist.

Return Value

Type: Void

deleteWishlist(webstoreId, effectiveAccountId, wishlistId)

Delete a wishlist.

API Version

51.0

Requires Chatter

No

Signature

```
public static Void deleteWishlist(String webstoreId, String effectiveAccountId, String wishlistId)
```

Parameters

webstoreId

Type: [String](#)



ID of the account for which the request is made. If `null`, defaults to the account ID for the context user.

wishlistId

Type: [String](#)

ID of the wishlist.

Return Value

Type: Void

getWishlist(webstoreId, effectiveAccountId, wishlistId, productFields, sortItemsBy)

Get a wishlist with product fields sorted by items.

API Version

51.0

Requires Chatter

No

Signature

```
public static ConnectApi.Wishlist getWishlist(String webstoreId, String effectiveAccountId,
String wishlistId, String productFields, ConnectApi.WishlistItemSortOrder sortItemsBy)
```

Parameters

webstoreId

Type: [String](#)

ID of the webstore.

effectiveAccountId

Type: [String](#)

ID of the account for which the request is made. If `null`, defaults to the account ID for the context user.

wishlistId

Type: [String](#)

ID of the wishlist.

productFields

Type: [String](#)

Comma-separated list of custom product fields. Fields aren't case-sensitive. For example, `ProductCode` and `productcode` return the same results.

sortItemsBy

Type: [ConnectApi.WishlistItemSortOrder](#)

Sort order for wishlist items. Values are:

- `CreatedDateAsc`—Sorts by oldest creation date.
- `CreatedDateDesc`—Sorts by most recent creation date.

The default sort order is `CreatedDateDesc`.



getWishlist(webstoreId, effectiveAccountId, wishlistId, productFields, pageSize, sortItemsBy)

Get a wishlist with product fields sorted by items with a specified number of items per page.

API Version

51.0

Requires Chatter

No

Signature

```
public static ConnectApi.Wishlist getWishlist(String webstoreId, String effectiveAccountId,
String wishlistId, String productFields, Integer pageSize, ConnectApi.WishlistItemSortOrder
sortItemsBy)
```

Parameters

webstoreId

Type: [String](#)

ID of the webstore.

effectiveAccountId

Type: [String](#)

ID of the account for which the request is made. If `null`, defaults to the account ID for the context user.

wishlistId

Type: [String](#)

ID of the wishlist.

productFields

Type: [String](#)

Comma-separated list of custom product fields. Fields aren't case-sensitive. For example, `ProductCode` and `productcode` return the same results.

pageSize

Type: [Integer](#)

Specifies the number of items per page. Valid values are from 1 through 100. If you pass in `null`, the default size is 25.

sortItemsBy

Type: [ConnectApi.WishlistItemSortOrder](#)

Sort order for wishlist items. Values are:

- `CreatedDateAsc`—Sorts by oldest creation date.
- `CreatedDateDesc`—Sorts by most recent creation date.

The default sort order is `CreatedDateDesc`.

Return Value

Type: [ConnectApi.Wishlist](#)



API Version

51.0

Requires Chatter

No

Signature

```
public static ConnectApi.WishlistItemCollection getWishlistItems(String webstoreId, String effectiveAccountId, String wishlistId, String productFields, String pageParam, ConnectApi.WishlistItemSortOrder sortItemsBy)
```

Parameters

webstoreId

Type: [String](#)

ID of the webstore.

effectiveAccountId

Type: [String](#)

ID of the account for which the request is made. If `null`, defaults to the account ID for the context user.

wishlistId

Type: [String](#)

ID of the wishlist.

productFields

Type: [String](#)

Comma-separated list of custom product fields. Fields aren't case-sensitive. For example, `ProductCode` and `productcode` return the same results.

pageParam

Type: [String](#)

Specifies the page token to use to view a page of information. Page tokens are returned as part of the response class, such as `currentPageToken` or `nextPageToken`. If you pass in `null`, the first page is returned.

sortItemsBy

Type: [ConnectApi.WishlistItemSortOrder](#)

Sort order for wishlist items. Values are:

- `CreatedDateAsc`—Sorts by oldest creation date.
- `CreatedDateDesc`—Sorts by most recent creation date.

The default sort order is `CreatedDateDesc`.

Return Value

Type: [ConnectApi.WishlistItemCollection](#)

`getWishlistItems(webstoreId, effectiveAccountId, wishlistId, productFields, pageParam, pageSize, sortItemsBy)`



Requires Chatter

No

Signature

```
public static ConnectApi.WishlistItemCollection getWishlistItems(String webstoreId, String effectiveAccountId, String wishlistId, String productFields, String pageParam, Integer pageSize, ConnectApi.WishlistItemSortOrder sortItemsBy)
```

Parameters

webstoreId

Type: [String](#)

ID of the webstore.

effectiveAccountId

Type: [String](#)

ID of the account for which the request is made. If `null`, defaults to the account ID for the context user.

wishlistId

Type: [String](#)

ID of the wishlist.

productFields

Type: [String](#)

Comma-separated list of custom product fields. Fields aren't case-sensitive. For example, `ProductCode` and `productcode` return the same results.

pageParam

Type: [String](#)

Specifies the page token to use to view a page of information. Page tokens are returned as part of the response class, such as `currentPageToken` or `nextPageToken`. If you pass in `null`, the first page is returned.

pageSize

Type: [Integer](#)

Specifies the number of items per page. Valid values are from 1 through 200. If you pass in `null`, the default size is 25.

sortItemsBy

Type: [ConnectApi.WishlistItemSortOrder](#)

Sort order for wishlist items. Values are:

- `CreatedDateAsc`—Sorts by oldest creation date.
- `CreatedDateDesc`—Sorts by most recent creation date.

The default sort order is `CreatedDateDesc`.

Return Value

Type: [ConnectApi.WishlistItemCollection](#)

**API Version**

49.0

Requires Chatter

No

Signature

```
public static ConnectApi.WishlistsSummary getWishlistSummaries(String webstoreId, String effectiveAccountId, Boolean includeDisplayedList)
```

Parameters***webstoreId***Type: [String](#)

ID of the webstore.

effectiveAccountIdType: [String](#)ID of the account for which the request is made. If `null`, defaults to the account ID for the context user.***includeDisplayedList***Type: [Boolean](#)Specifies whether to include the displayed list (`true`) or not (`false`). If `null`, defaults to `false`.**Return Value**Type: [ConnectApi.WishlistsSummary](#)**getWishlistSummaries(webstoreId, effectiveAccountId, includeDisplayedList, productFields, sortItemsBy)**

Get wishlist summaries with product fields sorted by items.

API Version

51.0

Requires Chatter

No

Signature

```
public static ConnectApi.WishlistsSummary getWishlistSummaries(String webstoreId, String effectiveAccountId, Boolean includeDisplayedList, String productFields, ConnectApi.WishlistItemSortOrder sortItemsBy)
```

Parameters***webstoreId***Type: [String](#)

ID of the webstore.

effectiveAccountId

***includeDisplayedList***Type: [Boolean](#)

Specifies whether to include the displayed list (`true`) or not (`false`).

productFieldsType: [String](#)

Comma-separated list of custom product fields. Fields aren't case-sensitive. For example, `ProductCode` and `productcode` return the same results.

If `includeDisplayedList` is `false`, `productFields` is ignored.

sortItemsByType: [ConnectApi.WishlistItemSortOrder](#)

Sort order for wishlist items. Values are:

- `CreatedDateAsc`—Sorts by oldest creation date.
- `CreatedDateDesc`—Sorts by most recent creation date.

The default sort order is `CreatedDateDesc`.

If `includeDisplayedList` is `false`, `sortItemsBy` is ignored.

Return ValueType: [ConnectApi.WishlistsSummary](#)**`getWishlistSummaries(webstoreId, effectiveAccountId, includeDisplayedList, productFields, pageSize, sortItemsBy)`**

Get wishlist summaries with product fields sorted by items with a specified number of items per page.

API Version

51.0

Requires Chatter

No

Signature

```
public static ConnectApi.WishlistsSummary getWishlistSummaries(String webstoreId, String effectiveAccountId, Boolean includeDisplayedList, Integer pageSize, String productFields, Integer pageSize, ConnectApi.WishlistItemSortOrder sortItemsBy)
```

Parameters***webstoreId***Type: [String](#)

ID of the webstore.

effectiveAccountIdType: [String](#)

ID of the account for which the request is made. If `null`, defaults to the account ID for the context user.

includeDisplayedListType: [Boolean](#)



Comma-separated list of custom product fields. Fields aren't case-sensitive. For example, `ProductCode` and `productcode` return the same results.

If `includeDisplayedList` is `false`, `productFields` is ignored.

pageSize

Type: [Integer](#)

Specifies the number of items per page. Valid values are from 1 through 100. If you pass in `null`, the default size is 25.

sortItemsBy

Type: [ConnectApi.WishlistItemSortOrder](#)

Sort order for wishlist items. Values are:

- `CreatedDateAsc`—Sorts by oldest creation date.
- `CreatedDateDesc`—Sorts by most recent creation date.

The default sort order is `CreatedDateDesc`.

If `includeDisplayedList` is `false`, `sortItemsBy` is ignored.

Return Value

Type: [ConnectApi.WishlistsSummary](#)

removeWishlistItem(webstoreId, effectiveAccountId, wishlistId, wishlistItemId)

Remove an item from a wishlist.

API Version

49.0

Requires Chatter

No

Signature

```
public static void removeWishlistItem(String webstoreId, String effectiveAccountId, String wishlistId, String wishlistItemId)
```

Parameters

webstoreId

Type: [String](#)

ID of the webstore.

effectiveAccountId

Type: [String](#)

ID of the account for which the request is made. If `null`, defaults to the account ID for the context user.

wishlistId

Type: [String](#)

ID of the wishlist.

wishlistItemId



Type: Void

updateWishlist(webstoreId, wishlistId, wishlistUpdateInput)

Update the name of a wishlist for the context user.

API Version

50.0

Requires Chatter

No

Signature

```
public static ConnectApi.WishlistSummary updateWishlist(String webstoreId, String wishlistId,
ConnectApi.WishlistUpdateInput wishlistUpdateInput)
```

Parameters

webstoreId

Type: [String](#)

ID of the webstore.

wishlistId

Type: [String](#)

ID of the wishlist.

wishlistUpdateInput

Type: [ConnectApi.WishlistUpdateInput](#)

A [ConnectApi.WishlistUpdateInput](#) body with the wishlist name to update.

Return Value

Type: [ConnectApi.WishlistSummary](#)

updateWishlist(webstoreId, effectiveAccountId, wishlistId, wishlistUpdateInput)

Update the name of a wishlist.

API Version

50.0

Requires Chatter

No

Signature

```
public static ConnectApi.WishlistSummary updateWishlist(String webstoreId, String
effectiveAccountId, String wishlistId, ConnectApi.WishlistUpdateInput wishlistUpdateInput)
```

Parameters

webstoreId

Type: [String](#)



ID of the account for which the request is made. If `null`, defaults to the account ID for the context user.

wishlistId

Type: [String](#)

ID of the wishlist.

wishlistUpdateInput

Type: [ConnectApi.WishlistUpdateInput](#)

A [ConnectApi.WishlistUpdateInput](#) body with the wishlist name to update.

Return Value

Type: [ConnectApi.WishlistSummary](#)

DID THIS ARTICLE SOLVE YOUR ISSUE?

Let us know so we can improve!

[Share your feedback](#)



DEVELOPER CENTERS

[Heroku](#)
[MuleSoft](#)
[Tableau](#)
[Commerce Cloud](#)
[Lightning Design System](#)
[Einstein](#)
[Quip](#)

POPULAR RESOURCES

[Documentation](#)
[Component Library](#)
[APIs](#)
[Trailhead](#)
[Sample Apps](#)
[Podcasts](#)
[AppExchange](#)

COMMUNITY

[Trailblazer Community](#)
[Events and Calendar](#)
[Partner Community](#)
[Blog](#)
[Salesforce Admins](#)
[Salesforce Architects](#)

© Copyright 2025 Salesforce, Inc. [All rights reserved](#). Various trademarks held by their respective owners. Salesforce, Inc.
Salesforce Tower, 415 Mission Street, 3rd Floor, San Francisco, CA 94105, United States

[Privacy Information](#) [Terms of Service](#) [Legal](#) [Use of Cookies](#) [Trust](#) [Cookie Preferences](#)

[Your Privacy Choices](#) [Responsible Disclosure](#) [Contact](#)