

Developers







Apex Reference Guide / Auth Namespace / AuthProviderTokenResponse Class

AuthProviderTokenResponse Class

Stores the response from the AuthProviderPlugin.handleCallback method.

Namespace

Auth

- AuthProviderTokenResponse Constructors
- AuthProviderTokenResponse Properties

AuthProviderTokenResponse Constructors

The following are constructors for AuthProviderTokenResponse.

 AuthProviderTokenResponse(provider, oauthToken, oauthSecretOrRefreshToken, state)

Creates an instance of the AuthProviderTokenResponse class for a custom authentication provider plug-in using the specified arguments.

 AuthProviderTokenResponse(provider, oauthToken, oauthSecretOrRefreshToken, state, idToken)

Creates an instance of the AuthProviderTokenResponse class for a custom authentication provider plug-in using the specified arguments. This constructor includes a parameter for the ID token.

AuthProviderTokenResponse(provider, oauthToken, oauthSecretOrRefreshToken, state)

Creates an instance of the AuthProviderTokenResponse class for a custom authentication provider plug-in using the specified arguments.

Signature

public AuthProviderTokenResponse(String provider, String oauthToken, String oauthSecretOrRefreshToken, String state)

Parameters

provider

Type: String

The custom authentication provider.

oauthToken

Type: String

The OAuth access token.

oauthSecretOrRefreshToken

Type: String

The OAuth secret or refresh token for the currently logged-in user.





AuthProviderTokenResponse(provider, oauthToken, oauthSecretOrRefreshToken, state, idToken)

Creates an instance of the AuthProviderTokenResponse class for a custom authentication provide plug-in using the specified arguments. This constructor includes a parameter for the ID token.

Signature

public AuthProviderTokenResponse(String provider, String oauthToken, String oauthSecretOrRefreshToken, String state)

Parameters

provider

Type: String

The custom authentication provider.

oauthToken

Type: String

The OAuth access token.

oauthSecretOrRefreshToken

Type: String

The OAuth secret or refresh token for the currently logged-in user.

state

Type: String

The state passed in to initiate the authentication request for the user.

idToken

Type: String

The ID token in encoded JWT format.

AuthProviderTokenResponse Properties

The following are properties for AuthProviderTokenResponse.

• oauthSecretOrRefreshToken

The OAuth secret or refresh token for the currently logged-in user.

oauthToken

The OAuth access token.

provider

The authentication provider.

state

The state passed in to initiate the authentication request for the user.

idToker

The ID token from the third party in encoded JWT format.

oauthSecretOrRefreshToken

The OAuth secret or refresh token for the currently logged-in user.

Signature





oauthToken

The OAuth access token.

Signature

public String oauthToken {get; set;}

Property Value

Type: String

provider

The authentication provider.

Signature

```
public String provider {get; set;}
```

Property Value

Type: String

state

The state passed in to initiate the authentication request for the user.

Signature

```
public String state {get; set;}
```

Property Value

Type: String

idToken

The ID token from the third party in encoded JWT format.

Signature

```
public String idToken {get; set;}
```

Property Value

Type: String


DID THIS ARTICLE SOLVE YOUR ISSUE?

Let us know so we can improve!

Share your feedback

Responsible Disclosure





Contact

✓ X Your Privacy Choices