Developers

getContentHostname()

DomainCreator Class

Use the DomainCreator class to return a hostname specific to the org. For example, get the org's Visualforce hostname. Values are returned as a hostname, such as *MyDomainName*`.lightning.force.com`.

Namespace

[System](#)

Examples

This example code fetches the org's My Domain login hostname and the Visualforce hostname for the `uat` package.

```
//Get the My Domain login hostname
String myDomainHostname = DomainCreator.getOrgMyDomainHostname();

//Get the Visualforce hostname
String vfHostname = DomainCreator.getVisualforceHostname('uat');
```

In this case, in a production org with a My Domain name of `mycompany`, `myDomainHostname` returns `mycompany.my.salesforce.com`. And in the same production org, `vfHostname` returns `mycompany--uat.vf.force.com`.

This example code creates a link to a Salesforce Account record. It gets the Lightning hostname associated with this org. It then gets the Account record ID and uses concatenation to build the link URL.

```
//Get the org's Lightning hostname
String myLightningHostname = DomainCreator.getLightningHostname();

//Get the ID of a record Account with the name 'Acme'
Account acct = [SELECT Id FROM Account WHERE Name = 'Acme' LIMIT 1];

//Build the URL to view the account record
String fullRecordURL = 'https://' + myLightningHostname + '/lightning/r/Account/' + acct.I
```

- **DomainCreator Methods**

DomainCreator Methods

The following are methods for `DomainCreator`.

- **getContentHostname()**
  Returns the hostname for content stored in the org, such as files.

- **getExperienceCloudSitesBuilderHostname()**
  Returns the hostname to access Experience Builder for the org's Experience Cloud sites.

- **getExperienceCloudSitesHostname()**
  Returns the system-managed hostname for the org's Experience Cloud sites, such as

Cloud sites.

- **getExperienceCloudSitesPreviewHostname()**
  Returns the hostname to access Experience Builder Preview for the org's Experience Cloud sites.

- **getLightningContainerComponentHostname(packageName)**
  Returns the hostname for the org's Lightning Container Components.

- **getLightningHostname()**
  Returns the hostname for the org's Lightning pages.

- **getOrgMyDomainHostname()**
  Returns the hostname for the org's My Domain login domain.

- **getSalesforceSitesHostname()**
  Returns the hostname for the org's Salesforce Sites. If Salesforce Sites aren't enabled, this method throws an `InvalidParameterValueException`.

- **getSetupHostname()**
  Returns the hostname for the org's setup domain, which hosts Setup pages in Salesforce.

- **getVisualforceHostname(packageName)**
  Returns the hostname for the org's Visualforce pages.

getContentHostname()

Returns the hostname for content stored in the org, such as files.

Signature

```
public static String getContentHostname()
```

Return Value

Type: String

getExperienceCloudSitesBuilderHostname()

Returns the hostname to access Experience Builder for the org's Experience Cloud sites.

Signature

```
public static String getExperienceCloudSitesBuilderHostname()
```

Return Value

Type: String

getExperienceCloudSitesHostname()

Returns the system-managed hostname for the org's Experience Cloud sites, such as `ExperienceCloudSitesSubdomainName.force.com`. If Digital Experiences aren't enabled, this method throws an `InvalidParameterValueException`.

Signature

```
public static String getExperienceCloudSitesHostname()
```

Return Value

Type: String

getExperienceCloudSitesLivePreviewHostname()

```
public static String getExperienceCloudSitesLivePreviewHostname()
```

Return Value

Type: String

getExperienceCloudSitesPreviewHostname()

Returns the hostname to access Experience Builder Preview for the org's Experience Cloud sites.

Signature

```
public static String getExperienceCloudSitesPreviewHostname()
```

Return Value

Type: String

getLightningContainerComponentHostname(packageName)

Returns the hostname for the org's Lightning Container Components.

Signature

```
public static String getLightningContainerComponentHostname(String packageName)
```

Parameters

packageName

Type: String

The package name for this component.
If packageName is `null`, this method uses the org's namespace prefix as the package name.
Otherwise, it uses the default namespace.

Return Value

Type: String

getLightningHostname()

Returns the hostname for the org's Lightning pages.

Signature

```
public static String getLightningHostname()
```

Return Value

Type: String

getOrgMyDomainHostname()

Returns the hostname for the org's My Domain login domain.

Signature

```
public static String getOrgMyDomainHostname()
```

Return Value

Type: String

∨

Signature

```
public static String getSalesforceSitesHostname()
```

Return Value

Type: String

getSetupHostname()

Returns the hostname for the org's setup domain, which hosts Setup pages in Salesforce.

Signature

```
public static String getSetupHostname()
```

Return Value

Type: String

getVisualforceHostname(packageName)

Returns the hostname for the org's Visualforce pages.

Signature

```
public static String getVisualforceHostname(String packageName)
```

Parameters

packageName

Type: String

The package name for this component.
If packageName is `null`, this method uses the org's namespace prefix as the package name.
Otherwise, it uses the default namespace.

Return Value

Type: String

DID THIS ARTICLE SOLVE YOUR ISSUE?
Let us know so we can improve!

Share your feedback

DEVELOPER CENTERS

Heroku

MuleSoft

Tableau

Commerce Cloud

POPULAR RESOURCES

Documentation

Component Library

APIs

Trailhead

COMMUNITY

Trailblazer Community

Events and Calendar

Partner Community

Blog

Privacy Information   Terms of Service   Legal   Use of Cookies   Trust   Cookie Preferences

Your Privacy Choices   Responsible Disclosure   Contact