



BaseRequest Class

`BaseRequest` is extended by all the request classes.

Namespace

CommercePayments

- [BaseRequest Methods](#)

BaseRequest Methods

The following are methods for `BaseRequest`.

- [BaseRequest\(AdditionalData, IdempotencyKey\)](#)
Used for testing.

BaseRequest(AdditionalData, IdempotencyKey)

Used for testing.

Signature

```
global Void BaseRequest(String AdditionalData, Map<String, String> IdempotencyKey)
```

Parameters

AdditionalData

Type: [String](#)

Contains additional data that may be required for a payment request. The `additionalData` object consists of key-value pairs. You can retrieve the `additionalData` object from the request object:

```
Map<String, String> additionalData=request.additionalData
```

IdempotencyKey

Type: `Map<String, String>`

Unique value that's generated by a client and sent to the server in the request. The server stores the value and uses the it to keep track of the request status.

Return Value

Type: `Void`

DID THIS ARTICLE SOLVE YOUR ISSUE?

Let us know so we can improve!

[Share your feedback](#)



MuleSoft
Tableau
Commerce Cloud
Lightning Design System
Einstein
Quip

Component Library
APIs
Trailhead
Sample Apps
Podcasts
AppExchange

Events and Calendar
Partner Community
Blog
Salesforce Admins
Salesforce Architects

© Copyright 2025 Salesforce, Inc. [All rights reserved.](#) Various trademarks held by their respective owners. Salesforce, Inc.
Salesforce Tower, 415 Mission Street, 3rd Floor, San Francisco, CA 94105, United States

[Privacy Information](#) [Terms of Service](#) [Legal](#) [Use of Cookies](#) [Trust](#) [Cookie Preferences](#)

[Your Privacy Choices](#) [Responsible Disclosure](#) [Contact](#)