



CommunityModeration Class

Get information about flagged feed items and comments in an Experience Cloud site. Add and remove flags from comments and feed items.

Namespace

[ConnectApi](#)

CommunityModeration Methods

These methods are for `CommunityModeration`. All methods are static.

All methods in this class require Chatter and are subject to the per user, per namespace, per hour rate limit.

- [addFlagToComment\(`communityId`, `commentId`\)](#)
Add a moderation flag to a comment.
- [addFlagToComment\(`communityId`, `commentId`, `visibility`\)](#)
Add a moderation flag of the specified visibility to a comment.
- [addFlagToComment\(`communityId`, `commentId`, `type`\)](#)
Add a moderation flag of the specified type to a comment.
- [addFlagToComment\(`communityId`, `commentId`, `note`\)](#)
Add a moderation flag with a note to a comment.
- [addFlagToComment\(`communityId`, `commentId`, `type`, `note`\)](#)
Add a moderation flag of the specified type with a note to a comment.
- [addFlagToComment\(`communityId`, `commentId`, `type`, `visibility`\)](#)
Add a moderation flag of the specified type and visibility to a comment.
- [addFlagToComment\(`communityId`, `commentId`, `visibility`, `note`\)](#)
Add a moderation flag of the specified visibility with a note to a comment.
- [addFlagToComment\(`communityId`, `commentId`, `type`, `visibility`, `note`\)](#)
Add a moderation flag of the specified type and visibility with a note to a comment.
- [addFlagToFeedElement\(`communityId`, `feedElementId`\)](#)
Add a moderation flag to a feed element.
- [addFlagToFeedElement\(`communityId`, `feedElementId`, `visibility`\)](#)
Add a moderation flag of the specified visibility to a feed element.
- [addFlagToFeedElement\(`communityId`, `feedElementId`, `type`\)](#)
Add a moderation flag of the specified type to a feed element.
- [addFlagToFeedElement\(`communityId`, `feedElementId`, `note`\)](#)
Add a moderation flag with a note to a feed element.
- [addFlagToFeedElement\(`communityId`, `feedElementId`, `type`, `note`\)](#)
Add a moderation flag of the specified type with a note to a feed element.
- [addFlagToFeedElement\(`communityId`, `feedElementId`, `type`, `visibility`\)](#)
Add a moderation flag of the specified type and visibility to a feed element.
- [addFlagToFeedElement\(`communityId`, `feedElementId`, `visibility`, `note`\)](#)
Add a moderation flag of the specified visibility with a note to a feed element.
- [addFlagToFeedElement\(`communityId`, `feedElementId`, `type`, `visibility`, `note`\)](#)
Add a moderation flag of the specified type and visibility with a note to a feed element.



- **[getFlagsOnComment\(communityId, commentId, pageSize, pageParam\)](#)**
Get a page of moderation flags on a comment.
- **[getFlagsOnComment\(communityId, commentId, visibility, pageSize, pageParam\)](#)**
Get a page of moderation flags with specified visibility on a comment.
- **[getFlagsOnFeedElement\(communityId, feedElementId\)](#)**
Get the moderation flags on a feed element.
- **[getFlagsOnFeedElement\(communityId, feedElementId, visibility\)](#)**
Get the moderation flags with specified visibility on a feed element.
- **[getFlagsOnFeedElement\(communityId, feedElementId, pageParam, pageSize\)](#)**
Get a page of moderation flags on a feed element.
- **[getFlagsOnFeedElement\(communityId, feedElementId, visibility, pageSize, pageParam\)](#)**
Get a page of moderation flags with specified visibility on a feed element.
- **[removeFlagFromComment\(communityId, commentId, userId\)](#)**
Remove a moderation flag from a comment.
- **[removeFlagFromFeedElement\(communityId, feedElementId, userId\)](#)**
Remove a moderation flag from a feed element.

addFlagToComment(communityId, commentId)

Add a moderation flag to a comment.

API Version

29.0

Requires Chatter

Yes

Signature

```
public static ConnectApi.ModerationFlags addFlagToComment(String communityId, String commentId)
```

Parameters

communityId

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

commentId

Type: [String](#)

ID for a comment.

Return Value

Type: [ConnectApi.ModerationFlags](#)

Usage

To add a flag to a comment, Allow members to flag content must be selected for an Experience Cloud site.

addFlagToComment(communityId, commentId, visibility)

Add a moderation flag of the specified visibility to a comment.

API Version



Signature

```
public static ConnectApi.ModerationFlags addFlagToComment(String communityId, String commentId,
ConnectApi.CommunityFlagVisibility visibility)
```

Parameters

communityId

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

commentId

Type: [String](#)

ID for a comment.

visibility

Type: [ConnectApi.CommunityFlagVisibility](#)

Visibility behavior of a flag for various user types.

- `ModeratorsOnly` –The flag is visible only to users with moderation permissions on the flagged element or item.
- `SelfAndModerators` –The flag is visible to the creator of the flag and to users with moderation permissions on the flagged element or item.

Return Value

Type: [ConnectApi.ModerationFlags](#)

Usage

To add a flag to a comment, Allow members to flag content must be selected for an Experience Cloud site.

addFlagToComment(communityId, commentId, type)

Add a moderation flag of the specified type to a comment.

API Version

38.0

Requires Chatter

Yes

Signature

```
public static ConnectApi.ModerationFlags addFlagToComment(String communityId, String commentId,
ConnectApi.CommunityFlagType type)
```

Parameters

communityId

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

commentId

Type: [String](#)



Type of moderation flag.

- `FlagAsInappropriate` –Flag for inappropriate content.
- `FlagAsSpam` –Flag for spam.

If a type isn't specified, it defaults to `FlagAsInappropriate`.

Return Value

Type: [ConnectApi.ModerationFlags](#)

Usage

To add a flag to a comment, Allow members to flag content must be selected for an Experience Cloud site.

addFlagToComment(*communityId*, *commentId*, *note*)

Add a moderation flag with a note to a comment.

API Version

38.0

Requires Chatter

Yes

Signature

```
public static ConnectApi.ModerationFlags addFlagToComment(String communityId, String commentId, String note)
```

Parameters

communityId

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

commentId

Type: [String](#)

ID for a comment.

note

Type: [String](#)

A note of up to 4,000 characters about the flag.

Return Value

Type: [ConnectApi.ModerationFlags](#)

Usage

To add a flag to a comment, Allow members to flag content must be selected for an Experience Cloud site.

addFlagToComment(*communityId*, *commentId*, *type*, *note*)

Add a moderation flag of the specified type with a note to a comment.



Yes

Signature

```
public static ConnectApi.ModerationFlags addFlagToComment(String communityId, String commentId,
ConnectApi.CommunityFlagType type, String note)
```

Parameters

communityId

Type: [String](#)

ID for an Experience Cloud site, internal, or null.

commentId

Type: [String](#)

ID for a comment.

type

Type: [ConnectApi.CommunityFlagType](#)

Type of moderation flag.

- `FlagAsInappropriate`—Flag for inappropriate content.
- `FlagAsSpam`—Flag for spam.

If a type isn't specified, it defaults to `FlagAsInappropriate`.

note

Type: [String](#)

A note of up to 4,000 characters about the flag.

Return Value

Type: [ConnectApi.ModerationFlags](#)

Usage

To add a flag to a comment, Allow members to flag content must be selected for an Experience Cloud site.

addFlagToComment(communityId, commentId, type, visibility)

Add a moderation flag of the specified type and visibility to a comment.

API Version

38.0

Requires Chatter

Yes

Signature

```
public static ConnectApi.ModerationFlags addFlagToComment(String communityId, String commentId,
ConnectApi.CommunityFlagType type, ConnectApi.CommunityFlagVisibility visibility)
```

Parameters

communityId



Type: [String](#)

ID for a comment.

type

Type: [ConnectApi.CommunityFlagType](#)

Type of moderation flag.

- `FlagAsInappropriate` –Flag for inappropriate content.
- `FlagAsSpam` –Flag for spam.

If a type isn't specified, it defaults to `FlagAsInappropriate`.

visibility

Type: [ConnectApi.CommunityFlagVisibility](#)

Visibility behavior of a flag for various user types.

- `ModeratorsOnly` –The flag is visible only to users with moderation permissions on the flagged element or item.
- `SelfAndModerators` –The flag is visible to the creator of the flag and to users with moderation permissions on the flagged element or item.

Return Value

Type: [ConnectApi.ModerationFlags](#)

Usage

To add a flag to a comment, Allow members to flag content must be selected for an Experience Cloud site.

addFlagToComment(*communityId*, *commentId*, *visibility*, *note*)

Add a moderation flag of the specified visibility with a note to a comment.

API Version

38.0

Requires Chatter

Yes

Signature

```
public static ConnectApi.ModerationFlags addFlagToComment(String communityId, String commentId,
ConnectApi.CommunityFlagVisibility visibility, String note)
```

Parameters

communityId

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

commentId

Type: [String](#)

ID for a comment.

visibility

Type: [ConnectApi.CommunityFlagVisibility](#)



permissions on the flagged element or item.

note

Type: [String](#)

A note of up to 4,000 characters about the flag.

Return Value

Type: [ConnectApi.ModerationFlags](#)

Usage

To add a flag to a comment, Allow members to flag content must be selected for an Experience Cloud site.

addFlagToComment(*communityId*, *commentId*, *type*, *visibility*, *note*)

Add a moderation flag of the specified type and visibility with a note to a comment.

API Version

38.0

Requires Chatter

Yes

Signature

```
public static ConnectApi.ModerationFlags addFlagToComment(String communityId, String commentId,
ConnectApi.CommunityFlagType type, ConnectApi.CommunityFlagVisibility visibility, String note)
```

Parameters

communityId

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

commentId

Type: [String](#)

ID for a comment.

type

Type: [ConnectApi.CommunityFlagType](#)

Type of moderation flag.

- `FlagAsInappropriate`—Flag for inappropriate content.
- `FlagAsSpam`—Flag for spam.

If a type isn't specified, it defaults to `FlagAsInappropriate`.

visibility

Type: [ConnectApi.CommunityFlagVisibility](#)

Visibility behavior of a flag for various user types.

- `ModeratorsOnly`—The flag is visible only to users with moderation permissions on the flagged element or item.



Type: [String](#)

A note of up to 4,000 characters about the flag.

Return Value

Type: [ConnectApi.ModerationFlags](#)

Usage

To add a flag to a comment, Allow members to flag content must be selected for an Experience Cloud site.

addFlagToFeedElement(communityId, feedElementId)

Add a moderation flag to a feed element.

API Version

31.0

Requires Chatter

Yes

Signature

```
public static ConnectApi.ModerationCapability addFlagToFeedElement(String communityId, String feedElementId)
```

Parameters

communityId

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

feedElementId

Type: [String](#)

ID of the feed element.

Return Value

Type: [ConnectApi.ModerationCapability](#)

If the feed element doesn't support this capability, the return value is [ConnectApi.NotFoundException](#).

Usage

To add a flag to a feed element, Allow members to flag content must be selected for an Experience Cloud site.

addFlagToFeedElement(communityId, feedElementId, visibility)

Add a moderation flag of the specified visibility to a feed element.

API Version

31.0

Requires Chatter



`feedElementId, ConnectApi.CommunityFlagVisibility visibility)`

Parameters

communityId

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

feedElementId

Type: [String](#)

ID of the feed element.

visibility

Type: [ConnectApi.CommunityFlagVisibility](#)

Visibility behavior of a flag for various user types. One of these values:

- `ModeratorsOnly` –The flag is visible only to users with moderation permissions on the flagged element or item.
- `SelfAndModerators` –The flag is visible to the creator of the flag and to users with moderation permissions on the flagged element or item.

Return Value

Type: [ConnectApi.ModerationCapability](#)

If the feed element doesn't support this capability, the return value is [ConnectApi.NotFoundException](#).

Usage

To add a flag to a feed element, Allow members to flag content must be selected for an Experience Cloud site.

addFlagToFeedElement(*communityId*, *feedElementId*, *type*)

Add a moderation flag of the specified type to a feed element.

API Version

38.0

Requires Chatter

Yes

Signature

```
public static ConnectApi.ModerationCapability addFlagToFeedElement(String communityId, String feedElementId, ConnectApi.CommunityFlagType type)
```

Parameters

communityId

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

feedElementId

Type: [String](#)

ID of the feed element.



- `FlagAsInappropriate` –Flag for inappropriate content.
- `FlagAsSpam` –Flag for spam.

If a type isn't specified, it defaults to `FlagAsInappropriate`.

Return Value

Type: [ConnectApi.ModerationCapability](#)

Usage

To add a flag to a feed element, Allow members to flag content must be selected for an Experience Cloud site.

`addFlagToFeedElement(communityId, feedElementId, note)`

Add a moderation flag with a note to a feed element.

API Version

38.0

Requires Chatter

Yes

Signature

```
public static ConnectApi.ModerationCapability addFlagToFeedElement(String communityId, String feedElementId, String note)
```

Parameters

communityId

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

feedElementId

Type: [String](#)

ID of the feed element.

note

Type: [String](#)

A note of up to 4,000 characters about the flag.

Return Value

Type: [ConnectApi.ModerationCapability](#)

Usage

To add a flag to a feed element, Allow members to flag content must be selected for an Experience Cloud site.

`addFlagToFeedElement(communityId, feedElementId, type, note)`

Add a moderation flag of the specified type with a note to a feed element.

API Version



Signature

```
public static ConnectApi.ModerationCapability addFlagToFeedElement(String communityId, String feedElementId, ConnectApi.CommunityFlagType type, String note)
```

Parameters

communityId

Type: [String](#)

ID for an Experience Cloud site, internal, or null.

feedElementId

Type: [String](#)

ID of the feed element.

type

Type: [ConnectApi.CommunityFlagType](#)

Type of moderation flag.

- `FlagAsInappropriate`—Flag for inappropriate content.
- `FlagAsSpam`—Flag for spam.

If a type isn't specified, it defaults to `FlagAsInappropriate`.

note

Type: [String](#)

A note of up to 4,000 characters about the flag.

Return Value

Type: [ConnectApi.ModerationCapability](#)

Usage

To add a flag to a feed element, Allow members to flag content must be selected for an Experience Cloud site.

addFlagToFeedElement(communityId, feedElementId, type, visibility)

Add a moderation flag of the specified type and visibility to a feed element.

API Version

38.0

Requires Chatter

Yes

Signature

```
public static ConnectApi.ModerationCapability addFlagToFeedElement(String communityId, String feedElementId, ConnectApi.CommunityFlagType type, ConnectApi.CommunityFlagVisibility visibility)
```

Parameters

***feedElementId***Type: [String](#)

ID of the feed element.

typeType: [ConnectApi.CommunityFlagType](#)

Type of moderation flag.

- `FlagAsInappropriate` –Flag for inappropriate content.
- `FlagAsSpam` –Flag for spam.

If a type isn't specified, it defaults to `FlagAsInappropriate`.***visibility***Type: [ConnectApi.CommunityFlagVisibility](#)

Visibility behavior of a flag for various user types. One of these values:

- `ModeratorsOnly` –The flag is visible only to users with moderation permissions on the flagged element or item.
- `SelfAndModerators` –The flag is visible to the creator of the flag and to users with moderation permissions on the flagged element or item.

Return ValueType: [ConnectApi.ModerationCapability](#)**Usage**

To add a flag to a feed element, Allow members to flag content must be selected for an Experience Cloud site.

`addFlagToFeedElement(communityId, feedElementId, visibility, note)`

Add a moderation flag of the specified visibility with a note to a feed element.

API Version

38.0

Requires Chatter

Yes

Signature

```
public static ConnectApi.ModerationCapability addFlagToFeedElement(String communityId, String feedElementId, ConnectApi.CommunityFlagVisibility visibility, String note)
```

Parameters***communityId***Type: [String](#)ID for an Experience Cloud site, `internal`, or `null`.***feedElementId***Type: [String](#)

ID of the feed element.



- **ModeratorsOnly** –The flag is visible only to users with moderation permissions on the flagged element or item.
- **SelfAndModerators** –The flag is visible to the creator of the flag and to users with moderation permissions on the flagged element or item.

note

Type: [String](#)

A note of up to 4,000 characters about the flag.

Return Value

Type: [ConnectApi.ModerationCapability](#)

Usage

To add a flag to a feed element, Allow members to flag content must be selected for an Experience Cloud site.

addFlagToFeedElement(*communityId*, *feedElementId*, *type*, *visibility*, *note*)

Add a moderation flag of the specified type and visibility with a note to a feed element.

API Version

38.0

Requires Chatter

Yes

Signature

```
public static ConnectApi.ModerationCapability addFlagToFeedElement(String communityId, String feedElementId, ConnectApi.CommunityFlagType type, ConnectApi.CommunityFlagVisibility visibility, String note)
```

Parameters***communityId***

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

feedElementId

Type: [String](#)

ID of the feed element.

type

Type: [ConnectApi.CommunityFlagType](#)

Type of moderation flag.

- **FlagAsInappropriate** –Flag for inappropriate content.
- **FlagAsSpam** –Flag for spam.

If a type isn't specified, it defaults to `FlagAsInappropriate`.

visibility

Type: [ConnectApi.CommunityFlagVisibility](#)



permissions on the flagged element or item.

note

Type: [String](#)

A note of up to 4,000 characters about the flag.

Return Value

Type: [ConnectApi.ModerationCapability](#)

Usage

To add a flag to a feed element, Allow members to flag content must be selected for an Experience Cloud site.

getFlagsOnComment(*communityId*, *commentId*)

Get the moderation flags on a comment.

API Version

29.0

Requires Chatter

Yes

Signature

```
public static ConnectApi.ModerationFlags getFlagsOnComment(String communityId, String commentId)
```

Parameters

communityId

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

commentId

Type: [String](#)

ID for a comment.

Return Value

Type: [ConnectApi.ModerationFlags](#)

Usage

To get moderation flags, the context user must have the Moderate Experiences Feeds permission.

getFlagsOnComment(*communityId*, *commentId*, *visibility*)

Get the moderation flags with specified visibility on a comment.

API Version

30.0

Requires Chatter



```
commentId, ConnectApi.CommunityFlagVisibility visibility)
```

Parameters

communityId

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

commentId

Type: [String](#)

ID for a comment.

visibility

Type: [ConnectApi.CommunityFlagVisibility](#)

Visibility behavior of a flag for various user types.

- `ModeratorsOnly` –The flag is visible only to users with moderation permissions on the flagged element or item.
- `SelfAndModerators` –The flag is visible to the creator of the flag and to users with moderation permissions on the flagged element or item.

Return Value

Type: [ConnectApi.ModerationFlags](#)

Usage

To get moderation flags, the context user must have the Moderate Experiences Feeds permission.

getFlagsOnComment(*communityId*, *commentId*, *pageSize*, *pageParam*)

Get a page of moderation flags on a comment.

API Version

40.0

Requires Chatter

Yes

Signature

```
public static ConnectApi.ModerationFlags getFlagsOnComment(String communityId, String  
commentId, Integer pageSize, String pageParam)
```

Parameters

communityId

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

commentId

Type: [String](#)

ID for a comment.

pageSize



Type: [String](#)

Page token to use to view the page. Page tokens are returned as part of the response class, for example, `currentPageToken` or `nextPageToken`. If you pass in `null`, the first page is returned.

Return Value

Type: [ConnectApi.ModerationFlags](#)

Usage

To get moderation flags, the context user must have the Moderate Experiences Feeds permission.

getFlagsOnComment(*communityId*, *commentId*, *visibility*, *pageSize*, *pageParam*)

Get a page of moderation flags with specified visibility on a comment.

API Version

40.0

Requires Chatter

Yes

Signature

```
public static ConnectApi.ModerationFlags getFlagsOnComment(String communityId, String
commentId, ConnectApi.CommunityFlagVisibility visibility, Integer pageSize, String pageParam)
```

Parameters

communityId

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

commentId

Type: [String](#)

ID for a comment.

visibility

Type: [ConnectApi.CommunityFlagVisibility](#)

Visibility behavior of a flag for various user types.

- `ModeratorsOnly` –The flag is visible only to users with moderation permissions on the flagged element or item.
- `SelfAndModerators` –The flag is visible to the creator of the flag and to users with moderation permissions on the flagged element or item.

pageSize

Type: [Integer](#)

Specifies the number of items per page. Valid values are from 1 through 100. The default size is 0.

pageParam

Type: [String](#)

Page token to use to view the page. Page tokens are returned as part of the response class, for example, `currentPageToken` or `nextPageToken`. If you pass in `null`, the first page is returned.



To get moderation flags, the context user must have the Moderate Experiences Feeds permission.

getFlagsOnFeedElement(*communityId*, *feedElementId*)

Get the moderation flags on a feed element.

API Version

31.0

Requires Chatter

Yes

Signature

```
public static ConnectApi.ModerationCapability getFlagsOnFeedElement(String communityId, String feedElementId)
```

Parameters

communityId

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

feedElementId

Type: [String](#)

ID of the feed element.

Return Value

Type: [ConnectApi.ModerationCapability](#)

If the feed element doesn't support this capability, the return value is [ConnectApi.NotFoundException](#).

Usage

To get moderation flags, the context user must have the Moderate Experiences Feeds permission.

getFlagsOnFeedElement(*communityId*, *feedElementId*, *visibility*)

Get the moderation flags with specified visibility on a feed element.

API Version

31.0

Requires Chatter

Yes

Signature

```
public static ConnectApi.ModerationCapability getFlagsOnFeedElement(String communityId, String feedElementId, ConnectApi.CommunityFlagVisibility visibility)
```

Parameters

communityId

Type: [String](#)



ID of the feed element.

visibility

Type: [ConnectApi.CommunityFlagVisibility](#)

Visibility behavior of a flag for various user types. One of these values:

- **ModeratorsOnly** –The flag is visible only to users with moderation permissions on the flagged element or item.
- **SelfAndModerators** –The flag is visible to the creator of the flag and to users with moderation permissions on the flagged element or item.

Return Value

Type: [ConnectApi.ModerationCapability](#)

If the feed element doesn't support this capability, the return value is [ConnectApi.NotFoundException](#).

Usage

To get moderation flags, the context user must have the Moderate Experiences Feeds permission.

getFlagsOnFeedElement(*communityId*, *feedElementId*, *pageParam*, *pageSize*)

Get a page of moderation flags on a feed element.

API Version

40.0

Requires Chatter

Yes

Signature

```
public static ConnectApi.ModerationCapability getFlagsOnFeedElement(String communityId, String feedElementId, String pageParam, Integer pageSize)
```

Parameters

communityId

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

feedElementId

Type: [String](#)

ID of the feed element.

pageParam

Type: [String](#)

Page token to use to view the page. Page tokens are returned as part of the response class, for example, `currentPageToken` or `nextPageToken`. If you pass in `null`, the first page is returned.

pageSize

Type: [Integer](#)

Specifies the number of items per page. Valid values are from 1 through 100. The default size is 0.



[ConnectApi.NotFoundException](#).

Usage

To get moderation flags, the context user must have the Moderate Experiences Feeds permission.

getFlagsOnFeedElement(*communityId*, *feedElementId*, *visibility*, *pageSize*, *pageParam*)

Get a page of moderation flags with specified visibility on a feed element.

API Version

40.0

Requires Chatter

Yes

Signature

```
public static ConnectApi.ModerationCapability getFlagsOnFeedElement(String communityId, String feedElementId, ConnectApi.CommunityFlagVisibility visibility, Integer pageSize, String pageParam)
```

Parameters

communityId

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

feedElementId

Type: [String](#)

ID of the feed element.

visibility

Type: [ConnectApi.CommunityFlagVisibility](#)

Visibility behavior of a flag for various user types.

- `ModeratorsOnly`—The flag is visible only to users with moderation permissions on the flagged element or item.
- `SelfAndModerators`—The flag is visible to the creator of the flag and to users with moderation permissions on the flagged element or item.

pageSize

Type: [Integer](#)

Specifies the number of items per page. Valid values are from 1 through 100. The default size is 0.

pageParam

Type: [String](#)

Page token to use to view the page. Page tokens are returned as part of the response class, for example, `currentPageToken` or `nextPageToken`. If you pass in `null`, the first page is returned.

Return Value

Type: [ConnectApi.ModerationCapability](#)



To get moderation flags, the context user must have the Moderate Experiences Feeds permission.

removeFlagFromComment(*communityId*, *commentId*, *userId*)

Remove a moderation flag from a comment.

API Version

29.0

Requires Chatter

Yes

Signature

```
public static ConnectApi.ModerationFlags removeFlagFromComment(String communityId, String commentId, String userId)
```

Parameters

communityId

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

commentId

Type: [String](#)

ID for a comment.

userId

Type: [String](#)

ID of the context user for whom the flag is removed. Specify `null` to remove the flag for all users.

Return Value

Type: `Void`

Usage

To remove a moderation flag, the context user must have added the flag or must have the Moderate Experiences Feeds permission.

removeFlagFromFeedElement(*communityId*, *feedElementId*, *userId*)

Remove a moderation flag from a feed element.

API Version

31.0

Requires Chatter

Yes

Signature

```
public static void removeFlagFromFeedElement(String communityId, String feedElementId, String userId)
```



ID for an Experience Cloud site, internal, or null.

feedElementId

Type: [String](#)

ID of the feed element.

userId

Type: [String](#)

ID of the context user for whom the flag is removed. Specify `null` to remove the flag for all users.

Return Value

Type: [ConnectApi.ModerationCapability](#)

If the feed element doesn't support this capability, the return value is [ConnectApi.NotFoundException](#).

Usage

To remove a moderation flag, the context user must have added the flag or must have the Moderate Experiences Feeds permission.

Retired CommunityModeration Methods

These methods for `CommunityModeration` are retired.

- [addFlagToFeedItem\(communityId, feedItemId\)](#)
Add a moderation flag to a feed item.
- [addFlagToFeedItem\(communityId, feedItemId, visibility\)](#)
Add a moderation flag with specified visibility to a feed item.
- [getFlagsOnFeedItem\(communityId, feedItemId\)](#)
Get the moderation flags on a feed item.
- [getFlagsOnFeedItem\(communityId, feedItemId, visibility\)](#)
Get the moderation flags with specified visibility on a feed item.
- [removeFlagsOnFeedItem\(communityId, feedItemId, userId\)](#)
Remove a moderation flag from a feed item.

addFlagToFeedItem(communityId, feedItemId)

Add a moderation flag to a feed item.

API Version

29.0–31.0



Important

In version 32.0 and later, use [addFlagToFeedElement\(communityId, feedElementId\)](#).

Requires Chatter

Yes

Signature

```
public static ConnectApi.ModerationFlags addFlagToFeedItem(String communityId, String feedItemId)
```



ID for an Experience Cloud site, `internal`, or `null`.

feedItemId

Type: [String](#)

ID for a feed item.

Return Value

Type: [ConnectApi.ModerationFlags](#)

Usage

To add a flag to a feed item, Allow members to flag content must be selected for an Experience Cloud site.

addFlagToFeedItem(*communityId*, *feedItemId*, *visibility*)

Add a moderation flag with specified visibility to a feed item.

API Version

30.0–31.0



Important

In version 32.0 and later, use [addFlagToFeedElement\(*communityId*, *feedElementId*, *visibility*\)](#).

Requires Chatter

Yes

Signature

```
public static ConnectApi.ModerationFlags addFlagToFeedItem(String communityId, String feedItemId, ConnectApi.CommunityFlagVisibility visibility)
```

Parameters

communityId

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

feedItemId

Type: [String](#)

ID for a feed item.

visibility

Type: [ConnectApi.CommunityFlagVisibility](#)

Visibility behavior of a flag for various user types.

- **ModeratorsOnly**—The flag is visible only to users with moderation permissions on the flagged element or item.
- **SelfAndModerators**—The flag is visible to the creator of the flag and to users with moderation permissions on the flagged element or item.

Return Value



Cloud site.

getFlagsOnFeedItem(communityId, feedItemId)

Get the moderation flags on a feed item.

API Version

29.0–31.0



Important

In version 32.0 and later, use [getFlagsOnFeedElement\(communityId, feedElementId\)](#).

Requires Chatter

Yes

Signature

```
public static ConnectApi.ModerationFlags getFlagsOnFeedItem(String communityId, String feedItemId)
```

Parameters

communityId

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

feedItemId

Type: [String](#)

ID for a feed item.

Return Value

Type: [ConnectApi.ModerationFlags](#)

Usage

To get moderation flags, the context user must have the Moderate Experiences Feeds permission.

getFlagsOnFeedItem(communityId, feedItemId, visibility)

Get the moderation flags with specified visibility on a feed item.

API Version

30.0–31.0



Important

In version 32.0 and later, use [getFlagsOnFeedElement\(communityId, feedElementId, visibility\)](#).

Requires Chatter

Yes



Parameters

communityId

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

feedItemId

Type: [String](#)

ID for a feed item.

visibility

Type: [ConnectApi.CommunityFlagVisibility](#)

Visibility behavior of a flag for various user types. Values are:

- `ModeratorsOnly` –The flag is visible only to users with moderation permissions on the flagged element or item.
- `SelfAndModerators` –The flag is visible to the creator of the flag and to users with moderation permissions on the flagged element or item.

Return Value

Type: [ConnectApi.ModerationFlags](#)

Usage

To get moderation flags, the context user must have the `Moderate Experiences Feeds` permission.

removeFlagsOnFeedItem(*communityId*, *feedItemId*, *userId*)

Remove a moderation flag from a feed item.

API Version

29.0–31.0

Important

In version 32.0 and later, use [removeFlagFromFeedElement\(*communityId*, *feedElementId*, *userId*\)](#).

Requires Chatter

Yes

Signature

```
public static ConnectApi.ModerationFlags removeFlagsOnFeedItem(String communityId, String feedItemId, String userId)
```

Parameters

communityId

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

feedItemId

Type: [String](#)



ID of the context user for whom the flag is removed. Specify `null` to remove the flag for all users.

Return Value

Type: Void

Usage

To remove a moderation flag, the context user must have added the flag or must have the Moderate Experiences Feeds permission.

DID THIS ARTICLE SOLVE YOUR ISSUE?

Let us know so we can improve!

[Share your feedback](#)



DEVELOPER CENTERS

- [Heroku](#)
- [MuleSoft](#)
- [Tableau](#)
- [Commerce Cloud](#)
- [Lightning Design System](#)
- [Einstein](#)
- [Quip](#)

POPULAR RESOURCES

- [Documentation](#)
- [Component Library](#)
- [APIs](#)
- [Trailhead](#)
- [Sample Apps](#)
- [Podcasts](#)
- [AppExchange](#)

COMMUNITY

- [Trailblazer Community](#)
- [Events and Calendar](#)
- [Partner Community](#)
- [Blog](#)
- [Salesforce Admins](#)
- [Salesforce Architects](#)

© Copyright 2025 Salesforce, Inc. [All rights reserved.](#) Various trademarks held by their respective owners. Salesforce, Inc. Salesforce Tower, 415 Mission Street, 3rd Floor, San Francisco, CA 94105, United States

[Privacy Information](#) [Terms of Service](#) [Legal](#) [Use of Cookies](#) [Trust](#) [Cookie Preferences](#)

[Your Privacy Choices](#) [Responsible Disclosure](#) [Contact](#)