



CdpActivation Class

Get, create, update, and delete Data Cloud activations.

Namespace

[ConnectApi](#)

CdpActivation Methods

These methods are for `CdpActivation`. All methods are static.

- [getActivations\(\)](#)
Get activations.
- [getActivationsPaginated\(batchSize, offset, orderBy, filters\)](#)
Get a paginated list of activations.
- [createActivation\(input\)](#)
Create an activation.
- [deleteActivation\(activationId\)](#)
Delete an activation.
- [getActivation\(activationId\)](#)
Get an activation by ID.
- [updateActivation\(activationId, input\)](#)
Update an activation by ID.

getActivations()

Get activations.

API Version

60.0

Requires Chatter

No

Signature

```
public static ConnectApi.ActivationCollection getActivations()
```

Return Value

Type: [ConnectApi.ActivationCollection](#)

getActivationsPaginated(batchSize, offset, orderBy, filters)

Get a paginated list of activations.

API Version



Signature

```
public static ConnectApi.ActivationCollection getActivationsPaginated(Integer batchSize, Integer offset, String orderBy, String filters)
```

Parameters

batchSize

Type: [Integer](#)

Number of results to return. Values are from 1 through 200. If unspecified, the default value is 20.

offset

Type: [Integer](#)

Number of rows to skip before returning results. Must be greater than or equal to 0. If unspecified, no rows are skipped.

orderBy

Type: [String](#)

Specify `createdDate` to sort results by creation date. If unspecified, items are returned by ID in ascending order.

filters

Type: [String](#)

Filter the result set to a more narrow scope or specific type. These filters are supported:

- `name` (field name: `name`; description: name of the activation)
- `marketSegmentId` (field name: `segmentId`; description: segment ID of the activation)
- `activationTargetId` (field name: `activationTarget.id`; description: activation target ID of the activation)
- `activationRefreshType` (field name: `refreshType`; description: refresh type of the activation; example: `incremental`)
- `activationStatus` (field name: `status`; description: status of the activation, which accepts only the values in the status response field; example: `active`)

Return Value

Type: [ConnectApi.ActivationCollection](#)

createActivation(input)

Create an activation.

API Version

60.0

Requires Chatter

No

Signature

```
public static ConnectApi.Activation createActivation(ConnectApi.ActivationDefinitionInput input)
```

Parameters

input

Type: [ConnectApi.ActivationDefinitionInput](#)



deleteActivation(activationId)

Delete an activation.

API Version

Before deleting an activation, ensure there are no downstream systems that expect data from it. After you delete an activation, Data Cloud stops sending data to any downstream systems that are associated with the deleted activation. To identify the downstream system (activation target) that's associated with the activation, use the `getActivation(activationId)` resource. It provides the activation target details needed to evaluate the impact before deleting the activation.

Note

60.0

Requires Chatter

No

Signature

```
public static Void deleteActivation(String activationId)
```

Parameters

activationId

Type: [String](#)

The unique identifier (ID) or developer name of a specific activation target.

Return Value

Type: Void

getActivation(activationId)

Get an activation by ID.

API Version

60.0

Requires Chatter

No

Signature

```
public static ConnectApi.Activation getActivation(String activationId)
```

Parameters

activationId

Type: [String](#)

The unique identifier (ID) or developer name of a specific activation target.

Return Value

Type: [ConnectApi.Activation](#)



60.0

Requires Chatter

No

Signature

```
public static ConnectApi.Activation updateActivation(String activationId,
ConnectApi.ActivationDefinitionInput input)
```

Parameters

activationId

Type: [String](#)

The unique identifier (ID) or developer name of a specific activation target.

input

Type: [ConnectApi.ActivationDefinitionInput](#)

Input representation for an activation.

Return Value

Type: [ConnectApi.Activation](#)



DEVELOPER CENTERS

- [Heroku](#)
- [MuleSoft](#)
- [Tableau](#)
- [Commerce Cloud](#)
- [Lightning Design System](#)
- [Einstein](#)
- [Quip](#)

POPULAR RESOURCES

- [Documentation](#)
- [Component Library](#)
- [APIs](#)
- [Trailhead](#)
- [Sample Apps](#)
- [Podcasts](#)
- [AppExchange](#)

COMMUNITY

- [Trailblazer Community](#)
- [Events and Calendar](#)
- [Partner Community](#)
- [Blog](#)
- [Salesforce Admins](#)
- [Salesforce Architects](#)

© Copyright 2025 Salesforce, Inc. [All rights reserved.](#) Various trademarks held by their respective owners. Salesforce, Inc. Salesforce Tower, 415 Mission Street, 3rd Floor, San Francisco, CA 94105, United States

[Privacy Information](#) [Terms of Service](#) [Legal](#) [Use of Cookies](#) [Trust](#) [Cookie Preferences](#)

[Your Privacy Choices](#) [Responsible Disclosure](#) [Contact](#)