



Repricing Class

Perform functions related to repricing orders in Order Management.

Namespace

[ConnectApi](#)

Repricing Methods

These methods are for `Repricing`. All methods are static.

- [productDetails\(webstoreId, skuOrProductId, effectiveAccountId, currencyCode, locale\)](#)
Get details of a product in a web store.
- [searchProducts\(webstoreId, searchTerm, pageParam, pageSize, effectiveAccountId, facets\)](#)
Search products in a webstore.

`productDetails(webstoreId, skuOrProductId, effectiveAccountId, currencyCode, locale)`

Get details of a product in a web store.

API Version

55.0

Requires Chatter

No

Signature

```
public static ConnectApi.ProductDetailsOutputRepresentation productDetails(String webstoreId,
String skuOrProductId, String effectiveAccountId, String currencyCode, String locale)
```

Parameters

webstoreId

Type: [String](#)

ID of the WebStore.

skuOrProductId

Type: [String](#)

SKU or ID of the Product.

effectiveAccountId

Type: [String](#)

Effective Account ID. Required for B2B stores. For other stores, pass null.

***locale***Type: [String](#)

Locale. If you pass null, the default store value is used.

excludeAttributeSetInfoType: [String](#)

Specifies whether the attribute set information for the product is returned.

excludeMediaType: [String](#)

Specifies whether the media groups and default images of the product are returned.

excludeQuantityRuleType: [String](#)

Specifies whether the quantity rule information for the product is returned.

excludeVariationInfoType: [String](#)

Specifies whether the variation information for the product is returned.

excludePricesType: [String](#)

Specifies whether the prices for the product is returned.

Return ValueType: [ConnectApi.ProductDetailsOutputRepresentation](#)**searchProducts(webstoreId, searchTerm, pageParam, pageSize, effectiveAccountId, facets)**

Search products in a webstore.

API Version

59.0

Requires Chatter

No

Signature

```
public static ConnectApi.ProductSearchOutputRepresentation searchProducts(String webstoreId,
String searchTerm, Integer pageParam, Integer pageSize, String effectiveAccountId, String
facets)
```

Parameters***webstoreId***Type: [String](#)

ID of the webstore.

searchTermType: [String](#)



Maximum number of search results pages to return. If you don't specify a value, the default is 1.

pageSize

Type: [Integer](#)

Number of items per page. Valid values are from 1 through 100. If you don't specify a value, the default size is 20.

effectiveAccountId

Type: [String](#)

ID of the account for which the request is made. If unspecified, defaults to the account ID for the context user.

facets

Type: [String](#)

A list of facet names to filter the search. For example, ["size_medium", "color_red"] is encoded to WyJzaXp1X211ZG11bSIzICJjb2xvc19yZWQiXQ==

Return Value

Type: [ConnectApi.ProductSearchOutputRepresentation](#)

DID THIS ARTICLE SOLVE YOUR ISSUE?

Let us know so we can improve!

[Share your feedback](#)



DEVELOPER CENTERS

[Heroku](#)
[MuleSoft](#)
[Tableau](#)
[Commerce Cloud](#)
[Lightning Design System](#)
[Einstein](#)
[Quip](#)

POPULAR RESOURCES

[Documentation](#)
[Component Library](#)
[APIs](#)
[Trailhead](#)
[Sample Apps](#)
[Podcasts](#)
[AppExchange](#)

COMMUNITY

[Trailblazer Community](#)
[Events and Calendar](#)
[Partner Community](#)
[Blog](#)
[Salesforce Admins](#)
[Salesforce Architects](#)

© Copyright 2025 Salesforce, Inc. [All rights reserved](#). Various trademarks held by their respective owners. Salesforce, Inc.
Salesforce Tower, 415 Mission Street, 3rd Floor, San Francisco, CA 94105, United States

[Privacy Information](#) [Terms of Service](#) [Legal](#) [Use of Cookies](#) [Trust](#) [Cookie Preferences](#)

[Your Privacy Choices](#) [Responsible Disclosure](#) [Contact](#)