



Announcements Class

Access information about announcements and post announcements.


Namespace

ConnectApi

Usage

Use the `ConnectApi.Announcements` class to get, create, update, and delete announcements. Use an announcement to highlight information. Users can discuss, like, and post comments on announcements. Deleting the feed post deletes the announcement.

This image shows an announcement displayed in a group. Creating an announcement also creates a feed item with the announcement text.



An announcement displays in a designated location in the Salesforce UI until 11:59 p.m. on its expiration date, unless it's deleted or replaced by another announcement.

Announcements Methods



Delete an announcement.

- [getAnnouncement\(communityId, announcementId\)](#)
Get an announcement.
- [getAnnouncements\(communityId, parentId\)](#)
Get the first page of announcements.
- [getAnnouncements\(communityId, parentId, pageParam, pageSize\)](#)
Get a page of announcements.
- [postAnnouncement\(communityId, announcement\)](#)
Post an announcement.
- [updateAnnouncement\(communityId, announcementId, expirationDate\)](#)
Update the expiration date of an announcement.

deleteAnnouncement(communityId, announcementId)

Delete an announcement.

API Version

31.0

Requires Chatter

Yes

Signature

```
public static void deleteAnnouncement(String communityId, String announcementId)
```

Parameters

communityId

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

announcementId

Type: [String](#)

An announcement ID, which has a prefix of `OBT`.

Return Value

Type: `Void`

Usage

To get a list of announcements in a group, call [getAnnouncements\(communityId, parentId\)](#) or [getAnnouncements\(communityId, parentId, pageParam, pageSize\)](#).

To post an announcement to a group, call [postAnnouncement\(communityId, announcement\)](#).

getAnnouncement(communityId, announcementId)

Get an announcement.

API Version

31.0

Requires Chatter

Yes



communityId

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

announcementId

Type: [String](#)

An announcement ID, which has a prefix of OBT.

Return Value

Type: [ConnectApi.Announcement](#)

Usage

To get a list of announcements in a group, call [getAnnouncements\(communityId, parentId\)](#) or [getAnnouncements\(communityId, parentId, pageParam, pageSize\)](#).

To post an announcement to a group, call [postAnnouncement\(communityId, announcement\)](#).

getAnnouncements(communityId, parentId)

Get the first page of announcements.

API Version

36.0

Available to Guest Users

38.0

Requires Chatter

Yes

Signature

```
public static ConnectApi.AnnouncementPage getAnnouncements(String communityId, String parentId)
```

Parameters

communityId

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

parentId

Type: [String](#)

ID of the parent entity for the announcement, that is, a group ID when the announcement appears in a group.

Return Value

Type: [ConnectApi.AnnouncementPage](#)

getAnnouncements(communityId, parentId, pageParam, pageSize)

Get a page of announcements.

API Version

**Requires Chatter**

Yes

Signature

```
public static ConnectApi.AnnouncementPage getAnnouncements(String communityId, String parentId, Integer pageParam, Integer pageSize)
```

Parameters

communityId

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

parentId

Type: [String](#)

ID of the parent entity for the announcement, that is, a group ID when the announcement appears in a group.

pageParam

Type: [Integer](#)

Number of the page you want returned. Starts at 0. If you pass in `null` or 0, the first page is returned.

pageSize

Type: [Integer](#)

Specifies the number of announcements per page.

Return Value

Type: [ConnectApi.AnnouncementPage](#)

postAnnouncement(communityId, announcement)

Post an announcement.

API Version

36.0

Requires Chatter

Yes

Signature

```
public static ConnectApi.Announcement postAnnouncement(String communityId, ConnectApi.AnnouncementInput announcement)
```

Parameters

communityId

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

announcement

Type: [ConnectApi.AnnouncementInput](#)



updateAnnouncement(*communityId*, *announcementId*, *expirationDate*)

Update the expiration date of an announcement.

API Version

31.0

Requires Chatter

Yes

Signature

```
public static ConnectApi.Announcement updateAnnouncement(String communityId, String announcementId, Datetime expirationDate)
```

Parameters

communityId

Type: [String](#)

ID for an Experience Cloud site, `internal`, or `null`.

announcementId

Type: [String](#)

An announcement ID, which has a prefix of OBT.

expirationDate

Type: [Datetime](#)

The Salesforce UI displays an announcement until 11:59 p.m. on this date unless another announcement is posted first. The Salesforce UI ignores the time value in the `expirationDate`. However, you can use the time value to create your own display logic in your own UI.

Return Value

Type: [ConnectApi.Announcement](#)

Usage

To get a list of announcements in a group, call [getAnnouncements\(*communityId*, *parentId*\)](#) or [getAnnouncements\(*communityId*, *parentId*, *pageParam*, *pageSize*\)](#).

To post an announcement to a group, call [postAnnouncement\(*communityId*, *announcement*\)](#).





- Einstein
Quip
- Podcasts
AppExchange
- Salesforce Architects

© Copyright 2025 Salesforce, Inc. [All rights reserved.](#) Various trademarks held by their respective owners. Salesforce, Inc. Salesforce Tower, 415 Mission Street, 3rd Floor, San Francisco, CA 94105, United States

- [Privacy Information](#)
- [Terms of Service](#)
- [Legal](#)
- [Use of Cookies](#)
- [Trust](#)
- [Cookie Preferences](#)
- [Your Privacy Choices](#)
- [Responsible Disclosure](#)
- [Contact](#)