



EinsteinLLM Class

Get a list of prompt templates and generate LLM responses for prompt templates.

Namespace

[ConnectApi](#)

EinsteinLLM Methods

These methods are for `EinsteinLLM`. All methods are static.

- [generateMessagesForPromptTemplate\(promptTemplateDevName, promptTemplateGenerationsInput\)](#)
Generates a response using the specified prompt template and input parameters.
- [getPromptTemplates\(query, sortBy, offset, pageLimit, fields, type, relatedEntity, isActive\)](#)
Get a list of prompt templates using the specified filters.

`generateMessagesForPromptTemplate(promptTemplateDevName, promptTemplateGenerationsInput)`

Generates a response using the specified prompt template and input parameters.

API Version

60.0

Requires Chatter

No

Signature

```
public static ConnectApi.EinsteinPromptTemplateGenerationsRepresentation  
generateMessagesForPromptTemplate(String promptTemplateDevName,  
ConnectApi.EinsteinPromptTemplateGenerationsInput promptTemplateGenerationsInput)
```

Parameters

`promptTemplateDevName`

Type: [String](#)

Developer name or ID of a prompt template record.

`promptTemplateGenerationsInput`

Type: [ConnectApi.EinsteinPromptTemplateGenerationsInput](#)

Input for generating a response using the specified prompt template.

Return Value

Type: [ConnectApi.EinsteinPromptTemplateGenerationsRepresentation](#)



```
// Create input
ConnectApi.EinsteinPromptTemplateGenerationsInput promptGenerationsInput = new ConnectApi.EinsteinPromptTemplateGenerationsInput();
promptGenerationsInput.isPreview = false;

// Build input map
Map<String, ConnectApi.WrappedValue> valueMap = new Map<String, ConnectApi.WrappedValue>();

Map<String, String> recipientEntityRecordIdMap = new Map<String, String>();
recipientEntityRecordIdMap.put('id', '00Qxx000002ToPvEAK');

Map<String, String> senderEntityRecordIdMap = new Map<String, String>();
senderEntityRecordIdMap.put('id', '005xx000001XiWLAA0');

ConnectApi.WrappedValue recipientEntityWrappedValue = new ConnectApi.WrappedValue();
recipientEntityWrappedValue.value = recipientEntityRecordIdMap;

ConnectApi.WrappedValue senderEntityWrappedValue = new ConnectApi.WrappedValue();
senderEntityWrappedValue.value = senderEntityRecordIdMap;

valueMap.put('Input:Account', recipientEntityWrappedValue);
valueMap.put('Input:Recipient', recipientEntityWrappedValue);
valueMap.put('Input:Sender', senderEntityWrappedValue);

promptGenerationsInput.inputParams = valueMap;

// Set additional configuration values
promptGenerationsInput.additionalConfig = new ConnectApi.EinsteinLlmAdditionalConfigInput();
promptGenerationsInput.additionalConfig.applicationName = 'PromptTemplateGenerationsInvocation';

// Call the service
ConnectApi.EinsteinPromptTemplateGenerationsRepresentation generationsOutput =
ConnectApi.EinsteinLLM.generateMessagesForPromptTemplate('0hfxx000000KTNA2', promptGenerationsInput);

// Consume response
System.debug('Prompt Testing: ' + generationsOutput.prompt);
```

getPromptTemplates(query, sortBy, offset, pageLimit, fields, type, relatedEntity, isActive)

Get a list of prompt templates using the specified filters.

API Version

62.0

Requires Chatter

No

Signature

```
public static ConnectApi.EinsteinPromptRecordCollectionOutputRepresentation
getPromptTemplates(String query, String sortBy, Integer offset, Integer pageLimit, List<String>
fields, String type, String relatedEntity, Boolean isActive)
```

Parameters

query

Type: [String](#)

User-entered search string. If null, all prompt template records are returned.

sortBy

**offset**Type: [Integer](#)

Used for pagination. Number of rows to skip between returned prompt template records. The default value is 0.

pageLimitType: [Integer](#)

Used for pagination. Maximum number of prompt template records returned per page. The default value is 50.

fieldsType: [List<String>](#)

Comma-separated list of prompt template record fields to return, such as `createdDate`. If `null`, all fields are returned.

typeType: [String](#)

Prompt template type to filter records by, such as `einstein_gpt__salesEmail`. If `null`, records of all types are returned.

relatedEntityType: [String](#)

Related entity to filter records by, such as `Contact`. If `null`, all records with all related entities are returned.

isActiveType: [Boolean](#)

Specifies whether to return active prompt templates only. The default is `false`.

Return ValueType: [ConnectApi.EinsteinPromptRecordCollectionOutputRepresentation](#)**Usage**

To get a list of prompt templates, you must have Einstein Generative AI enabled and the Execute Prompt Templates user permission.

Example

```

ConnectApi.EinsteinPromptRecordCollectionOutputRepresentation promptTemplateList = Connect

// Get information from the prompt templates in the list
if (promptTemplateList != null && promptTemplateList.promptRecords != null) {
    for (ConnectApi.EinsteinPromptRecordRepresentation promptTemplate : promptTemplateList
        System.debug('Prompt Template ID: ' + promptTemplate.id);
        for (String fieldName : promptTemplate.fields.keySet()) {
            System.debug('Field Name: ' + fieldName + ', Value: ' + promptTemplate.fields.
        }
    }
} else {
    System.debug('No prompt templates found.');
```



DEVELOPER CENTERS

- Heroku
- MuleSoft
- Tableau
- Commerce Cloud
- Lightning Design System
- Einstein
- Quip

POPULAR RESOURCES

- Documentation
- Component Library
- APIs
- Trailhead
- Sample Apps
- Podcasts
- AppExchange

COMMUNITY

- Trailblazer Community
- Events and Calendar
- Partner Community
- Blog
- Salesforce Admins
- Salesforce Architects

© Copyright 2025 Salesforce, Inc. [All rights reserved.](#) Various trademarks held by their respective owners. Salesforce, Inc. Salesforce Tower, 415 Mission Street, 3rd Floor, San Francisco, CA 94105, United States

[Privacy Information](#) [Terms of Service](#) [Legal](#) [Use of Cookies](#) [Trust](#) [Cookie Preferences](#)

[Your Privacy Choices](#) [Responsible Disclosure](#) [Contact](#)