



PaymentsHttp Class

Makes an HTTP request to start the interaction with the payment gateway.

Namespace

[CommercePayments](#)

Usage

You must specify the `CommercePayments` namespace when creating an instance of this class. The constructor of this class takes no arguments. For example:

```
CommercePayments.PaymentsHttp payhttp = new CommercePayments.PaymentsHttp();
```

- [PaymentsHttp Methods](#)
- [PaymentsHttp Constructors](#)

PaymentsHttp Methods

The following are methods for `PaymentsHttp`. All methods are instance methods.

- [send\(Request\)](#)
Sends an `HttpRequest` and returns the response.

send(Request)

Sends an `HttpRequest` and returns the response.

Signature

```
global HttpResponse send(HttpRequest request)
```

Parameters

request

Type: [System.HttpRequest](#)

Return Value

Type: [System.HttpResponse](#)

PaymentsHttp Constructors

The following are constructors for `PaymentsHttp`.

- [PaymentsHttp\(\)](#)
Initiates an HTTP request and response.

PaymentsHttp()

Initiates an HTTP request and response.



DID THIS ARTICLE SOLVE YOUR ISSUE?
Let us know so we can improve!

Share your feedback



DEVELOPER CENTERS

- Heroku
- MuleSoft
- Tableau
- Commerce Cloud
- Lightning Design System
- Einstein
- Quip

POPULAR RESOURCES

- Documentation
- Component Library
- APIs
- Trailhead
- Sample Apps
- Podcasts
- AppExchange

COMMUNITY

- Trailblazer Community
- Events and Calendar
- Partner Community
- Blog
- Salesforce Admins
- Salesforce Architects

© Copyright 2025 Salesforce, Inc. [All rights reserved.](#) Various trademarks held by their respective owners. Salesforce, Inc. Salesforce Tower, 415 Mission Street, 3rd Floor, San Francisco, CA 94105, United States

[Privacy Information](#) [Terms of Service](#) [Legal](#) [Use of Cookies](#) [Trust](#) [Cookie Preferences](#)
[✔✕ Your Privacy Choices](#) [Responsible Disclosure](#) [Contact](#)