



CalculateTaxResponse Class

Sets the values of the tax transaction following a response from the external tax engine. Extends the [AbstractTransactionResponse](#) class and is the top-level response class.

Namespace

CommerceTax

Example

```
if(requestType == commercetax.RequestType.CalculateTax){
    commercetax.calculatetaxtype type = request.taxtype;
    String docCode='';
    if(request.DocumentCode == 'simulateEmptyDocumentCode')
        docCode = '';
    else if(request.DocumentCode != null)
        docCode =request.DocumentCode;
    else if(request.ReferenceEntityId != null) docCode = request.ReferenceEntityId;
    else docCode = String.valueOf(getRandomInteger(0,2147483647));
    commercetax.CalculateTaxResponse response = new commercetax.CalculateTaxResponse();
    if(request.isCommit == true) {
        response.setStatus(commercetax.TaxTransactionStatus.Committed);
    } else {
        response.setStatus(commercetax.TaxTransactionStatus.Uncommitted);
    }
    response.setDocumentCode(docCode);
    response.setReferenceDocumentCode(request.referenceDocumentCode);
    response.setTaxType(type);
    response.setStatusDescription('statusDescription');
    if(request.sellerDetails.code == 'testSellerCode') {
        response.setDescription('SellerCode fetched from TaxEngine entity');
    }
    else {
        response.setDescription('description');
    }
    response.setEffectiveDate(system.now());
    if(request.transactionDate == null) {
        response.setTransactionDate(system.now());
    } else {
        response.setTransactionDate(request.transactionDate);
    }
    if(request.taxTransactionType == null) {
        response.setTaxTransactionType(commercetax.TaxTransactionType.Debit);
    } else {
        response.setTaxTransactionType(request.taxTransactionType);
    }
    if(request.currencyIsoCode == null || request.currencyIsoCode == '') {
        response.setCurrencyIsoCode('USD');
    } else {
        response.setCurrencyIsoCode(request.currencyIsoCode);
    }
    response.setReferenceEntityId(request.ReferenceEntityId);
}
```

- [CalculateTaxResponse Methods](#)

Learn more about the available methods with the `CalculateTaxResponse` class.



- **[setAddresses\(addresses\)](#)**
Sets the value of the Addresses field using the addresses contained in an instance of the [AddressesResponse](#) class.
- **[setAmountDetails\(amountDetails\)](#)**
Sets the value of the AmountDetails field using an instance of [AmountDetailsResponse](#).
- **[setCurrencyIsoCode\(currencyIsoCode\)](#)**
Sets the value of the CurrencyIsoCode field of the [CalculateTaxResponse](#) object.
- **[setDescription\(dscptn\)](#)**
Sets the value of the Description field of the [CalculateTaxResponse](#) object.
- **[setDocumentCode\(documentCode\)](#)**
Sets the value of the DocumentCode field of the [CalculateTaxResponse](#) object.
- **[setEffectiveDate\(effectiveDate\)](#)**
Sets the value of the EffectiveDate field of the [CalculateTaxResponse](#) object.
- **[setLineItems\(lineItems\)](#)**
Sets the value of the LineItems field of the [CalculateTaxResponse](#) object.
- **[setReferenceDocumentCode\(referenceDocumentCode\)](#)**
Sets the value of the ReferenceDocumentCode field of the [CalculateTaxResponse](#) object.
- **[setReferenceEntityId\(referenceEntityId\)](#)**
Sets the value of the ReferenceEntityId field of the [CalculateTaxResponse](#) object.
- **[setStatus\(status\)](#)**
Sets the value of the Status field of the [CalculateTaxResponse](#) object.
- **[setStatusDescription\(statusDescription\)](#)**
Sets the value of the StatusDescription field of the [CalculateTaxResponse](#) object.
- **[setTaxTransactionId\(taxTrxnId\)](#)**
Sets the value of the TaxTransactionId field of the [CalculateTaxResponse](#) object.
- **[setTaxTransactionType\(taxTransactionType\)](#)**
Sets the value of the TaxTransactionType field of the [CalculateTaxResponse](#) object.
- **[setTaxType\(taxType\)](#)**
Sets the value of the TaxType field of the [CalculateTaxResponse](#) object.
- **[setTransactionDate\(transactionDate\)](#)**
Sets the value of the TransactionDate field of the [CalculateTaxResponse](#) object.

setAddresses(addresses)

Sets the value of the Addresses field using the addresses contained in an instance of the [AddressesResponse](#) class.

Signature

```
global void setAddresses(commercetax.AddressesResponse addresses)
```

Parameters

addresses

Type: [AddressesResponse](#)

Contains Ship To, Ship From, and Sold To addresses.

Return Value

Type: void

setAmountDetails(amountDetails)

Sets the value of the AmountDetails field using an instance of [AmountDetailsResponse](#).



amountDetails

Type: [AmountDetailsResponse](#)

The tax amount details for a line item on which tax was calculated.

Return Value

Type: void

setCurrencyIsoCode(currencyIsoCode)

Sets the value of the CurrencyIsoCode field of the `CalculateTaxResponse` object.

Signature

```
global void setCurrencyIsoCode(String currencyIsoCode)
```

Parameters

currencyIsoCode

Type: [String](#)

Three-letter ISO 4217 currency code associated with a tax object.

Return Value

Type: void

setDescription(dscptn)

Sets the value of the Description field of the `CalculateTaxResponse` object.

Signature

```
global void setDescription(String dscptn)
```

Parameters

dscptn

Type: [String](#)

Optional description for providing more information about the calculate tax response.

Return Value

Type: void

setDocumentCode(documentCode)

Sets the value of the DocumentCode field of the `CalculateTaxResponse` object.

Signature

```
global void setDocumentCode(String documentCode)
```

Parameters

documentCode

Type: [String](#)

Code for a tax document that's created by the tax engine for the calculation process.



setEffectiveDate(effectiveDate)

Sets the value of the EffectiveDate field of the `CalculateTaxResponse` object.

Signature

```
global void setEffectiveDate(Datetime effectiveDate)
```

Parameters

effectiveDate

Type: [Datetime](#)

The date a tax calculation action takes effect. This parameter is optional and is provided only for recordkeeping purpose. Additionally, this parameter is used to determine the tax rates or rules and overrides the transaction date. For example, if the tax calculation request is placed on January 3 and the transaction date is January 1, you can set the effective date as January 1.

Return Value

Type: void

setLineItems(lineItems)

Sets the value of the LineItems field of the `CalculateTaxResponse` object.

Signature

```
global void setLineItems(List<commercetax.LineItemResponse> lineItems)
```

Parameters

lineItems

Type: List<[LineItemResponse](#)>

Response object that the tax adapter populates from the response of the external tax engine.

Return Value

Type: void

setReferenceDocumentCode(referenceDocumentCode)

Sets the value of the ReferenceDocumentCode field of the `CalculateTaxResponse` object.

Signature

```
global void setReferenceDocumentCode(String referenceDocumentCode)
```

Parameters

referenceDocumentCode

Type: [String](#)

Code for a reference document used in the tax calculation process.

Return Value

Type: void

setReferenceEntityId(referenceEntityId)

Sets the value of the ReferenceEntityId field of the `CalculateTaxResponse` object.



referenceEntityId

Type: [String](#)

ID of an entity related to the line items submitted for tax calculation. For example, if order items were sent for tax calculation, you could use the ID of their parent order.

Return Value

Type: void

setStatus(status)

Sets the value of the Status field of the `CalculateTaxResponse` object.

Signature

```
global void setStatus(commercetax.TaxTransactionStatus status)
```

Parameters

status

Type: [TaxTransactionStatus](#)

Indicates whether a tax transaction has been committed.

Return Value

Type: void

setStatusDescription(statusDescription)

Sets the value of the StatusDescription field of the `CalculateTaxResponse` object.

Signature

```
global void setStatusDescription(String statusDescription)
```

Parameters

statusDescription

Type: [String](#)

Optional value for providing more information about a tax transaction's status.

Return Value

Type: void

setTaxTransactionId(taxTrxnId)

Sets the value of the TaxTransactionId field of the `CalculateTaxResponse` object.

Signature

```
public void setTaxTransactionId(String taxTrxnId)
```

Parameters

taxTrxnId

Type: [String](#)



Type: void

setTaxTransactionType(taxTransactionType)

Sets the value of the TaxTransactionType field of the CalculateTaxResponse object.

Signature

```
global void setTaxTransactionType(commercetax.TaxTransactionType taxTransactionType)
```

Parameters

taxTransactionType

Type: [TaxTransactionType](#)

Whether the tax transaction was for a credit or debit transaction.

Return Value

Type: void

setTaxType(taxType)

Sets the value of the TaxType field of the CalculateTaxResponse object.

Signature

```
global void setTaxType(commercetax.CalculateTaxType taxType)
```

Parameters

taxType

Type: [CalculateTaxType](#)

Indicates whether a tax calculation request is for estimated or actual tax.

Return Value

Type: void

setTransactionDate(transactionDate)

Sets the value of the TransactionDate field of the CalculateTaxResponse object.

Signature

```
global void setTransactionDate(Datetime transactionDate)
```

Parameters

transactionDate

Type: [Datetime](#)

The date that the tax transaction occurred.

Return Value

Type: void

DID THIS ARTICLE SOLVE YOUR ISSUE?

Let us know so we can improve!

[Share your feedback](#)



DEVELOPER CENTERS

- Heroku
- MuleSoft
- Tableau
- Commerce Cloud
- Lightning Design System
- Einstein
- Quip

POPULAR RESOURCES

- Documentation
- Component Library
- APIs
- Trailhead
- Sample Apps
- Podcasts
- AppExchange

COMMUNITY

- Trailblazer Community
- Events and Calendar
- Partner Community
- Blog
- Salesforce Admins
- Salesforce Architects

© Copyright 2025 Salesforce, Inc. [All rights reserved.](#) Various trademarks held by their respective owners. Salesforce, Inc. Salesforce Tower, 415 Mission Street, 3rd Floor, San Francisco, CA 94105, United States

[Privacy Information](#) [Terms of Service](#) [Legal](#) [Use of Cookies](#) [Trust](#) [Cookie Preferences](#)

[Your Privacy Choices](#) [Responsible Disclosure](#) [Contact](#)