



# BuyerGroupResponse Class

Contains constructors and methods to retrieve the buyer groups associated with a user.

## Namespace

CommerceBuyGrp

- [BuyerGroupResponse Constructors](#)
- [BuyerGroupResponse Methods](#)

## BuyerGroupResponse Constructors

The following are constructors for `BuyerGroupResponse`.

- [BuyerGroupResponse\(buyerGroupIds\)](#)  
Creates a new instance of the `CommerceBuyGrp.BuyerGroupResponse` class using the specified `buyerGroupIds` payload parameter.
- [BuyerGroupResponse\(\)](#)  
Creates a new instance of the `CommerceBuyGrp.BuyerGroupResponse` class.

### BuyerGroupResponse(buyerGroupIds)

Creates a new instance of the `CommerceBuyGrp.BuyerGroupResponse` class using the specified `buyerGroupIds` payload parameter.

#### Signature

```
public BuyerGroupResponse(Set<String> buyerGroupIds)
```

#### Parameters

##### *buyerGroupIds*

Type: Set<[String](#)>

List of buyer group IDs for a user.

### BuyerGroupResponse()

Creates a new instance of the `CommerceBuyGrp.BuyerGroupResponse` class.

#### Signature

```
public BuyerGroupResponse()
```

## BuyerGroupResponse Methods

The following are methods for `BuyerGroupResponse`.

- [getBuyerGroupIds\(\)](#)  
Retrieves a list of evaluated buyer group IDs assigned to a user.



## getBuyerGroupIds()

Retrieves a list of evaluated buyer group IDs assigned to a user.

### Signature

```
public Set<String> getBuyerGroupIds()
```

### Return Value

Type: Set<[String](#)>

## setBuyerGroupIds(buyerGroupIds)

Sets a list of evaluated buyer group IDs assigned to a user.

### Signature

```
public void setBuyerGroupIds(Set<String> buyerGroupIds)
```

### Parameters

#### *buyerGroupIds*

Type: Set<[String](#)>

### Return Value

Type: void

## setError(errorMessage, localizedErrorMessage)

Sets the error message to be returned when the evaluation of buyer group IDs fails.

### Signature

```
public void setError(String errorMessage, String localizedErrorMessage)
```

### Parameters

#### *errorMessage*

Type: [String](#)

The message stating the reason for the error.

#### *localizedErrorMessage*

Type: [String](#)

The translated error message.

### Return Value

Type: void

### DID THIS ARTICLE SOLVE YOUR ISSUE?

Let us know so we can improve!

[Share your feedback](#)



MuleSoft  
Tableau  
Commerce Cloud  
Lightning Design System  
Einstein  
Quip

Component Library  
APIs  
Trailhead  
Sample Apps  
Podcasts  
AppExchange

Events and Calendar  
Partner Community  
Blog  
Salesforce Admins  
Salesforce Architects

© Copyright 2025 Salesforce, Inc. [All rights reserved.](#) Various trademarks held by their respective owners. Salesforce, Inc. Salesforce Tower, 415 Mission Street, 3rd Floor, San Francisco, CA 94105, United States

[Privacy Information](#) [Terms of Service](#) [Legal](#) [Use of Cookies](#) [Trust](#) [Cookie Preferences](#)  
[✔✕ Your Privacy Choices](#) [Responsible Disclosure](#) [Contact](#)