

**Developers** 







Apex Reference Guide / CommercePayments Namespace / ReferencedRefundResponse Class

# ReferencedRefundResponse Class

The payment gateway adapter sends this response for the ReferencedRefund request type.

## **Namespace**

CommercePayments

## Usage

The constructor of this class takes no arguments. For example:

CommercePayments.ReferencedRefundResponse refr = new
CommercePayments.ReferencedRefundResponse();

· ReferencedRefundResponse Methods

## ReferencedRefundResponse Methods

The following are methods for  ${\tt ReferencedRefundResponse}\,.$ 

- setAmount(amount)
  - Sets the transaction amount. The value must be a postive number.
- setGatewayAvsCode(gatewayAvsCode)
   Sets the payment gateway's address verification system (AVS) code.
- setGatewayDate(gatewayDate)
  Sets the payment gateway's date.
- setGatewayMessage(gatewayMessage)
  Sets information or messages that the gateway returned.
- setGatewayReferenceDetails(gatewayReferenceDetails)
   Sets the payment gateway's reference details.
- setGatewayReferenceNumber(gatewayReferenceNumber)
  Sets the payment gateway's reference number.
- setGatewayResultCode(gatewayResultCode)
   Sets the payment gateway's result code.
- setGatewayResultCodeDescription(gatewayResultCodeDescription)
   Sets the payment gateway's result code description.
- setSalesforceResultCodeInfo(salesforceResultCodeInfo)
   Set the Salesforce result code info.

#### setAmount(amount)

Sets the transaction amount. The value must be a postive number.

#### Signature

global void setAmount(Double amount)

#### **Parameters**





#### **Return Value**

Type: void

## setGatewayAvsCode(gatewayAvsCode)

Sets the payment gateway's address verification system (AVS) code.

#### Signature

global void setGatewayAvsCode(String gatewayAvsCode)

#### **Parameters**

#### gatewayAvsCode

Type: String

Code sent by gateways that use an address verification system.

#### **Return Value**

Type: void

## setGatewayDate(gatewayDate)

Sets the payment gateway's date.

### Signature

global void setGatewayDate(Datetime gatewayDate)

#### **Parameters**

#### gatewayDate

Type: Datetime

Date and time of the gateway communication.

#### Return Value

Type: void

## setGatewayMessage(gatewayMessage)

Sets information or messages that the gateway returned.

#### Signature

 ${\tt global\ void\ setGatewayMessage}({\tt String\ gatewayMessage})$ 

#### **Parameters**

#### gatewayMessage

Type: String

Information or error messages returned by the gateway.

#### **Return Value**

Type: void

## setGatewayReferenceDetails(gatewayReferenceDetails)





#### **Parameters**

#### gatewayReferenceDetails

Type: String

Information about the gateway communication.

#### **Return Value**

Type: void

## setGatewayReferenceNumber(gatewayReferenceNumber)

Sets the payment gateway's reference number.

#### Signature

global void setGatewayReferenceNumber(String gatewayReferenceNumber)

#### **Parameters**

#### gatewayReferenceNumber

Type: String

Unique transaction ID created by the payment gateway.

#### **Return Value**

Type: void

## setGatewayResultCode(gatewayResultCode)

Sets the payment gateway's result code.

#### Signature

global void setGatewayResultCode(String gatewayResultCode)

#### **Parameters**

#### gatewayResultCode

Type: String

The gateway result code. Must be mapped to a Salesforce result code.

#### **Return Value**

Type: void

## setGatewayResultCodeDescription(gatewayResultCodeDescription)

Sets the payment gateway's result code description.

#### Signature

 $\verb|global void setGatewayResultCodeDescription(String gatewayResultCodeDescription)|\\$ 

#### **Parameters**

### gatewayResultCodeDescription

Type: String





Type: void

## setSalesforceResultCodeInfo(salesforceResultCodeInfo)

Set the Salesforce result code info.

#### Signature

 $\verb|global void setSales force Result CodeInfo (commerce payments. Sales force Result CodeInfo)| \\$ salesforceResultCodeInfo)

#### **Parameters**

#### salesforceResultCodeInfo

Type: commerce payments. Sales force Result Code Info

Describes the Salesforce result code value.

#### **Return Value**

Type: void

#### DID THIS ARTICLE SOLVE YOUR ISSUE?

Let us know so we can improve!

Share your feedback











## **DEVELOPER CENTERS**

MuleSoft Tableau Commerce Cloud Lightning Design System Einstein

Quip

Heroku

POPULAR RESOURCES

Documentation **Component Library** 

Trailhead Sample Apps **Podcasts** 

AppExchange

APIs

COMMUNITY

Trailblazer Commur **Events and Calenda** Partner Community

Blog

Salesforce Admins Salesforce Architect

© Copyright 2025 Salesforce, Inc. All rights reserved. Various trademarks held by their respective owners. Salesforce, Inc. Salesforce Tower, 415 Mission Street, 3rd Floor, San Francisco, CA 94105, United States

<u>Privacy Information</u> <u>Terms of Service</u> <u>Legal</u> <u>Use of Cookies</u> <u>Trust</u> <u>Cookie Preferences</u>

Your Privacy Choices Responsible Disclosure Contact