



CaptureResponse Class

The payment gateway adapter sends this response for the capture request type. This class extends `AbstractResponse` and inherits its methods.

Namespace

[CommercePayments](#)

Usage

You must specify the `CommercePayments` namespace when creating an instance of this class. The constructor of this class takes no arguments. For example:

```
CommercePayments.CaptureResponse ctr = new CommercePayments.CaptureResponse();
```

- [CaptureResponse Methods](#)

CaptureResponse Methods

The following are methods for `CaptureResponse`.

- [setAmount\(amount\)](#)
Sets the transaction amount.
- [setAsync\(async\)](#)
Indicates whether the payment gateway adapter used in the payment capture was asynchronous (`True`) or synchronous (`False`).
- [setGatewayAvsCode\(gatewayAvsCode\)](#)
Sets the payment gateway's AVS (address verification system) code.
- [setGatewayDate\(gatewayDate\)](#)
Sets the payment gateway's date.
- [setGatewayMessage\(gatewayMessage\)](#)
Sets information or messages that the gateway returned.
- [setGatewayReferenceDetails\(gatewayReferenceDetails\)](#)
Sets the payment gateway's reference details.
- [setGatewayReferenceNumber\(gatewayReferenceNumber\)](#)
Sets the payment gateway's reference number.
- [setGatewayResultCode\(gatewayResultCode\)](#)
Sets the payment gateway's result code.
- [setGatewayResultCodeDescription\(gatewayResultCodeDescription\)](#)
Sets the payment gateway's result code description.
- [setSalesforceResultCodeInfo\(salesforceResultCodeInfo\)](#)
Sets Salesforce result code information.

setAmount(amount)

Sets the transaction amount.

Signature



Type: [Double](#)

The amount to be debited or captured.

Return Value

Type: void

setAsync(async)

Indicates whether the payment gateway adapter used in the payment capture was asynchronous (True) or synchronous (False).

Signature

```
global void setAsync(Boolean async)
```

Parameters

async

Type: [Boolean](#)

Return Value

Type: void

setGatewayAvsCode(gatewayAvsCode)

Sets the payment gateway's AVS (address verification system) code.

Signature

```
global void setGatewayAvsCode(String gatewayAvsCode)
```

Parameters

gatewayAvsCode

Type: [String](#)

Payment gateways that use an AVS system return this code.

Return Value

Type: void

setGatewayDate(gatewayDate)

Sets the payment gateway's date.

Signature

```
global void setGatewayDate(Datetime gatewayDate)
```

Parameters

gatewayDate

Type: [Datetime](#)

The date that communication happened with the gateway.

Return Value

Type: void



```
global void setGatewayMessage(String gatewayMessage)
```

Parameters

gatewayMessage

Type: [String](#)

Information or error messages returned by the gateway.

Return Value

Type: void

setGatewayReferenceDetails(gatewayReferenceDetails)

Sets the payment gateway's reference details.

Signature

```
global void setGatewayReferenceDetails(String gatewayReferenceDetails)
```

Parameters

gatewayReferenceDetails

Type: [String](#)

Provides information about the gateway communication.

Return Value

Type: void

setGatewayReferenceNumber(gatewayReferenceNumber)

Sets the payment gateway's reference number.

Signature

```
global void setGatewayReferenceNumber(String gatewayReferenceNumber)
```

Parameters

gatewayReferenceNumber

Type: [String](#)

Unique transaction ID created by the payment gateway.

Return Value

Type: void

setGatewayResultCode(gatewayResultCode)

Sets the payment gateway's result code.

Signature

```
global void setGatewayResultCode(String gatewayResultCode)
```

Parameters

gatewayResultCode



Type: void

setGatewayResultCodeDescription(gatewayResultCodeDescription)

Sets the payment gateway's result code description.

Signature

```
global void setGatewayResultCodeDescription(String gatewayResultCodeDescription)
```

Parameters

gatewayResultCodeDescription

Type: [String](#)

Description of the GatewayResultCode. Provides additional context about the result code that the gateway returned.

Return Value

Type: void

setSalesforceResultCodeInfo(salesforceResultCodeInfo)

Sets Salesforce result code information.

Signature

```
global void setSalesforceResultCodeInfo(commercepayments.SalesforceResultCodeInfo salesforceResultCodeInfo)
```

Parameters

salesforceResultCodeInfo

[SalesforceResultCodeInfo](#) Type: commercepayments.SalesforceResultCodeInfo

Description of the Salesforce result code value.

Return Value

Type: void

DID THIS ARTICLE SOLVE YOUR ISSUE?

Let us know so we can improve!

[Share your feedback](#)



DEVELOPER CENTERS

[Heroku](#)

[MuleSoft](#)

POPULAR RESOURCES

[Documentation](#)

[Component Library](#)

COMMUNITY

[Trailblazer Community](#)

[Events and Calendar](#)



Quip

AppExchange

© Copyright 2025 Salesforce, Inc. [All rights reserved.](#) Various trademarks held by their respective owners. Salesforce, Inc. Salesforce Tower, 415 Mission Street, 3rd Floor, San Francisco, CA 94105, United States

[Privacy Information](#) [Terms of Service](#) [Legal](#) [Use of Cookies](#) [Trust](#) [Cookie Preferences](#)

 [Your Privacy Choices](#) [Responsible Disclosure](#) [Contact](#)