



# JurisdictionResponse Class

Stores details from the external tax engine about the tax jurisdiction used in the tax calculation process. A tax jurisdiction represents a government entity that collects tax.

## Namespace

[CommerceTax](#)

## Example

In this mock adapter example, the adapter sets the `TaxDetailsResponse.setJurisdiction()` method parameter to null if the request's document code indicates that the tax calculation didn't require any exceptions. Otherwise, it creates an instance of `JurisdictionResponse` and sets its address values. Because this code represents a mock adapter, the example defines the address parameters directly. In a standard implementation, the jurisdiction's setters receive values passed from the external tax engine.

```
if(request.DocumentCode == 'SetsNullForResponseWithoutException'){
    taxDetailsResponse.setJurisdiction(null);
}else{
    commercetax.JurisdictionResponse jurisdiction = new commercetax.JurisdictionResponse();
    jurisdiction.setCountry('country');
    jurisdiction.setRegion('region');
    jurisdiction.setName('name');
    jurisdiction.setStateAssignedNumber('stateAssignedNo');
    jurisdiction.setId('id');
    jurisdiction.setLevel('level');
    taxDetailsResponse.setJurisdiction(jurisdiction);
}
```

- [JurisdictionResponse Methods](#)

Learn more about the available methods with the `JurisdictionResponse` class.

## JurisdictionResponse Methods

Learn more about the available methods with the `JurisdictionResponse` class.

The `JurisdictionResponse` class includes these methods.

- [setCountry\(country\)](#)  
Sets the Country field of the `JurisdictionResponse` class.
- [setId\(id\)](#)  
Sets the ID field of the `JurisdictionResponse` class.
- [setLevel\(level\)](#)  
Sets the Level field of the `JurisdictionResponse` class.
- [setName\(name\)](#)  
Sets the Name field of the `JurisdictionResponse` class.
- [setRegion\(region\)](#)  
Sets the Region value of the `JurisdictionResponse` class.



Sets the Country field of the `JurisdictionResponse` class.

#### Signature

```
global void setCountry(String country)
```

#### Parameters

##### *country*

Type: [String](#)

The country of the tax jurisdiction entity's address.

#### Return Value

Type: void

### setId(id)

Sets the ID field of the `JurisdictionResponse` class.

#### Signature

```
global void setId(String id)
```

#### Parameters

##### *id*

Type: [String](#)

User-defined Id value used to reference the jurisdiction response.

#### Return Value

Type: void

### setLevel(level)

Sets the Level field of the `JurisdictionResponse` class.

#### Signature

```
global void setLevel(String level)
```

#### Parameters

##### *level*

Type: [String](#)

Level value used in the jurisdiction entity's address.

#### Return Value

Type: void

### setName(name)

Sets the Name field of the `JurisdictionResponse` class.

#### Signature

```
global void setName(String name)
```



Optional user-defined name field for referencing the jurisdiction response.

#### Return Value

Type: void

### setRegion(region)

Sets the Region value of the `JurisdictionResponse` class.

#### Signature

```
global void setRegion(String region)
```

#### Parameters

##### *region*

Type: [String](#)

Region value used in the tax jurisdiction entity's address.

#### Return Value

Type: void

### setStateAssignedNumber(stateAssignedNo)

Sets the StateAssignedNumber field of the `JurisdictionResponse` class.

#### Signature

```
global void setStateAssignedNumber(String stateAssignedNo)
```

#### Parameters

##### *stateAssignedNo*

Type: [String](#)

State assigned number value of the tax jurisdiction entity's address.

#### Return Value

Type: void

#### DID THIS ARTICLE SOLVE YOUR ISSUE?

Let us know so we can improve!

[Share your feedback](#)

#### DEVELOPER CENTERS

[Heroku](#)  
[MuleSoft](#)

#### POPULAR RESOURCES

[Documentation](#)  
[Component Library](#)

#### COMMUNITY

[Trailblazer Community](#)  
[Events and Calendar](#)



Quip

AppExchange

© Copyright 2025 Salesforce, Inc. [All rights reserved.](#) Various trademarks held by their respective owners. Salesforce, Inc. Salesforce Tower, 415 Mission Street, 3rd Floor, San Francisco, CA 94105, United States

[Privacy Information](#) [Terms of Service](#) [Legal](#) [Use of Cookies](#) [Trust](#) [Cookie Preferences](#)

☒ [Your Privacy Choices](#) [Responsible Disclosure](#) [Contact](#)