



Packaging Class

Contains a method for obtaining information about managed and unlocked packages.

Namespace

System

Usage

In the context of a package, use the `getCurrentPackageId` method to retrieve the `packageId`.

- [Packaging Methods](#)

Packaging Methods

The following are methods for `Packaging`.

- [getCurrentPackageId\(\)](#)
Returns the context `packageId` in managed and unlocked packages.

getCurrentPackageId()

Returns the context `packageId` in managed and unlocked packages.

Signature

```
public String getCurrentPackageId()
```

Return Value

Type: [String](#)

Usage

For managed packages, this method can be combined with [isCurrentUserLicensedForPackage\(packageId\)](#) to retrieve the `packageId` at runtime. Then, use `packageId` to confirm that the contextual user is licensed to use that managed package.

DID THIS ARTICLE SOLVE YOUR ISSUE?

Let us know so we can improve!

[Share your feedback](#)



Tableau
Commerce Cloud
Lightning Design System
Einstein
Quip

APIs
Trailhead
Sample Apps
Podcasts
AppExchange

Partner Community
Blog
Salesforce Admins
Salesforce Architects

© Copyright 2025 Salesforce, Inc. [All rights reserved.](#) Various trademarks held by their respective owners. Salesforce, Inc.
Salesforce Tower, 415 Mission Street, 3rd Floor, San Francisco, CA 94105, United States

[Privacy Information](#) [Terms of Service](#) [Legal](#) [Use of Cookies](#) [Trust](#) [Cookie Preferences](#)

[Your Privacy Choices](#) [Responsible Disclosure](#) [Contact](#)