



ConnectApi Enums

Enums specific to the ConnectApi namespace.

ConnectApi enums inherit all properties and methods of Apex enums.

Enums are not versioned. Enum values are returned in all API versions. Clients must handle values they don't understand gracefully.

Enum	Description
ConnectApi.ActionLinkExecutionsAllowed	Number of times an action link can be executed. <ul style="list-style-type: none">Once –An action link can be executed only one time across all users.OncePerUser –An action link can be executed only c time for each user.Unlimited –An action link can be executed an unlin number of times by each user. If the action link's actionType is Api or ApiAsync , you can't use this
ConnectApi.ActionLinkType	Type of action link. <ul style="list-style-type: none">Api –The action link calls a synchronous API at the a URL. Salesforce sets the status to SuccessfulStatu: FailedStatus based on the HTTP status code retur by your server.ApiAsync –The action link calls an asynchronous AP the action URL. The action remains in a PendingSta state until a third party makes a request to /connect/action-links/actionLinkId to set the : to SuccessfulStatus or FailedStatus when the asynchronous operation is complete.Download –The action link downloads a file from the action URL.Ui –The action link takes the user to a web page at t action URL.
ConnectApi.ActivationPlatformCustomerFileSource	Customer file source of the activation platform. <ul style="list-style-type: none">First_And_Third_PartyFirst_PartyThird_Party
ConnectApi.ActivationStatus	Status of the activation. <ul style="list-style-type: none">ActiveProcessingErrorInactive



	<ul style="list-style-type: none"> Processing Error Inactive
ConnectApi.ActivitySharingType	<p>Type of sharing operation.</p> <ul style="list-style-type: none"> Everyone –The activity is shared with everyone. MyGroups –The activity is shared only with a selection of the context user's groups. OnlyMe –The activity is private.
ConnectApi.ActivityType	<p>Type of activity.</p> <ul style="list-style-type: none"> All Event Task
ConnectApi.AdjustmentAmountScope	<p>Scope of the price adjustment amount.</p> <ul style="list-style-type: none"> Total –The adjustment scope is the total price. Unit –The adjustment scope is the unit price. UnproratedTotal –The adjustment scope is the unprorated total price.
ConnectApi.AdjustmentType	<p>How the price adjustment amount is calculated.</p> <ul style="list-style-type: none"> AdjustmentAmount –The adjustment is a fixed amount. AdjustmentPercentage –The adjustment is a percentage.
ConnectApi.ArticleTopicJobType	<p>Type of operation to perform on articles and topics.</p> <ul style="list-style-type: none"> AssignTopicsToArticle –Assign topics to articles in a data category. UnassignTopicsFromArticle –Unassign topics from articles in a data category.
ConnectApi.AsyncOperationStatus	<p>Asynchronous processing status of the cart, if asynchronous processing is enabled for the store.</p> <ul style="list-style-type: none"> Completed Errored Processing
ConnectApi.AudienceCriteriaOperator	<p>Operator used in the personalization audience criterion.</p> <ul style="list-style-type: none"> Contains Equal GreaterThan GreaterThanOrEqual Includes LessThan LessThanOrEqual



	<ul style="list-style-type: none"> StartsWith
ConnectApi.AudienceCriteriaType	<p>Type of personalization audience criterion.</p> <ul style="list-style-type: none"> Audience –Criterion based on audience. Default –Audience has no criteria. Domain –Criterion based on domain. FieldBased –Criterion based on object fields. GeoLocation –Criterion based on location. Permission –Criterion based on standard or custom permissions. Profile –Criterion based on profile.
ConnectApi.AudienceDMODeltaType	<p>Delta type of the activation.</p> <ul style="list-style-type: none"> A –ADDED D –DELETED E –EXISTING U –UPDATED
ConnectApi.BannerStyle	<p>Decorates a feed item with a color and set of icons.</p> <ul style="list-style-type: none"> Announcement –An announcement displays in a designated location in the Salesforce UI until 11:59 on its expiration date, unless it's deleted or replaced another announcement.
ConnectApi.BillingFrequency	<p>Billing frequency for a subscription.</p> <ul style="list-style-type: none"> Annual Monthly
ConnectApi.BotVersionActivationStatus	<p>Activation status of the bot version.</p> <ul style="list-style-type: none"> Active Inactive
ConnectApi.BundleType	<p>Type of bundle.</p> <ul style="list-style-type: none"> GenericBundle –A bundle that contains no additional information and is just a collection of feed elements TrackedChanges –A bundle that represents a collection of feed-tracked changes. The bundle includes summary information about the feed-tracked changes that make up the bundle.
ConnectApi.CalculatedInsightDefinitionTypeEnum	<p>Definition type of the calculated insight.</p> <ul style="list-style-type: none"> CALCULATED_METRIC CALCULATED_METRIC CALCULATED_METRIC



	<p>Estimated – Calculated tax represents the final taxed amount for the transaction.</p> <ul style="list-style-type: none">Estimated – Calculated tax represents only an estimated value before the transaction is finalized.
ConnectApi.CalloutStatus	<p>Indicates whether a named credential is enabled for callout</p> <ul style="list-style-type: none">DisabledEnabled
ConnectApi.CardCategory	<p>Indicates a credit card or debit card.</p> <ul style="list-style-type: none">CreditCardDebitCard
ConnectApi.CardType	<p>Credit card issuer.</p> <ul style="list-style-type: none">AmericanExpressDinersClubJCBMaestroMasterCardVisa
ConnectApi.CartItemSortOrder	<p>Sort order for items in a cart.</p> <ul style="list-style-type: none">CreatedDateAsc – Sorts by oldest creation date.CreatedDateDesc – Sorts by most recent creation date.NameAsc – Sorts by name in ascending alphabetical order (A–Z).NameDesc – Sorts by name in descending alphabetical order (Z–A).SalesPriceAsc – Sorts from lowest to highest negotiated price.SalesPriceDesc – Sorts from highest to lowest negotiated price.
ConnectApi.CartItemSubType	<p>Subtype of item in a cart.</p> <ul style="list-style-type: none">Bonus – A bonus product.Gift – A gift product.
ConnectApi.CartItemType	<p>Type of item in a cart.</p> <ul style="list-style-type: none">DeliveryChargeProduct
ConnectApi.CartMessageSeverity	<p>Severity of cart message.</p> <ul style="list-style-type: none">ErrorInfoWarning

`ConnectApi.CartStatus`

Status of the cart.

- **Active**—Cart is created and available for modification like adding or removing products or promotions.
- **Checkout**—Cart is in checkout. If the customer modifies the cart, the current checkout session is canceled.
- **Closed**—Checkout is complete and an order was created. The cart cannot be modified.
- **PendingClosed**—Cart is marked to be closed, but the request isn't completed yet. The cart can't be modified. This value is available in API version 57.0 and later.
- **PendingDelete**—Cart is marked for delete, but the request isn't completed yet. The cart can't be modified.
- **Processing**—Cart is processing. For example, taxes are being calculated. The cart can't be modified.

`ConnectApi.CartTaxType`

Tax type of the cart.

- **Automatic**—Automatic taxation policy.
- **Gross**—Gross taxation policy.
- **Net**—Net taxation policy.

`ConnectApi.CartType`

Type of cart.

- **Cart**—Cart created by a customer.
- **PayNowReadOnly**—Clone of a Template cart that the customer can check out with using the Pay Now feature.
- **Template**—Cart created by an internal user.

`ConnectApi.CaseActorType`

Type of user who made the comment.

- **Customer**—if a Chatter customer made the comment
- **CustomerService**—if a service representative made comment

`ConnectApi.CaseCommentEventType`

Event type of a comment in Case Feed.

- **NewInternal**—A case comment that has newly been marked Internal Only.
- **NewPublished**—A newly published case comment.
- **NewPublishedByCustomer**—A case comment by a customer that was newly published.
- **PublishExisting**—An existing case comment that was republished.
- **PublishExistingByCustomer**—An existing case comment by a customer that was republished.
- **UnpublishExistingByCustomer**—An existing case comment by a customer that was unpublished.
- **UnpublishExisting**—An existing case comment that was unpublished.



Unfortunately, this typo is in the code, not the documentation. Use this spelling in your code.

`ConnectApi.CdpIdentityResolutionConfigurationType`

Source object for an identity resolution ruleset.

- Account
- Individual

`ConnectApi.CdpIdentityResolutionMatchMethodType`

Match method for a match rule criterion.

- Exact –Exact match.
- ExactNormalized –Exact normalized match.
- Fuzzy –Fuzzy match with medium precision.
- FuzzyHigh –Fuzzy match with high precision.
- FuzzyLow –Fuzzy match with low precision.

`ConnectApi.CdpIdentityResolutionReconciliationRuleType`

Default reconciliation rule applied to fields in the object the reconciliation rule applies to.

- LastUpdated
- MostFrequent
- SourceSequence

`ConnectApi.CdpIdentityResolutionRunNowResultCode`

Result of an identity resolution ruleset job run.

- ExceededMaximumNumberOfSuccessfulRunsAllowedIn24Hours
- IdentityResolutionJobIsAlreadyRunning
- NoPendingChangesJobRunSkipped
- SuccessfullySubmittedIdentityResolutionJobRunRequest

`ConnectApi.CdpMLModelPredictionTypeEnum`

Type of the model prediction.

- BinaryClassification -Binary classification.
- Generic -Generic/unknown.
- MulticlassClassification -Multiclass classificatio
- Regression -Regression.

`ConnectApi.CdpMLPredictAggregateFunctionStatusEnum`

Status of the prediction aggregate function.

- Error
- Success

`ConnectApi.CdpMLPredictAggregateFunctionTypeEnum`

Type of the prediction aggregate function.

- Average
- Median
- Sum



	<ul style="list-style-type: none"> • Success
ConnectApi.CdpMlPredictTypeEnum	<p>Type of input data for the prediction.</p> <ul style="list-style-type: none"> • RawData -Raw data. • RecordOverrides -Record IDs with user-provided overrides. • Records -Record IDs.
ConnectApi.CommentType	<p>Type of comment.</p> <ul style="list-style-type: none"> • ContentComment –Comment holds a content capabi • TextComment –Comment contains only text.
ConnectApi.CommerceAddressSort	<p>Sort order for Commerce addresses.</p> <ul style="list-style-type: none"> • CreatedDateAsc –Sort in ascending order of create date. • CreatedDateDesc –Sort in descending order of create date. • NameAsc –Sort in ascending order of name. • NameDesc –Sort in descending order of name.
ConnectApi.CommerceSearchAttributeType	<p>Search attribute type.</p> <ul style="list-style-type: none"> • Custom • PricebookEntry • ProductAttribute • ProductCategory • Product2 • Standard
ConnectApi.CommerceSearchFacetDisplayType	<p>Display type of the facet.</p> <ul style="list-style-type: none"> • CategoryTree • DatePicker • MultiSelect • SingleSelect
ConnectApi.CommerceSearchFacetType	<p>Search facet type.</p> <ul style="list-style-type: none"> • DistinctValue • Range
ConnectApi.CommerceSearchGroupingOption	<p>Grouping option for search results.</p> <ul style="list-style-type: none"> • BestMatch –Search results are grouped by the best-match product of the variation group. • NoGrouping –Search results aren't grouped. • VariationParent –Search results are grouped by the variation parent.



	<ul style="list-style-type: none">Incremental
ConnectApi.CommerceSearchIndexCreationType	<div>Creation type of the index.</div> <ul style="list-style-type: none">ManualScheduled
ConnectApi.CommerceSearchIndexStatus	<div>Status of the index.</div> <ul style="list-style-type: none">CompletedFailedInProgress
ConnectApi.CommerceSearchIndexUsage	<div>Usage of the index.</div> <ul style="list-style-type: none">LiveOutOfUse
ConnectApi.CommerceSearchSortRuleDirection	<div>Direction of the sort rule.</div> <ul style="list-style-type: none">Ascending –Sorts in ascending alphanumeric order (0–9).Default –When no direction is defined, sorts by relevance.Descending –Sorts in descending alphanumeric order (A, 9–0).
ConnectApi.CommerceSearchSortRuleLabelSuffix	<div>Label suffix of the sort rule.</div> <ul style="list-style-type: none">Ascen –Label suffix for 'Asc'Ascending –Label suffix for 'Ascending'Az –Label suffix for 'A-Z'Descen –Label suffix for 'Desc'Descending –Label suffix for 'Descending'FewMany –Label suffix for 'Few-Many'HeavyLight –Label suffix for 'Heavy-Light'HighLow –Label suffix for 'High-Low'HighestLowest –Label suffix for 'Highest-Lowest'LightHeavy –Label suffix for 'Light-Heavy'LowHigh –Label suffix for 'Low-High'LowestHighest –Label suffix for 'Lowest-Highest'ManyFew –Label suffix for 'Many-Few'NewOld –Label suffix for 'New-Old'Newest –Label suffix for 'Newest'NewestOldest –Label suffix for 'Newest-Oldest'NineZero –Label suffix for '9-0'OldNew –Label suffix for 'Old-New'Oldest –Label suffix for 'Oldest'OldestNewest –Label suffix for 'Oldest-Newest'PriceDecreasing –Label suffix for '\$\$-\$'



	<ul style="list-style-type: none"> ThinThick –Label suffix for 'Thin-Thick' Za –Label suffix for 'Z-A' ZeroNine –Label suffix for '0-9'
ConnectApi.CommerceSearchSortRuleType	<p>Type of sort rule.</p> <ul style="list-style-type: none"> ProductAttributeBased –Sorts by product attribute fields. ProductBased –Sorts by product field data. Relevancy –Sorts by product and catalog term frequency. SortByPricebook –Sorts by product prices defined in a specified pricebook (version 55.0 and later).
ConnectApi.CommerceSearchTopProductType	<p>Type of the top product to return for each product group in search results.</p> <ul style="list-style-type: none"> VariationParent
ConnectApi.CommunityFlagReasonType	<p>Reason a post, comment, or file is flagged.</p> <ul style="list-style-type: none"> FlaggedByRule –Moderation rule flagged the item. FlaggedBySystem –Einstein flagged the item. FlaggedByUserAsInappropriate –User flagged the item as inappropriate. FlaggedByUserAsSpam –User flagged the item as spam.
ConnectApi.CommunityFlagType	<p>Type of moderation flag.</p> <ul style="list-style-type: none"> FlagAsInappropriate –Flag for inappropriate content. FlagAsSpam –Flag for spam.
ConnectApi.CommunityFlagVisibility	<p>Visibility behavior of a flag for various user types.</p> <ul style="list-style-type: none"> ModeratorsOnly –The flag is visible only to users with moderation permissions on the flagged element or item. SelfAndModerators –The flag is visible to the creator of the flag and to users with moderation permissions on the flagged element or item.
ConnectApi.CommunityStatus	<p>Status of the Experience Cloud site.</p> <ul style="list-style-type: none"> Live Inactive UnderConstruction
ConnectApi.CompressionFormatEnum	<p>Type of compression for the output.</p> <ul style="list-style-type: none"> Bzip2 Gzip None -No compression
ConnectApi.ConnectInsightUnitEnum	<p>Unit for an insight.</p> <ul style="list-style-type: none"> Count



	<ul style="list-style-type: none"> • Number • Percent
ConnectApi.ContactPointType	<p>Type of contact point.</p> <ul style="list-style-type: none"> • Email • Maid • Ott • Phone • Push • Subscriber_Key_Email • Subscriber_Key_Phone • WhatsApp
ConnectApi.ContactPointPref	<p>Type of contact point.</p> <ul style="list-style-type: none"> • ContactPointPrefAny • ContactPointPrefBusiness • ContactPointPrefPersonal • ContactPointPrefPrimary
ConnectApi.ContentHubAuthenticationProtocol	<p>Authentication protocol used for the repository.</p> <ul style="list-style-type: none"> • NoAuthentication –Repository doesn't require authentication. • OAuth –Repository uses OAuth authentication protocol. • Password –Repository uses user name and password authentication protocol.
ConnectApi.ContentHubDirectoryEntryType	<p>Type of directory entry.</p> <ul style="list-style-type: none"> • GroupEntry • UserEntry
ConnectApi.ContentHubExternalItemSharingType	<p>Sharing status for the external file.</p> <ul style="list-style-type: none"> • DomainSharing –File is shared with the domain. • PrivateSharing –File is private or shared only with individuals. • PublicSharing –File is publicly shared.
ConnectApi.ContentHubGroupType	<p>Type of group.</p> <ul style="list-style-type: none"> • Everybody –Group is public to everybody. • EverybodyInDomain –Group is public to everybody in same domain. • Unknown –Group type is unknown.
ConnectApi.ContentHubItemType	<p>Item types.</p> <ul style="list-style-type: none"> • Any –Includes files and folders. • FilesOnly –Includes files only.



<code>ConnectApi.ContentHubStreamSupport</code>	Support for content streaming. <ul style="list-style-type: none"><code>ContentStreamAllowed</code><code>ContentStreamNotAllowed</code><code>ContentStreamRequired</code>
<code>ConnectApi.ContentHubVariableType</code>	Data type of the value of the field. <ul style="list-style-type: none"><code>BooleanType</code><code>DateTimeType</code><code>DecimalType</code><code>HtmlType</code><code>IdType</code><code>IntegerType</code><code>StringType</code><code>UriType</code><code>XmlType</code>
<code>ConnectApi.ConversationApplicationIntegrationType</code>	Conversation application integration types. <ul style="list-style-type: none"><code>Api</code><code>Slack</code>
<code>ConnectApi.CreateCredentialAction</code>	Action to take when creating the credential. <ul style="list-style-type: none"><code>Refresh</code>
<code>ConnectApi.CredentialAuthenticationProtocol</code>	Authentication protocol of the external credential. <ul style="list-style-type: none"><code>AwsSv4</code><code>Basic</code><code>Custom</code><code>Jwt</code><code>OAuth</code>



	<ul style="list-style-type: none"> • <code>RolesAnywhere</code> –AWS Signature Version 4 with Identity and Access Management (IAM) Roles Anywhere.
<code>ConnectApi.CredentialAuthenticationStatus</code>	<p>Status of the credential authentication.</p> <ul style="list-style-type: none"> • <code>Configured</code> –Credential has all required credentials and at least one principal. • <code>NotConfigured</code> –Credential isn't configured. • <code>Unknown</code> –Credential status can't be determined because the authentication protocol is custom.
<code>ConnectApi.CredentialPrincipalType</code>	<p>Type of credential principal.</p> <ul style="list-style-type: none"> • <code>AwsStsPrincipal</code> • <code>NamedPrincipal</code> • <code>PerUserPrincipal</code>
<code>ConnectApi.CurrencyInfoDisplayTypeEnum</code>	<p>Display metadata type of the currency info.</p> <ul style="list-style-type: none"> • <code>IsoCode</code> –ISO code of the currency.
<code>ConnectApi.DataCategoryOperator</code>	<p>Data category operator.</p> <ul style="list-style-type: none"> • <code>Above</code> –Queries the data category and all of its parent categories. • <code>AboveOrBelow</code> –Queries the data category, all of its parent categories, and all of its subcategories. • <code>At</code> –Queries the data category. • <code>Below</code> –Queries the data category and all of its subcategories.
<code>ConnectApi.DataConnectorTypeEnum</code>	<p>Data connector type of the activation target.</p> <ul style="list-style-type: none"> • <code>AmazonS3</code> • <code>AzureBlob</code> • <code>DataCloud</code> • <code>GoogleCloudStorage</code> • <code>SalesforceMarketingCloud</code> • <code>Sftp</code>



	<ul style="list-style-type: none"> • Related
ConnectApi.DataExportAttributeType	<p>Type of activation attribute.</p> <ul style="list-style-type: none"> • Computed_Dimension • Computed_Measure • Model • Model_Related • Non_Aggregatable_Computed_Measure
ConnectApi.DataExportRefreshMode	<p>Refresh type of the activation.</p> <ul style="list-style-type: none"> • Full_Refresh • Incremental
ConnectApi.DataExportRunStatus	<p>Last publish status of the activation.</p> <ul style="list-style-type: none"> • Error • Partner_Error • Partner_Processing • Publishing • Queued • Segment_Error • Skipped • Success
ConnectApi.DatacloudUserType	<p>Type of user.</p> <ul style="list-style-type: none"> • Monthly –A user type that's assigned monthly point for purchasing Data.com records. Only the assigned can use monthly points. Points expire at the end of 1 month. Monthly is the default setting for DatacloudUserType. • Listpool –A user type that allows users to draw from pool of points to purchase Data.com records.
ConnectApi.DatacloudImportStatusTypeEnum	<p>Status of the import.</p> <ul style="list-style-type: none"> • Success –Indicates that selected records were added to the org's CRM. • Duplicate –Marks a record that is already in the org CRM. The API determines whether an org allows the addition of duplicate records in its CRM. • Error –Indicates that the selected records weren't added to the org's CRM.
ConnectApi.DataSpaceStatusEnum	<p>Status of the data space.</p> <ul style="list-style-type: none"> • Active –The data space is active. • Error –The data space has an error. • Processing –The data space is being processed.



	<p>DailyDigest –The email includes up to the 50 latest posts from the previous day.</p> <ul style="list-style-type: none"> WeeklyDigest –The email includes up to the 50 latest posts from the previous week.
<code>ConnectApi.EgressFileNameTypeEnum</code>	<p>Type of egress file name.</p> <ul style="list-style-type: none"> <code>Custom</code> <code>Predetermined</code>
<code>ConnectApi.EmailMessageAutomationType</code>	<p>Automation type of the email message.</p> <ul style="list-style-type: none"> <code>aiAssisted</code> –The email message was created with the assistance of AI. <code>aiAutomated</code> –The email message was created automatically by AI.
<code>ConnectApi.EmailMessageDirection</code>	<p>Direction of an email message on a case.</p> <ul style="list-style-type: none"> <code>Inbound</code> –An inbound message (sent by a customer) <code>Outbound</code> –An outbound message (sent to a customer or a support agent).
<code>ConnectApi.EmailMessageStatus</code>	<p>Status of an email message on a case.</p> <ul style="list-style-type: none"> <code>DraftStatus</code> <code>ForwardedStatus</code> <code>NewStatus</code> <code>ReadStatus</code> <code>RepliedStatus</code> <code>SentStatus</code>
<code>ConnectApi.ExtensionInformationType</code>	<p>Information type of the extension.</p> <ul style="list-style-type: none"> <code>Lightning</code>
<code>ConnectApi.ExternalAuthIdentityProviderParamType</code>	<p>Parameter type for an external auth identity provider.</p> <ul style="list-style-type: none"> <code>AuthorizeRequestQueryParameter</code> <code>IdentityProviderOptions</code> <code>ManagedByComponent</code> <code>ManagedByFeature</code> <code>RefreshRequestBodyParameter</code> <code>RefreshRequestHttpHeader</code> <code>RefreshRequestQueryParameter</code> <code>TokenRequestBodyParameter</code> <code>TokenRequestHttpHeader</code> <code>TokenRequestQueryParameter</code>
<code>ConnectApi.ExternalCredentialParameterType</code>	<p>Parameter type of the external credential.</p> <ul style="list-style-type: none"> <code>AdditionalRefreshStatusCode</code> <code>AuthParameter</code>



	<ul style="list-style-type: none"> • AuthProviderUrlQueryParameter • JwtBodyClaim • JwtHeaderClaim • ManagedByComponent • ManagedByFeature • SigningCertificate
ConnectApi.ExternalCredentialPrincipalAccessType	<p>Access type of the external credential principal.</p> <ul style="list-style-type: none"> • PermissionSet • PermissionSetGroup • Profile
ConnectApi.FeedCommentSortOrder	<p>Order of comments.</p> <ul style="list-style-type: none"> • CreatedDateLatestAsc –Sorts by most recently created comments in ascending order. • CreatedDateOldestAsc –Sorts by oldest comments in ascending order. • Relevance –Sorts by most relevant content.
ConnectApi.FeedDensity	<p>Density of the feed.</p> <ul style="list-style-type: none"> • AllUpdates –Displays all updates from people and records the user follows and groups the user is a member of. Also displays custom recommendations. • FewerUpdates –Displays all updates from people and records the user follows and groups the user is a member of. Also displays custom recommendations, but hides some system-generated updates from records.
ConnectApi.FeedElementCapabilityType	<p>Capabilities of a feed element in API versions 31.0 and later. If a capability exists on a feed element, the capability is available even if the value doesn't exist or is null. If the capability doesn't exist, it isn't available.</p> <ul style="list-style-type: none"> • AssociatedActions –The feed element includes information about actions associated with it. • Approval –The feed element includes information about an approval. • Banner –The body of the feed element has an icon and a border. • Bookmarks –The context user can bookmark the feed element. Bookmarked feed elements are visible in the bookmarks feed. • Bundle –The feed element has a group of other feed elements that display as a bundle in the feed. The bundle type determines the additional data associated with the bundle. • CallCollaboration –The feed element has a record comment. • Canvas –The feed element renders a canvas app. • CaseComment –The feed element has a case comment in the case feed.



- **Close** –The feed element can't be edited, comment on, or deleted. If the feed element is a poll, it can't be voted on.
- **Comments** –The context user can add comments to the feed element.
- **Content** –The feed element has a file.
- **DashboardComponentSnapshot** –The feed element has a dashboard component snapshot.
- **DirectMessage** –The feed element is a direct message.
- **Edit** –Users who have permission can edit the feed element.
- **EmailMessage** –The feed element has an email message from a case.
- **EnhancedLink** –The feed element has a link that can contain supplemental information like an icon, a title, and a description.
- **Extensions** –The feed element has one or more extension attachments.
- **FeedEntityShare** –The feed element has a feed entity shared with it.
- **Files** –The feed element has one or more file attachments.
- **Interactions** –The feed element has information about user interactions.
- **Link** –The feed element has a URL.
- **MediaReferences** –The feed element has one or more media references.
- **Moderation** –Users in an Experience Cloud site can mark the feed element for moderation.
- **Mute** –The context user can mute the feed element.
- **Origin** –A feed action created the feed element.
- **Pin** –Users who have permission can pin the feed element.
- **Poll** –The feed element has poll voting.
- **QuestionAndAnswers** –The feed element has a question and users can add answers to the feed element instead of comments. Users can also select the best answer.
- **ReadBy** –The context user can mark the feed element as read.
- **Recommendations** –The feed element has a recommendation.
- **Record** –The comment has a record attachment.
- **RecordSnapshot** –The feed element has all the snapshot fields of a record for a single create record event.
- **SocialPost** –The feed element can interact with a social post on a social network.
- **Status** –The feed element has a status that determines its visibility.
- **Topics** –The context user can add topics to the feed element.



	<ul style="list-style-type: none">• UpDownVote –Users can upvote or downvote the feed element.• Verified –Users who have permission can mark a comment as verified or unverified.
ConnectApi.FeedElementType	<p>Feed elements are the top-level objects that a feed contains: feed element type describes the characteristics of that feed element.</p> <ul style="list-style-type: none">• Bundle –A container of feed elements. A bundle also has a body made up of message segments that can always gracefully degrade to text-only values.• FeedItem –A feed item has a single parent and is scoped to one Experience Cloud site or across all Experience Cloud sites. A feed item can have capabilities such as bookmarks, canvas, content, comment, link, poll. Feed items have a body made up of message segments that can always be gracefully degraded to text-only values.• Recommendation –A recommendation is a feed element with a recommendations capability. A recommendation suggests records to follow, groups to join, or applications that are helpful to the context user.
ConnectApi.FeedEntityStatus	<p>Status of the feed post or comment.</p> <ul style="list-style-type: none">• Draft –The feed post isn't published but is visible to the author and users with Modify All Data or View All Data permission. Comments can't be drafts.• Isolated –The feed post or comment is isolated, and only admins can see it.• PendingReview –The feed post or comment isn't approved yet and therefore isn't published or visible.• Published –The feed post or comment is approved and visible.
ConnectApi.FeedFavoriteType	<p>Origin of the feed favorite.</p> <ul style="list-style-type: none">• ListView• Search• Topic
ConnectApi.FeedFilter	<p>Filter value for a feed.</p> <ul style="list-style-type: none">• AllQuestions –Feed elements that are questions.• AuthoredBy –Feed elements authored by the user profile owner. This value is valid only for the UserProfile feed.• CommunityScoped –Feed elements that are scoped to Experience Cloud sites. Currently, these feed elements have a User or a Group parent record. However, other parent record types could be scoped to sites in the feed. Feed elements that are always visible in all sites are filtered out. This value is valid only for the UserProfile feed.• QuestionsWithCandidateAnswers –Feed elements that are questions that have candidate answers associated.



- **QuestionsWithCandidateAnswersReviewedPublished** –Feed elements that are questions that have candidate answers that have been reviewed or published. This is valid only for users with the Access Einstein-Generative AI permission.
- **Read** –Feed elements that are older than 30 days or marked as read for the context user. Includes existing feed elements when the context user joined the group. This value is valid only for the Record feed of a group.
- **SolvedQuestions** –Feed elements that are questions that have a best answer.
- **UnansweredQuestions** –Feed elements that are questions and that don't have any answers.
- **UnansweredQuestionsWithCandidateAnswers** –Feed elements that are questions that don't have answers but have candidate answers associated with them. This is valid only for users with the Access Einstein-Generative AI permission.
- **Unread** –Feed elements that are created in the past 30 days and aren't marked as read for the context user. This value is valid only for the Record feed of a group.
- **UnsolvedQuestions** –Feed elements that are questions and that don't have a best answer.

ConnectApi.FeedItemAttachmentType

Attachment type for feed item output objects.

- **Approval** –A feed item requiring approval.
- **BasicTemplate** –A feed item with a generic rendering of an image, link, and title.
- **Canvas** –A feed item that contains the metadata to render a link to a canvas app.
- **CaseComment** –A feed item created from a comment on a case record.
- **CaseComment** –A feed item created from a comment on a case record.
- **Content** –A feed item with a file attached.
- **DashboardComponent** –A feed item with a dashboard component attached.
- **EmailMessage** –An email attached to a case record in a Case Feed.
- **Link** –A feed item with a URL attached.
- **Poll** –A feed item with a poll attached.
- **Question** –A feed item with a question attached.
- **RecordSnapshot** –The feed item attachment contains a view of a record at a single point in time. `ConnectApi.FeedItemType.CreateRecordEvent`.
- **TrackedChange** –All changes to a record for a single `ConnectApi.FeedItemType.TrackedChange` event.

ConnectApi.FeedItemType

Type of feed item.

- **ActivityEvent** –Feed item generated in Case Feed as an event or task associated with a parent record with feed enabled is created or updated.



- **ApprovalPost** –Feed item with an approval capability. Approvers can act on the feed item parent.
 - **AttachArticleEvent** –Feed item generated when a article is attached to a case in Case Feed.
 - **BasicTemplateFeedItem** –Feed item with an enhanced link capability.
 - **CallLogPost** –Feed item generated when a call log saved to a case in Case Feed.
 - **CanvasPost** –Feed item generated by a canvas app publisher or from Connect REST API or Connect in A. The post itself is a link to a canvas app.
 - **CaseCommentPost** –Feed item generated when a case comment is saved in Case Feed.
 - **ChangeStatusPost** –Feed item generated when the status of a case is changed in Case Feed.
 - **ChatTranscriptionPost** –Feed item generated in Case Feed when a Live Agent chat transcript is saved to a case.
 - **CollaborationGroupCreated** –Feed item generated when a new public group is created. Contains a link to the new group.
 - **CollaborationGroupUnarchived** –Deprecated. Feed item generated when an archived group is activated.
 - **ContentPost** –Feed item with a content capability.
 - **CreateRecordEvent** –Feed item that describes a record created in the publisher.
 - **DashboardComponentAlert** –Feed item with a dashboard alert.
 - **DashboardComponentSnapshot** –Feed item with a dashboard component snapshot capability.
 - **EmailMessageEvent** –Feed item generated when an email is sent from a case in Case Feed.
 - **FacebookPost** –Deprecated. Feed item generated when a Facebook post is created from a case in Case Feed.
 - **LinkPost** –Feed item with a link capability.
 - **MilestoneEvent** –Feed item generated when a case milestone is either completed or reaches a violation status. Contains a link to the case milestone.
 - **PollPost** –Feed item with a poll capability. Viewers of the feed item are allowed to vote on the options in the poll.
 - **ProfileSkillPost** –Feed item generated when a skill added to a user's profile.
 - **QuestionPost** –Feed item generated when a question asked.
- As of API version 33.0, a feed item of this type can have content capability and a link capability.
- **ReplyPost** –Feed item generated by a Chatter Answer reply.
 - **RypplePost** –Feed item generated when a user posts thanks.
 - **SocialPost** –Feed item generated when a social post created from a case in Case Feed.



	<p>fields on a record have been changed.</p> <ul style="list-style-type: none">• <code>UserStatus</code> –Deprecated. A user's post to their own profile.
<code>ConnectApi.FeedItemVisibilityType</code>	<p>Type of users who can see a feed item.</p> <ul style="list-style-type: none">• <code>AllUsers</code> –Visibility is not limited to internal users.• <code>InternalUsers</code> –Visibility is limited to internal users
<code>ConnectApi.FeedSortOrder</code>	<p>Order of feed items in the feed.</p> <ul style="list-style-type: none">• <code>CreatedDateAsc</code> –Sorts by oldest creation date. This order is available only for <code>DirectMessageModerationDraft</code>, <code>Isolated</code>, <code>Moderation</code>, and <code>PendingReview</code> feeds.• <code>CreatedDateDesc</code> –Sorts by most recent creation date.• <code>LastModifiedDateDesc</code> –Sorts by most recent active date.• <code>MostViewed</code> –Sorts by most viewed content. This sort order is available only for <code>Home</code> feeds when the <code>ConnectApi.FeedFilter</code> is <code>UnansweredQuestions</code>.• <code>Relevance</code> –Sorts by most relevant content. This sort order is available only for <code>Company</code>, <code>Home</code>, and <code>Topic</code> feeds.
<code>ConnectApi.FeedType</code>	<p>Type of feed.</p> <ul style="list-style-type: none">• <code>Bookmarks</code> –Contains all feed items saved as bookmarks by the context user.• <code>Company</code> –Contains all feed items except feed items of type <code>TrackedChange</code>. To see the feed item, the user must have sharing access to its parent.• <code>DirectMessageModeration</code> –Contains all direct messages that are flagged for moderation. The Direct Message Moderation feed is available only to users with <code>ModifiableExperiencesChatterMessages</code> permissions.• <code>DirectMessages</code> –Contains all feed items of the context user's direct messages.• <code>Draft</code> –Contains all the feed items that the context user drafted.• <code>Files</code> –Contains all feed items that contain files posted by people or groups that the context user follows.• <code>Filter</code> –Contains the news feed filtered to contain only items whose parent is a specified object type.• <code>Groups</code> –Contains all feed items from all groups the context user either owns or is a member of.• <code>Home</code> –Contains all feed items associated with any managed topic in an Experience Cloud site.• <code>Isolated</code> –Contains all the feed items and comments that are isolated.• <code>Landing</code> –Contains all feed items that best drive user engagement when the feed is requested. Allows clients to avoid an empty feed when there aren't many personalized feed items.



		<p>feed is available only to users with moderate Experience Feed permissions.</p> <ul style="list-style-type: none">• Mute –Contains all feed items that the context user muted.• News –Contains all updates for people the context user follows, groups the user is a member of, and files and records the user is following. Contains all updates for records whose parent is the context user.• PendingReview –Contains all feed items and comments that are pending review.• People –Contains all feed items posted by all people the context user follows.• Record –Contains all feed items whose parent is a specified record, which could be a group, user, object, file, or any other standard or custom object. When the record is a group, the feed also contains feed items that mention the group. When the record is a user, the feed contains only feed items on that user. You can get another user's record feed.• Streams –Contains all feed items for any combination up to 25 feed-enabled entities that the context user subscribes to in a stream. Examples of feed-enabled entities include people, groups, and records,• To –Contains all feed items with mentions of the context user. Contains feed items the context user commented on and feed items created by the context user that are commented on.• Topics –Contains all feed items that include the specified topic.• UserProfile –Contains feed items created when a user changes records that can be tracked in a feed. Contains feed items whose parent is the user and feed items that mention the user. This feed is different than the user's feed, which returns more feed items, including group updates. You can get another user's user profile feed.
	<code>ConnectApi.FieldChangeValueType</code>	<p>Value type of a field change.</p> <ul style="list-style-type: none">• NewValue –A new value• OldValue –An old value
	<code>ConnectApi.FieldType</code>	<p>Field type.</p> <ul style="list-style-type: none">• Address• AnyType• Base64• Boolean• Combobox• ComplexValue• Currency• DataCategoryGroupReference• Date• DateTime• Double



	<ul style="list-style-type: none">• ExtensionEntityLookup• ExternalLookup• FloatArray• Id• ImageUrl• IndirectLookup• Integer• Json• Location• Long• MultiPicklist• Percent• PersonName• Phone• Picklist• PlainTextArea• Reference• RichTextArea• Subject• String• SwitchablePersonName• TextArea• Time• Url
ConnectApi.FileDelimiterEnum	<p>Field delimiter to use in output files.</p> <ul style="list-style-type: none">• BrokenPipe• Caret• Colon• Comma• Hash• Pipe• Semicolon• Slash• Tab• Tilde• Underscore



	<p>– Preview format is SVG.</p> <ul style="list-style-type: none"> • Pdf –Preview format is PDF. • Svg –Preview format is compressed SVG. • Thumbnail –Preview format is 240 x 180 PNG. • ThumbnailBig –Preview format is 720 x 480 PNG. • ThumbnailTiny –Preview format is 120 x 90 PNG.
ConnectApi.FilePreviewStatus	<p>Availability status of the file preview.</p> <ul style="list-style-type: none"> • Available –Preview is available. • InProgress –Preview is being processed. • NotAvailable –Preview is unavailable. • NotScheduled –Generation of the preview isn't scheduled yet.
ConnectApi.FilePublishStatus	<p>Publish status of the file.</p> <ul style="list-style-type: none"> • PendingAccess –File is pending publishing. • PrivateAccess –File is private. • PublicAccess –File is public.
ConnectApi.FileSharingOption	<p>Sharing option of the file.</p> <ul style="list-style-type: none"> • Allowed –Resharing of the file is allowed. • Restricted –Resharing of the file is restricted.
ConnectApi.FileSharingPrivacy	<p>Sharing privacy of a file.</p> <ul style="list-style-type: none"> • None –File is visible to anyone with record access. • PrivateOnRecords –File is private on records.
ConnectApi.FileSharingType	<p>Sharing role of the file.</p> <ul style="list-style-type: none"> • Admin –Owner permission, but doesn't own the file. • Collaborator –Viewer permission, and can edit, change permissions, and upload a new version of a file. • Owner –Collaborator permission, and can make a file private, and delete a file. • Viewer –Can view, download, and share a file. • WorkspaceManaged –Permission controlled by the list
ConnectApi.FilterConjunction	<p>Conjunction for the activation attribute filter expression.</p> <ul style="list-style-type: none"> • FilterConjunctionAnd • FilterConjunctionOr
ConnectApi.FilterOperator	<p>Filter operator.</p> <ul style="list-style-type: none"> • EqOp –Equal • ExcludesOp –Excludes • GtOp –Greater than • GteOp –Greater than or equal



	<ul style="list-style-type: none">• LikeOp –Like• LtOp –Less than• LteOp –Less than or equal• NeOp –Not equal• NinOp –Not in
ConnectApi.FilterOperatorDataType	Type of attribute. <ul style="list-style-type: none">• FilterOperatorDataTypeBoolean• FilterOperatorDataTypeDate• FilterOperatorDataTypeDateOnly• FilterOperatorDataTypeExactlyRelativeDate• FilterOperatorDataTypeNumber• FilterOperatorDataTypeRelateToNowDate• FilterOperatorDataTypeText
ConnectApi.FilterSortOrder	The sort order for filtering. <ul style="list-style-type: none">• FilterSortOrderAsc• FilterSortOrderDesc
ConnectApi.FolderItemType	Type of item in a folder. <ul style="list-style-type: none">• file• folder
ConnectApi.FormFieldType	Type of marketing integration form field. <ul style="list-style-type: none">• Boolean• Date• EmailAddress• Number• Text
ConnectApi.FormulaFilterType	Formula filter type for the personalization audience. <ul style="list-style-type: none">• AllCriteriaMatch –All audience criteria are true (A operation).• AnyCriterionMatches –Any audience criterion is true (OR operation).• CustomLogicMatches –Audience criteria match the custom formula (for example, (1 AND 2) OR 3).
ConnectApi.GoalDefinitionCategoryEnum	Definition category of the business objective, or goal. <ul style="list-style-type: none">• Webstore
ConnectApi.GroupArchiveStatus	Archive status of groups. <ul style="list-style-type: none">• All –All groups, including groups that are archived and groups that aren't archived.• Archived –Groups that are archived.



<code>ConnectApi.GroupEmailFrequency</code>	<p>Frequency with which a user receives email.</p> <ul style="list-style-type: none"> • <code>EachPost</code> • <code>DailyDigest</code> • <code>WeeklyDigest</code> • <code>Never</code> • <code>UseDefault</code>
<code>ConnectApi.GroupMembershipType</code>	<p>Type of membership the user has with the group.</p> <ul style="list-style-type: none"> • <code>GroupOwner</code> • <code>GroupManager</code> • <code>NotAMember</code> • <code>NotAMemberPrivateRequested</code> • <code>StandardMember</code>
<code>ConnectApi.GroupMembershipRequestStatus</code>	<p>Status of a request to join a private group.</p> <ul style="list-style-type: none"> • <code>Accepted</code> • <code>Declined</code> • <code>Pending</code>
<code>ConnectApi.GroupViralInvitationsStatus</code>	<p>Status of an invitation to join a group.</p> <ul style="list-style-type: none"> • <code>ActedUponUser</code> –The user was added to the group. / email was sent asking the user to visit the group. • <code>Invited</code> –An email was sent asking the user to sign for the org. • <code>MaxedOutUsers</code> –The group has the maximum allow members. • <code>MultipleError</code> –The user wasn't invited due to multi errors. • <code>NoActionNeededUser</code> –The user is already a member the group. • <code>NotVisibleToExternalInviter</code> –The user is not accessible to the user sending the invitation. • <code>Unhandled</code> –The user couldn't be added to the group an unknown reason.
<code>ConnectApi.GroupVisibilityType</code>	<p>Group visibility type.</p> <ul style="list-style-type: none"> • <code>PrivateAccess</code> –Only members of the group can see posts to this group. • <code>PublicAccess</code> –All users within the Experience Cloud can see posts to this group. • <code>Unlisted</code> –Reserved for future use.
<code>ConnectApi.HttpRequestMethod</code>	<p>HTTP method.</p> <ul style="list-style-type: none"> • <code>HttpDelete</code> –Returns HTTP 204 on success. Response body or output class is empty. • <code>HttpGet</code> –Returns HTTP 200 on success.



	<ul style="list-style-type: none"> • <code>HttpPatch</code> –Returns HTTP 200 on success or HTTP 204 if the response body or output class is empty. • <code>HttpPost</code> –Returns HTTP 201 on success or HTTP 204 if the response body or output class is empty. Exceptions are the batch posting resources and methods, which return HTTP 200 on success. • <code>HttpPut</code> –Return HTTP 200 on success or HTTP 204 if response body or output class is empty.
<code>ConnectApi.IdentityProviderAuthFlow</code>	<p>Authentication flow to get tokens to call protected APIs.</p> <ul style="list-style-type: none"> • <code>AuthorizationCode</code>
<code>ConnectApi.IdentityProviderAuthProtocol</code>	<p>Authentication protocol required to access the external system.</p> <ul style="list-style-type: none"> • <code>OAuth</code>
<code>ConnectApi.IdentityProviderClientAuth</code>	<p>Client authentication method that describes how credentials are sent to the authorization server.</p> <ul style="list-style-type: none"> • <code>ClientSecretBasic</code> • <code>ClientSecretPost</code>
<code>ConnectApi.LinkMetadataSource</code>	<p>Source of the link metadata.</p> <ul style="list-style-type: none"> • <code>None</code> –Link metadata wasn't retrieved. • <code>Sfdc</code> –Salesforce is the source.
<code>ConnectApi.LinkMetadataType</code>	<p>Type of link that the metadata represents.</p> <ul style="list-style-type: none"> • <code>Error</code> –Link metadata couldn't be retrieved. • <code>Link</code> –Represents a link. • <code>None</code> –Link metadata wasn't retrieved because the link isn't an allowed domain. • <code>Photo</code> –Represents a photo. • <code>Rich</code> –Represents rich content, typically HTML content. • <code>Unknown</code> –Link metadata was retrieved, but the type is unknown. • <code>Video</code> –Represents a video.
<code>ConnectApi.MaintenanceType</code>	<p>Type of maintenance.</p> <ul style="list-style-type: none"> • <code>Downtime</code> –Downtime maintenance. • <code>GenerallyAvailable</code> –Generally available mode. • <code>MaintenanceAndAvailable</code> –Maintenance with available mode. • <code>MaintenanceWithDowntime</code> –Scheduled maintenance with downtime. • <code>ReadOnly</code> –Maintenance with read-only mode.
<code>ConnectApi.ManagedContentChannelType</code>	<p>Type of managed content channel.</p> <ul style="list-style-type: none"> • <code>CloudToCloud</code> –Cloud-to-Cloud integrated channel. • <code>Community</code> –Experience Cloud site channel.



	<p>content is publicly available.</p> <ul style="list-style-type: none"> • UserPermission –Channel backed by a system permission. All published content is available only to users with the permission.
<code>ConnectApi.ManagedContentCloneStatus</code>	<p>Status of the managed content clone.</p> <ul style="list-style-type: none"> • PartialSuccess • Success
<code>ConnectApi.ManagedContentMediaType</code>	<p>Type of managed content media.</p> <ul style="list-style-type: none"> • Document • Image
<code>ConnectApi.ManagedContentNodeType</code>	<p>Type of managed content node.</p> <ul style="list-style-type: none"> • Date • DateTime • Media • MediaSource • MultilineText • NameField • RichText • Text • Url
<code>ConnectApi.ManagedContentSpaceChannelOperation</code>	<p>Operation to perform on the channel and managed content space.</p> <ul style="list-style-type: none"> • Add –Add a channel to a managed content space. • Remove –Remove a channel from a managed content space.
<code>ConnectApi.ManagedContentSpaceChannelStatus</code>	<p>Status of the add or remove operation for a channel and managed content space.</p> <ul style="list-style-type: none"> • Added –Channel was added to the managed content space. • Failed –Add or remove operation failed. • Pending –Add or remove operation is pending. • Removed –Channel was removed from the managed content space.
<code>ConnectApi.ManagedContentSpaceType</code>	<p>Type of managed content space.</p> <ul style="list-style-type: none"> • Content • Marketing
<code>ConnectApi.ManagedContentVariantStatus</code>	<p>Status of the managed content variant.</p> <ul style="list-style-type: none"> • Draft –Content isn't published. • Published –Content is published and available for use on your live sites.



		ive sites.
ConnectApi.ManagedTopicType	Type of managed topic. <ul style="list-style-type: none">Content –Topics that are associated with native content.Featured –Topics that are featured, for example, on Experience Cloud site home page, but don't provide overall navigation.Navigational –Topics that display in a navigational in the Experience Cloud site.	
ConnectApi.MarkupType	Type of rich text markup. <ul style="list-style-type: none">Bold –Bold tag.Code –Code tag.Hyperlink –Hyperlink anchor tag.Italic –Italic tag.ListItem –List item tag.OrderedList –Ordered list tag.Paragraph –Paragraph tag.Strikethrough –Strikethrough tag.Underline –Underline tag.UnorderedList –Unordered list tag.	
ConnectApi.MCSFolderShareStatus	Status of sharing a managed content space folder. <ul style="list-style-type: none">PendingSharePendingUnshareShared	
ConnectApi.MentionCompletionType	Type of mention completion. <ul style="list-style-type: none">All –All mention completions, regardless of the type record to which the mention refers.Group –Mention completions for groups.User –Mention completions for users.	
ConnectApi.MentionValidationStatus	Type of validation error for a proposed mention, if any. <ul style="list-style-type: none">Disallowed –The proposed mention is invalid and is rejected because the context user is trying to mention something that is not allowed. For example, a user who is not a member of a private group is trying to mention a private group.Inaccessible –The proposed mention is allowed, but the user or record being mentioned isn't notified. They don't have access to the parent record that's being discussed.Ok –There is no validation error for this proposed mention.	
ConnectApi.MessageSegmentType	Type of message segment, such as text, link, field change notification, or field change value.	



	<ul style="list-style-type: none">FieldChangeNameFieldChangeValueHashtagInlineImageLinkMarkupBeginMarkupEndMentionMoreChangesResourceLinkText
ConnectApi.NamedCredentialParameterType	Type of named credential parameter. <ul style="list-style-type: none">AllowedManagedPackageNamespacesClientCertificateConnectionStatus
ConnectApi.NamedCredentialType	Type of named credential. <ul style="list-style-type: none">PrivateEndpointSecuredEndpoint
ConnectApi.NavigationMenuItemActionType	Event, URL type, or modal navigation menu item. <ul style="list-style-type: none">Event –Event-based navigation. <div><div></div><div>Note Event is internal only and can't be use in custom components.</div></div> <ul style="list-style-type: none">ExternalLink –URL outside of your Experience Cloud site.InternalLink –Relative URL inside your Experience Cloud site.Modal –Modal, such as Account Switcher.
ConnectApi.NavigationMenuItemOpenTarget	Target for the navigation menu item. <ul style="list-style-type: none">CurrentWindow –Navigation menu item opens in the current window.NewWindow –Navigation menu item opens in a new window.
ConnectApi.NavigationMenuItemType	Type of navigation menu item. <ul style="list-style-type: none">DataSourceDriven –Menu items dynamically added from a data source.Event –Event, such as logging in, logging out, or switching accounts.



		<p>related to other records.</p> <ul style="list-style-type: none">InternalLink –Relative URL inside your site.MenuItem –Menu label.Modal –Modal, such as Account Switcher.NavigationalTopic –Dropdown list with links to the navigational topics in your site.SalesforceObject –Objects such as accounts, case contacts, and custom objects.SystemLink –System link, such as a link to Builder, Workspaces, or Setup.
ConnectApi.NBAActionType	Type of action.	<ul style="list-style-type: none">Flow –Automated process tool with multiple subtypes
ConnectApi.NBAFlowType	Type of recommended flow.	<ul style="list-style-type: none">AutoLaunchedFlow –Autolaunched flow that runs in background.Flow –Screen flow that accepts user inputs.
ConnectApi.NBATargetType	Type of target.	<ul style="list-style-type: none">Recommendation
ConnectApi.OperationType	Operation to carry out on the file.	<ul style="list-style-type: none">Add –Adds the file to the feed element.Remove –Removes the file from the feed element.
ConnectApi.OrchestrationInstanceStatus	Status of the orchestration instance.	<ul style="list-style-type: none">CanceledCompletedDiscontinuedErrorInProgressNotStartedSuspended
ConnectApi.OrchestrationStepType	Type of orchestration step.	<ul style="list-style-type: none">AsynchronousBackgroundStepApprovalStepBackgroundStepInteractiveStepManagedContentRoleInteractiveStepManagedContentVariantAutoPublishBackgroundStepManagedContentVariantAutoUnpublishBackgroundStepManagedContentVariantSetLockBackgroundStepManagedContentVariantSetReadyBackgroundStep



<code>ConnectApi.OrchestrationWorkItemStatus</code>	<p>Status of the orchestration work item.</p> <ul style="list-style-type: none"> Assigned Completed
<code>ConnectApi.OrderDeliveryGroupSummarySort</code>	<p>Sort order for order delivery group summaries.</p> <ul style="list-style-type: none"> <code>IdAsc</code> –Sorts by ID in ascending alphanumeric order (Z, 0–9). <code>IdDesc</code> –Sorts by ID in descending alphanumeric order (Z–A, 9–0).
<code>ConnectApi.OrderItemSummarySort</code>	<p>Sort order for order item summaries.</p> <ul style="list-style-type: none"> <code>IdAsc</code> –Sorts by ID in ascending alphanumeric order (Z, 0–9). <code>IdDesc</code> –Sorts by ID in descending alphanumeric order (Z–A, 9–0).
<code>ConnectApi.OrderNulls</code>	<p>Null value order.</p> <ul style="list-style-type: none"> <code>Firsts</code> –Null values are sorted first. <code>Lasts</code> –Null values are sorted last.
<code>ConnectApi.OrderShipmentItemSort</code>	<p>Sort order for order shipment items.</p> <ul style="list-style-type: none"> <code>IdAsc</code> –Sorts by ID in ascending alphanumeric order (Z, 0–9). <code>IdDesc</code> –Sorts by ID in descending alphanumeric order (Z–A, 9–0).
<code>ConnectApi.OrderShipmentSort</code>	<p>Sort order for order shipments.</p> <ul style="list-style-type: none"> <code>ExpectedDeliveryDateAsc</code> –Sorts by the oldest expected delivery date. <code>ExpectedDeliveryDateDesc</code> –Sorts by the most recent expected delivery date. <code>ShipmentNumberAsc</code> –Sorts by shipment number in ascending order (0–9). <code>ShipmentNumberDesc</code> –Sorts by shipment number in descending order (9–0).
<code>ConnectApi.OrderSummaryAdjustmentAggregatesStatus</code>	<p>Order summary adjustment aggregate job status.</p> <ul style="list-style-type: none"> <code>Failed</code> –The adjustment aggregate data job for the summary failed. <code>InProgress</code> –The adjustment aggregate data job for order summary is in progress. <code>NotInitiated</code> –The adjustment aggregate data job for the order summary is not initiated. <code>Submitted</code> –The adjustment aggregate data job for the order summary is submitted.



	<ul style="list-style-type: none"> • SPARELINE –Price adjustment on an order item. • Header –Price adjustment on the entire order.
<code>ConnectApi.OrderSummarySortOrder</code>	<p>Sort order for order summaries.</p> <ul style="list-style-type: none"> • CreatedDateAsc –Sorts by the oldest created date. • CreatedDateDesc –Sorts by the most recent created date. • OrderedDateAsc –Sorts by the oldest ordered date. • OrderedDateDesc –Sorts by the most recent ordered date.
<code>ConnectApi.PeriodType</code>	<p>Time period used for forecasting.</p> <ul style="list-style-type: none"> • Month • Quarter • Week • Year
<code>ConnectApi.PlatformActionGroupCategory</code>	<p>Location of an action link group on an associated feed element.</p> <ul style="list-style-type: none"> • Primary –The action link group is displayed in the body of the feed element. • Overflow –The action link group is displayed in the overflow menu of the feed element.
<code>ConnectApi.PlatformActionStatus</code>	<p>Status of the action.</p> <ul style="list-style-type: none"> • FailedStatus –The action link execution failed. • NewStatus –The action link is ready to be executed. Available for Download and Ui action links only. • PendingStatus –The action link is executing. Choosing this value triggers the API call for Api and ApiAsync action links. • SuccessfulStatus –The action link executed successfully.
<code>ConnectApi.PlatformActionType</code>	<p>Type of platform action.</p> <ul style="list-style-type: none"> • ActionLink –An indicator on a feed element that takes an API, a web page, or a file, represented by a button in the Salesforce UI. • CustomButton –When clicked, opens a URL or a Visualforce page in a window or executes JavaScript. • ProductivityAction –Productivity actions are predefined and attached to a limited set of objects. Productivity actions include Send Email, Call, Map, \Website, and Read News. Except for the Call action, can't edit productivity actions. • QuickAction –A global or object-specific action. • StandardButton –A predefined Salesforce button such as New, Edit, or Delete.



	<ul style="list-style-type: none">SegmentSegmentActivation
ConnectApi.PriceAdjustmentTierType	<div>Type of price adjustment for the tier.</div> <ul style="list-style-type: none">AmountBasedAdjustment –Price is adjusted by a specified amount.PercentageBasedAdjustment –Price is adjusted by a specified percentage.
ConnectApi.PricingTermUnit	<div>Unit of time used to define a pricing term.</div> <ul style="list-style-type: none">Months –Product is priced on a monthly basis.Annual –Product is priced on an annual basis.
ConnectApi.ProductAttributeViewType	<div>View type for product attributes.</div> <ul style="list-style-type: none">ColorSwatchDropdownPill
ConnectApi.ProductClass	<div>Class of product.</div> <ul style="list-style-type: none">BundleSetSimpleVariationVariationParent
ConnectApi.ProductMediaType	<div>Type of product media.</div> <ul style="list-style-type: none">DocumentImageVideo
ConnectApi.ProductMediaUsageType	<div>Usage type of a product media item within a media group.</div> <ul style="list-style-type: none">Attachment –Product media group with product documents as attachments.Banner –Product category media group with banner images of the product.Listing –Product media group with listing images of the product.Standard –Product media group with standard images and videos of the product.Tile –Product category media group with tile images of the product.
ConnectApi.PublishSchedule	<div>Publish refresh schedule.</div> <ul style="list-style-type: none">One –Refreshes every hour. Used to rapidly publish new DBT-based segments.



	<ul style="list-style-type: none"> • Twelve –Refreshes every twelve hours. • TwentyFour –Refreshes every twenty-four hours.
ConnectApi.PublishStatus	<p>Publish status of a personalization audience, target, or navigation menu item.</p> <ul style="list-style-type: none"> • Draft • Live
ConnectApi.SwatchDisplayTypeEnum	<p>Swatch display metadata type.</p> <ul style="list-style-type: none"> • Color –Color of the swatch.
ConnectApi.QuerySqlStatusEnum	<p>Completion status of the query.</p> <ul style="list-style-type: none"> • Finished • ResultsProduced • Running • Unspecified
ConnectApi.RecommendationActionType	<p>Action to take on a recommendation.</p> <ul style="list-style-type: none"> • follow –Follow a file, record, topic, or user. • join –Join a group. • view –View a file, group, article, record, user, custom static recommendation.
ConnectApi.RecommendationAudienceCriteriaType	<p>Custom recommendation audience criteria type.</p> <ul style="list-style-type: none"> • CustomList –A custom list of users makes up the audience. • MaxDaysInCommunity –New members make up the audience.
ConnectApi.RecommendationAudienceMemberOperationType	<p>Operation to carry out on the custom recommendation audience members.</p> <ul style="list-style-type: none"> • Add –Adds specified members to the audience. • Remove –Removes specified members from the audience.
ConnectApi.RecommendationChannel	<p>A way to tie custom recommendations together. For example, display recommendations in specific places in the UI or show recommendations based on time of day or geographic location.</p> <ul style="list-style-type: none"> • CustomChannel1 –Custom recommendation channel. Not used by default. Work with your community manager to define custom channels. For example, community managers can use Experience Builder to determine where recommendations appear. • CustomChannel2 –Custom recommendation channel. Not used by default. Work with your community manager to define custom channels. • CustomChannel3 –Custom recommendation channel. Not used by default. Work with your community manager to define custom channels.



to define custom channels.

- **CustomChannel15** –Custom recommendation channel. Not used by default. Work with your community manager to define custom channels.
- **DefaultChannel1** –Default recommendation channel. Recommendations appear by default on the Home, Question Detail pages of Customer Service and Part Central Experience Builder templates. They also appear in the feed in the Salesforce mobile web and anywhere community managers add recommendations using Experience Builder.

ConnectApi.RecommendationExplanationType

Reason for a Chatter recommendation.

- **ArticleHasRelatedContent** –Articles with related content to a context article.
- **ArticleViewedTogether** –Articles often viewed together with the article that the context user just viewed.
- **ArticleViewedTogetherWithViewers** –Articles often viewed together with other records that the context user views.
- **Custom** –Custom recommendations.
- **FilePopular** –Files with many followers or views.
- **FileViewedTogether** –Files often viewed at the same time as other files that the context user views.
- **FollowedTogetherWithFollowees** –Users often followed together with other records that the context user follows.
- **GroupMembersFollowed** –Groups with members that the context user follows.
- **GroupNew** –Recently created groups.
- **GroupPopular** –Groups with many active members.
- **ItemViewedTogether** –Records often viewed at the same time as other records that the context user views.
- **PopularApp** –Applications that are popular.
- **RecordOwned** –Records that the context user owns.
- **RecordParentOfFollowed** –Parent records of records that the context user follows.
- **RecordViewed** –Records that the context user recently viewed.
- **TopicFollowedTogether** –Topics often followed together with the record that the context user just followed.
- **TopicFollowedTogetherWithFollowees** –Topics often followed together with other records that the context user follows.
- **TopicPopularFollowed** –Topics with many followers.
- **TopicPopularLiked** –Topics on posts that have many likes.
- **UserDirectReport** –Users who report to the context user.
- **UserFollowedTogether** –Users often followed together with the record that the context user followed.
- **UserFollowsSameUsers** –Users who follow the same users as the context user.



	<ul style="list-style-type: none">UserPeer –Users who report to the same manager as the context user.UserPopular –Users with many followers.UserViewingSameRecords –Users who view the same records as the context user.
ConnectApi.RecommendationReactionType	Type of reaction to a recommendation. <ul style="list-style-type: none">AcceptedRejected
ConnectApi.RecommendationType	Type of record being recommended. <ul style="list-style-type: none">appsarticlesfilesgroupsrecordstopicsusers
ConnectApi.RecommendedObjectType	Type of object being recommended. <ul style="list-style-type: none">Today –Static recommendations that don't have an associated record, for example, the Today app recommendation.
ConnectApi.RecordColumnOrder	Order in which fields are rendered in a grid. <ul style="list-style-type: none">LeftRight –Fields are rendered from left to right.TopDown –Fields are rendered from the top down.
ConnectApi.RecordFieldType	Data type of a record field. <ul style="list-style-type: none">AddressBlankBooleanCompoundCreatedByDateDateTimeEmailLastModifiedByLocationNameNumberPercentPhonePicklistReferenceText



<code>ConnectApi.RelatedFeedPostType</code>	<p>Type of related feed post.</p> <ul style="list-style-type: none"> • Answered –Related questions that have at least one answer. • BestAnswer –Related questions that have a best answer. • Generic –All types of related questions, including answered, with a best answer, and unanswered. • Unanswered –Related questions that don't have an answer.
<code>ConnectApi.SearchBoostBuryRuleAction</code>	<p>Action of the boost and bury rule.</p> <ul style="list-style-type: none"> • Boost –Boost rule. Increases search result rankings for targeted products. • Bury –Bury rule. Decreases search result rankings for targeted products.
<code>ConnectApi.SearchBoostBuryRuleOperation</code>	<p>Operation for the conditions of the target expression in the boost and bury rule.</p> <ul style="list-style-type: none"> • AllOf –All-of operation. • AnyOf –Any-of operation.
<code>ConnectApi.SearchOrder</code>	<p>Order direction.</p> <ul style="list-style-type: none"> • Ascending • Descending
<code>ConnectApi.SegmentType</code>	<p>Type of segment.</p> <ul style="list-style-type: none"> • Dbt –Data build tool
<code>ConnectApi.SellingModelType</code>	<p>Type of product selling model.</p> <ul style="list-style-type: none"> • Evergreen –A subscription without an end date. An evergreen subscription continues until the shopper affirmatively cancels it. • OneTime –A product that isn't sold as a subscription. • TermDefined –A subscription with a defined end date. The subscription continues for a specified time period. When the term ends, the subscription ends.
<code>ConnectApi.SitesPageType</code>	<p>Type of site search result item.</p> <ul style="list-style-type: none"> • ContentPage • SitePage
<code>ConnectApi.SocialNetworkProvider</code>	<p>Social network provider.</p> <ul style="list-style-type: none"> • Facebook • GooglePlus • Instagram • InstagramBusiness • KakaoTalk • Kik



	<ul style="list-style-type: none">• Messenger• Other• Pinterest• QQ• Rypple• SinaWeibo• SMS• Snapchat• Telegram• Twitter• VKontakte• WeChat• WhatsApp• YouTube
ConnectApi.SocialPostMessageType	<div>Message type of the social post.</div> <ul style="list-style-type: none">• Comment• Direct• Post• PrivateMessage• Reply• Retweet• Tweet
ConnectApi.SocialPostStatusType	<div>State of the social post.</div> <ul style="list-style-type: none">• ApprovalPending• ApprovalRecalled• ApprovalRejected• Deleted• Failed• Hidden• Pending• Sent• Unknown
ConnectApi.SortOrder	<div>Order for sorting.</div> <ul style="list-style-type: none">• Ascending –Items are in ascending alphabetical order (A-Z).• Descending –Items are in descending alphabetical order (Z-A).• MostRecentlyViewed –Items are in descending chronological order by view. This sort order is valid only for Chatter feed streams.
ConnectApi.SurveyEmailStatusEnum	<div>Status of a survey invitation email.</div> <ul style="list-style-type: none">• Failed –The survey invitation email wasn't sent.



ConnectApi.SvcApptModeEnum	Mode of the service appointment. <ul style="list-style-type: none">Group – Service appointment mode is Group.Regular – Default mode of service appointment.
ConnectApi.TargetType	Target type of a promotion discount. <ul style="list-style-type: none">Shipping –Promotion discounts shipping amount.Transaction –Promotion discounts total transaction amount.
ConnectApi.SwatchDisplayTypeEnum	Display metadata type of the swatch. <ul style="list-style-type: none">Color –Color of the swatch.
ConnectApi.TaxTransactionStatus	Status of a tax transaction. <ul style="list-style-type: none">Committed –Tax has been committed to the transaction.Uncommitted –Tax hasn't been committed to the transaction.
ConnectApi.TaxTransactionType	Type of tax transaction. <ul style="list-style-type: none">Credit –Transaction is a credit transaction.Debit –Transaction is a debit transaction.
ConnectApi.TopicSort	Order returned by the sort. <ul style="list-style-type: none">popularDesc –Sorts topics by popularity with the most popular first. This value is the default.alphaAsc –Sorts topics alphabetically.
ConnectApi.TypeEnum	Type of the SQL parameter. <ul style="list-style-type: none">ArrayOfXBigIntBoolCharDateDoubleFoatIntegerNumericOidSmallIntTimeTimestampTimestampTZUnspecifiedVarchar



- None
- Up

ConnectApi.UserActivityType

Type of user activity.

- Bookmark –User bookmarked a post.
- ChatterActivity –Total counts of posts and comments made and likes and comments received for a user.
- ChatterLike –User liked a post or comment.
- Comment –User commented on a post.
- CompanyVerify –User verified comment.
- DownVote –User downvoted a post or comment.
- FeedEntityRead –User read a post.
- FeedRead –User read a feed.
- Mute –User muted a post.
- Post –User made a post.
- TopicEndorsement –User endorsed another user on topic or received endorsement on a topic.
- UpVote –User upvoted a post or comment.

ConnectApi.UserMissionActivityType

Type of mission activity for a user.

- FeedItemAnswerAQuestion –User answered a question.
- FeedItemLikeSomething –User liked a post or comment.
- FeedItemMarkAnswerAsBest –User marked an answer as the best answer.
- FeedItemPostQuestion –User posted a question.
- FeedItemReceiveAComment –User received a comment on a post.
- FeedItemReceiveALike –User received a like on a post or comment.
- FeedItemReceiveAnAnswer –User received an answer to a question.
- FeedItemWriteAComment –User commented on a post or comment.
- FeedItemWriteAPost –User made a post.
- FeedItemYourAnswerMarkedBest –User's answer was marked as the best answer.

ConnectApi.UserProfileTabType

Type of user profile tab.

- CustomVisualForce –Tab that displays data from a Visualforce page.
- CustomWeb –Tab that displays data from any external based application or web page.
- Element –Tab that displays generic content inline.
- Feed –Tab that displays the Chatter feed.
- Overview –Tab that displays user details.

ConnectApi.UserType

Type of user.



	<ul style="list-style-type: none">• ChatterOnly –User is a Chatter Free customer.• Guest –User is unauthenticated.• Internal –User is a standard org member.• Portal –User is an external user in an Experience Cl site.• System –User is Chatter Expert or a system user.• Undefined –User is a user type that is a custom obje
ConnectApi.WishlistItemSortOrder	<div>Sort order for wishlist items.</div> <ul style="list-style-type: none">• CreatedDateAsc –Sorts by oldest creation date.• CreatedDateDesc –Sorts by most recent creation da
ConnectApi.WorkflowProcessStatus	<div>Status of a workflow process.</div> <ul style="list-style-type: none">• Approved• Fault• Held• NoResponse• Pending• Reassigned• Rejected• Removed• Started
ConnectApi.ZoneSearchResultType	<div>Zone search result type.</div> <ul style="list-style-type: none">• Article –Search results contain only articles.• Question –Search results contain only questions.
ConnectApi.ZoneShowIn	<div>Zone search result location.</div> <ul style="list-style-type: none">• Community –Available in an Experience Cloud site.• Internal –Available internally only.• Portal –Available in a portal.

DID THIS ARTICLE SOLVE YOUR ISSUE?
Let us know so we can improve!

[Share your feedback](#)



Commerce Cloud
Lightning Design System
Einstein
Quip

Trailhead
Sample Apps
Podcasts
AppExchange

Blog
Salesforce Admins
Salesforce Architects

© Copyright 2025 Salesforce, Inc. [All rights reserved.](#) Various trademarks held by their respective owners. Salesforce, Inc.
Salesforce Tower, 415 Mission Street, 3rd Floor, San Francisco, CA 94105, United States

[Privacy Information](#) [Terms of Service](#) [Legal](#) [Use of Cookies](#) [Trust](#) [Cookie Preferences](#)

[Your Privacy Choices](#) [Responsible Disclosure](#) [Contact](#)