

快速入门

什么是 GoClaw?

安装

快速开始

配置

Web Dashboard 导览

从 OpenClaw 迁移

核心概念

GoClaw 工作原理

Agent 详解

Session 与历史记录

Tools 概览

Memory 系统

多租户

AGENT

创建 Agent

Open vs. Predefined Agent

Context 文件

Summoning 与 Bootstrap

编辑 Agent Personality

共享与访问控制

用户覆盖

System Prompt 结构

PROVIDER

Provider 概览

Anthropic (Claude)

OpenAI / Azure OpenAI

OpenRouter

Google Gemini

DeepSeek

Groq

Mistral

xAI (Grok)

MiniMax

Cohere

REST API 端点目录

自动生成的全部 REST 端点完整索引。请求/响应详情、示例和认证说明，请参见 [REST API 参考](#)。

Total endpoints: 308 — generated from goclaw `d85bf171` on `2026-06-07` .

如何使用本页

这是一个扁平目录 — 每行对应一个端点。

端点按处理器域分组（ `goclaw/internal/http/` 中的源文件）。

有关 OpenAI 兼容端点（ `/v1/chat/completions` 、 `/v1/responses` ）的完整请求/响应 schema，请参见 [REST API 参考](#)。

认证：所有 `/v1/*` 端点均需 `Authorization: Bearer <api-key>`，另有说明的除外。

按领域分组的端点

Activity (`internal/http/activity.go`)

Method	Path
GET	<code>/v1/activity</code>
GET	<code>/v1/activity/aggregate</code>

Browser Cookies (`internal/http/browser_cookies.go`)

Method	Path
GET	<code>/v1/browser/cookies</code>
DELETE	<code>/v1/browser/cookies</code>
POST	<code>/v1/browser/cookies/sync</code>

Agents (`internal/http/agents.go`)

- 快速入门
- 什么是 GoClaw?
- 安装
- 快速开始
- 配置
- Web Dashboard 导览
- 从 OpenClaw 迁移
- 核心概念
- GoClaw 工作原理
- Agent 详解
- Session 与历史记录
- Tools 概览
- Memory 系统
- 多租户

- AGENT
- 创建 Agent
- Open vs. Predefined Agent
- Context 文件
- Summoning 与 Bootstrap
- 编辑 Agent Personality
- 共享与访问控制
- 用户覆盖
- System Prompt 结构

- PROVIDER
- Provider 概览
- Anthropic (Claude)
- OpenAI / Azure OpenAI
- OpenRouter
- Google Gemini
- DeepSeek
- Groq
- Mistral
- xAI (Grok)
- MiniMax
- Cohere

Method	Path	Home	GitHub
GET	/v1/agents		
POST	/v1/agents		
DELETE	/v1/agents/{id}		
GET	/v1/agents/{id}		
PUT	/v1/agents/{id}		
POST	/v1/agents/{id}/cancel-summon		
GET	/v1/agents/{id}/codex-pool-activity		
GET	/v1/agents/{id}/export		
GET	/v1/agents/{id}/export/download/{token}		
GET	/v1/agents/{id}/export/preview		
POST	/v1/agents/{id}/import		
GET	/v1/agents/{id}/instances		
GET	/v1/agents/{id}/instances/{userID}/files		
PUT	/v1/agents/{id}/instances/{userID}/files/{fileName}		
PATCH	/v1/agents/{id}/instances/{userID}/metadata		
POST	/v1/agents/{id}/regenerate		
POST	/v1/agents/{id}/resummon		
GET	/v1/agents/{id}/shares		
POST	/v1/agents/{id}/shares		
DELETE	/v1/agents/{id}/shares/{userID}		
GET	/v1/agents/{id}/system-prompt-preview		
POST	/v1/agents/import		
POST	/v1/agents/import/preview		
POST	/v1/agents/sync-workspace		
GET	/v1/export/download/{token}		
GET	/v1/teams/{id}/export		
GET	/v1/teams/{id}/export/preview		
POST	/v1/teams/import		

API Keys (`internal/http/api_keys.go`)

快速入门

什么是 GoClaw?

安装

快速开始

配置

Web Dashboard 导览

从 OpenClaw 迁移

核心概念

GoClaw 工作原理

Agent 详解

Session 与历史记录

Tools 概览

Memory 系统

多租户

AGENT

创建 Agent

Open vs. Predefined Agent

Context 文件

Summoning 与 Bootstrap

编辑 Agent Personality

共享与访问控制

用户覆盖

System Prompt 结构

PROVIDER

Provider 概览

Anthropic (Claude)

OpenAI / Azure OpenAI

OpenRouter

Google Gemini

DeepSeek

Groq

Mistral

xAI (Grok)

MiniMax

Cohere

GET	/v1/api-keys
POST	/v1/api-keys
POST	/v1/api-keys/{id}/revoke

Backup (internal/http/backup_handler.go)

Method	Path
POST	/v1/system/backup
GET	/v1/system/backup/download/{token}
GET	/v1/system/backup/preflight

Backup (S3) (internal/http/backup_s3_handler.go)

Method	Path
POST	/v1/system/backup/s3/backup
GET	/v1/system/backup/s3/config
PUT	/v1/system/backup/s3/config
GET	/v1/system/backup/s3/list
POST	/v1/system/backup/s3/upload

Builtin Tools (internal/http/builtin_tools.go)

Method	Path
GET	/v1/tools/builtin
GET	/v1/tools/builtin/{name}
PUT	/v1/tools/builtin/{name}
DELETE	/v1/tools/builtin/{name}/tenant-config
GET	/v1/tools/builtin/{name}/tenant-config
PUT	/v1/tools/builtin/{name}/tenant-config

Channels (internal/http/channel_instances.go)

Method	Path
GET	/v1/channels/instances

快速入门

什么是 GoClaw?

安装

快速开始

配置

Web Dashboard 导览

从 OpenClaw 迁移

核心概念

GoClaw 工作原理

Agent 详解

Session 与历史记录

Tools 概览

Memory 系统

多租户

AGENT

创建 Agent

Open vs. Predefined Agent

Context 文件

Summoning 与 Bootstrap

编辑 Agent Personality

共享与访问控制

用户覆盖

System Prompt 结构

PROVIDER

Provider 概览

Anthropic (Claude)

OpenAI / Azure OpenAI

OpenRouter

Google Gemini

DeepSeek

Groq

Mistral

xAI (Grok)

MiniMax

Cohere

Method	Path	Home
		GitHub
POST	/v1/channels/instances	
DELETE	/v1/channels/instances/{id}	
GET	/v1/channels/instances/{id}	
PUT	/v1/channels/instances/{id}	
GET	/v1/channels/instances/{id}/writers	
POST	/v1/channels/instances/{id}/writers	
POST	/v1/channels/instances/{id}/writers/test	
DELETE	/v1/channels/instances/{id}/writers/{userId}	
GET	/v1/channels/instances/{id}/writers/groups	
GET	/v1/contacts	
POST	/v1/contacts/merge	
GET	/v1/contacts/merged/{tenantUserId}	
GET	/v1/contacts/resolve	
POST	/v1/contacts/unmerge	
GET	/v1/tenant-users	
GET	/v1/users/search	

Edition (internal/http/edition.go)

Method	Path
GET	/v1/edition

Episodic Memory (internal/http/episodic_handlers.go)

Method	Path
GET	/v1/agents/{agentID}/episodic
POST	/v1/agents/{agentID}/episodic/search

Evolution (internal/http/evolution_handlers.go)

Method	Path
GET	/v1/agents/{agentID}/evolution/metrics
GET	/v1/agents/{agentID}/evolution/suggestions

- 快速入门
- 什么是 GoClaw?
- 安装
- 快速开始
- 配置
- Web Dashboard 导览
- 从 OpenClaw 迁移

- 核心概念
- GoClaw 工作原理
- Agent 详解
- Session 与历史记录
- Tools 概览
- Memory 系统
- 多租户

- AGENT
- 创建 Agent
- Open vs. Predefined Agent
- Context 文件
- Summoning 与 Bootstrap
- 编辑 Agent Personality
- 共享与访问控制
- 用户覆盖
- System Prompt 结构

- PROVIDER
- Provider 概览
- Anthropic (Claude)
- OpenAI / Azure OpenAI
- OpenRouter
- Google Gemini
- DeepSeek
- Groq

- Mistral
- xAI (Grok)
- MiniMax
- Cohere

PATCH	/v1/agents/{agentID}/evolution/suggestions/{suggestionID}
-------	---

Feature Flags

(internal/http/v3_flags_handlers.go)

Method	Path
GET	/v1/agents/{agentID}/v3-flags
PATCH	/v1/agents/{agentID}/v3-flags

Files (internal/http/files.go)

Method	Path
GET	/v1/files/{path...}
POST	/v1/files/sign

Gateway Upgrade

(internal/http/gateway_upgrade.go)

Method	Path
POST	/v1/system/gateway/upgrade
GET	/v1/system/gateway/upgrade/status

Knowledge Graph

(internal/http/knowledge_graph.go)

Method	Path
GET	/v1/agents/{agentID}/kg/dedup
POST	/v1/agents/{agentID}/kg/dedup/dismiss
POST	/v1/agents/{agentID}/kg/dedup/scan
GET	/v1/agents/{agentID}/kg/entities
POST	/v1/agents/{agentID}/kg/entities
DELETE	/v1/agents/{agentID}/kg/entities/{entityID}
GET	/v1/agents/{agentID}/kg/entities/{entityID}
POST	/v1/agents/{agentID}/kg/extract
GET	/v1/agents/{agentID}/kg/graph
POST	/v1/agents/{agentID}/kg/merge

快速入门

什么是 GoClaw?

安装

快速开始

配置

Web Dashboard 导览

从 OpenClaw 迁移

核心概念

GoClaw 工作原理

Agent 详解

Session 与历史记录

Tools 概览

Memory 系统

多租户

AGENT

创建 Agent

Open vs. Predefined Agent

Context 文件

Summoning 与 Bootstrap

编辑 Agent Personality

共享与访问控制

用户覆盖

System Prompt 结构

PROVIDER

Provider 概览

Anthropic (Claude)

OpenAI / Azure OpenAI

OpenRouter

Google Gemini

DeepSeek

Groq

Mistral

xAI (Grok)

MiniMax

Cohere

GET /v1/agents/{agentID}/kg/stats

POST /v1/agents/{agentID}/kg/traverse

Logs (internal/http/logs.go)

Method	Path
GET	/v1/logs/runtime/aggregate

MCP Servers (internal/http/mcp.go)

Method	Path
GET	/v1/mcp/export
GET	/v1/mcp/export/preview
GET	/v1/mcp/grants/agent/{agentID}
POST	/v1/mcp/import
GET	/v1/mcp/requests
POST	/v1/mcp/requests
POST	/v1/mcp/requests/{id}/review
GET	/v1/mcp/servers
POST	/v1/mcp/servers
DELETE	/v1/mcp/servers/{id}
GET	/v1/mcp/servers/{id}
PUT	/v1/mcp/servers/{id}
GET	/v1/mcp/servers/{id}/grants
POST	/v1/mcp/servers/{id}/grants/agent
DELETE	/v1/mcp/servers/{id}/grants/agent/{agentID}
POST	/v1/mcp/servers/{id}/grants/user
DELETE	/v1/mcp/servers/{id}/grants/user/{userID}
POST	/v1/mcp/servers/{id}/reconnect
GET	/v1/mcp/servers/{id}/tools
POST	/v1/mcp/servers/test

快速入门

什么是 GoClaw?

安装

快速开始

配置

Web Dashboard 导览

从 OpenClaw 迁移

核心概念

GoClaw 工作原理

Agent 详解

Session 与历史记录

Tools 概览

Memory 系统

多租户

AGENT

创建 Agent

Open vs. Predefined Agent

Context 文件

Summoning 与 Bootstrap

编辑 Agent Personality

共享与访问控制

用户覆盖

System Prompt 结构

PROVIDER

Provider 概览

Anthropic (Claude)

OpenAI / Azure OpenAI

OpenRouter

Google Gemini

DeepSeek

Groq

Mistral

xAI (Grok)

MiniMax

Cohere

Method	Path
DELETE	/v1/mcp/servers/{id}/user-credentials
GET	/v1/mcp/servers/{id}/user-credentials
PUT	/v1/mcp/servers/{id}/user-credentials

Media (internal/http/media_serve.go)

Method	Path
GET	/v1/media/{id}
POST	/v1/media/upload

Memory (internal/http/memory.go)

Method	Path
GET	/v1/agents/{agentID}/memory/chunks
GET	/v1/agents/{agentID}/memory/documents
DELETE	/v1/agents/{agentID}/memory/documents/{path...}
GET	/v1/agents/{agentID}/memory/documents/{path...}
PUT	/v1/agents/{agentID}/memory/documents/{path...}
POST	/v1/agents/{agentID}/memory/index
POST	/v1/agents/{agentID}/memory/index-all
POST	/v1/agents/{agentID}/memory/search
GET	/v1/memory/documents

Model Pricing (internal/http/usage_caps.go)

Method	Path
GET	/v1/model-pricing
GET	/v1/model-pricing/overrides
PUT	/v1/model-pricing/overrides
DELETE	/v1/model-pricing/overrides/{id}
POST	/v1/model-pricing/sync-openrouter

- 快速入门
- 什么是 GoClaw?
- 安装
- 快速开始
- 配置
- Web Dashboard 导览
- 从 OpenClaw 迁移
- 核心概念
- GoClaw 工作原理
- Agent 详解
- Session 与历史记录
- Tools 概览
- Memory 系统
- 多租户

- AGENT
- 创建 Agent
- Open vs. Predefined Agent
- Context 文件
- Summoning 与 Bootstrap
- 编辑 Agent Personality
- 共享与访问控制
- 用户覆盖
- System Prompt 结构

- PROVIDER
- Provider 概览
- Anthropic (Claude)
- OpenAI / Azure OpenAI
- OpenRouter
- Google Gemini
- DeepSeek
- Groq
- Mistral
- xAI (Grok)
- MiniMax
- Cohere

Method	Path
POST	<code>/v1/auth/chatgpt/{provider}/callback</code>
POST	<code>/v1/auth/chatgpt/{provider}/logout</code>
GET	<code>/v1/auth/chatgpt/{provider}/quota</code>
POST	<code>/v1/auth/chatgpt/{provider}/start</code>
GET	<code>/v1/auth/chatgpt/{provider}/status</code>
POST	<code>/v1/auth/openai/callback</code>
POST	<code>/v1/auth/openai/logout</code>
GET	<code>/v1/auth/openai/quota</code>
POST	<code>/v1/auth/openai/start</code>
GET	<code>/v1/auth/openai/status</code>

OpenAPI (`internal/http/openapi.go`)

Method	Path
GET	<code>/docs</code>
GET	<code>/docs/</code>
GET	<code>/v1/openapi.json</code>

Orchestration (`internal/http/orchestration_handlers.go`)

Method	Path
GET	<code>/v1/agents/{agentID}/orchestration</code>

Packages (`internal/http/packages.go`)

Method	Path
GET	<code>/v1/packages</code>
GET	<code>/v1/packages/github-releases</code>
POST	<code>/v1/packages/install</code>
GET	<code>/v1/packages/runtimes</code>
POST	<code>/v1/packages/uninstall</code>
POST	<code>/v1/packages/update</code>

- 快速入门
- 什么是 GoClaw?
- 安装
- 快速开始
- 配置
- Web Dashboard 导览
- 从 OpenClaw 迁移

- 核心概念
- GoClaw 工作原理
- Agent 详解
- Session 与历史记录
- Tools 概览
- Memory 系统
- 多租户

- AGENT
- 创建 Agent
- Open vs. Predefined Agent
- Context 文件
- Summoning 与 Bootstrap
- 编辑 Agent Personality
- 共享与访问控制
- 用户覆盖
- System Prompt 结构

- PROVIDER
- Provider 概览
- Anthropic (Claude)
- OpenAI / Azure OpenAI
- OpenRouter
- Google Gemini
- DeepSeek
- Groq
- Mistral
- xAI (Grok)
- MiniMax
- Cohere

GET	/v1/packages/updates
POST	/v1/packages/updates/apply-all
POST	/v1/packages/updates/refresh
GET	/v1/shell-deny-groups

Pending Messages

(`internal/http/pending_messages.go`)

Method	Path
DELETE	/v1/pending-messages
GET	/v1/pending-messages
POST	/v1/pending-messages/compact
GET	/v1/pending-messages/messages

Providers (`internal/http/providers.go`)

Method	Path
GET	/v1/embedding/status
GET	/v1/providers
POST	/v1/providers
DELETE	/v1/providers/{id}
GET	/v1/providers/{id}
PUT	/v1/providers/{id}
GET	/v1/providers/{id}/codex-pool-activity
GET	/v1/providers/{id}/models
POST	/v1/providers/{id}/reconnect
POST	/v1/providers/{id}/verify
POST	/v1/providers/{id}/verify-embedding
GET	/v1/providers/claude-cli/auth-status

Restore (`internal/http/restore_handler.go`)

Method	Path
POST	/v1/system/restore

- 快速入门
- 什么是 GoClaw?
- 安装
- 快速开始
- 配置
- Web Dashboard 导览
- 从 OpenClaw 迁移

- 核心概念
- GoClaw 工作原理
- Agent 详解
- Session 与历史记录
- Tools 概览
- Memory 系统
- 多租户

- AGENT
- 创建 Agent
- Open vs. Predefined Agent
- Context 文件
- Summoning 与 Bootstrap
- 编辑 Agent Personality
- 共享与访问控制
- 用户覆盖
- System Prompt 结构

- PROVIDER
- Provider 概览
- Anthropic (Claude)
- OpenAI / Azure OpenAI
- OpenRouter
- Google Gemini
- DeepSeek
- Groq
- Mistral
- xAI (Grok)
- MiniMax
- Cohere

Method	Path
GET	<code>/v1/cli-credentials</code>
POST	<code>/v1/cli-credentials</code>
DELETE	<code>/v1/cli-credentials/{id}</code>
GET	<code>/v1/cli-credentials/{id}</code>
PUT	<code>/v1/cli-credentials/{id}</code>
GET	<code>/v1/cli-credentials/{id}/agent-grants</code>
POST	<code>/v1/cli-credentials/{id}/agent-grants</code>
DELETE	<code>/v1/cli-credentials/{id}/agent-grants/{grantId}</code>
GET	<code>/v1/cli-credentials/{id}/agent-grants/{grantId}</code>
PUT	<code>/v1/cli-credentials/{id}/agent-grants/{grantId}</code>
POST	<code>/v1/cli-credentials/{id}/agent-grants/{grantId}/env:reveal</code>
POST	<code>/v1/cli-credentials/{id}/test</code>
GET	<code>/v1/cli-credentials/{id}/user-credentials</code>
DELETE	<code>/v1/cli-credentials/{id}/user-credentials/{userId}</code>
GET	<code>/v1/cli-credentials/{id}/user-credentials/{userId}</code>
PUT	<code>/v1/cli-credentials/{id}/user-credentials/{userId}</code>
POST	<code>/v1/cli-credentials/check-binary</code>
GET	<code>/v1/cli-credentials/presets</code>

Sessions (`internal/http/sessions.go`)

Method	Path
GET	<code>/v1/sessions</code>
POST	<code>/v1/chat/sessions/{key}/branch</code>
GET	<code>/v1/chat/sessions/{key}/history/follow</code>

Skills (`internal/http/skills.go`)

快速入门

什么是 GoClaw?

安装

快速开始

配置

Web Dashboard 导览

从 OpenClaw 迁移

核心概念

GoClaw 工作原理

Agent 详解

Session 与历史记录

Tools 概览

Memory 系统

多租户

AGENT

创建 Agent

Open vs. Predefined Agent

Context 文件

Summoning 与 Bootstrap

编辑 Agent Personality

共享与访问控制

用户覆盖

System Prompt 结构

PROVIDER

Provider 概览

Anthropic (Claude)

OpenAI / Azure OpenAI

OpenRouter

Google Gemini

DeepSeek

Groq

Mistral

xAI (Grok)

MiniMax

Cohere

GET	/v1/agents/{agentID}/skills
GET	/v1/skills
DELETE	/v1/skills/{id}
GET	/v1/skills/{id}
PUT	/v1/skills/{id}
GET	/v1/skills/{id}/files
GET	/v1/skills/{id}/files/{path...}
GET	/v1/skills/{id}/grants/agent
POST	/v1/skills/{id}/grants/agent
DELETE	/v1/skills/{id}/grants/agent/{agentID}
POST	/v1/skills/{id}/grants/user
DELETE	/v1/skills/{id}/grants/user/{userID}
DELETE	/v1/skills/{id}/tenant-config
PUT	/v1/skills/{id}/tenant-config
POST	/v1/skills/{id}/toggle
GET	/v1/skills/{id}/versions
GET	/v1/skills/export
GET	/v1/skills/export/preview
POST	/v1/skills/import
POST	/v1/skills/install-dep
POST	/v1/skills/install-deps
POST	/v1/skills/rescan-deps
GET	/v1/skills/runtimes
POST	/v1/skills/upload

Storage (internal/http/storage.go)

Method	Path
GET	/v1/storage/files
POST	/v1/storage/files
DELETE	/v1/storage/files/{path...}

- 快速入门
- 什么是 GoClaw?
- 安装
- 快速开始
- 配置
- Web Dashboard 导览
- 从 OpenClaw 迁移
- 核心概念
- GoClaw 工作原理
- Agent 详解
- Session 与历史记录
- Tools 概览
- Memory 系统
- 多租户

- AGENT
- 创建 Agent
- Open vs. Predefined Agent
- Context 文件
- Summoning 与 Bootstrap
- 编辑 Agent Personality
- 共享与访问控制
- 用户覆盖
- System Prompt 结构
- PROVIDER
- Provider 概览
- Anthropic (Claude)
- OpenAI / Azure OpenAI
- OpenRouter
- Google Gemini
- DeepSeek
- Groq
- Mistral
- xAI (Grok)
- MiniMax
- Cohere

GET	/v1/storage/files/{path...}
PUT	/v1/storage/move
GET	/v1/storage/size

System Config (internal/http/system_configs.go)

Method	Path
GET	/v1/system-configs
DELETE	/v1/system-configs/{key}
GET	/v1/system-configs/{key}
PUT	/v1/system-configs/{key}

Teams (internal/http/team_attachments.go)

Method	Path
GET	/v1/teams/{id}/events
GET	/v1/teams/{teamId}/attachments/{attachmentId}/download

Tenant Backup (internal/http/tenant_backup_handler.go)

Method	Path
POST	/v1/tenant/backup
GET	/v1/tenant/backup/download/{token}
GET	/v1/tenant/backup/preflight
POST	/v1/tenant/restore

Tenants (internal/http/tenants.go)

Method	Path
GET	/v1/tenants
POST	/v1/tenants
GET	/v1/tenants/{id}
PATCH	/v1/tenants/{id}
GET	/v1/tenants/{id}/users

快速入门

什么是 GoClaw?

安装

快速开始

配置

Web Dashboard 导览

从 OpenClaw 迁移

核心概念

GoClaw 工作原理

Agent 详解

Session 与历史记录

Tools 概览

Memory 系统

多租户

AGENT

创建 Agent

Open vs. Predefined Agent

Context 文件

Summoning 与 Bootstrap

编辑 Agent Personality

共享与访问控制

用户覆盖

System Prompt 结构

PROVIDER

Provider 概览

Anthropic (Claude)

OpenAI / Azure OpenAI

OpenRouter

Google Gemini

DeepSeek

Groq

Mistral

xAI (Grok)

MiniMax

Cohere

POST

/v1/tenants/{id}/users

DELETE

/v1/tenants/{id}/users/{userId}

Traces (`internal/http/traces.go`)

Method	Path
GET	/v1/costs/summary
GET	/v1/traces
GET	/v1/traces/follow
GET	/v1/traces/{traceID}
GET	/v1/traces/{traceID}/export

TTS (`internal/http/tts.go`)

Method	Path
GET	/v1/tts/capabilities
GET	/v1/tts/config
POST	/v1/tts/config
POST	/v1/tts/synthesize
POST	/v1/tts/test-connection
GET	/v1/voices
POST	/v1/voices/refresh

Usage (`internal/http/usage.go`)

Method	Path
GET	/v1/usage/breakdown
GET	/v1/usage/summary
GET	/v1/usage/timeseries

Usage Caps (`internal/http/usage_caps.go`)

Method	Path
GET	/v1/usage-caps/policies
POST	/v1/usage-caps/policies

- 快速入门
- 什么是 GoClaw?
- 安装
- 快速开始
- 配置
- Web Dashboard 导览
- 从 OpenClaw 迁移

- 核心概念
- GoClaw 工作原理
- Agent 详解
- Session 与历史记录
- Tools 概览
- Memory 系统
- 多租户
- AGENT
- 创建 Agent
- Open vs. Predefined Agent
- Context 文件
- Summoning 与 Bootstrap
- 编辑 Agent Personality
- 共享与访问控制
- 用户覆盖
- System Prompt 结构

- PROVIDER
- Provider 概览
- Anthropic (Claude)
- OpenAI / Azure OpenAI
- OpenRouter
- Google Gemini
- DeepSeek
- Groq
- Mistral
- xAI (Grok)
- MiniMax
- Cohere

Method	Path
PATCH	/v1/usage-caps/policies/{id}
DELETE	/v1/usage-caps/policies/{id}
GET	/v1/usage-caps/utilization
GET	/v1/usage-caps/events

Vault (internal/http/vault_graph_handler.go)

Method	Path
GET	/v1/agents/{agentID}/kg/graph/compact
GET	/v1/agents/{agentID}/vault/documents
POST	/v1/agents/{agentID}/vault/documents
DELETE	/v1/agents/{agentID}/vault/documents/{docID}
GET	/v1/agents/{agentID}/vault/documents/{docID}
PUT	/v1/agents/{agentID}/vault/documents/{docID}
GET	/v1/agents/{agentID}/vault/documents/{docID}/links
POST	/v1/agents/{agentID}/vault/links
DELETE	/v1/agents/{agentID}/vault/links/{linkID}
POST	/v1/agents/{agentID}/vault/search
GET	/v1/vault/documents
POST	/v1/vault/documents
DELETE	/v1/vault/documents/{docID}
GET	/v1/vault/documents/{docID}
PUT	/v1/vault/documents/{docID}
GET	/v1/vault/documents/{docID}/links
GET	/v1/vault/enrichment/status
POST	/v1/vault/enrichment/stop
GET	/v1/vault/graph
POST	/v1/vault/links
DELETE	/v1/vault/links/{linkID}
POST	/v1/vault/links/batch
POST	/v1/vault/rescan

- 快速入门
- 什么是 GoClaw?
- 安装
- 快速开始
- 配置
- Web Dashboard 导览
- 从 OpenClaw 迁移

- 核心概念
- GoClaw 工作原理
- Agent 详解
- Session 与历史记录
- Tools 概览
- Memory 系统
- 多租户

- AGENT
- 创建 Agent
- Open vs. Predefined Agent
- Context 文件
- Summoning 与 Bootstrap
- 编辑 Agent Personality
- 共享与访问控制
- 用户覆盖
- System Prompt 结构

- PROVIDER
- Provider 概览
- Anthropic (Claude)
- OpenAI / Azure OpenAI
- OpenRouter
- Google Gemini
- DeepSeek
- Groq
- Mistral
- xAI (Grok)
- MiniMax
- Cohere

POST	/v1/vault/search
GET	/v1/vault/tree
POST	/v1/vault/upload

Wake (internal/http/wake.go)

Method	Path
POST	/v1/agents/{id}/wake

Webhooks (internal/http/webhooks_admin.go , webhooks_llm.go , webhooks_message.go)

Method	Path
GET	/v1/webhooks
POST	/v1/webhooks
DELETE	/v1/webhooks/{id}
GET	/v1/webhooks/{id}
PATCH	/v1/webhooks/{id}
POST	/v1/webhooks/{id}/rotate
POST	/v1/webhooks/llm
POST	/v1/webhooks/message

Workspace (internal/http/workspace_upload.go)

Method	Path
PUT	/v1/teams/{teamId}/workspace/move
POST	/v1/teams/{teamId}/workspace/upload

Workstations (internal/http/workstations.go)

仅 Standard 版本 — Lite 版 gateway 返回 403 。

Method	Path
GET	/v1/workstations
POST	/v1/workstations

- 快速入门
- 什么是 GoClaw?
- 安装
- 快速开始
- 配置
- Web Dashboard 导览
- 从 OpenClaw 迁移
- 核心概念
- GoClaw 工作原理
- Agent 详解
- Session 与历史记录
- Tools 概览
- Memory 系统
- 多租户

- AGENT
- 创建 Agent
- Open vs. Predefined Agent
- Context 文件
- Summoning 与 Bootstrap
- 编辑 Agent Personality
- 共享与访问控制
- 用户覆盖
- System Prompt 结构

- PROVIDER
- Provider 概览
- Anthropic (Claude)
- OpenAI / Azure OpenAI
- OpenRouter
- Google Gemini
- DeepSeek
- Groq
- Mistral
- xAI (Grok)
- MiniMax
- Cohere

Method	Path	Home
DELETE	/v1/workstations/{id}	
GET	/v1/workstations/{id}	
PUT	/v1/workstations/{id}	
GET	/v1/workstations/{id}/activity	
GET	/v1/workstations/{id}/permissions	
POST	/v1/workstations/{id}/permissions	
DELETE	/v1/workstations/{id}/permissions/{permId}	
PUT	/v1/workstations/{id}/permissions/{permId}/toggle	
POST	/v1/workstations/{id}/test	

 d85bf171 · 最后更新于 2026-06-07