

# Smith Replication Data Analysis

Laura Marusich, Jon Bakdash, Emilie Caron

2022-05-04

```
sessionInfo()
```

```
## R version 4.1.2 (2021-11-01)
## Platform: x86_64-w64-mingw32/x64 (64-bit)
## Running under: Windows 10 x64 (build 19044)
##
## Matrix products: default
##
## locale:
## [1] LC_COLLATE=English_United States.1252 LC_CTYPE=English_United States.1252
## [3] LC_MONETARY=English_United States.1252 LC_NUMERIC=C
## [5] LC_TIME=English_United States.1252
##
## attached base packages:
## [1] stats      graphics  grDevices  utils      datasets  methods   base
##
## other attached packages:
## [1] scales_1.1.1      rlang_1.0.2      cowplot_1.1.1    readxl_1.3.1
## [5] reshape2_1.4.4    superb_0.9.7.8    psychReport_3.0.1  apaTables_2.0.8
## [9] psych_2.1.9        BayesFactor_0.9.12-4.3 coda_0.19-4       ez_4.4-0
## [13] afex_1.0-1         lme4_1.1-27.1     Matrix_1.3-4      forcats_0.5.1
## [17] stringr_1.4.0      dplyr_1.0.8       purrr_0.3.4       readr_2.1.1
## [21] tidyr_1.1.4        tibble_3.1.6      ggplot2_3.3.5     tidyverse_1.3.1
## [25] plyr_1.8.6         rmarkdown_2.11    knitr_1.36        pacman_0.5.1
##
## loaded via a namespace (and not attached):
## [1] TH.data_1.1-0      minqa_1.2.4        colorspace_2.0-2    ellipsis_0.3.2
## [5] estimability_1.3    fs_1.5.1            rstudioapi_0.13     MatrixModels_0.5-0
## [9] fansi_0.5.0        mvtnorm_1.1-3       lubridate_1.8.0     xml2_1.3.3
## [13] codetools_0.2-18    splines_4.1.2       mnormt_2.0.2        jsonlite_1.7.2
## [17] lsr_0.5.2           nloptr_1.2.2.3      broom_0.7.10        dbplyr_2.1.1
## [21] shiny_1.7.1         compiler_4.1.2      httr_1.4.2          emmeans_1.7.1-1
## [25] backports_1.4.0     assertthat_0.2.1    fastmap_1.1.0       cli_3.1.0
## [29] later_1.3.0         htmltools_0.5.2     tools_4.1.2         lmerTest_3.1-3
## [33] gtable_0.3.0        glue_1.5.1          Rcpp_1.0.7          carData_3.0-4
## [37] cellranger_1.1.0    vctrs_0.3.8         nlme_3.1-153        xfun_0.28
## [41] rbibutils_2.2.7     rvest_1.0.2         mime_0.12           lifecycle_1.0.1
## [45] gtools_3.9.2        MASS_7.3-54         zoo_1.8-9           shinyBS_0.61
## [49] promises_1.2.0.1    hms_1.1.1           parallel_4.1.2      sandwich_3.0-1
## [53] yaml_2.2.1          pbapply_1.5-0       stringi_1.7.6       boot_1.3-28
## [57] Rdpack_2.1.3        pkgconfig_2.0.3     evaluate_0.14       lattice_0.20-45
## [61] tidyselect_1.1.2    magrittr_2.0.1      R6_2.5.1            generics_0.1.2
## [65] multcomp_1.4-17     DBI_1.1.1           foreign_0.8-81      pillar_1.7.0
```

```
## [69] haven_2.4.3      withr_2.4.3      mgcv_1.8-38      survival_3.2-13
## [73] abind_1.4-5      modelr_0.1.8     crayon_1.5.1     car_3.0-12
## [77] utf8_1.2.2       tmvnsim_1.0-2    tzdb_0.2.0       grid_4.1.2
## [81] reprex_2.0.1     digest_0.6.29    xtable_1.8-4     httpuv_1.6.3
## [85] numDeriv_2016.8-1.1 munsell_0.5.0
```

## Experiment 1 - Stroop

### Import and clean data

```
stroop_files = list.files(path = "Experiment 1 Data/", full.names = T)
stroop_files = stroop_files[str_detect(stroop_files, pattern="(?!.*SJ)(?!.*.txt)")]

mergedStroopData <- ldply(stroop_files,
  read.delim,
  header=FALSE,
  stringsAsFactors = FALSE,
  sep = "") #for each item in the list apply the function read.delim

names(mergedStroopData) = c("sj",
  "cb",
  "blockNumber",
  "blockType",
  "trialNum",
  "congruency",
  "posture",
  "wordStim",
  "inkColour",
  "rt",
  "cResp",
  "resp",
  "ac")

#...remove problem subjects
#.. No subjects pre-identified as needing to be removed (see ethics protocol)

#...check number of observations per condition
ftable(posture+congruency~sj, mergedStroopData)
```

```
##      posture      SITTING      STANDING
##      congruency congruent incongruent neutral congruent incongruent neutral
## sj
## 1           60           60           60           60           60           60
## 2           60           60           60           60           60           60
## 3           60           60           60           60           60           60
## 4           60           60           60           60           60           60
## 5           60           60           60           60           60           60
## 6           60           60           60           60           60           60
## 7           60           60           60           60           60           60
## 8           60           60           60           60           60           60
## 9           60           60           60           60           60           60
## 10          60           60           60           60           60           60
## 11          60           60           60           60           60           60
## 12          60           60           60           60           60           60
```

## 13	60	60	60	60	60	60
## 14	60	60	60	60	60	60
## 15	60	60	60	60	60	60
## 16	60	60	60	60	60	60
## 17	60	60	60	60	60	60
## 18	60	60	60	60	60	60
## 19	60	60	60	60	60	60
## 20	60	60	60	60	60	60
## 21	60	60	60	60	60	60
## 22	120	120	120	120	120	120
## 24	60	60	60	60	60	60
## 25	60	60	60	60	60	60
## 26	60	60	60	60	60	60
## 27	60	60	60	60	60	60
## 28	60	60	60	60	60	60
## 29	60	60	60	60	60	60
## 30	60	60	60	60	60	60
## 31	60	60	60	60	60	60
## 32	60	60	60	60	60	60
## 33	60	60	60	60	60	60
## 34	60	60	60	60	60	60
## 35	60	60	60	60	60	60
## 36	60	60	60	60	60	60
## 37	60	60	60	60	60	60
## 38	60	60	60	60	60	60
## 39	60	60	60	60	60	60
## 40	60	60	60	60	60	60
## 41	60	60	60	60	60	60
## 42	60	60	60	60	60	60
## 43	60	60	60	60	60	60
## 44	60	60	60	60	60	60
## 45	60	60	60	60	60	60
## 46	60	60	60	60	60	60
## 47	60	60	60	60	60	60
## 48	60	60	60	60	60	60
## 49	60	60	60	60	60	60
## 50	60	60	60	60	60	60

```
ftable(blockType~sj, mergedStroopData)
```

##	blockType	experimental	practice
## sj			
## 1	288	72	
## 2	288	72	
## 3	288	72	
## 4	288	72	
## 5	288	72	
## 6	288	72	
## 7	288	72	
## 8	288	72	
## 9	288	72	
## 10	288	72	
## 11	288	72	
## 12	288	72	
## 13	288	72	

```
## 14          288      72
## 15          288      72
## 16          288      72
## 17          288      72
## 18          288      72
## 19          288      72
## 20          288      72
## 21          288      72
## 22          576     144
## 24          288      72
## 25          288      72
## 26          288      72
## 27          288      72
## 28          288      72
## 29          288      72
## 30          288      72
## 31          288      72
## 32          288      72
## 33          288      72
## 34          288      72
## 35          288      72
## 36          288      72
## 37          288      72
## 38          288      72
## 39          288      72
## 40          288      72
## 41          288      72
## 42          288      72
## 43          288      72
## 44          288      72
## 45          288      72
## 46          288      72
## 47          288      72
## 48          288      72
## 49          288      72
## 50          288      72
```

```
##...need to fix SJ - same one was used with two counterbalances
mergedStroopData$sj = paste(mergedStroopData$sj, "_", mergedStroopData$cb, sep="")
```

```
##...check for missing data
mergedStroopData[!complete.cases(mergedStroopData),]
```

##	sj	cb	blockNumber	blockType	trialNum	congruency	posture	wordStim	inkColour	rt	cResp
## 646	10_2	2	8	experimental	34	incongruent	STANDING	RED	green	0	2
## 1081	12_2	2	1	practice	1	neutral	SITTING	XXXXX	green	0	2
## 1117	12_2	2	2	experimental	1	incongruent	SITTING	GREEN	red	0	1
## 1445	13_1	1	1	practice	5	incongruent	STANDING	GREEN	red	0	1
## 1801	14_2	2	1	practice	1	neutral	SITTING	XXX	green	0	2
## 2162	15_1	1	1	practice	2	congruent	STANDING	GREEN	green	0	2
## 2163	15_1	1	1	practice	3	neutral	STANDING	XXXXX	green	0	2
## 2615	16_2	2	3	experimental	23	incongruent	SITTING	RED	green	0	2
## 2720	16_2	2	6	practice	20	neutral	STANDING	XXX	red	0	1
## 2737	16_2	2	7	experimental	1	incongruent	STANDING	GREEN	red	0	1
## 2885	17_1	1	1	practice	5	incongruent	STANDING	RED	green	0	2

## 3360	18_2	2	4	experimental	12	incongruent	SITTING	GREEN	red	0	1
## 3457	18_2	2	7	experimental	1	incongruent	STANDING	RED	green	0	2
## 3601	19_1	1	1	practice	1	congruent	STANDING	RED	red	0	1
## 4370	20_2	2	2	experimental	14	neutral	SITTING	XXXXX	red	0	1
## 4505	20_2	2	6	practice	5	incongruent	STANDING	GREEN	red	0	1
## 4681	21_1	1	1	practice	1	congruent	STANDING	RED	red	0	1
## 4682	21_1	1	1	practice	2	neutral	STANDING	XXX	red	0	1
## 4692	21_1	1	1	practice	12	incongruent	STANDING	RED	green	0	2
## 5041	22_1	1	1	practice	1	incongruent	STANDING	GREEN	red	0	1
## 5042	22_1	1	1	practice	2	incongruent	STANDING	RED	green	0	2
## 5043	22_1	1	1	practice	3	neutral	STANDING	XXX	red	0	1
## 5422	22_2	2	1	practice	22	incongruent	SITTING	GREEN	red	0	1
## 5428	22_2	2	1	practice	28	incongruent	SITTING	RED	green	0	2
## 5501	22_2	2	3	experimental	29	neutral	SITTING	XXXXX	red	0	1
## 5530	22_2	2	4	experimental	22	incongruent	SITTING	RED	green	0	2
## 5533	22_2	2	4	experimental	25	incongruent	SITTING	RED	green	0	2
## 5608	22_2	2	6	practice	28	incongruent	STANDING	GREEN	red	0	1
## 5621	22_2	2	7	experimental	5	neutral	STANDING	XXXXX	green	0	2
## 5644	22_2	2	7	experimental	28	neutral	STANDING	XXX	green	0	2
## 5668	22_2	2	8	experimental	16	incongruent	STANDING	GREEN	red	0	1
## 5684	22_2	2	8	experimental	32	neutral	STANDING	XXXXX	red	0	1
## 5741	22_2	2	10	experimental	17	neutral	STANDING	XXX	green	0	2
## 5761	24_2	2	1	practice	1	congruent	SITTING	RED	red	0	1
## 5763	24_2	2	1	practice	3	congruent	SITTING	GREEN	green	0	2
## 5768	24_2	2	1	practice	8	neutral	SITTING	XXX	green	0	2
## 5770	24_2	2	1	practice	10	incongruent	SITTING	RED	green	0	2
## 5772	24_2	2	1	practice	12	congruent	SITTING	GREEN	green	0	2
## 5773	24_2	2	1	practice	13	neutral	SITTING	XXX	red	0	1
## 5775	24_2	2	1	practice	15	incongruent	SITTING	GREEN	red	0	1
## 5776	24_2	2	1	practice	16	neutral	SITTING	XXXXX	green	0	2
## 5797	24_2	2	2	experimental	1	neutral	SITTING	XXXXX	green	0	2
## 5798	24_2	2	2	experimental	2	incongruent	SITTING	RED	green	0	2
## 6018	24_2	2	8	experimental	6	congruent	STANDING	RED	red	0	1
## 6121	25_1	1	1	practice	1	neutral	STANDING	XXX	red	0	1
## 6482	26_2	2	1	practice	2	neutral	SITTING	XXXXX	red	0	1
## 6518	26_2	2	2	experimental	2	incongruent	SITTING	RED	green	0	2
## 6841	27_1	1	1	practice	1	congruent	STANDING	RED	red	0	1
## 6842	27_1	1	1	practice	2	neutral	STANDING	XXXXX	green	0	2
## 6843	27_1	1	1	practice	3	neutral	STANDING	XXXXX	red	0	1
## 7202	28_2	2	1	practice	2	incongruent	SITTING	GREEN	red	0	1
## 7921	3_1	1	1	practice	1	congruent	STANDING	GREEN	green	0	2
## 7957	3_1	1	2	experimental	1	neutral	STANDING	XXXXX	red	0	1
## 8858	31_1	1	7	experimental	2	congruent	SITTING	RED	red	0	1
## 9253	32_2	2	8	experimental	1	neutral	STANDING	XXX	green	0	2
## 9361	33_1	1	1	practice	1	congruent	STANDING	RED	red	0	1
## 9364	33_1	1	1	practice	4	incongruent	STANDING	GREEN	red	0	1
## 9386	33_1	1	1	practice	26	congruent	STANDING	GREEN	green	0	2
## 9390	33_1	1	1	practice	30	neutral	STANDING	XXX	red	0	1
## 9505	33_1	1	5	experimental	1	neutral	STANDING	XXXXX	red	0	1
## 10441	36_2	2	1	practice	1	congruent	SITTING	GREEN	green	0	2
## 10444	36_2	2	1	practice	4	incongruent	SITTING	GREEN	red	0	1
## 10447	36_2	2	1	practice	7	incongruent	SITTING	RED	green	0	2
## 10448	36_2	2	1	practice	8	neutral	SITTING	XXX	green	0	2
## 10535	36_2	2	3	experimental	23	incongruent	SITTING	GREEN	red	0	1

## 10639	36_2	2	6	practice	19	neutral	STANDING	XXXXX	green	0	2
## 10785	36_2	2	10	experimental	21	congruent	STANDING	GREEN	green	0	2
## 11294	38_2	2	4	experimental	26	incongruent	SITTING	RED	green	0	2
## 11387	38_2	2	7	experimental	11	neutral	STANDING	XXX	green	0	2
## 11418	38_2	2	8	experimental	6	incongruent	STANDING	RED	green	0	2
## 11421	38_2	2	8	experimental	9	incongruent	STANDING	GREEN	red	0	1
## 12202	4_2	2	9	experimental	34	incongruent	STANDING	GREEN	red	0	1
## 12241	40_2	2	1	practice	1	incongruent	SITTING	RED	green	0	2
## 13603	43_1	1	8	experimental	31	incongruent	SITTING	RED	green	0	2
## 13688	44_2	2	1	practice	8	incongruent	SITTING	RED	green	0	2
## 13689	44_2	2	1	practice	9	incongruent	SITTING	GREEN	red	0	1
## 13694	44_2	2	1	practice	14	incongruent	SITTING	GREEN	red	0	1
## 13695	44_2	2	1	practice	15	neutral	SITTING	XXXXX	red	0	1
## 13696	44_2	2	1	practice	16	incongruent	SITTING	RED	green	0	2
## 13702	44_2	2	1	practice	22	congruent	SITTING	GREEN	green	0	2
## 13709	44_2	2	1	practice	29	incongruent	SITTING	GREEN	red	0	1
## 13713	44_2	2	1	practice	33	incongruent	SITTING	RED	green	0	2
## 13715	44_2	2	1	practice	35	incongruent	SITTING	GREEN	red	0	1
## 13716	44_2	2	1	practice	36	congruent	SITTING	GREEN	green	0	2
## 13717	44_2	2	2	experimental	1	congruent	SITTING	RED	red	0	1
## 13721	44_2	2	2	experimental	5	incongruent	SITTING	GREEN	red	0	1
## 14041	45_1	1	1	practice	1	congruent	STANDING	GREEN	green	0	2
## 14379	45_1	1	10	experimental	15	neutral	SITTING	XXXXX	green	0	2
## 14864	47_1	1	3	experimental	32	congruent	STANDING	RED	red	0	1
## 14901	47_1	1	4	experimental	33	neutral	STANDING	XXX	green	0	2
## 14958	47_1	1	6	practice	18	incongruent	SITTING	RED	green	0	2
## 15121	48_2	2	1	practice	1	congruent	SITTING	GREEN	green	0	2
## 15842	5_1	1	1	practice	2	incongruent	STANDING	GREEN	red	0	1
## 15843	5_1	1	1	practice	3	congruent	STANDING	RED	red	0	1
## 15845	5_1	1	1	practice	5	congruent	STANDING	GREEN	green	0	2
## 15846	5_1	1	1	practice	6	incongruent	STANDING	RED	green	0	2
## 15847	5_1	1	1	practice	7	neutral	STANDING	XXX	green	0	2
## 16107	5_1	1	8	experimental	15	neutral	SITTING	XXX	red	0	1
## 16201	50_2	2	1	practice	1	incongruent	SITTING	GREEN	red	0	1
## 16565	6_2	2	1	practice	5	congruent	SITTING	RED	red	0	1
## 16957	7_1	1	2	experimental	1	neutral	STANDING	XXX	green	0	2
## 17282	8_2	2	1	practice	2	incongruent	SITTING	GREEN	red	0	1
## 17643	9_1	1	1	practice	3	congruent	STANDING	GREEN	green	0	2
## 17644	9_1	1	1	practice	4	incongruent	STANDING	RED	green	0	2
##	resp ac										
## 646	0	NA									
## 1081	0	NA									
## 1117	0	NA									
## 1445	0	NA									
## 1801	0	NA									
## 2162	0	NA									
## 2163	0	NA									
## 2615	0	NA									
## 2720	0	NA									
## 2737	0	NA									
## 2885	0	NA									
## 3360	0	NA									
## 3457	0	NA									
## 3601	0	NA									

## 4370	0 NA
## 4505	0 NA
## 4681	0 NA
## 4682	0 NA
## 4692	0 NA
## 5041	0 NA
## 5042	0 NA
## 5043	0 NA
## 5422	0 NA
## 5428	0 NA
## 5501	0 NA
## 5530	0 NA
## 5533	0 NA
## 5608	0 NA
## 5621	0 NA
## 5644	0 NA
## 5668	0 NA
## 5684	0 NA
## 5741	0 NA
## 5761	0 NA
## 5763	0 NA
## 5768	0 NA
## 5770	0 NA
## 5772	0 NA
## 5773	0 NA
## 5775	0 NA
## 5776	0 NA
## 5797	0 NA
## 5798	0 NA
## 6018	0 NA
## 6121	0 NA
## 6482	0 NA
## 6518	0 NA
## 6841	0 NA
## 6842	0 NA
## 6843	0 NA
## 7202	0 NA
## 7921	0 NA
## 7957	0 NA
## 8858	0 NA
## 9253	0 NA
## 9361	0 NA
## 9364	0 NA
## 9386	0 NA
## 9390	0 NA
## 9505	0 NA
## 10441	0 NA
## 10444	0 NA
## 10447	0 NA
## 10448	0 NA
## 10535	0 NA
## 10639	0 NA
## 10785	0 NA
## 11294	0 NA

```
## 11387    0 NA
## 11418    0 NA
## 11421    0 NA
## 12202    0 NA
## 12241    0 NA
## 13603    0 NA
## 13688    0 NA
## 13689    0 NA
## 13694    0 NA
## 13695    0 NA
## 13696    0 NA
## 13702    0 NA
## 13709    0 NA
## 13713    0 NA
## 13715    0 NA
## 13716    0 NA
## 13717    0 NA
## 13721    0 NA
## 14041    0 NA
## 14379    0 NA
## 14864    0 NA
## 14901    0 NA
## 14958    0 NA
## 15121    0 NA
## 15842    0 NA
## 15843    0 NA
## 15845    0 NA
## 15846    0 NA
## 15847    0 NA
## 16107    0 NA
## 16201    0 NA
## 16565    0 NA
## 16957    0 NA
## 17282    0 NA
## 17643    0 NA
## 17644    0 NA
```

```
###...THERE IS MISSING DATA, BUT IT IS EXPECTED:
###...There are trials where the the experiment times out
###...can be identified as RT == 0
###...trials where a response was not made have an RT =0, resp=0 and ac = NA

###...get the number of time outs
dim(mergedStroopData[!complete.cases(mergedStroopData),])[1]
```

```
## [1] 104
```

```
###...how are the missing trials distributed???
timeOutStroopData = mergedStroopData[!complete.cases(mergedStroopData),]

ftable(posture~congruency, timeOutStroopData)
```

```
##           posture SITTING STANDING
## congruency
## congruent           10           14
## incongruent          29           18
```



```
## neutral          13      20
```

```
fable(blockType~sj, timeOutStroopData)
```

```
##      blockType experimental practice
```

```
## sj
```

```
## 10_2          1      0
```

```
## 12_2          1      1
```

```
## 13_1          0      1
```

```
## 14_2          0      1
```

```
## 15_1          0      2
```

```
## 16_2          2      1
```

```
## 17_1          0      1
```

```
## 18_2          2      0
```

```
## 19_1          0      1
```

```
## 20_2          1      1
```

```
## 21_1          0      3
```

```
## 22_1          0      3
```

```
## 22_2          8      3
```

```
## 24_2          3      8
```

```
## 25_1          0      1
```

```
## 26_2          1      1
```

```
## 27_1          0      3
```

```
## 28_2          0      1
```

```
## 3_1           1      1
```

```
## 31_1          1      0
```

```
## 32_2          1      0
```

```
## 33_1          1      4
```

```
## 36_2          2      5
```

```
## 38_2          4      0
```

```
## 4_2           1      0
```

```
## 40_2          0      1
```

```
## 43_1          1      0
```

```
## 44_2          2     10
```

```
## 45_1          1      1
```

```
## 47_1          2      1
```

```
## 48_2          0      1
```

```
## 5_1           1      5
```

```
## 50_2          0      1
```

```
## 6_2           0      1
```

```
## 7_1           1      0
```

```
## 8_2           0      1
```

```
## 9_1           0      2
```

```
##...this code changes the "time-out" trials as errors
```

```
##...see Davoli et al.
```

```
mergedStroopData$sac[mergedStroopData$rt==0] = 0
```

```
##...remove practice trials
```

```
mergedStroopData <- mergedStroopData[!mergedStroopData$blockType=="practice",]
```

```
##...check that only experimental trials are left
```

```
unique(mergedStroopData$blockType)
```

```
## [1] "experimental"
```

```

totalStroopTrials = dim(mergedStroopData)[1]
observationDataStroop = data.frame(ftable(blockType~sj, mergedStroopData))[,c(1,3)]

#...remove trials faster than 100ms
# mergedStroopData= mergedStroopData[!mergedStroopData$rt==0,] #...greater than 1500ms
mergedStroopData= mergedStroopData[!(mergedStroopData$rt<=100 & mergedStroopData$rt > 0),]
validStroopRTTrials = dim(mergedStroopData)[1]
observationDataStroop$validTrials = data.frame(ftable(blockType~sj, mergedStroopData))[,c(3)]

print(paste("percent invalid trials = ",
            ((totalStroopTrials-validStroopRTTrials)/totalStroopTrials)*100))

## [1] "percent invalid trials = 0.006944444444444444"

write.table(mergedStroopData, file = "Experiment 1 Data/merged_stroop_data.txt",
            row.names = F)

stroopCorrect = mergedStroopData[mergedStroopData$ac == 1, ]

# mergedDataSet = mergedDataSet[mergedDataSet$ac ==1,]
errorsRemoved = dim(stroopCorrect)[1] #...total remaining trials
observationDataStroop$correctTrials = data.frame(ftable(blockType~sj, stroopCorrect))[,c(3)]
trimInfo = data.frame(totalStroopTrials, validStroopRTTrials,errorsRemoved)
head(trimInfo)

## totalStroopTrials validStroopRTTrials errorsRemoved
## 1 14400 14399 13852

#...percent of error trials lost
print(paste("percent errors removed = ",
            (((validStroopRTTrials-errorsRemoved)/totalStroopTrials)*100)))

## [1] "percent errors removed = 3.79861111111111"

#####
#...CHECK 20% CRITERION
#####
observationDataStroop$percentLoss =
  ((observationDataStroop$Freq-observationDataStroop$correctTrials)/
   observationDataStroop$Freq)*100

observationDataStroop$percentLoss

## [1] 3.472222 1.736111 0.347222 6.944444 1.736111 4.166667 4.513889 1.736111
## [9] 1.041667 1.736111 1.736111 3.125000 2.083333 4.513889 1.736111 10.069444
## [17] 8.680556 0.347222 2.083333 4.513889 4.861111 1.388889 1.388889 3.472222
## [25] 16.666667 1.736111 15.972222 1.041667 0.000000 5.555556 2.083333 8.680556
## [33] 0.347222 3.125000 1.736111 2.083333 4.166667 2.777778 2.430556 7.638889
## [41] 1.041667 4.166667 2.777778 1.041667 5.555556 3.125000 10.069444 1.736111
## [49] 3.472222 3.819444

sum(observationDataStroop$percentLoss>20)

## [1] 0

#...None!

```

```

#...RUN TRIMMING PROCEDURE
tempList = pjRecursiveTrim2(stroopCorrect, #...dataset
                             "rt", #...dependent variables
                             c("sj",
                               "cb",
                               "congruency",
                               "posture")) #.independent variables

trimmedStroopData=tempList[[1]]
totalStroopN = tempList[[2]]
rejectedStroop = tempList[[3]]
percentTrimmedStroop = tempList[[4]]
NcellsStroop = tempList[[5]]

#...get the trimming info
trimOutputStroop= data.frame(totalStroopN, rejectedStroop,percentTrimmedStroop,NcellsStroop)
head(trimOutputStroop)

##    totalStroopN rejectedStroop percentTrimmedStroop NcellsStroop
## 1          13852           292           2.107999           300

stroopRT = plyr::ddply(trimmedStroopData,
                       .(sj, cb,congruency,posture),
                       summarise,
                       meanRT = mean(rt))

head(stroopRT)

##    sj cb congruency posture meanRT
## 1 1_1 1 congruent SITTING 471.6458
## 2 1_1 1 congruent STANDING 400.0638
## 3 1_1 1 incongruent SITTING 430.0455
## 4 1_1 1 incongruent STANDING 439.8444
## 5 1_1 1 neutral SITTING 454.5455
## 6 1_1 1 neutral STANDING 408.4565

#...get error data
stroopPE = plyr::ddply(mergedStroopData,
                      .(sj, cb,congruency,posture),
                      summarise,
                      meanPE = 100 - (mean(ac)*100))

head(stroopPE)

##    sj cb congruency posture meanPE
## 1 1_1 1 congruent SITTING 0.000000
## 2 1_1 1 congruent STANDING 0.000000
## 3 1_1 1 incongruent SITTING 4.166667
## 4 1_1 1 incongruent STANDING 6.250000
## 5 1_1 1 neutral SITTING 6.250000
## 6 1_1 1 neutral STANDING 4.166667

#...combine the RT and error data
stroopCombined = cbind(stroopRT,meanPE =stroopPE$meanPE)

```

```
head(stroopCombined)
```

```
##      sj cb congruency posture meanRT meanPE
## 1 1_1 1 congruent SITTING 471.6458 0.000000
## 2 1_1 1 congruent STANDING 400.0638 0.000000
## 3 1_1 1 incongruent SITTING 430.0455 4.166667
## 4 1_1 1 incongruent STANDING 439.8444 6.250000
## 5 1_1 1 neutral SITTING 454.5455 6.250000
## 6 1_1 1 neutral STANDING 408.4565 4.166667
```

```
#...set as factors
```

```
stroopCombined$sj = factor(stroopCombined$sj)
stroopCombined$cb = factor(stroopCombined$cb)
```

## Reaction time results

```
rtModelStroop <- ezANOVA(stroopCombined,
  dv = .(meanRT),
  wid=.(sj),
  within=.(posture,congruency),
  detailed=TRUE,
  type=3,
  return_aov=TRUE)
```

```
## Warning: Converting "posture" to factor for ANOVA.
```

```
## Warning: Converting "congruency" to factor for ANOVA.
```

```
rtModelStroop$ANOVA
```

##	Effect	DFn	DFd	SSn	SSd	F	p	p<.05	ges
## 1	(Intercept)	1	49	6.530862e+07	1322013.63	2.420643e+03	2.233955e-43	*	0.9748634585
## 2	posture	1	49	8.221421e+02	156217.37	2.578776e-01	6.138604e-01		0.0004879807
## 3	congruency	2	98	7.093105e+04	154676.49	2.247026e+01	9.278220e-09	*	0.0404190166
## 4	posture:congruency	2	98	8.430066e+01	51054.35	8.090852e-02	9.223396e-01		0.0000500584

```
rtStroopMSE = rtModelStroop$ANOVA$SSd/rtModelStroop$ANOVA$DFd
```

```
#...print ANOVA in nice format
```

```
paste(rtModelStroop$ANOVA$Effect,": F(",
  rtModelStroop$ANOVA$DFn,
  ", ",
  rtModelStroop$ANOVA$DFd,
  ") = ",
  round(rtModelStroop$ANOVA$F,3),
  ", MSE = ",
  round(rtStroopMSE,3),
  ", p = ",
  round(rtModelStroop$ANOVA$p,3),
  ", partialEtaSq = ",
  round(rtModelStroop$ANOVA$SSn/(rtModelStroop$ANOVA$SSn+rtModelStroop$ANOVA$SSd),4),
  sep="")
```

```
## [1] "(Intercept): F(1, 49) = 2420.643, MSE = 26979.87, p = 0, partialEtaSq = 0.9802"
## [2] "posture: F(1, 49) = 0.258, MSE = 3188.11, p = 0.614, partialEtaSq = 0.0052"
## [3] "congruency: F(2, 98) = 22.47, MSE = 1578.332, p = 0, partialEtaSq = 0.3144"
```

```
## [4] "posture:congruency: F(2, 98) = 0.081, MSE = 520.963, p = 0.922, partialEtaSq = 0.0016"
```

```
##...CALCULATE THE BAYES FACTORS FOR THE RT ANALYSIS
```

```
stroopBF = stroopCombined
stroopBF$posture = factor(stroopBF$posture)
stroopBF$congruency = factor(stroopBF$congruency)
bfValues1 = anovaBF(meanRT~congruency*posture+sj,
                    data = stroopBF,
                    whichRandom = "sj",
                    method="laplace")
bfValues1
```

```
## Bayes factor analysis
## -----
## [1] congruency + sj : 35335703 ±NA%
## [2] posture + sj : 0.1461731 ±NA%
## [3] congruency + posture + sj : 5410998 ±NA%
## [4] congruency + posture + congruency:posture + sj : 346149.8 ±NA%
##
## Against denominator:
## meanRT ~ sj
## ---
## Bayes factor type: BFlinearModel, JZS
```

```
##...get the Bayes factor for the Null Interaction
```

```
bfValues1[3]/bfValues1[4]
```

```
## Bayes factor analysis
## -----
## [1] congruency + posture + sj : 15.63195 ±NA%
##
## Against denominator:
## meanRT ~ congruency + posture + congruency:posture + sj
## ---
## Bayes factor type: BFlinearModel, JZS
```

```
1/(bfValues1[3]/bfValues1[4])
```

```
## Bayes factor analysis
## -----
## [1] congruency + posture + congruency:posture + sj : 0.06397154 ±NA%
##
## Against denominator:
## meanRT ~ congruency + posture + sj
## ---
## Bayes factor type: BFlinearModel, JZS
```

```
# Difference scores and paired t-tests
```

```
##... stroop effect (incongruent - congruent) FOR Standing
```

```
standingStroop = stroopCombined[stroopCombined$posture=="STANDING", ]
standingStroop = standingStroop[standingStroop$congruency!="neutral", ]
t.test(standingStroop$meanRT[standingStroop$congruency=="congruent"],
       standingStroop$meanRT[standingStroop$congruency=="incongruent"],
       paired=TRUE )
```

```
##
## Paired t-test
```

```
##
## data: standingStroop$meanRT[standingStroop$congruency == "congruent"] and standingStroop$meanRT[stan
## t = -4.3805, df = 49, p-value = 6.226e-05
## alternative hypothesis: true difference in means is not equal to 0
## 95 percent confidence interval:
## -53.81756 -19.96796
## sample estimates:
## mean of the differences
## -36.89276

#... stroop effect (incongruent - congruent) FOR SITTING
sittingStroop = stroopCombined[stroopCombined$posture=="SITTING", ]
sittingStroop = sittingStroop[sittingStroop$congruency!="neutral", ]
t.test(sittingStroop$meanRT[sittingStroop$congruency=="congruent"],
       sittingStroop$meanRT[sittingStroop$congruency=="incongruent"],
       paired=TRUE )

##
## Paired t-test
##
## data: sittingStroop$meanRT[sittingStroop$congruency == "congruent"] and sittingStroop$meanRT[sitting
## t = -5.1209, df = 49, p-value = 5.104e-06
## alternative hypothesis: true difference in means is not equal to 0
## 95 percent confidence interval:
## -52.27703 -22.81052
## sample estimates:
## mean of the differences
## -37.54377
```

## Percent error results

```
errModelStroop <- ezANOVA(stroopCombined,
                          dv = .(meanPE),
                          wid=.(sj),
                          within=.(posture, congruency),
                          detailed=TRUE,
                          type=3,
                          return_aov = TRUE)

## Warning: Converting "posture" to factor for ANOVA.
## Warning: Converting "congruency" to factor for ANOVA.
errStroopMSE = errModelStroop$ANOVA$SSd/errModelStroop$ANOVA$DFd

paste(errModelStroop$ANOVA$Effect,": F(",
      errModelStroop$ANOVA$DFn,
      ", ",
      errModelStroop$ANOVA$DFd,
      ") = ",
      round(errModelStroop$ANOVA$F,3),
      ", MSE = ",
      round(errStroopMSE,3),
      ", p = ",
      round(errModelStroop$ANOVA$p,3),
```

```

", partialEtaSq = ",
round(errModelStroop$ANOVA$SSn/(errModelStroop$ANOVA$SSn+errModelStroop$ANOVA$SSd),4),
sep="")

## [1] "(Intercept): F(1, 49) = 57.526, MSE = 75.297, p = 0, partialEtaSq = 0.54"
## [2] "posture: F(1, 49) = 0.007, MSE = 16.562, p = 0.934, partialEtaSq = 1e-04"
## [3] "congruency: F(2, 98) = 11.598, MSE = 9.222, p = 0, partialEtaSq = 0.1914"
## [4] "posture:congruency: F(2, 98) = 1.59, MSE = 6.228, p = 0.209, partialEtaSq = 0.0314"

##...ERRORS
##... stroop effect (incongruent - congruent) FOR Standing
t.test(standingStroop$meanPE[standingStroop$congruency=="congruent"],
       standingStroop$meanPE[standingStroop$congruency=="incongruent"],
       paired=TRUE )

##
## Paired t-test
##
## data: standingStroop$meanPE[standingStroop$congruency == "congruent"] and standingStroop$meanPE[standingStroop$congruency == "incongruent"]
## t = -2.0681, df = 49, p-value = 0.04393
## alternative hypothesis: true difference in means is not equal to 0
## 95 percent confidence interval:
## -2.79325655 -0.04007678
## sample estimates:
## mean of the differences
## -1.416667

##... stroop effect (incongruent - congruent) FOR SITTING
t.test(sittingStroop$meanPE[sittingStroop$congruency=="congruent"],
       sittingStroop$meanPE[sittingStroop$congruency=="incongruent"],
       paired=TRUE )

##
## Paired t-test
##
## data: sittingStroop$meanPE[sittingStroop$congruency == "congruent"] and sittingStroop$meanPE[sittingStroop$congruency == "incongruent"]
## t = -4.6535, df = 49, p-value = 2.51e-05
## alternative hypothesis: true difference in means is not equal to 0
## 95 percent confidence interval:
## -3.758593 -1.491407
## sample estimates:
## mean of the differences
## -2.625

```

## Make plots for Stroop

```

##...pull out summary statistics per condition averaged across subjects for graph
graphRT = describeBy(stroopCombined$meanRT,
                      list(stroopCombined$posture, stroopCombined$congruency),
                      mat=TRUE,
                      digits = 1)

graphPE = describeBy(stroopCombined$meanPE,
                      list(stroopCombined$posture, stroopCombined$congruency),
                      mat=TRUE,

```

```

      digits = 1)
head(graphRT)

##      item  group1      group2 vars  n mean   sd median trimmed mad  min   max range skew
## X11     1  SITTING   congruent    1 50 450.8  56.3  443.0   446.5 45.5 348.3 598.3 250.0 0.7
## X12     2  STANDING   congruent    1 50 448.5  60.6  440.3   442.2 48.6 341.3 624.4 283.0 1.0
## X13     3  SITTING  incongruent    1 50 488.3  91.9  471.8   476.7 74.4 351.1 803.1 452.0 1.2
## X14     4  STANDING  incongruent    1 50 485.4 100.6  458.7   470.5 79.0 358.3 861.5 503.2 1.8
## X15     5  SITTING    neutral     1 50 465.6  66.3  456.6   460.1 49.7 357.8 702.6 344.7 1.0
## X16     6  STANDING    neutral     1 50 460.9  67.6  452.7   453.6 51.5 346.2 695.4 349.2 1.4
##      kurtosis  se
## X11         0.2  8.0
## X12         0.9  8.6
## X13         1.7 13.0
## X14         3.8 14.2
## X15         1.9  9.4
## X16         2.7  9.6

#...get rid of irrelevant columns
graphRT = graphRT[,c("group1","group2","mean","se")]
graphPE = graphPE[,c("group1","group2","mean","se")]

#...rename the variables
names(graphRT) = c("posture","congruency","mean","se")
names(graphPE) = c("posture","congruency","mean","se")

#...make sure posture is in UPPERCASE
graphRT$posture = str_to_upper(graphRT$posture)

#..calculate the within subjects confidence intervals based on loftus and masson
#..the confidence intervals are based on the interaction term.

inxn.rt.MSE = rtStroopMSE[4]
inxn.err.MSE = errStroopMSE[4]

graphRT$se = sqrt((inxn.rt.MSE)/length(unique(stroopCombined$sj)))
graphPE$se = sqrt((inxn.err.MSE)/length(unique(stroopCombined$sj)))

critT = qt(p=.025,df=length(unique(stroopCombined$sj))-2,lower.tail =FALSE)

#---add the min and max for the confidence intervals
graphRT$min = graphRT$mean - (graphRT$se*critT)
graphRT$max = graphRT$mean + (graphRT$se*critT)

####GET AC DATA FROM twoAnimalWordsPRPac.R
graphRT$ac = paste("(",format(round(graphPE$mean,digits=1),nsmall = 1),"),",sep="")
head(graphRT)

##      posture congruency mean      se      min      max      ac
## X11  SITTING   congruent 450.8 3.227887 444.3099 457.2901 (2.6)
## X12  STANDING   congruent 448.5 3.227887 442.0099 454.9901 (3.3)
## X13  SITTING  incongruent 488.3 3.227887 481.8099 494.7901 (5.2)
## X14  STANDING  incongruent 485.4 3.227887 478.9099 491.8901 (4.7)
## X15  SITTING    neutral 465.6 3.227887 459.1099 472.0901 (3.7)

```




```
## X16 STANDING      neutral 460.9 3.227887 454.4099 467.3901 (3.4)
#...used for positioning the accuracy data on the graph
graphRT$vAdj = 25 #down
graphRT$vAdj[graphRT$congruency=="incongruent"]=25 #up
graphRT$hAdj = 0 #right
#graphRT$hAdj[graphRT$posture=="SITTING"]=-60 #left
graphRT$congruency = factor(graphRT$congruency,labels = c("Congruent","Incongruent","Neutral"))
graphRT$congruency = factor(graphRT$congruency,levels=c("Congruent","Neutral","Incongruent"))

interactionPlot <- ggplot(graphRT, aes(congruency, mean, group=posture)) +
  theme(legend.position = "none")+
  scale_fill_manual(values=c("#FFFFFF","#999999","#FFFFFF","#999999")) +
  coord_cartesian(ylim=c(350,550),expand=TRUE) +
  scale_y_continuous(breaks = round(seq(350, 550, by = 50),0)) +
  geom_text(aes(label=ac),nudge_x=graphRT$hAdj,nudge_y =graphRT$vAdj, size=5) +
  geom_bar(stat="identity", aes(fill=interaction(congruency)),colour="black")+
  geom_errorbar(aes(ymin=min,ymax=max,group=interaction(posture,congruency)), width=.1)+
  labs(x = "Congruency", y = "Response Time (ms)") +
  theme(axis.ticks = element_line(size = 1, colour = "black", linetype = "solid"),
        axis.ticks.length = unit(.25,"cm"),
        axis.line = element_line(size = 1, colour = "black", linetype = "solid"),
        panel.background = element_rect(fill = "white", colour = "black", size = 1),
        axis.text=element_text(size=16),
        axis.title=element_text(size=22,face="bold"),
        strip.text = element_text(size = 20, face = "bold",colour = "black", angle = 0),
        strip.background = element_rect(fill=NA,colour="NA",size = 2))+
  facet_grid(~posture)

ggsave(interactionPlot,
        file = "plots/exp1_stroop_interaction_plot.pdf",
        units = "in",
        width = 8.5,
        height = 5,
        dpi = 600)

interactionPlot
```



```

expl.table <-
apa.2way.table(congruency,
               posture,
               meanRT,
               stroopCombined,
               show.conf.interval = TRUE,
               landscape=TRUE,
               filename = "Output/exp1_table.doc")
expl.table

```

```

##
##
## Means and standard deviations for meanRT as a function of a 3(congruency) X 2(posture) design
##
##           M           M_95%_CI      SD
## posture:SITTING
##   congruency
##     congruent 450.77 [434.78, 466.76] 56.26
##     incongruent 488.31 [462.20, 514.42] 91.87
##     neutral 465.62 [446.78, 484.47] 66.31
##
## posture:STANDING
##   congruency
##     congruent 448.51 [431.30, 465.72] 60.56
##     incongruent 485.40 [456.81, 513.99] 100.61
##     neutral 460.86 [441.64, 480.08] 67.64

```

```
##
## Note. M and SD represent mean and standard deviation, respectively.
## LL and UL indicate the lower and upper limits of the
## 95% confidence interval for the mean, respectively.
## The confidence interval is a plausible range of population means
## that could have created a sample mean (Cumming, 2014).
```

## Experiment 2 - Task-switching

### Import and clean data

```
### read in data

ts_path <- "/Experiment 2 Data/task-switching-replication-recoded-2.csv"
task_switching_raw <- read.csv(paste0(workingdir, ts_path))
head(task_switching_raw)

##   participant session condition trialType posture blockNum trialNum switchTrialType
## 1           1         1         1 experiment standing      1         1         buffer
## 2           1         1         1 experiment standing      1         2        noswitch
## 3           1         1         1 experiment standing      1         3         switch
## 4           1         1         1 experiment standing      1         4        noswitch
## 5           1         1         1 experiment standing      1         5        noswitch
## 6           1         1         1 experiment standing      1         6        noswitch
##   congruentTrialType cueType shapeType shapeColor response correctResponse correct reactionTime
## 1      incongruent   solid   square     blue    right         left        no    0.9088130
## 2      incongruent   solid   square     blue    left         left       yes    0.5947349
## 3      incongruent dashed   square     blue    right        right       yes    0.7084870
## 4      incongruent dashed   square     blue    right        right       yes    0.5995200
## 5      congruent   dashed   square    yellow    right        right       yes    0.4399409
## 6      congruent   dashed   square    yellow    right        right       yes    0.3847258
##           date      utcTime
## 1 2021-11-10 10:22:00 1636561737
## 2 2021-11-10 10:22:00 1636561744
## 3 2021-11-10 10:22:00 1636561746
## 4 2021-11-10 10:22:00 1636561748
## 5 2021-11-10 10:22:00 1636561750
## 6 2021-11-10 10:22:00 1636561752

### check data

#does every person have 392 trials?
ntrials_sub <- task_switching_raw %>%
  group_by(participant) %>%
  summarize(ntrials = n()) %>%
  pull(ntrials)

all(ntrials_sub == 392)

## [1] TRUE

#does every block start with a buffer and have 49 trials?
task_switching_raw <- task_switching_raw %>%
  mutate(condblock = paste0(posture, blockNum))
```

```

blocktrials <- task_switching_raw %>%
  group_by(participant, condblock) %>%
  summarize(ntrials = n(), firsttrial = first(switchTrialType))

## `summarise()` has grouped output by 'participant'. You can override using the `.groups` argument.
all(blocktrials$ntrials == 49)

## [1] TRUE
all(blocktrials$firsttrial == "buffer")

## [1] TRUE
### clean data

#Drop buffer trials
task_switching_raw2 <- task_switching_raw %>%
  filter(switchTrialType != "buffer")

#Recode Correct to 1 and Incorrect to 0
task_switching_raw2$correct_bin <- recode(task_switching_raw2$correct,
                                           "no" = 0,
                                           "yes" = 1)

#Calc overall acc by participant
ts_overall_acc <- task_switching_raw2 %>%
  group_by(participant) %>%
  summarize(Accuracy = mean(correct_bin))

#find participants with less than 80% accuracy
#2, 8, 15, 44, 49, 51
#First exclusion criteria
low_acc_subs <- ts_overall_acc %>% filter(Accuracy < 0.80) %>%
  pull(participant)

task_switching_raw3 <- task_switching_raw2 %>%
  filter(!(participant %in% low_acc_subs))

#Calc mean Acc by participant and conditions (posture, con, switch)
#Narrow format
ts_acc_mean <- task_switching_raw3 %>%
  group_by(participant,
            posture,
            congruentTrialType,
            switchTrialType) %>%
  summarize(Accuracy = mean(correct_bin))

## `summarise()` has grouped output by 'participant', 'posture', 'congruentTrialType'. You can
## override using the `.groups` argument.

#Convert data to wide format (for statview/SPSS/etc)
ts_acc_mean_wide <- ts_acc_mean %>%
  pivot_wider(names_from = c(posture,
                              congruentTrialType,
                              switchTrialType),
              values_from = Accuracy)

```

```

# ts_acc_mean <- data.frame(ts_acc_mean)
ts_acc_mean <- ts_acc_mean %>%
  ungroup() %>%
  mutate(across(posture:switchTrialType, as.factor))

str(ts_acc_mean)

## tibble [408 x 5] (S3: tbl_df/tbl/data.frame)
## $ participant      : int [1:408] 1 1 1 1 1 1 1 1 3 3 ...
## $ posture          : Factor w/ 2 levels "sitting","standing": 1 1 1 1 2 2 2 2 1 1 ...
## $ congruentTrialType: Factor w/ 2 levels "congruent","incongruent": 1 1 2 2 1 1 2 2 1 1 ...
## $ switchTrialType   : Factor w/ 2 levels "noswitch","switch": 1 2 1 2 1 2 1 2 1 2 ...
## $ Accuracy          : num [1:408] 0.96 0.978 0.957 0.88 0.981 ...

#Total N = 51 (6 dropped for total acc < 80%)
length(unique(ts_acc_mean$participant))

## [1] 51

```

## Summarize Demographics

```

demo_raw <- read.csv(paste0(workingdir,
                           "/Experiment 2 Data/Task Switching_February 24, 2022_13.05.csv"),
                   skip = 1) %>%
  slice(-1) %>%
  select(-c(Response.Type, IP.Address, Recipient.Last.Name:Distribution.Channel))
colnames(demo_raw)[10:15] <- c("Gender.Pick", "Gender.Text", "Age", "Race.Pick", "Race.Text", "Eng.First")

dim(demo_raw)

## [1] 59 15

#59 records
#first two are test data
# need to match up the 6 dropped participants from behavioral data
demo_df <- demo_raw %>%
  filter(!(X %in% c("test", low_acc_subs)))
dim(demo_df)

## [1] 51 15

demo_df <- demo_df %>%
  mutate(Gender.New = ifelse(Gender.Pick %in% c("Man", "Woman"), Gender.Pick, Gender.Text),
         Eng.First = toupper(Eng.First))

#gender breakdown
gender_table <- demo_df %>%
  group_by(Gender.New) %>%
  summarize(n = n())
gender_table


## # A tibble: 3 x 2
##   Gender.New      n
##   <chr>         <int>
## 1 Man           23
## 2 non binaary    1

```

```
## 3 Woman          27
```

```
#age breakdown
```

```
hist(as.numeric(demo_df$Age),  
     main = "Histogram of Participant Ages",  
     xlab = "Participant Age")
```



```
age_table <- demo_df %>%  
  group_by(Age) %>%  
  summarize(n = n())  
age_table
```

```
## # A tibble: 8 x 2  
##   Age      n  
##   <chr> <int>  
## 1 18      9  
## 2 19     10  
## 3 20     12  
## 4 21     11  
## 5 22      3  
## 6 23      3  
## 7 24      2  
## 8 25      1
```

```
#age mean and sd
```

```
mean_age <- mean(as.numeric(demo_df$Age))  
sd_age <- sd(as.numeric(demo_df$Age))
```

```
kable(matrix(c(mean_age, sd_age), nrow = 1), col.names = c("Mean of Age", "SD of Age"))
```

Mean of Age	SD of Age
20.21569	1.73567

```
#race breakdown
```

```
race_table <- demo_df %>%
  group_by(Race.Pick) %>%
  summarize(n = n()) %>%
  arrange(desc(n))
race_table
```

```
## # A tibble: 6 x 2
##   Race.Pick          n
##   <chr>          <int>
## 1 White /European American      22
## 2 Black / African American      11
## 3 Hispanic/Latino/Latina/Latinx  11
## 4 Asian /South Pacific Islander   3
## 5 Central Asian /Indian /Pakistani 3
## 6 Native American / American Indian 1
```

```
#language breakdown
```

```
lang_table <- demo_df %>%
  group_by(Eng.First) %>%
  summarize(n=n())
lang_table
```


```
## # A tibble: 2 x 2
##   Eng.First    n
##   <chr>    <int>
## 1 NO         8
## 2 YES        43
```

## Accuracy results

```
#Accuracy for all cells
```

```
hist(ts_acc_mean$Accuracy)
```

## Histogram of ts\_acc\_mean\$Accuracy



```
accModelTS <- aov_ez(data = ts_acc_mean,
  dv = "Accuracy",
  id = "participant",
  within = c("posture", "congruentTrialType", "switchTrialType"),
  type = 3,
  anova_table = list(es = "pes")
)

acc.stats.TS <- ezStats(ts_acc_mean,
  dv = Accuracy,
  wid = participant,
  within = .(posture, congruentTrialType, switchTrialType),
  type = 3
)
```

```
## Warning: Converting "participant" to factor for ANOVA.
```

```
write.csv(acc.stats.TS[, -7], file = "output/exp2_Descriptives_ACC.csv",
  row.names = F)
```

```
write.csv(accModelTS$anova_table, "output/exp2_ANOVA_acc.csv")
accModelTS
```

```
## Anova Table (Type 3 tests)
```

```
##
```

```
## Response: Accuracy
```



```
##              Effect    df  MSE        F    pes p.value
## 1              posture  1, 50 0.01      1.06 .021   .308
## 2      congruentTrialType  1, 50 0.01 99.66 *** .666  <.001
## 3      switchTrialType  1, 50 0.00 92.04 *** .648  <.001
## 4      posture:congruentTrialType  1, 50 0.00      0.02 <.001   .875
## 5      posture:switchTrialType  1, 50 0.00      0.74 .015   .395
## 6      congruentTrialType:switchTrialType  1, 50 0.00 58.43 *** .539  <.001
## 7 posture:congruentTrialType:switchTrialType  1, 50 0.00      1.26 .024   .268
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '+' 0.1 ' ' 1
```

```
#Calculate confidence interval: PES for posture x switch/condition interaction
#using ANOVA results (partial eta-squared)
interaction_effect_CI <- get.ci.partial.eta.squared(accModelTS$anova_table$F[5],
                                                    accModelTS$anova_table$num Df[5],
                                                    accModelTS$anova_table$den Df[5],
                                                    conf.level = 0.90)
                                                    #90% CI is the convention for PES

interaction_effect_CI
```

```
## $LL
## [1] 0
##
## $UL
## [1] 0.1073579
```

```
congruent.labs <- c("Congruent", "Incongruent")
names(congruent.labs) <- c("1", "2")
```

```
#make plot like Smith et al's
acc_plot <-
  superbPlot(ts_acc_mean_wide,
             WSFactors = c("Condition(2)", "Congruent(2)", "Posture(2)"),
             variables = colnames(ts_acc_mean_wide)[2:9],
             errorbar = "SE", #Tempted to change to CI, should stay SE to be consistent with SMith
             plotStyle = "line",
             factorOrder = c("Condition", "Posture", "Congruent"),
             adjustments = list(purpose = "difference"))+
  theme_classic() +
  ylim(0.77, 1) + #Trying to make ylim same as the Smith w/o cutting off error bars
  facet_wrap(vars(Congruent), labeller = labeller(Congruent = congruent.labs)) +
  scale_x_discrete(labels=c("1" = "No Switch", "2" = "Switch"))+
  scale_color_manual(values=c("#E69F00", "#0072B2"),
                     labels = c("Sitting", "Standing")) +
  labs(y = "Accuracy")
```


```
## superb::FYI: Here is how the within-subject variables are understood:
```

```
## Condition Congruent Posture          variable
##          1          1          1 sitting_congruent_noswitch
##          2          1          1 sitting_congruent_switch
##          1          2          1 sitting_incongruent_noswitch
##          2          2          1 sitting_incongruent_switch
##          1          1          2 standing_congruent_noswitch
##          2          1          2 standing_congruent_switch
##          1          2          2 standing_incongruent_noswitch
```

```
##          2          2          2  standing_incongruent_switch
```

```
ggsave(acc_plot,
  file = "plots/exp2_ts_acc_plot.pdf",
  units = "in",
  width = 6.62,
  height = 5.50,
  dpi = 600)
```

```
acc_plot
```



```
#...CALCULATE THE BAYES FACTORS FOR THE ACC ANALYSIS
```

```
taskswitchBF = data.frame(ts_acc_mean)
```

```
taskswitchBF$participant = factor(ts_acc_mean$participant)
```

```
taskswitchBF$posture = factor(ts_acc_mean$posture)
```

```
taskswitchBF$congruentTrialType = factor(taskswitchBF$congruentTrialType)
```

```
taskswitchBF$switchTrialType = factor(taskswitchBF$switchTrialType)
```

```
#str(taskswitchBF)
```

```
bfValues2 = anovaBF(Accuracy~ posture*switchTrialType+participant,
```

```
  data = taskswitchBF,
```

```
  whichRandom = "participant",
```

```
  method="laplace")
```

```
bfValues2
```

```
## Bayes factor analysis
## -----
## [1] posture + participant : 0.1836549 ±NA%
## [2] switchTrialType + participant : 5429475 ±NA%
## [3] posture + switchTrialType + participant : 1064550 ±NA%
## [4] posture + switchTrialType + posture:switchTrialType + participant : 168897.1 ±NA%
##
## Against denominator:
## Accuracy ~ participant
## ---
## Bayes factor type: BFlinearModel, JZS

#...get the Bayes factor for the Null Interaction (vs. model w/no interaction)
bfValues2[3]/bfValues2[4]

## Bayes factor analysis
## -----
## [1] posture + switchTrialType + participant : 6.302952 ±NA%
##
## Against denominator:
## Accuracy ~ posture + switchTrialType + posture:switchTrialType + participant
## ---
## Bayes factor type: BFlinearModel, JZS

1/(bfValues2[3]/bfValues2[4])

## Bayes factor analysis
## -----
## [1] posture + switchTrialType + posture:switchTrialType + participant : 0.1586558 ±NA%
##
## Against denominator:
## Accuracy ~ posture + switchTrialType + participant
## ---
## Bayes factor type: BFlinearModel, JZS
```

## Reaction time results

```
#look at reaction time for correct trials
ts_correct_only <- task_switching_raw3 %>%
  filter(correct_bin == 1)

#Second exclusion criteria
#How many trials faster than 100 ms? Only a single one
sum(ts_correct_only$reactionTime < 0.100)

## [1] 1
dim(ts_correct_only)

## [1] 17699 20
ts_correct_only2 <- ts_correct_only %>% filter(reactionTime >= 0.100)
#Sanity check, one trial is dropped. Now have 17,698 trials
dim(ts_correct_only2)

## [1] 17698 20
```

```

trimOutputTS = pjRecursiveTrim2(dataSet = ts_correct_only2,
                                dv = "reactionTime",
                                splitvars = c("participant",
                                                "posture",
                                                "switchTrialType",
                                                "congruentTrialType"))

trimmedTSDData=trimOutputTS[[1]]
totalN.TS = trimOutputTS[[2]]
rejectedTS = trimOutputTS[[3]]
percentTrimmedTS = trimOutputTS[[4]] #this is very close to the percentage trimmed for stroop
#2.14% of trials
percentTrimmedTS

```

```
## [1] 2.141485
```

```
NcellsTS = trimOutputTS[[5]] # 51 participants * 8 conditions
```

```

trimmed_rt_mean_TS <- trimmedTSDData %>%
  group_by(participant,
            posture,
            congruentTrialType,
            switchTrialType) %>%
  summarize(mean_rt = mean(reactionTime)*1000)

```

## `summarise()` has grouped output by 'participant', 'posture', 'congruentTrialType'. You can  
## override using the `.groups` argument.

*#Convert data to wide format*

```

trimmed_rt_mean_TS_wide <- trimmed_rt_mean_TS %>%
  pivot_wider(names_from = c(posture,
                              congruentTrialType,
                              switchTrialType),
              values_from = mean_rt)

```

```

trimmed_RT_plot <-
  superbPlot(trimmed_rt_mean_TS_wide,
              WSFactors = c("Condition(2)", "Congruent(2)", "Posture(2)"),
              variables = colnames(trimmed_rt_mean_TS_wide)[2:9],
              errorbar = "SE",
              plotStyle = "line",
              factorOrder = c("Condition", "Posture", "Congruent"),
              adjustments = list(purpose = "difference"))+
  theme_classic()+
  facet_wrap(vars(Congruent), labeller = labeller(Congruent = congruent.labs)) +
  scale_x_discrete(labels=c("1" = "No Switch", "2" = "Switch"))+
  scale_color_manual(values=c("#E69F00", "#0072B2"), labels = c("Sitting", "Standing")) +
  ylim(500, 700) +
  labs(y = "Response Time (ms)")

```

## superb::FYI: Here is how the within-subject variables are understood:

```


## Condition Congruent Posture variable
##      1      1      1 sitting_congruent_noswitch
##      2      1      1 sitting_congruent_switch
##      1      2      1 sitting_incongruent_noswitch
##      2      2      1 sitting_incongruent_switch

```

```
##      1      1      2  standing_congruent_noswitch
##      2      1      2  standing_congruent_switch
##      1      2      2  standing_incongruent_noswitch
##      2      2      2  standing_incongruent_switch
```

```
ggsave(trimmed_RT_plot,
       file = "plots/exp2_ts_trimmed_RT_plot.pdf",
       units = "in",
       width = 6.62,
       height = 5.50,
       dpi = 600)
```

trimmed\_RT\_plot



```
rtModelTS <- aov_ez(data = trimmed_rt_mean_TS,
                    dv = 'mean_rt',
                    id = 'participant',
                    within = c('posture',
                              'congruentTrialType',
                              'switchTrialType'),
                    type = 3,
                    anova_table = list(es = "pes"))

rt.stats.TS <- ezStats(trimmed_rt_mean_TS,
                      dv = mean_rt,
                      wid = participant,
                      within = .(posture, congruentTrialType, switchTrialType),
```

```

                                type = 3
)

## Warning: Converting "participant" to factor for ANOVA.
## Warning: Converting "posture" to factor for ANOVA.
## Warning: Converting "congruentTrialType" to factor for ANOVA.
## Warning: Converting "switchTrialType" to factor for ANOVA.
write.csv(rt.stats.TS[ , -7],
          file = "output/exp2_Descriptives_trimmed_RT.csv",
          row.names = F)

write.csv(rtModelTS$anova_table, file = "output/exp2_ANOVA_trimmed_RT.csv")
rtModelTS

## Anova Table (Type 3 tests)
##
## Response: mean_rt
##
##              Effect    df    MSE          F    pes p.value
## 1                posture 1, 50 9922.05      0.00 <.001    .995
## 2      congruentTrialType 1, 50 3302.21  48.98 ***    .495    <.001
## 3      switchTrialType 1, 50 4166.22 130.17 ***    .722    <.001
## 4 posture:congruentTrialType 1, 50 1592.27      0.17    .003    .679
## 5 posture:switchTrialType 1, 50 1519.08      0.00 <.001    .951
## 6 congruentTrialType:switchTrialType 1, 50 1252.33  14.32 ***    .223    <.001
## 7 posture:congruentTrialType:switchTrialType 1, 50 1552.36      0.50    .010    .483
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '+' 0.1 ' ' 1

```

## Experiment 3 - Visual search

### Import and clean data

```

vs_files = list.files(path = "Experiment 3 Data/", full.names = T)
vs_files = vs_files[str_detect(vs_files, pattern="(?!.*SJ)(?!.*.txt)")]

merged.VS.data <- ldply(vs_files,
                        read.delim,
                        header=FALSE,
                        stringsAsFactors = FALSE,
                        sep = "") #for each item in the list apply the function read.delim

#..ADD HEADERS
names(merged.VS.data) = c("sj",
                          "cb",
                          "blockNumber",
                          "blockType",
                          "trialNum",
                          "target",
                          "targetImage",
                          "distractor",
                          "distractorImage",

```

```

        "posture",
        "setSize",
        "rt",
        "resp",
        "cresp",
        "ac")

#...look at unique values from both columns
unique(merged.VS.data[c('sj')])

```

```

##      sj
## 1      1
## 265    10
## 529    11
## 793    12
## 1057   13
## 1321   14
## 1585   15
## 1849   16
## 2113   17
## 2377   18
## 2641   19
## 2905    2
## 3169   20
## 3433   21
## 3697   22
## 3961   23
## 4225   24
## 4489   25
## 4753   26
## 5017   27
## 5281   28
## 5545   29
## 5809    3
## 6073   30
## 6337   31
## 6601   32
## 6865   33
## 7129   34
## 7393   35
## 7657   36
## 7921   37
## 8185   38
## 8449   39
## 8713    4
## 8977   40
## 9241   41
## 9505   42
## 9769   43
## 10033  44
## 10297  45
## 10561  46
## 10825  47
## 11089  48

```

```
## 11353 49
## 11617 5
## 11881 50
## 12145 6
## 12409 7
## 12673 8
## 12937 9
```

```
unique(merged.VS.data[c('blockType')])
```

```
##      blockType
## 1      practice
## 9 experimental
```

```
##..DOES EACH SUBJECT HAVE THE SAME NUMBER OF TRIALS
```

```
ftable(blockType~sj, merged.VS.data)
```

```
##      blockType experimental practice
## sj
## 1              256            8
## 2              256            8
## 3              256            8
## 4              256            8
## 5              256            8
## 6              256            8
## 7              256            8
## 8              256            8
## 9              256            8
## 10             256            8
## 11             256            8
## 12             256            8
## 13             256            8
## 14             256            8
## 15             256            8
## 16             256            8
## 17             256            8
## 18             256            8
## 19             256            8
## 20             256            8
## 21             256            8
## 22             256            8
## 23             256            8
## 24             256            8
## 25             256            8
## 26             256            8
## 27             256            8
## 28             256            8
## 29             256            8
## 30             256            8
## 31             256            8
## 32             256            8
## 33             256            8
## 34             256            8
## 35             256            8
## 36             256            8
```



```
## 37          256          8
## 38          256          8
## 39          256          8
## 40          256          8
## 41          256          8
## 42          256          8
## 43          256          8
## 44          256          8
## 45          256          8
## 46          256          8
## 47          256          8
## 48          256          8
## 49          256          8
## 50          256          8
```

```
###DO WE HAVE EQUAL OBSERVATIONS FOR EACH COUNTERBALANCE
ftable(blockType~cb, merged.VS.data)
```

```
##      blockType experimental practice
## cb
## 1          6400          200
## 2          6400          200
```

```
###LOOK FOR MISSING DATA
```

```
merged.VS.data[!complete.cases(merged.VS.data),]
```

```
## [1] sj          cb          blockNumber    blockType      trialNum      target
## [7] targetImage    distractor     distractorImage posture      setSize      rt
## [13] resp          cresp         ac
## <0 rows> (or 0-length row.names)
```

```
### GET RID OF PRACTICE TRIALS
```

```
merged.VS.data <- merged.VS.data[!merged.VS.data$blockType=="practice",]
```

```
### CHECK TRIALS PER CONDITION
```

```
ftable(posture+target+distractor+setSize~sj, merged.VS.data)
```

```
##      posture      SITTING
##      target      h          s
##      distractor    e      u      e      u
##      setSize      4  8  4  8  4  8  4  8      h      u      s      u
##      sj          4  8  4  8  4  8  4  8      4  8  4  8  4  8  4  8
## 1
## 2
## 3
## 4
## 5
## 6
## 7
## 8
## 9
## 10
## 11
## 12
## 13
## 14
```

	SITTING								STANDING							
	target				distractor				target				distractor			
	h	u	e	s	e	u	e	s	h	u	e	s	e	u	e	s
1	16	16	16	16	16	16	16	16	16	16	16	16	16	16	16	16
2	16	16	16	16	16	16	16	16	16	16	16	16	16	16	16	16
3	16	16	16	16	16	16	16	16	16	16	16	16	16	16	16	16
4	16	16	16	16	16	16	16	16	16	16	16	16	16	16	16	16
5	16	16	16	16	16	16	16	16	16	16	16	16	16	16	16	16
6	16	16	16	16	16	16	16	16	16	16	16	16	16	16	16	16
7	16	16	16	16	16	16	16	16	16	16	16	16	16	16	16	16
8	16	16	16	16	16	16	16	16	16	16	16	16	16	16	16	16
9	16	16	16	16	16	16	16	16	16	16	16	16	16	16	16	16
10	16	16	16	16	16	16	16	16	16	16	16	16	16	16	16	16
11	16	16	16	16	16	16	16	16	16	16	16	16	16	16	16	16
12	16	16	16	16	16	16	16	16	16	16	16	16	16	16	16	16
13	16	16	16	16	16	16	16	16	16	16	16	16	16	16	16	16
14	16	16	16	16	16	16	16	16	16	16	16	16	16	16	16	16

```
## 15      16 16 16 16 16 16 16 16      16 16 16 16 16 16 16 16
## 16      16 16 16 16 16 16 16 16      16 16 16 16 16 16 16 16
## 17      16 16 16 16 16 16 16 16      16 16 16 16 16 16 16 16
## 18      16 16 16 16 16 16 16 16      16 16 16 16 16 16 16 16
## 19      16 16 16 16 16 16 16 16      16 16 16 16 16 16 16 16
## 20      16 16 16 16 16 16 16 16      16 16 16 16 16 16 16 16
## 21      16 16 16 16 16 16 16 16      16 16 16 16 16 16 16 16
## 22      16 16 16 16 16 16 16 16      16 16 16 16 16 16 16 16
## 23      16 16 16 16 16 16 16 16      16 16 16 16 16 16 16 16
## 24      16 16 16 16 16 16 16 16      16 16 16 16 16 16 16 16
## 25      16 16 16 16 16 16 16 16      16 16 16 16 16 16 16 16
## 26      16 16 16 16 16 16 16 16      16 16 16 16 16 16 16 16
## 27      16 16 16 16 16 16 16 16      16 16 16 16 16 16 16 16
## 28      16 16 16 16 16 16 16 16      16 16 16 16 16 16 16 16
## 29      16 16 16 16 16 16 16 16      16 16 16 16 16 16 16 16
## 30      16 16 16 16 16 16 16 16      16 16 16 16 16 16 16 16
## 31      16 16 16 16 16 16 16 16      16 16 16 16 16 16 16 16
## 32      16 16 16 16 16 16 16 16      16 16 16 16 16 16 16 16
## 33      16 16 16 16 16 16 16 16      16 16 16 16 16 16 16 16
## 34      16 16 16 16 16 16 16 16      16 16 16 16 16 16 16 16
## 35      16 16 16 16 16 16 16 16      16 16 16 16 16 16 16 16
## 36      16 16 16 16 16 16 16 16      16 16 16 16 16 16 16 16
## 37      16 16 16 16 16 16 16 16      16 16 16 16 16 16 16 16
## 38      16 16 16 16 16 16 16 16      16 16 16 16 16 16 16 16
## 39      16 16 16 16 16 16 16 16      16 16 16 16 16 16 16 16
## 40      16 16 16 16 16 16 16 16      16 16 16 16 16 16 16 16
## 41      16 16 16 16 16 16 16 16      16 16 16 16 16 16 16 16
## 42      16 16 16 16 16 16 16 16      16 16 16 16 16 16 16 16
## 43      16 16 16 16 16 16 16 16      16 16 16 16 16 16 16 16
## 44      16 16 16 16 16 16 16 16      16 16 16 16 16 16 16 16
## 45      16 16 16 16 16 16 16 16      16 16 16 16 16 16 16 16
## 46      16 16 16 16 16 16 16 16      16 16 16 16 16 16 16 16
## 47      16 16 16 16 16 16 16 16      16 16 16 16 16 16 16 16
## 48      16 16 16 16 16 16 16 16      16 16 16 16 16 16 16 16
## 49      16 16 16 16 16 16 16 16      16 16 16 16 16 16 16 16
## 50      16 16 16 16 16 16 16 16      16 16 16 16 16 16 16 16
```

```
#... UNLIKE THE STROOP, PARTICIPANTS WERE ALLOWED TO TAKE LONGER THAN 1500MS BUT WERE GIVEN A WARNING
#... TRIALS LONGER THAN 1500 MS will be considered errors (i.e., they will be dropped in RT but kept in
#... Set values in the ac column to 0 on trials where a response is > = 1500
```

```
#...check that only experimental trials are left
unique(merged.VS.data$blockType)
```

```
## [1] "experimental"
```

```
write.table(merged.VS.data, file = "Experiment 3 Data/merged_vs_data.txt", row.names = F)
```

```
#...count trials
```

```
totalTrialsVS = dim(merged.VS.data)[1]
```

```
observationDataVS = data.frame(ftable(blockType~sj, merged.VS.data))[c(1,3)]
```

```
#...get the number of extreme trials <100 - anticipatory or fast responses
```

```
merged.VS.data= merged.VS.data[!merged.VS.data$rt<=100,]
```

```
validRTTrialsVS = dim(merged.VS.data)[1]
```

```

observationDataVS$validTrials = data.frame(ftable(blockType~sj, merged.VS.data))[,c(3)]

print(paste("percent invalid trials = ", ((totalTrialsVS-validRTTrialsVS)/totalTrialsVS)*100))

## [1] "percent invalid trials = 0"
##...this code changes the 1550ms+ trials into errors
merged.VS.data$ac[merged.VS.data$rt>=1500] = 0

vsCorrect = merged.VS.data[merged.VS.data$ac ==1,]

errorsRemovedVS = dim(vsCorrect)[1]
observationDataVS$correctTrials = data.frame(ftable(blockType~sj, vsCorrect))[,c(3)]

trimInfo = data.frame(totalTrialsVS, validRTTrialsVS, errorsRemovedVS)
head(trimInfo)

##      totalTrialsVS validRTTrialsVS errorsRemovedVS
## 1      12800      12800      12397

#####
##...CHECK 20% CRITERION
#####
observationDataVS$percentLoss = ((observationDataVS$Freq-observationDataVS$correctTrials)/observationDataVS$Freq)*100
sum(observationDataVS$percentLoss>20)

## [1] 0

##...None!

##...RUN TRIMMING PROCEDURE
tempList = pjRecursiveTrim2(vsCorrect, ##...dataset
                             "rt", ##...dependent variables
                             c("sj",
                               "cb",
                               "setSize",
                               "posture")) ##.independent variables

trimmedData=tempList[[1]]
totalN = tempList[[2]]
rejected = tempList[[3]]
percentTrimmed = tempList[[4]]
Ncells = tempList[[5]]

print(paste("Percent of outliers removed: ",round(percentTrimmed,3)))

## [1] "Percent of outliers removed: 1.339"

##...get the trimming info
output.out= data.frame(totalN, rejected,percentTrimmed,Ncells)
head(output.out)

##      totalN rejected percentTrimmed Ncells
## 1  12397      166      1.339034      200

##...get mean error data
vsPE = plyr::ddply(merged.VS.data,

```

```

      .(sj,cb,setSize, posture),
      summarise,
      meanPE = 100 - (mean(ac)*100))
head(vsPE)

##   sj cb setSize  posture meanPE
## 1  1  1      4  SITTING 0.0000
## 2  1  1      4  STANDING 0.0000
## 3  1  1      8  SITTING 0.0000
## 4  1  1      8  STANDING 0.0000
## 5  2  1      4  SITTING 4.6875
## 6  2  1      4  STANDING 4.6875

vsRT = plyr::ddply(trimmedData,
  .(sj, cb, setSize,posture),
  summarise,
  meanRT = mean(rt))

#...combine the RT and error data
vsCombined = cbind(vsRT,meanPE =vsPE$meanPE)
str(vsCombined)

## 'data.frame':   200 obs. of  6 variables:
##  $ sj      : int  1 1 1 1 2 2 2 2 3 3 ...
##  $ cb      : int  1 1 1 1 1 1 1 1 1 1 ...
##  $ setSize: int  4 4 8 8 4 4 8 8 4 4 ...
##  $ posture: chr  "SITTING" "STANDING" "SITTING" "STANDING" ...
##  $ meanRT  : num  677 593 736 620 792 ...
##  $ meanPE  : num  0 0 0 0 4.69 ...

#...set as factors
vsCombined$sj = factor(vsCombined$sj)
vsCombined$cb = factor(vsCombined$cb)
vsCombined$setSize = factor(vsCombined$setSize)
vsCombined$postureFactor = factor(vsCombined$posture)
summary(vsCombined$cb)

##   1   2
## 100 100

```

## Reaction time results

```

rtModelVS <- ezANOVA(vsCombined,
  dv = .(meanRT),
  wid=.(sj),
  within=.(postureFactor,setSize),
  detailed=TRUE,
  type=3,
  return_aov=TRUE)

rtModelVS$ANOVA

##           Effect DFn DFd          SSn          SSd          F          p p<.05
## 1      (Intercept)    1  49 1.084958e+08 1189588.17 4.469020e+03 8.326740e-50      *
## 2      postureFactor    1  49 2.052064e+04  153738.29 6.540411e+00 1.369090e-02      *

```

```

## 3          setSize    1  49 3.574624e+05  46863.03 3.737628e+02 1.414816e-24      *
## 4 postureFactor:setSize 1  49 2.246613e+01  35654.35 3.087534e-02 8.612429e-01
##          ges
## 1 9.870285e-01
## 2 1.418774e-02
## 3 2.004492e-01
## 4 1.575613e-05

rt.VS.MSE <- rtModelVS$ANOVA$SSd/rtModelVS$ANOVA$DFd

#...print ANOVA in nice format
paste(rtModelVS$ANOVA$Effect,": F(",
      rtModelVS$ANOVA$DFn,
      ", ",
      rtModelVS$ANOVA$DFd,
      ") = ",
      round(rtModelVS$ANOVA$F,3),
      ", MSE = ",
      round(rt.VS.MSE,3),
      ", p = ",
      round(rtModelVS$ANOVA$p,3),
      ", partialEtaSq = ",
      round(rtModelVS$ANOVA$SSn/(rtModelVS$ANOVA$SSn+rtModelVS$ANOVA$SSd),4),sep="")

## [1] "(Intercept): F(1, 49) = 4469.02, MSE = 24277.31, p = 0, partialEtaSq = 0.9892"
## [2] "postureFactor: F(1, 49) = 6.54, MSE = 3137.516, p = 0.014, partialEtaSq = 0.1178"
## [3] "setSize: F(1, 49) = 373.763, MSE = 956.388, p = 0, partialEtaSq = 0.8841"
## [4] "postureFactor:setSize: F(1, 49) = 0.031, MSE = 727.64, p = 0.861, partialEtaSq = 6e-04"

#...CALCULATE THE BAYES FACTORS FOR THE RT ANALYSIS
bfValues3 = anovaBF(meanRT~setSize*postureFactor+sj,
                    data = vsCombined,
                    whichRandom = "sj",
                    method="laplace")

bfValues3

## Bayes factor analysis
## -----
## [1] setSize + sj : 2.916459e+26 ±NA%
## [2] postureFactor + sj : 1.51507 ±NA%
## [3] setSize + postureFactor + sj : 1.321058e+28 ±NA%
## [4] setSize + postureFactor + setSize:postureFactor + sj : 2.585184e+27 ±NA%
##
## Against denominator:
## meanRT ~ sj
## ---
## Bayes factor type: BFlinearModel, JZS

warnings()
#...get the Bayes factor for the Null Interaction
bfValues3[3]/bfValues3[4]

## Bayes factor analysis
## -----
## [1] setSize + postureFactor + sj : 5.110113 ±NA%
##

```

```

## Against denominator:
##   meanRT ~ setSize + postureFactor + setSize:postureFactor + sj
## ---
## Bayes factor type: BFlinearModel, JZS
1/(bfValues3[3]/bfValues3[4])

## Bayes factor analysis
## -----
## [1] setSize + postureFactor + setSize:postureFactor + sj : 0.1956904 ±NA%
##
## Against denominator:
##   meanRT ~ setSize + postureFactor + sj
## ---
## Bayes factor type: BFlinearModel, JZS
#####
# GET DIFFERENCE SCORES - SEARCH RATE
#####

wideData = dcast(vsCombined, #the name of the dataframe you want to reshape
                 sj+cb #row variables
                 ~posture+setSize, #row variables ~ column variables
                 value.var = "meanRT")
head(wideData)

##   sj cb SITTING_4 SITTING_8 STANDING_4 STANDING_8
## 1  1  1  676.5238  735.5397   593.1129   619.6406
## 2  2  1  792.4590  931.9474   815.7213   993.5000
## 3  3  1  721.2787  827.2222   654.1639   774.5238
## 4  4  1  695.7119  741.9298   660.2632   653.0172
## 5  5  1  693.6034  839.2903   705.1967   759.7419
## 6  6  1  625.3750  694.0484   592.4531   687.5645

wideData$sittingEffect = (wideData$SITTING_8-wideData$SITTING_4)/4
wideData$standingEffect = (wideData$STANDING_8-wideData$STANDING_4)/4
wideData$interaction = wideData$sittingEffect - wideData$standingEffect

searchratestand = mean(wideData$standingEffect) #...search rate in standing condition
searchratesit = mean(wideData$sittingEffect) #...search rate in the sitting condition

searchratestand

## [1] 21.30589
searchratesit

## [1] 20.97073
#One-sample t-tests
t.test(wideData$standingEffect)

##
## One Sample t-test
##
## data: wideData$standingEffect
## t = 16.69, df = 49, p-value < 2.2e-16
## alternative hypothesis: true mean is not equal to 0

```

```
## 95 percent confidence interval:
## 18.74050 23.87127
## sample estimates:
## mean of x
## 21.30589

t.test(wideData$sittingEffect)

##
## One Sample t-test
##
## data: wideData$sittingEffect
## t = 13.055, df = 49, p-value < 2.2e-16
## alternative hypothesis: true mean is not equal to 0
## 95 percent confidence interval:
## 17.74261 24.19884
## sample estimates:
## mean of x
## 20.97073

#...Exact Binomial SIGN TEST
binom.test(length(wideData$interaction[wideData$interaction>=0]),
            length(unique(vsCombined$sj)))

##
## Exact binomial test
##
## data: length(wideData$interaction[wideData$interaction >= 0]) and length(unique(vsCombined$sj))
## number of successes = 25, number of trials = 50, p-value = 1
## alternative hypothesis: true probability of success is not equal to 0.5
## 95 percent confidence interval:
## 0.355273 0.644727
## sample estimates:
## probability of success
## 0.5
```

## Percent error results

```
errModelVS <- ezANOVA(vsCombined,
                      dv = .(meanPE),
                      wid=.(sj),
                      within=.(postureFactor,setSize),
                      detailed=TRUE,
                      type=3,
                      return_aov = TRUE)

errModelVS

## $ANOVA
##           Effect DFn DFd      SSn      SSd        F      p p<.05      ges
## 1      (Intercept)   1  49 1982.531738 1158.9478 83.8209098 3.463466e-12 * 0.504342884
## 2      postureFactor   1  49   3.527832  227.7954  0.7588554 3.879351e-01  0.001807368
## 3           setSize   1  49 129.504395  343.5181 18.4727266 8.162026e-05 * 0.062324860
## 4 postureFactor:setSize 1  49  20.520020  218.1274  4.6096032 3.676850e-02 * 0.010422027
##
## $aov
```

```

##
## Call:
## aov(formula = formula(aov_formula), data = data)
##
## Grand Mean: 3.148438
##
## Stratum 1: sj
##
## Terms:
##              Residuals
## Sum of Squares   1158.948
## Deg. of Freedom      49
##
## Residual standard error: 4.863332
##
## Stratum 2: sj:postureFactor
##
## Terms:
##           postureFactor Residuals
## Sum of Squares      3.52783 227.79541
## Deg. of Freedom        1      49
##
## Residual standard error: 2.156128
## 1 out of 2 effects not estimable
## Estimated effects are balanced
##
## Stratum 3: sj:setSize
##
## Terms:
##           setSize Residuals
## Sum of Squares 129.5044 343.5181
## Deg. of Freedom      1      49
##
## Residual standard error: 2.647749
## 1 out of 2 effects not estimable
## Estimated effects are balanced
##
## Stratum 4: sj:postureFactor:setSize
##
## Terms:
##           postureFactor:setSize Residuals
## Sum of Squares      20.52002 218.12744
## Deg. of Freedom        1      49
##
## Residual standard error: 2.109877
## Estimated effects are balanced

err.VS.MSE <- errModelVS$ANOVA$SSd/errModelVS$ANOVA$DFd

paste(errModelVS$ANOVA$Effect,": F(",
      errModelVS$ANOVA$DFn,
      ", ",
      errModelVS$ANOVA$DFd,
      ") = ",

```



```

round(errModelVS$ANOVA$F,3),
", MSE = ",
round(err.VS.MSE,3),
", p = ",
round(errModelVS$ANOVA$p,3),
", partialEtaSq = ",
round(errModelVS$ANOVA$SSn/(errModelVS$ANOVA$SSn+errModelVS$ANOVA$SSd),4),sep="")

## [1] "(Intercept): F(1, 49) = 83.821, MSE = 23.652, p = 0, partialEtaSq = 0.6311"
## [2] "postureFactor: F(1, 49) = 0.759, MSE = 4.649, p = 0.388, partialEtaSq = 0.0153"
## [3] "setSize: F(1, 49) = 18.473, MSE = 7.011, p = 0, partialEtaSq = 0.2738"
## [4] "postureFactor:setSize: F(1, 49) = 4.61, MSE = 4.452, p = 0.037, partialEtaSq = 0.086"

wideData = dcast(vsCombined, #the name of the dataframe you want to reshape
sj+cb #row variables
~posture+setSize, #row variables ~ column variables
value.var = "meanPE")

head(wideData)

## sj cb SITTING_4 SITTING_8 STANDING_4 STANDING_8
## 1 1 1 0.0000 0.0000 0.0000 0.0000
## 2 2 1 4.6875 10.9375 4.6875 15.6250
## 3 3 1 1.5625 1.5625 0.0000 0.0000
## 4 4 1 6.2500 10.9375 4.6875 6.2500
## 5 5 1 3.1250 3.1250 1.5625 1.5625
## 6 6 1 0.0000 1.5625 0.0000 1.5625

wideData$sittingEffect = (wideData$SITTING_8-wideData$SITTING_4)/4
wideData$standingEffect = (wideData$STANDING_8-wideData$STANDING_4)/4
wideData$interaction = wideData$sittingEffect - wideData$standingEffect

searchratestand = mean(wideData$standingEffect) #...search rate in standing condition
searchratesit = mean(wideData$sittingEffect) #...search rate in the sitting condition

searchratestand

## [1] 0.5625

searchratesit

## [1] 0.2421875

#One-sample t-tests
t.test(wideData$standingEffect)

##
## One Sample t-test
##
## data: wideData$standingEffect
## t = 4.0858, df = 49, p-value = 0.0001623
## alternative hypothesis: true mean is not equal to 0
## 95 percent confidence interval:
## 0.2858399 0.8391601
## sample estimates:
## mean of x
## 0.5625

```

```
t.test(wideData$sittingEffect)
```

```
##
## One Sample t-test
##
## data: wideData$sittingEffect
## t = 2.4588, df = 49, p-value = 0.01752
## alternative hypothesis: true mean is not equal to 0
## 95 percent confidence interval:
## 0.04424588 0.44012912
## sample estimates:
## mean of x
## 0.2421875
```

## Make plots for visual search

```
graphRT = describeBy(vsCombined$meanRT,
                      list(vsCombined$posture,vsCombined$setSize),
                      mat=TRUE,
                      digits = 1)
graphPE = describeBy(vsCombined$meanPE,
                      list(vsCombined$posture,vsCombined$setSize),
                      mat=TRUE,
                      digits = 1)

graphRT = graphRT[,c("group1","group2","mean","se")]
graphPE = graphPE[,c("group1","group2","mean","se")]

names(graphRT) = c("posture","setSize","mean","se")
names(graphPE) = c("posture","setSize","mean","se")

graphRT$posture = str_to_upper(graphRT$posture)

#####
#..calculate the within subjects confidence intervals based on loftus and masson
#..the confidence intervals are based on the interaction term.
#####

graphRT$se = sqrt((rt.VS.MSE[4])/length(unique(vsCombined$sj)))
graphPE$se= sqrt((err.VS.MSE[4])/length(unique(vsCombined$sj)))

#####
#..calculate the within subjects confidence intervals based on loftus and masson
#..the confidence intervals are based on the interaction term.
#####

critT = qt(p=.025,df=length(unique(vsCombined$sj))-2,lower.tail =FALSE)

#---add the min and max for the confidence intervals
graphRT$min = graphRT$mean - (graphRT$se*critT)
graphRT$max = graphRT$mean + (graphRT$se*critT)
```

```

####GET AC DATA FROM twoAnimalWordsPRPac.R
graphRT$ac = paste("(",format(round(graphPE$mean,digits=1),nsmall = 1),")",sep="")
head(graphRT)

##      posture setSize mean      se      min      max      ac
## X11  SITTING      4 704.7 3.814813 697.0298 712.3702 (2.5)
## X12  STANDING      4 683.8 3.814813 676.1298 691.4702 (2.2)
## X13  SITTING      8 788.6 3.814813 780.9298 796.2702 (3.5)
## X14  STANDING      8 769.0 3.814813 761.3298 776.6702 (4.4)

graphRT$vAdj = 35 #down
graphRT$vAdj[graphRT$setSize=="incongruent"]=35 #up
graphRT$hAdj = 0 #right
#graphRT$hAdj[graphRT$posture=="SITTING"]=-60 #left


graphRT$congruency = factor(graphRT$setSize,labels = c("4","8"))

interactionPlot <- ggplot(graphRT, aes(setSize, mean, group=posture)) +
  theme(legend.position = "none")+
  scale_fill_manual(values=c("#FFFFFF", "#999999", "#FFFFFF", "#999999"))+
  coord_cartesian(ylim=c(500,950),expand=TRUE)+
  scale_y_continuous(breaks = round(seq(500, 950, by = 100),0))+
  geom_text(aes(label=ac),nudge_x=graphRT$hAdj,nudge_y =graphRT$vAdj,size=5)+
  geom_bar(stat="identity", aes(fill=interaction(setSize)),colour="black")+
  geom_errorbar(aes(ymin=min,ymax=max,group=interaction(posture,setSize)), width=.1)+
  labs(x = "Set Size", y = "Response Time (ms)") +
  theme(axis.ticks = element_line(size = 1, colour = "black", linetype = "solid"),
        axis.ticks.length = unit(.25,"cm"),
        axis.line = element_line(size = 1, colour = "black", linetype = "solid"),
        panel.background = element_rect(fill = "white", colour = "black", size = 1),
        axis.text=element_text(size=16),
        axis.title=element_text(size=22,face="bold"),
        strip.text = element_text(size = 20, face = "bold",colour = "black", angle = 0),
        strip.background = element_rect(fill=NA,colour="NA",size = 2))+
  facet_grid(~posture)

ggsave(interactionPlot,
  file = "plots/exp3_visual_search_interaction_plot.pdf",
  units = "in",
  width = 8.5,
  height = 5,
  dpi = 600)

interactionPlot

```



Reproduce results from Smith et al.

```
# Data source: The data from all the experiments are available at:
# http://rabrams.net under the Resources tab.

### Experiment 1 (Stroop)

#load acc data
Smith_Exp1_acc <- read_excel("smith_data.xlsx",
                             sheet = "Exp1Acc",
                             n_max = 14) #Sample size in Smith

#load rt data
Smith_Exp1_rt <- read_excel("smith_data.xlsx",
                             sheet = "Exp1RT",
                             n_max = 14)

#Restructure from wide to narrow, using tidyr
Smith_Exp1_acc_narrow <- Smith_Exp1_acc %>%
  pivot_longer(cols = sit_neut:sta_con, names_to = "condition", values_to = "acc") %>%
  separate(col = condition, into = c("posture", "con"))

Smith_Exp1_rt_narrow <- Smith_Exp1_rt %>%
  pivot_longer(cols = sit_neut:sta_con, names_to = "condition", values_to = "rt") %>%
  separate(col = condition, into = c("posture", "con"))
```

```
Smith_Exp1 <- merge(Smith_Exp1_acc_narrow, Smith_Exp1_rt_narrow)

Smith_exp1_anova_acc <- aov_ez(data = Smith_Exp1,
  dv = 'acc',
  id = 'subj',
  within = c('posture', 'con'),
  anova_table = list(es = "pes", correction = "none"),
  type = 3)
kable(nice(Smith_exp1_anova_acc), caption = "ANOVA results for Smith Exp 1 - accuracy")
```

Table 2: ANOVA results for Smith Exp 1 - accuracy

Effect	df	MSE	F	pes	p.value
posture	1, 13	4.59	0.51	.038	.488
con	2, 26	3.19	3.76 *	.224	.037
posture:con	2, 26	2.18	1.47	.101	.250

```
Smith_exp1_anova_rt <- aov_ez(data = Smith_Exp1,
  dv = 'rt',
  id = 'subj',
  within = c('posture', 'con'),
  anova_table = list(es = "pes", correction = "none"),
  type = 3)
kable(nice(Smith_exp1_anova_rt), caption = "ANOVA results for Smith Exp 1 - RT")
```

Table 3: ANOVA results for Smith Exp 1 - RT

Effect	df	MSE	F	pes	p.value
posture	1, 13	816.34	0.09	.007	.768
con	2, 26	150.32	3.45 *	.210	.047
posture:con	2, 26	128.10	4.73 *	.267	.018

```
### Experiment 2 (Task-switching)

#load acc data
Smith_Exp2_acc <- read_excel("smith_data.xlsx",
  sheet = "Exp2Acc",
  n_max = 30)

#load rt data
Smith_Exp2_rt <- read_excel("smith_data.xlsx",
  sheet = "Exp2RT",
  n_max = 30)

#Restructure from wide to narrow, using tidyr
Smith_Exp2_acc_narrow <- Smith_Exp2_acc %>%
  pivot_longer(cols = sit_congruent_noswitch:stand_incongruent_switch,
    names_to = "condition", values_to = "acc") %>%
  separate(col = condition, into = c("posture", "con", "switch"))
```

```

Smith_Exp2_rt_narrow <- Smith_Exp2_rt %>%
  pivot_longer(cols = sit_congruent_noswitch:stand_incongruent_switch,
    names_to = "condition", values_to = "rt") %>%
  separate(col = condition, into = c("posture", "con", "switch"))

Smith_Exp2 <- merge(Smith_Exp2_acc_narrow, Smith_Exp2_rt_narrow)

Smith_exp2_anova_acc <- aov_ez(data = Smith_Exp2,
  dv = 'acc',
  id = 'subj',
  within = c('posture', 'con', 'switch'),
  anova_table = list(es = "pes", correction = "none"),
  type = 3)
kable(nice(Smith_exp2_anova_acc), caption = "ANOVA results for Smith Exp 2 - accuracy")

```

Table 4: ANOVA results for Smith Exp 2 - accuracy

Effect	df	MSE	F	pes	p.value
posture	1, 29	0.00	2.86	.090	.101
con	1, 29	0.00	67.40 ***	.699	<.001
switch	1, 29	0.00	62.94 ***	.685	<.001
posture:con	1, 29	0.00	1.68	.055	.205
posture:switch	1, 29	0.00	5.54 *	.160	.026
con:switch	1, 29	0.00	23.34 ***	.446	<.001
posture:con:switch	1, 29	0.00	0.50	.017	.484

```

Smith_exp2_anova_rt <- aov_ez(data = Smith_Exp2,
  dv = 'rt',
  id = 'subj',
  within = c('posture', 'con', 'switch'),
  anova_table = list(es = "pes", correction = "none"),
  type = 3)
kable(nice(Smith_exp2_anova_rt), caption = "ANOVA results for Smith Exp 2 - RT")

```

Table 5: ANOVA results for Smith Exp 2 - RT

Effect	df	MSE	F	pes	p.value
posture	1, 29	0.02	0.03	.001	.856
con	1, 29	0.00	40.95 ***	.585	<.001
switch	1, 29	0.00	115.10 ***	.799	<.001
posture:con	1, 29	0.00	0.49	.017	.489
posture:switch	1, 29	0.00	0.10	.004	.751
con:switch	1, 29	0.00	4.77 *	.141	.037
posture:con:switch	1, 29	0.00	0.67	.023	.420

### ### Experiment 3 (Visual Search)

```

#load acc data
Smith_Exp3_acc <- read_excel("smith_data.xlsx",

```

```

        sheet = "Exp3Acc",
        n_max = 12) %>%

select(subj:sit8)

#load rt data
Smith_Exp3_rt <- read_excel("smith_data.xlsx",
        sheet = "Exp3RT",
        n_max = 12)%>%

select(subj:sit8)

#Restructure from wide to narrow, using tidyr
Smith_Exp3_acc_narrow <- Smith_Exp3_acc %>%
  pivot_longer(cols = stand4:sit8, names_to = "condition", values_to = "acc") %>%
  separate(col = condition, into = c("posture", "set.size"), sep = -1)

Smith_Exp3_rt_narrow <- Smith_Exp3_rt %>%
  pivot_longer(cols = stand4:sit8, names_to = "condition", values_to = "rt") %>%
  separate(col = condition, into = c("posture", "set.size"), sep = -1)

Smith_Exp3 <- merge(Smith_Exp3_acc_narrow, Smith_Exp3_rt_narrow)

Smith_exp3_anova_acc <- aov_ez(data = Smith_Exp3,
        dv = 'acc',
        id = 'subj',
        within = c('posture', 'set.size'),
        anova_table = list(es = "pes", correction = "none"),
        type = 3)
kable(nice(Smith_exp3_anova_acc), caption = "ANOVA results for Smith Exp 3 - accuracy")

```

Table 6: ANOVA results for Smith Exp 3 - accuracy

Effect	df	MSE	F	pes	p.value
posture	1, 11	4.61	0.76	.065	.401
set.size	1, 11	1.75	3.44 +	.238	.090
posture:set.size	1, 11	1.38	7.96 *	.420	.017

```

Smith_exp3_anova_rt <- aov_ez(data = Smith_Exp3,
        dv = 'rt',
        id = 'subj',
        within = c('posture', 'set.size'),
        anova_table = list(es = "pes", correction = "none"),
        type = 3)
kable(nice(Smith_exp3_anova_rt), caption = "ANOVA results for Smith Exp 3 - RT")

```

Table 7: ANOVA results for Smith Exp 3 - RT

Effect	df	MSE	F	pes	p.value
posture	1, 11	2323.81	0.23	.021	.639
set.size	1, 11	473.24	81.88 ***	.882	<.001
posture:set.size	1, 11	298.96	5.91 *	.350	.033

## Overall summary plots: Smith and replication

```
smith_anovas <- lst(Smith_exp1_anova_acc$anova_table,
  Smith_exp1_anova_rt$anova_table,
  Smith_exp2_anova_acc$anova_table,
  Smith_exp2_anova_rt$anova_table,
  Smith_exp3_anova_acc$anova_table,
  Smith_exp3_anova_rt$anova_table)

repl_anovas <- lst(aov_ez(data = stroopCombined,
  dv = "meanPE",
  id = "sj",
  within = c("posture", "congruency"),
  type = 3,
  anova_table = list(es = "pes")),
  aov_ez(data = stroopCombined,
  dv = "meanRT",
  id = "sj",
  within = c("posture", "congruency"),
  type = 3,
  anova_table = list(es = "pes")),
  accModelTS,
  rtModelTS,
  aov_ez(data = vsCombined,
  dv = "meanPE",
  id = "sj",
  within = c("postureFactor", "setSize"),
  type = 3,
  anova_table = list(es = "pes")),
  aov_ez(data = vsCombined,
  dv = "meanRT",
  id = "sj",
  within = c("postureFactor", "setSize"),
  type = 3,
  anova_table = list(es = "pes")))

for (i in 1:6){

  smith_anovas[[i]] <- smith_anovas[[i]] %>%
    rownames_to_column() %>%
    as.data.frame() %>%
    rowwise() %>%
    mutate(LL = get.ci.partial.eta.squared(F, `num Df`, `den Df`, conf.level = 0.9)$LL,
      UL = get.ci.partial.eta.squared(F, `num Df`, `den Df`, conf.level = 0.9)$UL)

  repl_anovas[[i]] <- repl_anovas[[i]]$anova_table %>%
    rownames_to_column() %>%
    as.data.frame() %>%
    rowwise() %>%
    mutate(LL = get.ci.partial.eta.squared(F, `num Df`, `den Df`, conf.level = 0.9)$LL,
      UL = get.ci.partial.eta.squared(F, `num Df`, `den Df`, conf.level = 0.9)$UL)
}
```



```

###Exp1 (Stroop)
smith.stroop <- smith_anovas[[1]] %>%
  ungroup() %>%
  bind_rows(smith_anovas[[2]]) %>%
  select(Effect = rowname, pes, LL, UL) %>%
  mutate(dv = rep(c("acc", "rt"), each = 3), col = rep(c("black", "black", "red"), 2))

repl.stroop <- repl_anovas[[1]] %>%
  ungroup() %>%
  bind_rows(repl_anovas[[2]]) %>%
  select(Effect = rowname, pes, LL, UL) %>%
  mutate(dv = rep(c("acc", "rt"), each = 3), col = rep(c("black", "black", "red"), 2),
         Effect = smith.stroop$Effect)

stroop.effects <- merge(smith.stroop, repl.stroop,
                      by = c("Effect", "dv"), suffixes = c("Smith", "Replication"))

stroop.plot <- ggplot(data = stroop.effects, aes(x = pesSmith, y = pesReplication, shape = dv)) +
  geom_point(size = 2.5, col = stroop.effects$colSmith) +
  xlim(0, 1.00) +
  ylim(0, 1.00) +
  geom_abline(slope = 1, intercept = 0, col = "blue") +
  theme_classic() +
  theme(legend.position = c(0.2, 0.85),
        legend.background = element_rect(colour = "black",
                                           linetype = "solid",
                                           fill = "lightgray"),
        legend.title = element_blank(),
        legend.margin = margin(-3, 5, 0, 0)) +
  labs(y = "Replication", x = "Smith", title = "Stroop")

###Exp2 (Task-switching)
smith.ts <- smith_anovas[[3]] %>%
  ungroup() %>%
  bind_rows(smith_anovas[[4]]) %>%
  select(Effect = rowname, pes, LL, UL) %>%
  mutate(dv = rep(c("acc", "rt"), each = 7),
         col = rep(c("black", "black", "black", "black", "red", "black", "black"), 2))

repl.ts <- repl_anovas[[3]] %>%
  ungroup() %>%
  bind_rows(repl_anovas[[4]]) %>%
  select(Effect = rowname, pes, LL, UL) %>%
  mutate(dv = rep(c("acc", "rt"), each = 7),
         col = rep(c("black", "black", "black", "black", "red", "black", "black"), 2),
         Effect = smith.ts$Effect)

ts.effects <- merge(smith.ts, repl.ts,
                  by = c("Effect", "dv"), suffixes = c("Smith", "Replication"))

```

```

ts.plot <- ggplot(data = ts.effects, aes(x = pesSmith, y = pesReplication, shape = dv)) +
  geom_point(size = 2.5, col = ts.effects$colSmith) +
  xlim(0, 1.00) +
  ylim(0, 1.00) +
  geom_abline(slope = 1, intercept = 0, col = "blue") +
  theme_classic() +
  theme(legend.position = c(0.2, 0.85),
        legend.background = element_rect(colour = "black",
                                           linetype = "solid",
                                           fill = "lightgray"),
        legend.title = element_blank(),
        legend.margin=margin(-3,5,0,0)) +
  labs(y = "Replication", x = "Smith et al.", title = "Task-Switching")

###Exp3 (Visual Search)
smith.vs <- smith_anovas[[5]] %>%
  ungroup() %>%
  bind_rows(smith_anovas[[6]]) %>%
  select(Effect = rowname, pes, LL, UL) %>%
  mutate(dv = rep(c("acc","rt"), each = 3),
         col = rep(c("black","black","red"),2))

repl.vs <- repl_anovas[[5]] %>%
  ungroup() %>%
  bind_rows(repl_anovas[[6]]) %>%
  select(Effect = rowname, pes, LL, UL) %>%
  mutate(dv = rep(c("acc","rt"), each = 3),
         col = rep(c("black","black","red"),2),
         Effect = smith.vs$Effect)

vs.effects <- merge(smith.vs, repl.vs,
                   by = c("Effect","dv"), suffixes = c("Smith",
                                                         "Replication"))

vs.plot <- ggplot(data = vs.effects, aes(x = pesSmith, y = pesReplication, shape = dv)) +
  geom_point(size = 2.5, col = vs.effects$colSmith) +
  xlim(0, 1) +
  ylim(0, 1) +
  geom_abline(slope = 1, intercept = 0, col = "blue") +
  theme_classic() +
  theme(legend.position = c(0.2, 0.85),
        legend.background = element_rect(colour = "black",
                                           linetype = "solid",
                                           fill = "lightgray"),
        legend.title = element_blank(),
        legend.margin=margin(-3,5,0,0)) +
  labs(y = "Replication", x = "Smith", title = "Visual Search")

all.plot <- plot_grid(stroop.plot, ts.plot, vs.plot, ncol = 3)

title <- ggdraw() +


```

```

draw_label(
  "Effect Size Comparisons",
  fontface = 'bold',
  x = 0,
  hjust = 0
) +
theme(
  # add margin on the left of the drawing canvas,
  # so title is aligned with left edge of first plot
  plot.margin = margin(0, 0, 0, 7)
)
all.plot <- plot_grid(
  title, all.plot,
  ncol = 1,
  # rel_heights values control vertical title margins
  rel_heights = c(0.1, 1)
)
all.plot

```

## Effect Size Comparisons



```

ggsave(all.plot,
  file = "plots/all_effects_plot.pdf",
  units = "in",
  width = 9.5,
  height = 4.50,
  dpi = 600)

```

```

### Forest plot
#Graph comparison of key effects for all three experiments
forest.colors <- c("black", "red")

forest.data <- data.frame(Experiment = rep(c("Smith", "Replication"), 3),
                           name = rep(c("Stroop", "Task-switching", "Visual Search"), each = 2),
                           dv = rep(c("rt", "acc", "rt"), each = 2),
                           pes = numeric(6),
                           LL = numeric(6),
                           UL = numeric(6))

forest.data[1,4:6] <- smith_anovas[[2]][3,c(6,8,9)]
forest.data[2,4:6] <- repl_anovas[[2]][3,c(6,8,9)]


forest.data[3,4:6] <- smith_anovas[[3]][5,c(6,8,9)]
forest.data[4,4:6] <- repl_anovas[[3]][5,c(6,8,9)]

forest.data[5,4:6] <- smith_anovas[[6]][3,c(6,8,9)]
forest.data[6,4:6] <- repl_anovas[[6]][3,c(6,8,9)]

forest.comp <- mod.forestplot(df = forest.data,
                              estimate = pes,
                              ci.lower = LL,
                              ci.upper = UL,
                              colour = Experiment,
                              xlab = "Partial Eta-Squared"
) +
  scale_color_manual(values = forest.colors) +
  scale_x_continuous(labels = label_number(accuracy = 0.01), breaks = seq(0.00, 0.60, 0.10)) +
  #Too busy w/numbers for effects?
  geom_label(data = subset(forest.data, Experiment == "Smith"),
             aes(label = round(pes, digits = 2))) +
  geom_label(data = subset(forest.data, Experiment == "Replication"),
             aes(label = round(pes, digits = 3),
                 vjust = 2.50)) +
  coord_cartesian(clip="off") #Disable clipping to draw outside plot area

## Scale for 'colour' is already present. Adding another scale for 'colour', which will replace the
## existing scale.
forest.comp

```



```
ggsave(forest.comp,
       file = "plots/forest_plot.pdf",
       units = "in",
       width = 6,
       height = 6,
       dpi = 600)

#Compare proportions: replication divided by original effect sizes
replication.effects <- subset(forest.data, Experiment == "Replication")
original.effects    <- subset(forest.data, Experiment == "Smith")

#As a percentage
prop.effects <- (replication.effects$pes/original.effects$pes)*100
#< 1%, ~9%, and < 101%
prop.effects

## [1] 0.6181838 9.0496059 0.1801278

#Average proportion is 3.28%
mean(prop.effects)

## [1] 3.282639
```