

FORK COMPATIBILITY LIST FOR PROGUARD BOLT ON MUDGUARDS

*** ALWAYS CHECK BOTTOM OUT CLEARANCE BEFORE USE AS MANUFACTURERS ARE CHANGING THEIR DESIGNS CONSTANTLY ***

THIS LIST IS ONLY BASED ON 27.5" & 29" FORKS THAT HAVE THREADED HOLES WITH A MIN OFFSET OF 44MM - PLEASE CHECK YOUR FORK

KEY

	COMPATIBLE	➡	ANY NUMBER SHOWN RELATES TO THE ADAPTER REQUIRED
	MAY BE COMPATIBLE	➡	SEE NOTES - MAY BE MODEL SPECIFIC OR NEED MODIFICATION - NUMBER SHOWS ADAPTER BRACKET ALSO REQUIRED - SEE ADAPTERS
	UNKNOWN / NOT TESTED	➡	COMPATABILITY UNKNOWN / NOT TESTED
	NOT COMPATIBLE	➡	CABLE TIE PROGUARDS ARE COMPATIBLE WITH MOST CONVENTIONAL FORKS (VELCRO PACKS ALSO AVAILABLE)
V1	ORIGINAL BOLT ON V1	➡	SIZES AVAILABLE - MINI / STANDARD
V2	NEW BOLT ON V2	➡	SIZES AVAILABLE - MINI / STANDARD / MAX PROTECTION

MAKE / MODEL	*MODEL YEAR (MY)					NOTES
FOX	2019	2020	2021	2022	2023	
32						
34 NON STEP-CAST				1	1	V2 ONLY - Hollow fork brace versions with no supports need an adapter bracket (see below)
34 STEP-CAST				2	2	V1 & V2 (V2 tight fit) - Hollow fork brace versions with no supports need an adapter bracket (see below)
36			3	3	3	Rounded arch MY2021 needs the Fox 36 Stability Bracket (supplied in pack) - Must check earlier models for bottom out
38						
40	4	4				
49	4	4				
AWL 29"						
MARZOCCHI	2019	2020	2021	2022	2023	NOTES
BOMBER Z1						
BOMBER Z2						Z2 forks don't come with any threaded holes - if you decide to add helicoil threads then it will fit
BOMBER 58						
BOMBER DJ						
ROCKSHOX	2019	2020	2021	2022	2023	NOTES
RECON GOLD						
RECON SILVER						BOOST HUB FORKS ONLY - Use the M6 bolt for the centre threaded hole only
JUDY GOLD						
JUDY SILVER						If it has threaded holes, use the M6 bolt for the centre threaded hole only (tight fit)
BLUTO						No threaded holes
REBA						If it has threaded holes, use the M6 bolt for the centre threaded hole only
35 GOLD / SILVER						Use the M6 bolt for the centre threaded hole only
SID ULTIMATE						

SID SELECT+						
SID SELECT / BASE						
SID SL						
REVELATION						
PARAGON						Use the M6 bolt for the centre threaded hole only
YARI						
RUDY XPLR						Use the M6 bolt for the centre threaded hole only
PIKE				12	12	Need to use Lyrik / Pike Adapter Bracket
LYRIK - MTB FORK				12	12	V2 only - Need to use Lyrik / Pike Adapter Bracket
LYRIK UTILITY FORK						As used on Utility bikes with additional mounts - Use the M6 bolt for the centre threaded hole only
ZEB			5	5	5	V2 ONLY - v1 not compatible - Needs Zeb / Domain adapter bracket
DOMAIN				5	5	V2 ONLY - v1 not compatible - Needs Zeb / Domain adapter bracket
BOXXER						
OHLINS	<2020	2020	2021	2022	2023	NOTES
RXF32						
RXF34		6	6	6	6	Need to use RXF34 Fitting Kit
RXF36		7	7	7	7	Need to use Ohlins Stability Bracket
RXF38			8	8	8	V1 not compatible with 70mm XL CSU crown - see how to modify the bolt on v1 below
DH38		7	7	7	7	Needs Ohlins RXF36 Stability Bracket - Max size not suitable for DH due to poor rubber contact with fork
DVO	<2020	2020	2021	2022	2023	NOTES
DIAMOND D1 TO E3			9	9	9	Needs our custom bolt / washer
ONYX SC - D1 TO E1			10	10	10	Needs our DVO D1 Onyx SC Adapter Bracket and bolt / washer
ONYX D1 38						
ONYX DC						
SAPPHIRE D1						
SR SUNTOUR	<2020	2020	2021	2022	2023	NOTES
RUX38						Forks with an unthreaded straight through hole in the centre needs our SLEEVE PACK (PGBOSP)
DUROLUX36						
DUROLUX38						
AURON35						
AXON-WERX						
AXON-ELITE						
AXON32/34/35						
AXON36/38						
ZERON35/36						
RAIDON32/34						

XCR32						Use the M6 bolt for the centre threaded hole only
XCR34						May need supplied tilt bracket to raise the front
XCM						Use M6 bolt for centre threaded hole
XCM32						
XCM34						Use M6 bolt for centre threaded hole
XCT					13	Needs SR SUNTOUR Sleeve Pack
XCE 27.5"						May need to use supplied Tilt Bracket to lower front
XFUSION	<2020	2020	2021	2022	2023	NOTES
RV-1 HLR / METRIC						Not enough tyre clearance
TRACE 34						OEM fork
TRACE 36		11	11	11	11	
SWEEP / SLANT						No threaded holes
MCQUEEN						
REVEL X						Not compatible with any upside down fork
SLIDE 32MM/ 34MM						No threaded holes
VELVET						No threaded holes
RC32						No threaded holes
MIG 27.5 32		11	11	11	11	Bolt On v1 use just M6 centre bolt to secure / for v2 use Adapter Bracket 11 detailed below
EXTREME SHOX	<2020	2020	2021	2022	2023	NOTES
ERA V1		11	11	11	11	Needs our EXT ERA Adapter Bracket (see bracket 11 below)
ERA V2				11	11	Needs our EXT ERA Adapter Bracket (see bracket 11 below)
OTHERS FORKS NOT LISTED ABOVE						NOTES
CANE CREEK						Adapter was designed but there was insufficient tyre clearance
BRIGHT RACING						Doesn't fit upside-down forks
FORMULA						2023 Earlier - No threaded holes in rear of fork brace
RST SELVA						
MANITOU						Doesn't fit upside-down or reverse arch forks
BOS						No threaded holes in rear of fork brace
MRP						No threaded holes in rear of fork brace
DT SWISS						Adapter was designed but there was insufficient stability and clearance
TRUST						No threaded holes or rear fork brace
WREN						Doesn't fit upside-down forks
INTEND						Doesn't fit upside-down forks

* The year your fork or bike was purchased brand new isn't always the model year (MY) of your fork - older model year forks are sold on brand new bikes so check first

EVERY EFFORT IS MADE TO ENSURE THE ABOVE DETAILS ARE CORRECT, THERE ARE HUNDREDS OF FORKS / VARIATIONS SO PLEASE ADVISE IF NOT CORRECT

PROGUARD ADAPTER BRACKET DETAILS

No	CODE	PRODUCT NAME	MUDGUARD	PRODUCT / DESCRIPTION
1	PGBOF34	FOX 34 (HOLLOW BRACE) NON STEP-CAST ADAPTER BRACKET	V2	FOX 34 (HOLLOW BRACE) NON STEP-CAST ADAPTER BRACKET - NON STEP-CAST version only
2	PGBOF34S	FOX 34 (HOLLOW BRACE) STEP-CAST ADAPTER BRACKET	V1 & V2	FOX 34 (HOLLOW BRACE) STEP-CAST ADAPTER BRACKET - STEP-CAST version only
3	PGBOF36	FOX 36 STABILITY BRACKET	V1 & V2	FOX 36 STABILITY BRACKET - Supplied with v1 mudguard / not supplied with v2 mudguard
4	PGBOF40	FOX 40/49 ADAPTER BRACKET (49 v2 ONLY) 26" & 27.5"	V1 & V2	FOX 40/49 ADAPTER BRACKET (49 v2 ONLY) 26" & 27.5" forks only (includes bolts / washer)
5	PGBOZD	ROCKSHOX ZEB / DOMAIN ADAPTER BRACKET	V2	ROCKSHOX ZEB / DOMAIN ADAPTER BRACKET (includes bolt)
6	PGBORXF34	OHLINS RXF34 FITTING KIT	V1 & V2	OHLINS RXF34 FITTING KIT required (includes spacer and bolt)
7	PGOSB	OHLINS RXF36 / DH38 STABILITY BRACKET	V1 & V2	Ohlins STABILITY BRACKET for RXF36 / DH38
8	PGBORXF38	OHLINS RXF38 STABILITY BRACKET	V2	OHLINS RXF38 STABILITY BRACKET
9	PGBODVOB	DVO DIAMOND M4 x 14mm / Washer	V1 & V2	DVO DIAMOND M4 x 14mm / Washer
10	PGBODVO	DVO ONYX SC ADAPTER BRACKET & BOLT/WASHER	V1 & V2	DVO ONYX SC ADAPTER BRACKET & BOLT/WASHER (includes bolt / washer)
11	PGERAXFT36	EXT ERA/XFUSION TRACE36 ADAPTER BRACKET	V1 & V2	v1 & v2 EXT ERA / v1 & v2 XFUSION TRACE36 - MIG 27.5 32 needs bracket only for v2 bolt on
12	PGBOLP	ROCKSHOX LYRIK / PIKE ADAPTER BRACKET	V2	For 2022 Lyrik / Pike
13	PGBOSP	SR SUNTOUR - FITTING KIT (OPEN HOLE)	V1 & V2	For straight through UNTHREADED centre holes

MODIFYING THE ORIGINAL BOLT ON V1

Some fork versions (RXF38) have extra large CSU crown that won't clear the bolt on v1 bracket on bottoming, however you still may be able to modify it to fit. You can see if your CSU is the standard or extra large version by simply measuring the widest point of the round top crown and checking the details below:



- 1. STANDARD CSU CROWN = Approximately 60mm
- 2. EXTRA LARGE CSU CROWN = Approximately 66mm -70mm

NOTE: You can check your bottom out clearance by removing the air from your fork and slowly depressing the fork to see if it clears the bracket

If yours is the XL version then you need to either buy the new bolt on v2 (which doesn't need modifying) or modify the bracket on your v1 mudguard for more bottom out clearance, you will still need the appropriate adapter bracket stated for you fork.
See how to modify below (WARNING - ADULTS ONLY):



WARNING ADULTS ONLY: BE CAREFUL NOT TO SLIP AND PUNCTURE THE MUDGUARD OR HURT YOURSELF

MODEL YEAR 2022 Fox 34

If you have the new MY22 Fox 34 fork with the hollowed out fork brace with no supports struts at the back (like the picture below), then you will need an adapter bracket, see compatibility below:

V2 COMPATIBLE WITH THE STEP-CAST VERSION & NORMAL NON-STEP CAST VERSION

V1 COMPATIBLE WITH THE STEP-CAST VERSION ONLY

EXAMPLE - HOLLOW BRACE WITHOUT SUPPORTS:



If you have a fork brace WITH centre support struts in the rear of the brace to support a mudguard, it will fit without an additional adapter bracket

EXAMPLES - FOX FORK BRACES WITH SUPPORTS BELOW:



EXAMPLE - FOX 34 STEP-CAST BELOW:



← STEP-CAST