

Hosting Queryable and Highly Available Linked Data for Free

Luca Matteis and Ruben Verborgh

<http://lucaa.org> / <http://ruben.verborgh.org/>

@lmatteis / @RubenVerborgh

Bioversity International / Multimedia Lab — Ghent University — iMinds

Motivation 1

SPARQL endpoints require the need to buy and configure complex servers.

You need to worry about:

- having the funds to keep the server running
- making sure the system is up-to-date
- many other sys-admin tasks


TL;DR

Hosting an RDF file is a lot easier than hosting a SPARQL endpoint.

Motivation 2

SPARQL endpoints suffer from low-availability.

They offer consumers the ability to run any query they want. Consumers will run any query they want and will quickly overload the server with too many complex requests.



Problem

Hosting SPARQL endpoints requires too much effort, both in terms of cost and server maintenance.

Fortunately SPARQL endpoints are not the only way of publishing queryable Linked Data.

Triple Pattern Fragments is a way of publishing queryable Linked Data on low cost servers.

LDstatic & LDF-GAE

We have developed two tools, LDstatic & LDF-GAE, that implement the *TPF* protocol on low cost servers.

TL;DR

Users can run SPARQL queries against Linked Data published on online file repositories and cloud hosting services such as **GitHub**, **Google Code**, **Google App Engine** or **Dropbox**.

LDstatic



GitHub Pages, and other online file repositories, can serve static HTML files.

It can also serve other type of content, such as N-Triples (**.nt**).

This means that GitHub Pages can serve triple pattern fragments.

LDstatic

We want to match

```
<foo> <bar> "literal" .
```

using:

```
/?subject=<foo>  
/?predicate=<bar>  
/?object="literal"  
/?subject=<foo>&predicate=<bar>  
...
```

We need at least 8 static files for each triple if we want to match all combinations.

LDstatic

Having all combinations is important for triple pattern fragments enabled clients so they can run complex queries, even SPARQL queries!

So we can host queryable linked data on GitHub Pages:

<http://lmatteis.github.io/ldstatic/>

LDF-GAE



Now we talk about our other TPF implementation, which lets us run SPARQL queries on Google App Engine.

<http://ldf-gae.appspot.com/>

Instead of static files we use their native APIs to store and retrieve triples.

LDF-GAE

Storing triples on App Engine's high-replication datastore is quite simple, and we can even match combinations using their native APIs.

Stored as:

```
{
  "subject"  : triple.getSubject().toString(),
  "predicate": triple.getPredicate().toString(),
  "object"   : triple.getObject().toString()
}
```

LDF-GAE

To retrieve each triple pattern combination we use their native API calls:

```
// query datastore
var query = new Query('triple');
query.addFilter('subject',
    Query.FilterOperator.EQUAL, request.getParameter('subject'));
query.addFilter('predicate',
    Query.FilterOperator.EQUAL, request.getParameter('predicate'));
query.addFilter('object',
    Query.FilterOperator.EQUAL, request.getParameter('object'));
```

LDF-GAE

To retrieve each triple pattern combination we use their native API calls:

```
$curl http://ldf-gae.appspot.com/↵  
?predicate=↵  
http%3A%2F%2Fxmlns.com%2Ffoaf%2F0.1%2Fname
```

Response:

```
<http://www.kjetil.kjernsmo.net/foaf#me> <http://xmlns.com/foaf/0.1/name> "Kjetil Kjernsmo" .  
<http://www.cs.umd.edu/~hendler/2003/foaf.rdf#jhendler> <http://xmlns.com/foaf/0.1/name> "Jim Hendler" .  
<http://www.w3.org/People/Jacobs/contact.rdf#IanJacobs> <http://xmlns.com/foaf/0.1/name> "Ian Jacobs" .  
<http://id.ecs.soton.ac.uk/person/60> <http://xmlns.com/foaf/0.1/name> "Les Carr" .  
<http://people.csail.mit.edu/psz/foaf.rdf#me> <http://xmlns.com/foaf/0.1/name> "Peter Szolovits" .  
<http://www.w3.org/People/EM/contact#me> <http://xmlns.com/foaf/0.1/name> "Eric Miller" .
```

How is this novel?

We can exploit a variety of [free](#) hosting services to publish our Linked Data and have clients query them. No more sys-admin tasks. Less down times.

For small datasets this is **more sustainable**, **more economical** and best of all it's **easier**!

How to use?

Both tools are on GitHub with documentation and you can use them right now:

<https://github.com/lmatteis/ldstatic>

<https://github.com/lmatteis/ldf-gae>

Conclusion

We proved that triple pattern fragments is a type of linked data can be published with high availability on low-cost Web servers ranging from basic file repositories to highly scalable cloud platforms.

References

Linked Data Fragments –

<http://linkeddatafragments.org/>

Triple Pattern Fragments protocol –

<http://www.hydra-cg.com/spec/latest/triple-pattern-fragments/>

Thank you!