

Annexure B5-2

Flood Compatible Material

Table 1 List of suitable flood compatible materials

Building Component	
Flooring and sub-floor	• Concrete slab-on-ground monolith
	• suspended reinforced concrete slab
Floor covering	• clay tiles
	• concrete, precast or in situ
	• concrete tiles
	• epoxy, formed-in-place
	• mastic flooring, formed-in-place
	• rubber sheets or tiles with chemicals-set-adhesive
	• silicone floors formed-in-place
	• vinyl sheets or tiles with chemical-set adhesive
	• ceramic tiles, fixed with mortar or chemical-set
	• asphalt tiles, fixed with water resistant adhesive
Wall structure	• Solid brickwork, block work, reinforced, concrete or
Roofing structure (for situations where the relevant flood level is	• reinforced concrete construction
	• galvanised metal construction
Doors	• solid panel with water proof adhesives
	• flush door with marine ply filled with cell foam
	• painted metal construction
	• aluminium or galvanised steel frame
Wall and ceiling linings	• fibro-cement board
	• brick face or glazed
	• clay tile glazed in waterproof mortar
	• concrete
	• concrete block
	• steel with waterproof applications
	• stone, natural solid or veneer, waterproof grout
	• glass blocks
	• glass
	• plastic sheeting or wall with waterproof adhesive
Insulation windows	• Foam (closed cell types)
	• Aluminium frame with stainless steel rollers or similar corrosion and water resistant material
Nails, bolts, hinges and fittings	• Brass, nylon or stainless steel;
	• Removable pin hinges
	• Hot dipped galvanised steel wire nails or similar.