Gestiona Gateway API Documentation

Versão 1.9.4

Index

Models

- UploadDocumentRequest
- CreateProcessRequest
- RelatedProcessesRequest
- RelatedProcessItem
- GatewayResponse
- UploadDocumentResult
- UploadDocumentError
- ThirdResult
- ThirdError
- ActivityItem
- ProcedureItem
- ActivityError
- ProcessResult
- ProcessError
- ProcessThirdsResult
- ProcessThirdsError
- ProcessDocumentItem
- ProcessDocumentSignatureResult
- ProcessDocumentsError
- ProcessAssigneeUserRequest
- ProcessAssigneeUserResult
- ProcessAssigneeGroupResult
- QueueConnectorMessageResult
- SendQueueConnectorResponseRequest
- QueueConnectorResponseResult
- QueueError
- AddOnAuthorizationResult
- AddOnAuthorizationStatusResult
- Download Success Output

Shared

- Request headers

Endpoints

- 1. POST `/processes`
- 2. POST `/processes/related`
- 3. GET `/processes/{process_id}/related`
- 4. DELETE `/processes/{process_id}/related/{related_process_id}`
- 5. GET `/processes?process_number=<numero>`
- 6. POST `/processes/documents?process_number=<numero>`
- 7. POST `/processes/{process_id}/documents`

- 8. POST `/processes/documents/{folder_id}?process_number=<numero>`
- 9. POST `/processes/{process_id}/documents/{folder_id}`
- 10. GET `/processes/thirds?process_number=<numero>`
- 11. GET `/processes/{process_id}/thirds`
- 12. GET `/processes/{process_id}/documents`
- 13. GET `/processes/{process_id}/documents/{document_id}`
- 14. GET `/processes/{process_id}/documents/{document_id}/signatures`
- 15. GET `/processes/assignees/users`
- 16. GET `/processes/assignees/groups`
- 17. GET `/activities`
- 18. GET `/activities/{activity_id}/procedures`
- 19. GET `/documents/{document_id}`
- 20. GET `/thirds?nif=<nif>`
- 21. GET `/thirds/{third_id}`
- 22. GET `/queues/connectors/{connector_name}`
- 23. GET `/queues/connectors/{connector_name}/{message_id}`
- 24. POST `/queues/connectors/{connector_name}/{message_id}`
- 25. POST `/addon/authorizations`
- 26. GET `/addon/authorizations/{auth_id}`
- 27. GET `/processes/{process_id}/procedure-data`
- 28. GET `/processes/{process_id}/procedure-data/{reference_id}`

Models

AddOnAuthorizationResult

Returned inside `GatewayResponse.result` after creating an add-on authorization.

```
{
  "authId": "string"
}
```

AddOnAuthorizationStatusResult

Returned inside `GatewayResponse.result` when checking an add-on authorization.

Pending authorization:

```
{
  "authorized": false,
  "authorizeUrl": "string"
}
```

Authorized:

```
{
  "authorized": true,
  "authorizedInfo": {
    "userId": "string",
    "accessToken": "string"
  }
}
```

UploadDocumentRequest

Used as the request body for all upload endpoints.

```
{
  "operationId": "string | null",
  "id": "string | null",
  "name": "string | null",
  "fileName": "string | null",
  "documentSourceType": "string | null",
  "url": "string | null",
  "content": "string | null",
  "elaboration_state": "string | null",
  "metadata_type": "string | null",
  "metadata_subtype": "string | null"
}
```

Field notes

- `documentSourceType` Expected values in the current implementation are `DIGITAL`, `EXTERNAL_URL`, and `FOLDER`.
- `fileName` Used for DIGITAL uploads when the file is read from local storage.
- `content` Base64-encoded file content for DIGITAL uploads.
- `url` External URL used when `documentSourceType` is `EXTERNAL_URL`.
- `elaboration_state` Optional. Defaults to `EE01` when omitted or null.
- `metadata_type` Optional. Defaults to `TD99` when omitted or null.
- `metadata_subtype` Optional. When omitted or null, this field is not sent to Gestiona.

These three fields are forwarded to the Gestiona document-creation call for `DIGITAL` and `EXTERNAL_URL` requests. They are not included in folder-creation payloads.

CreateProcessRequest

Used as the request body for `POST /processes`.

```
{
  "activityId": "string",
  "procedureId": "string",
  "userId": "string",
  "groupId": "string",
  "freeSubject": "string"
}
```

Field notes

- `activityId` Sent upstream as the Gestiona catalog procedure id in `catalog-2015/procedures/{activityId}`.
- `procedureId` Sent upstream as the Gestiona external procedure id in `external-procedures/{procedureId}`.
- `userId` Used to build the file-opening initial assignation link: `{GestionaApiBaseUrl}/users/{userId}`.
- `groupId` Used to build the file-opening management unit group link: `{GestionaApiBaseUrl}/groups/{groupId}`.
- `freeSubject` Sent upstream as `free_title`.

RelatedProcessesRequest

Used as the request body for `POST /processes/related`.

```
{
  "id1": "string",
  "id2": "string"
}
```

Field notes

- `id1` The Gestiona file id that will receive the related-file link.
- `id2` The Gestiona file id to link as a related file.

RelatedProcessItem

Used for each item in `GatewayResponse.result` returned by `GET /processes/{process_id}/related`.

```
{
  "id": "string | null",
  "processNumber": "string | null"
}
```

Field notes

- `id` Mapped from each upstream related file `content` item `id` field.
- `processNumber` Mapped from each upstream related file `content` item `code` field.

GatewayResponse

Used as the response envelope for gateway success and error responses.

```
{
  "operationId": "string | null",
  "success": true,
  "result": {}
}
```

UploadDocumentResult

Used inside `GatewayResponse.result` on upload success.

```
{
  "id": "string",
  "processId": "string",
  "creation_date": "string",
  "modification_date": "string"
}
```

Field notes

- `id` The API returns the created Gestiona entity id. If the upstream create response does not include `id`, the service resolves it from the last path segment of the `self` link in the upstream `links` collection.

UploadDocumentError

Used inside `GatewayResponse.result` on upload errors and download errors.

```
{
  "code": 400,
  "name": "Bad Request",
  "kind": "Validation",
  "message": "string"
}
```

Possible `kind` values for upload

- `Configuration`
- `Validation`
- `NotFound`
- `Upstream`

Possible `kind` values for download

- `Configuration`
- `Validation`
- `NotFound`
- `Upstream`

ThirdResult

Used inside `GatewayResponse.result` on third lookup success.

```
{
  "full_name": "string | null",
  "first_name": "string | null",
  "second_surname": "string | null",
  "nif_country": "string | null",
  "id": "string | null",
  "nif": "string | null",
  "type": "string | null",
  "email": "string | null",
  "mobile": "string | null",
  "nif_type": "string | null",
  "address": "string | null",
  "number": "string | null",
  "block": "string | null",
  "stair": "string | null",
  "floor": "string | null",
  "door": "string | null",
  "extension": "string | null",
  "zip_code": "string | null",
  "province": "string | null",
  "country": "string | null",
  "type_of_road": "string | null",
  "zone": "string | null",
  "parish_code": "string | null"
}
```

Field notes

- Address fields are obtained from Gestiona `GET /thirds/{third_id}/default-address` after the base third is retrieved.
- `block`, `stair`, `floor`, `door`, and `extension` are mapped from the corresponding fields in the default-address response.

ThirdError

Used inside `GatewayResponse.result` on third lookup errors.

```
{
  "code": 400,
  "name": "Bad Request",
  "kind": "Validation",
  "message": "string"
}
```

Possible `kind` values for third lookup

- `Configuration`
- `Validation`
- `NotFound`
- `Upstream`

ActivityItem

Used for each item in `GatewayResponse.result` returned by `GET /activities`.

```
{
  "id": "string | null",
  "name": "string | null"
}
```

ProcedureItem

Used for each item in `GatewayResponse.result` returned by `GET /activities/{activity_id}/procedures`.

```
{
  "id": "string | null",
  "name": "string | null",
  "activityId": "string | null"
}
```

Field notes

- `name` Mapped from the upstream external procedure `title` field.
- `activityId` Copied from the `activity_id` route parameter.

ActivityError

Used inside `GatewayResponse.result` on activity and procedure lookup errors.

```
{
  "code": 400,
  "name": "Bad Request",
  "kind": "Upstream",
  "message": "string"
}
```

Possible `kind` values

- `Configuration`
- `Upstream`

ProcessResult

Used inside `GatewayResponse.result` on process lookup success.

```
{
  "Id": "string",
  "processNumber": "string"
}
```

Field notes

- `Id` The resolved Gestiona file id.
- `processNumber` The process number used to resolve the file id.

ProcessError

Used inside `GatewayResponse.result` on process lookup errors.

```
{
  "code": 400,
  "name": "Bad Request",
  "kind": "Validation",
  "message": "string"
}
```

Possible `kind` values for process lookup

- `Configuration`
- `Validation`
- `NotFound`
- `Upstream`

ProcessThirdsResult

Used inside `GatewayResponse.result` on process thirds lookup success.

```
{
  "processId": "string",
  "thirds": "third-id-1;third-id-2"
}
```

Field notes

- `thirds` Semicolon-separated third ids extracted from each upstream `rel: third` link.

ProcessThirdsError

Used inside `GatewayResponse.result` on process thirds lookup errors.

```
{
  "code": 400,
  "name": "Bad Request",
  "kind": "Validation",
  "message": "string"
}
```

Possible `kind` values for process thirds lookup

- `Configuration`
- `Validation`
- `NotFound`
- `Upstream`

ProcessDocumentItem

Used for each item in `GatewayResponse.result` returned by the process document-listing endpoints.

```
{
  "type": "DOC",
  "name": "POC_SIGMA_Gestiona",
  "id": "f5e0364b-9951-449d-8d38-34a6cbfec4d3"
}
```

Field notes

- `type` The upstream item type, such as `DOC` or `FOLDER`.
- `name` The upstream `rel` value.
- `id` The last path segment of the upstream `href`.

ProcessDocumentSignatureResult

Used for each item in `GatewayResponse.result` returned by `GET /processes/{process_id}/documents/{document_id}/signatures`.

```
{
  "date_signed": "string | null",
  "signature_state": "string | null",
  "username": "string | null",
  "name": "string | null"
}
```

Field notes

- `date_signed` Mapped from the upstream signature `date` field after formatting with `DateTimeHelpers.FormatUnixTimestamp`.
- `signature_state` Mapped from the upstream signature `signature_state` field.
- `username` Mapped from the user response obtained by following the signature link where `rel` is `signed-user` or `signer-user`.
- `name` Mapped from the user response obtained by following the signature link where `rel` is `signed-user` or `signer-user`.

ProcessDocumentsError

Used inside `GatewayResponse.result` when a process document-listing request fails.

```
{
  "code": 400,
  "name": "Bad Request",
  "kind": "Validation",
  "message": "string"
}
```

Possible `kind` values

- `Configuration`
- `Validation`
- `NotFound`
- `Upstream`

ProcessAssigneeUserRequest

Used as the JSON request body for `GET /processes/assignees/users`.

```
{
  "username": "string"
}
```

ProcessAssigneeUserResult

Used inside `GatewayResponse.result` on assignee user lookup success.

```
{
  "id": "string | null",
  "username": "string | null",
  "name": "string | null"
}
```

ProcessAssigneeGroupResult

Used for each item in `GatewayResponse.result` returned by `GET /processes/assignees/groups`.

```
{
  "id": "string | null",
  "name": "string | null"
}
```

QueueConnectorMessageResult

Used inside `GatewayResponse.result` on queue connector message success. For `GET /queues/connectors/{connector_name}`, `result` is an array of this model.

```
{
  "message_id": "string | null",
  "date_signed": "string | null"
}
```

Field notes

- `message_id` Mapped from the upstream queue message `payload.target` field.
- `date_signed` Mapped from the upstream queue message `entry` field after formatting with `DateTimeHelpers.FormatUnixTimestamp`.

SendQueueConnectorResponseRequest

Used as the JSON request body for `POST /queues/connectors/{connector_name}/{message_id}`.

```
{
  "result_success": "string",
  "message": "string | null"
}
```

Field notes

- `result_success` Required. Sent upstream as `result_success`.
- `message` Optional. When null or not present, it is not sent in the upstream JSON payload.

QueueConnectorResponseResult

Used inside `GatewayResponse.result` when a connector response is sent successfully.

```
{
  "connector_name": "string",
  "message_id": "string"
}
```

QueueError

Used inside `GatewayResponse.result` on queue connector errors.

```
{
  "code": 400,
  "name": "Bad Request",
  "kind": "Validation",
  "message": "string"
}
```

Possible `kind` values for queue connector message

- `Configuration`
- `Validation`
- `NotFound`
- `NoActiveSubscription`
- `Upstream`

Download Success Output

The download endpoint does not return JSON on success. It returns the raw document bytes in the response body.

Relevant response characteristics

- Body: binary file content
- `Content-Type`: document MIME type returned by Gestiona, or `application/octet-stream` as fallback
- `Content-Disposition`: attachment, with automatic download filename

The underlying DLL model used by the service layer is

```
{
  "documentId": "string",
  "fileName": "string | null",
  "contentType": "string | null",
  "storageSize": 0,
  "storageExtension": "string | null",
  "storageMimeType": "string | null",
  "storageMd5": "string | null",
  "storageSha1": "string | null",
  "storageSha512": "string | null",
  "content": "byte[]"
}
```

Request headers

All endpoints can optionally receive:

- `X-User-Access-Token` When present and not blank, the gateway uses this value as the upstream Gestiona `X-Gestiona-Access-Token`.

If `X-User-Access-Token` is absent or blank, the gateway uses the configured token from `Gestiona:AccessToken`.

The queue connector endpoints are exceptions: they always use the configured token from `Gestiona:AccessToken` and ignore the request header token.

Endpoints

1. POST `/processes`

Creates a new Gestiona process by creating the upstream file from the catalog/external procedure pair and then opening that file through the `file-open` link returned by Gestiona.

Query parameters

- `operationId` optional

Request body model

- `CreateProcessRequest`

Request body example

```
{
  "activityId": "82722c9b-cecc-4299-8a7b-ce5abeb8170b",
  "procedureId": "external-procedure-id",
  "userId": "3f18aa72-4091-4a50-8210-6c05ca234647",
  "groupId": "2bb7ddb2-a870-470d-ae87-3d4b2d3dd4af",
  "freeSubject": "Mais um processo criado a partir da API"
}
```

Upstream calls

1. `POST /catalog-2015/procedures/{activityId}/external-procedures/{procedureId}/create-file`
2. `GET /files/{process_id}/selectable-titles`

- `process_id` is extracted from the `file-open` link returned by create-file.
- If `selectable_titles` contains at least one non-blank value, the first value is used as `selectable_title` in the file-open request.

3. `POST {file-open href returned by create-file}`

- `Content-Type: application/vnd.gestiona.file-opening+json; version=1`
- `entry_date` is copied from the create-file response.
- `free_title` is copied from `freeSubject`.
- `selectable_title` is included only when a selectable title was returned by `GET /files/{process_id}/selectable-titles`.
- `initial_assignation[0].href` is `{GestionaApiBaseUrl}/users/{userId}`.
- `links[0].href` is `{GestionaApiBaseUrl}/groups/{groupId}` with `rel` equal to `management-unit-group`.

Success response

- HTTP `200 OK`
- Body model: `GatewayResponse`
- `result` shape: `ProcessResult`

Success example

```
{
  "operationId": "op-01",
  "success": true,
  "result": {
    "Id": "a7a43429-a82c-4245-9f50-f1e853905a99",
    "processNumber": "16/2026"
  }
}
```

Error response

- HTTP `400`, `500`, or propagated upstream status code
- Body model: `GatewayResponse`

- `result` shape: `ProcessError`

Notes

- The first upstream response must include `entry_date` and a link with `rel` equal to `file-open`.
- The `file-open` link must include the created Gestiona process id so the gateway can call `GET /files/{process_id}/selectable-titles`.
- The selectable-titles response shape is `{"required": true, "selectable_titles": ["Teste 1", "Teste 2"]}`.
- If `selectable_titles` is null, empty, or contains only blank values, `selectable_title` is omitted from the file-open request.
- The file-open upstream response must include both `id` and `code`.
- `ProcessResult.Id` is mapped from the file-open upstream response `id`.
- `ProcessResult.processNumber` is mapped from the file-open upstream response `code`.

2. POST `/processes/related`

Creates a related-file link between two Gestiona process files.

Route parameters

- none

Query parameters

- `operationId` optional

Request body model

- `RelatedProcessesRequest`

Request body example

```
{
  "id1": "30bcb012-47e2-4e7e-92e0-a0f7278b52b8",
  "id2": "a7a43429-a82c-4245-9f50-f1e853905a99"
}
```

Upstream calls

1. `POST /files/{id1}/related-files`

- `Content-Type: application/vnd.gestiona.links+json`
- Sends a `links` array with one item where `rel` is `related-files`.
- The link `href` is `{GestionaApiBaseUrl}/files/{id2}`.

Success response

- HTTP `200 OK`
- Body model: `GatewayResponse`
- `result` shape: `RelatedProcessesRequest`

Success example

```
{
  "operationId": "op-01",
  "success": true,
  "result": {
    "id1": "30bcb012-47e2-4e7e-92e0-a0f7278b52b8",
    "id2": "a7a43429-a82c-4245-9f50-f1e853905a99"
  }
}
```

Error response

- HTTP `400`, `404`, `500`, or propagated upstream status code
- Body model: `GatewayResponse`
- `result` shape: `ProcessError`

Notes

- If the request body is missing, the endpoint returns HTTP `400`.
- If `id1` or `id2` is empty or whitespace, the endpoint returns HTTP `400`.
- If Postman sends an unresolved variable such as `{{id1}}` or `{{id2}}`, the endpoint returns HTTP `400`.

3. GET `/processes/{process_id}/related`

Gets the process files related to a Gestiona process file.

Route parameters

- `process_id` required

Query parameters

- `operationId` optional

Request body model

- none

Upstream calls

1. `GET /files/{process_id}/related-files`

Success response

- HTTP `200 OK`
- Body model: `GatewayResponse`
- `result` shape: array of `RelatedProcessItem`

Success example

```
{
  "operationId": "op-01",
  "success": true,
  "result": [
    {
      "id": "3234c22f-961c-4dec-af3e-af5629076a22",
      "processNumber": "98/2026"
    }
  ]
}
```

Error response

- HTTP `400`, `404`, `500`, or propagated upstream status code
- Body model: `GatewayResponse`
- `result` shape: `ProcessError`

Notes

- The gateway reads the upstream `content` array.
- Each upstream `content` item `id` is mapped to `id`.
- Each upstream `content` item `code` is mapped to `processNumber`.
- If `process_id` is empty or whitespace, the endpoint returns HTTP `400`.
- If Postman sends an unresolved variable such as `{{process_id}}`, the endpoint returns HTTP `400`.

4. DELETE `/processes/{process_id}/related/{related_process_id}`

Deletes a related-file link between two Gestiona process files.

Route parameters

- `process_id` required
- `related_process_id` required

Query parameters

- `operationId` optional

Request body model

- none

Upstream calls

1. `DELETE /files/{process_id}/related-files/{related_process_id}`

Success response

- HTTP `200 OK`
- Body model: `GatewayResponse`
- `result` shape: empty object

Success example

```
{
  "operationId": "op-01",
  "success": true,
  "result": {}
}
```

Error response

- HTTP `400`, `404`, `500`, or propagated upstream status code
- Body model: `GatewayResponse`
- `result` shape: `ProcessError`

Notes

- If `process_id` or `related_process_id` is empty or whitespace, the endpoint returns HTTP `400`.
- If Postman sends an unresolved variable such as `{{process_id}}` or `{{related_process_id}}`, the endpoint returns HTTP `400`.

5. GET `/processes?process_number=<numero>`

Resolves the Gestiona file id associated with `process_number`.

Route parameters

- none

Query parameters

- `process_number` required
- `operationId` optional

Request body model

- none

Upstream calls

1. `GET /files` with filter `exact_code = process_number`

Success response

- HTTP `200 OK`
- Body model: `GatewayResponse`
- `result` shape: `ProcessResult`

Success example

```
{
  "operationId": "op-01",
  "success": true,
  "result": {
    "Id": "30bcb012-47e2-4e7e-92e0-a0f7278b52b8",
    "processNumber": "PROC-2026-001"
  }
}
```

Error response

- HTTP `400`, `404`, `500`, or propagated upstream status code
- Body model: `GatewayResponse`
- `result` shape: `ProcessError`

Notes

- `Id` is the resolved Gestiona file id, not the original `process_number`
- If no Gestiona file is found for `process_number`, the endpoint returns HTTP `404`
- If `process_number` is empty or whitespace, the endpoint returns HTTP `400`
- If Postman sends an unresolved variable such as `{{process_number}}`, the endpoint returns HTTP `400`

6. POST `/processes/documents?process_number=<numero>`

Creates a document by resolving the target Gestiona process_id (file id in gestiona) from the query parameter `process_number`.

Query parameters

- `process_number` required

Request body model

- `UploadDocumentRequest`

For `DIGITAL` and `EXTERNAL_URL` documents, `elaboration_state` defaults to `EE01`, `metadata_type` defaults to `TD99`, and `metadata_subtype` is sent only when provided with a non-null value. All three fields are optional.

Request body examples

`DIGITAL`

```
{
  "operationId": "op-123",
  "name": "Contrato",
  "fileName": "contrato.pdf",
  "documentSourceType": "DIGITAL",
  "elaboration_state": "EE01",
  "metadata_type": "TD99",
  "content": "JVBERi0xLjQKJ..."
}
```

`FOLDER`

```
{
  "operationId": "op-123",
  "name": "Expediente 2026",
  "documentSourceType": "FOLDER"
}
```

`EXTERNAL_URL`

```
{
  "operationId": "op-123",
  "name": "Referencia externa",
  "documentSourceType": "EXTERNAL_URL",
  "url": "https://example.com/documento/123"
}
```

Upstream calls

1. `GET /files` with filter `exact_code = process_number`
2. For `DIGITAL` requests:

- `POST /uploads`
- `PUT {upload_location}`
- `POST /files/{resolved_process_id}/documents-and-folders`

3. For `FOLDER` requests:

- `POST /files/{resolved_process_id}/documents-and-folders`

4. For `EXTERNAL_URL` requests:

- `POST /files/{resolved_process_id}/documents-and-folders`

Success response

- HTTP `200 OK`
- Body model: `GatewayResponse`
- `result` shape: `UploadDocumentResult`

Success example

```
{
  "operationId": "op-123",
  "success": true,
  "result": {
    "id": "document-id",
    "processId": "file-id",
    "creation_date": "2026-05-08 10:00:00",
    "modification_date": "2026-05-08 10:00:00"
  }
}
```

Error response

- HTTP `400`, `404`, `500`, or propagated upstream status code
- Body model: `GatewayResponse`
- `result` shape: `UploadDocumentError`

Error example

```
{
  "operationId": "op-123",
  "success": false,
  "result": {
    "code": 400,
    "name": "Bad Request",
    "kind": "Validation",
    "message": "process_number query parameter is required."
  }
}
```

7. POST `/processes/{process_id}/documents`

Creates a document directly in the Gestiona file identified by `process_id`.

Route parameters

- `process_id` required

Request body model

- `UploadDocumentRequest`

For `DIGITAL` and `EXTERNAL_URL` documents, `elaboration_state` defaults to `EE01`, `metadata_type` defaults to `TD99`, and `metadata_subtype` is sent only when provided with a non-null value. All three fields are optional.

Request body examples

`DIGITAL`

```
{
  "operationId": "op-123",
  "name": "Contrato",
  "fileName": "contrato.pdf",
  "documentSourceType": "DIGITAL",
  "elaboration_state": "EE01",
  "metadata_type": "TD99",
  "content": "JVBERi0xLjQKJ..."
}
```

`FOLDER`

```
{
  "operationId": "op-123",
  "name": "Expediente 2026",
  "documentSourceType": "FOLDER"
}
```

`EXTERNAL_URL`

```
{
  "operationId": "op-123",
  "name": "Referencia externa",
  "documentSourceType": "EXTERNAL_URL",
  "url": "https://example.com/documento/123"
}
```

Upstream calls

1. For `DIGITAL` requests:

- `POST /uploads`
- `PUT {upload_location}`
- `POST /files/{process_id}/documents-and-folders`

2. For `FOLDER` requests:

- `POST /files/{process_id}/documents-and-folders`

3. For `EXTERNAL_URL` requests:

- `POST /files/{process_id}/documents-and-folders`

Success response

- HTTP `200 OK`
- Body model: `GatewayResponse`
- `result` shape: `UploadDocumentResult`

Error response

- HTTP `400`, `404`, `500`, or propagated upstream status code
- Body model: `GatewayResponse`
- `result` shape: `UploadDocumentError`

Notes

- For `DIGITAL` uploads, either `fileName` or `content` must be provided.
- If both `fileName` and `content` are provided, the current implementation uses `content`.
- On successful create operations, `result.id` may come either from the upstream `id` field or, when that field is missing, from the last segment of the upstream `self` link.

8. POST `/processes/documents/{folder_id}?process_number=<numero>`

Creates a document inside the Gestiona folder identified by `folder_id`, after resolving the target Gestiona file from the query parameter `process_number`.

Route parameters

- `folder_id` required

Query parameters

- `process_number` required

Request body model

- `UploadDocumentRequest`

For `DIGITAL` and `EXTERNAL_URL` documents, `elaboration_state` defaults to `EE01`, `metadata_type` defaults to `TD99`, and `metadata_subtype` is sent only when provided with a non-null value. All three fields are optional.

Request body examples

`DIGITAL`

```
{
  "operationId": "op-123",
  "name": "Contrato",
  "fileName": "contrato.pdf",
  "documentSourceType": "DIGITAL",
  "elaboration_state": "EE01",
  "metadata_type": "TD99",
  "content": "JVBERi0xLjQKJ..."
}
```

`FOLDER`

```
{
  "operationId": "op-123",
  "name": "Expediente 2026",
  "documentSourceType": "FOLDER"
}
```

`EXTERNAL_URL`

```
{
  "operationId": "op-123",
  "name": "Referencia externa",
  "documentSourceType": "EXTERNAL_URL",
  "url": "https://example.com/documento/123"
}
```

Upstream calls

1. `GET /files` with filter `exact_code = process_number`
2. For `DIGITAL` requests:

- `POST /uploads`
- `PUT {upload_location}`
- `POST /files/{resolved_process_id}/documents-and-folders/{folder_id}`

3. For `FOLDER` requests:

- `POST /files/{resolved_process_id}/documents-and-folders/{folder_id}`

4. For `EXTERNAL_URL` requests:

- `POST /files/{resolved_process_id}/documents-and-folders/{folder_id}`

Success response

- HTTP `200 OK`
- Body model: `GatewayResponse`
- `result` shape: `UploadDocumentResult`

Error response

- HTTP `400`, `404`, `500`, or propagated upstream status code
- Body model: `GatewayResponse`
- `result` shape: `UploadDocumentError`

Notes

- This route uses the same document creation flows as the process-number route, but targets the upstream Gestiona endpoint with the folder id in the last path segment.
- For `DIGITAL` uploads, either `fileName` or `content` must be provided.
- If both `fileName` and `content` are provided, the current implementation uses `content`.
- On successful create operations, `result.id` may come either from the upstream `id` field or, when that field is missing, from the last segment of the upstream `self` link.

9. POST `/processes/{process_id}/documents/{folder_id}`

Creates a document directly inside the Gestiona folder identified by `folder_id`, under the file identified by `process_id`.

Route parameters

- `process_id` required
- `folder_id` required

Request body model

- `UploadDocumentRequest`

For `DIGITAL` and `EXTERNAL_URL` documents, `elaboration_state` defaults to `EE01`, `metadata_type` defaults to `TD99`, and `metadata_subtype` is sent only when provided with a non-null value. All three fields are optional.

Request body examples

`DIGITAL`

```
{
  "operationId": "op-123",
  "name": "Contrato",
  "fileName": "contrato.pdf",
  "documentSourceType": "DIGITAL",
  "elaboration_state": "EE01",
  "metadata_type": "TD99",
  "content": "JVBERi0xLjQKJ..."
}
```

`FOLDER`

```
{
  "operationId": "op-123",
  "name": "Expediente 2026",
  "documentSourceType": "FOLDER"
}
```

`EXTERNAL_URL`

```
{
  "operationId": "op-123",
  "name": "Referencia externa",
  "documentSourceType": "EXTERNAL_URL",
  "url": "https://example.com/documento/123"
}
```

Upstream calls

1. For `DIGITAL` requests:
- `POST /uploads`
- `PUT {upload_location}`
- `POST /files/{process_id}/documents-and-folders/{folder_id}`
2. For `FOLDER` requests:
- `POST /files/{process_id}/documents-and-folders/{folder_id}`
3. For `EXTERNAL_URL` requests:
- `POST /files/{process_id}/documents-and-folders/{folder_id}`

Success response

- HTTP `200 OK`
- Body model: `GatewayResponse`
- `result` shape: `UploadDocumentResult`

Error response

- HTTP `400`, `404`, `500`, or propagated upstream status code
- Body model: `GatewayResponse`
- `result` shape: `UploadDocumentError`

Notes

- This route uses the same document creation flows as the file-level route, but targets the upstream Gestiona endpoint with the folder id in the last path segment.
- For `DIGITAL` uploads, either `fileName` or `content` must be provided.
- If both `fileName` and `content` are provided, the current implementation uses `content`.
- On successful create operations, `result.id` may come either from the upstream `id` field or, when that field is missing, from the last segment of the upstream `self` link.

10. GET `/processes/thirds?process_number=<numero>`

Gets the third identifiers associated with a Gestiona process file resolved from `process_number`.

Route parameters

- none

Query parameters

- `process_number` required
- `operationId` optional

Request body model

- none

Upstream calls

1. `GET /files` with filter `exact_code = process_number`
2. `GET /files/{resolved_process_id}/thirdparties`

Success response

- HTTP `200 OK`
- Body model: `GatewayResponse`
- `result` shape: `ProcessThirdsResult`

Success example

```
{
  "operationId": "op-01",
  "success": true,
  "result": {
    "processId": "30bcb012-47e2-4e7e-92e0-a0f7278b52b8",
    "thirds": "3aeff9c7-a865-4f1a-9cd6-47993b423873;4b18954c-b66c-4e55-af6d-acf6a2c7aaa3;ece5762f-ae00-4da4-a869-a
  }
}
```

Error response

- HTTP `400`, `404`, `500`, or propagated upstream status code
- Body model: `GatewayResponse`
- `result` shape: `ProcessThirdsError`

Notes

- The returned `processId` is the resolved Gestiona file id, not the original `process_number`
- If no Gestiona file is found for `process_number`, the endpoint returns HTTP `404`
- If `process_number` is empty or whitespace, the endpoint returns HTTP `400`
- If Postman sends an unresolved variable such as `{{process_number}}`, the endpoint returns HTTP `400`

11. GET `/processes/{process_id}/thirds`

Gets the third identifiers associated with a Gestiona process file.

Route parameters

- `process_id` required

Query parameters

- `operationId` optional

Request body model

- none

Upstream calls

1. `GET /files/{process_id}/thirdparties`

Success response

- HTTP `200 OK`
- Body model: `GatewayResponse`
- `result` shape: `ProcessThirdsResult`

Success example

```
{
  "operationId": "op-01",
  "success": true,
  "result": {
    "processId": "30bcb012-47e2-4e7e-92e0-a0f7278b52b8",
    "thirds": "3aeff9c7-a865-4f1a-9cd6-47993b423873;4b18954c-b66c-4e55-af6d-acf6a2c7aaa3;ece5762f-ae00-4da4-a869-a
  }
}
```

Error response

- HTTP `400`, `404`, `500`, or propagated upstream status code
- Body model: `GatewayResponse`
- `result` shape: `ProcessThirdsError`

Notes

- The service reads the upstream `content` array and, for each item, finds the link where `rel` is `third`
- The third id is extracted from the last segment of that link's `href`
- The returned `thirds` field joins all extracted third ids with semicolons
- If `process_id` is empty or whitespace, the endpoint returns HTTP `400`
- If Postman sends an unresolved variable such as `{{process_id}}`, the endpoint returns HTTP `400`

12. GET `/processes/{process_id}/documents`

Gets the documents and folders at the root of a Gestiona process file.

Route parameters

- `process_id` required

Query parameters

- `operationId` optional

Request body model

- none

Upstream calls

1. `GET /files/{process_id}/documents-and-folders`

Success response

- HTTP `200 OK`
- Body model: `GatewayResponse`
- `result` shape: array of `ProcessDocumentItem`

Success example

```
{
  "operationId": "op-01",
  "success": true,
  "result": [
    {
      "type": "DOC",
      "name": "POC_SIGMA_Gestiona",
      "id": "f5e0364b-9951-449d-8d38-34a6cbfec4d3"
    },
    {
      "type": "FOLDER",
      "name": "xxxx",
      "id": "12fb9b74-2111-417f-ae4f-c2b7fe2976f7"
    }
  ]
}
```

Error response

- HTTP `400`, `404`, `500`, or propagated upstream status code
- Body model: `GatewayResponse`
- `result` shape: `ProcessDocumentsError`

Notes

- Both `DOC` and `FOLDER` entries from the upstream `content` array are returned.
- Each upstream `rel` is mapped to `name`.
- Each `id` is extracted from the last path segment of the upstream `href`.
- If `process_id` is empty or whitespace, the endpoint returns HTTP `400`.
- If Postman sends an unresolved variable such as `{{process_id}}`, the endpoint returns HTTP `400`.

13. GET `/processes/{process_id}/documents/{document_id}`

Gets the documents and folders contained inside the specified Gestiona document or folder.

Route parameters

- `process_id` required
- `document_id` required

Query parameters

- `operationId` optional

Request body model

- none

Upstream calls

1. `GET /files/{process_id}/documents-and-folders/{document_id}`

Success response

- HTTP `200 OK`
- Body model: `GatewayResponse`
- `result` shape: array of `ProcessDocumentItem`

Success example

```
{
  "operationId": "op-01",
  "success": true,
  "result": [
    {
      "type": "DOC",
      "name": "Nested document",
      "id": "347d4226-093f-412d-8376-e36d36374d13"
    }
  ]
}
```

Error response

- HTTP `400`, `404`, `500`, or propagated upstream status code
- Body model: `GatewayResponse`
- `result` shape: `ProcessDocumentsError`

Notes

- The response mapping is identical to `GET /processes/{process_id}/documents`.
- Both `DOC` and `FOLDER` entries from the upstream `content` array are returned.
- If either route parameter is empty or whitespace, the endpoint returns HTTP `400`.
- If Postman sends an unresolved `{{process_id}}` or `{{document_id}}` variable, the endpoint returns HTTP `400`.

14. GET `/processes/{process_id}/documents/{document_id}/signatures`

Gets signatures associated with a Gestiona process document and enriches each signature with signer user information.

Route parameters

- `process_id` required
- `document_id` required

Query parameters

- `operationId` optional

Request body model

- none

Upstream calls

1. `GET /files/{process_id}/documents/{document_id}/signatures`
2. For each signature item with a link where `rel` is `signed-user` or `signer-user`:
- `GET {signer-user href}`

Success response

- HTTP `200 OK`
- Body model: `GatewayResponse`
- `result` shape: array of `ProcessDocumentSignatureResult`

Success example

```
{
  "operationId": "op-01",
  "success": true,
  "result": [
    {
      "date_signed": "2026-09-09 10:12:12",
      "signature_state": "SIGNED",
      "username": "081847637",
      "name": "Luis Silva"
    }
  ]
}
```

Error response

- HTTP `400`, `404`, `500`, or propagated upstream status code
- Body model: `GatewayResponse`
- `result` shape: `ProcessDocumentsError`

Notes

- The gateway reads the upstream signatures `content` array.
- Each upstream signature `date` is returned as `date_signed` after timestamp formatting.
- Each upstream signature `signature_state` is returned as `signature_state`.
- The gateway follows the signature user link to map `username` and `name`.
- If `process_id` or `document_id` is empty or whitespace, the endpoint returns HTTP `400`.
- If Postman sends an unresolved `{{process_id}}` or `{{document_id}}` variable, the endpoint returns HTTP `400`.

15. GET `/processes/assignees/users`

Gets the first Gestiona assignee user matching the provided username.

Route parameters

- none

Query parameters

- `operationId` optional
- `username` optional. When present and not blank, this value is used instead of the JSON request body.

Request body model

- `ProcessAssigneeUserRequest`, required only when `username` is not provided as a query parameter.

Request body example

```
{
  "username": "081847637"
}
```

Upstream calls

1. `GET /files/assignees/users`
- Request body: `{"username":"081847637"}`
- `Content-Type: application/vnd.gestiona.filter.assignees+json`

Success response

- HTTP `200 OK`
- Body model: `GatewayResponse`
- `result` shape: `ProcessAssigneeUserResult`

Success example

```
{
  "operationId": "op-01",
  "success": true,
  "result": {
    "id": "8be7a78b-787a-4061-a11c-1bfcdf2d627a",
    "username": "081847637",
    "name": "Luis Silva"
  }
}
```

Error response

- HTTP `400`, `404`, `415`, `500`, `502`, or propagated upstream status code
- Body model: `GatewayResponse`
- `result` shape: `ProcessError`

Notes

- When `username` is provided in the query string, no JSON request body is required.
- When `username` is not provided in the query string, the endpoint requires `Content-Type: application/json`.
- When using the JSON-body path, the request body must be valid JSON.
- The service returns the first item from the upstream `content` array.
- If no assignee user is found, the endpoint returns HTTP `404`.

16. GET `/processes/assignees/groups`

Gets the Gestiona assignee groups available for process assignment.

Route parameters

- none

Query parameters

- `operationId` optional

Request body model

- none

Upstream calls

1. `GET /files/assignees/groups`

Success response

- HTTP `200 OK`
- Body model: `GatewayResponse`
- `result` shape: array of `ProcessAssigneeGroupResult`

Success example

```
{
  "operationId": "op-01",
  "success": true,
  "result": [
    {
      "id": "43f83662-bb73-4c98-915a-de90219036f6",
      "name": "100. Exemplo"
    }
  ]
}
```

Error response

- HTTP `404`, `500`, `502`, or propagated upstream status code
- Body model: `GatewayResponse`
- `result` shape: `ProcessError`

Notes

- The service returns the upstream `content` array.
- Only `id` and `name` are exposed in each result item.
- If the upstream response contains no `content`, the endpoint returns an empty array.

17. GET `/activities`

Gets the activities available in the Gestiona catalog.

Route parameters

- none

Query parameters

- `operationId` optional

Request body model

- none

Upstream calls

1. `GET /catalog-2015/procedures`

Success response

- HTTP `200 OK`
- Body model: `GatewayResponse`
- `result` shape: array of `ActivityItem`

Success example

```
{
  "operationId": "op-01",
  "success": true,
  "result": [
    {
      "id": "82722c9b-cecc-4299-8a7b-ce5abeb8170b",
      "name": "Atividade exemplo"
    }
  ]
}
```

Error response

- HTTP `500`, `502`, or propagated upstream status code
- Body model: `GatewayResponse`
- `result` shape: `ActivityError`

Notes

- The service returns the upstream `content` array.
- If the upstream response contains no `content`, the endpoint returns an empty array.

18. GET `/activities/{activity_id}/procedures`

Gets the external procedures available for a Gestiona activity.

Route parameters

- `activity_id` required

Query parameters

- `operationId` optional

Request body model

- none

Upstream calls

1. `GET /catalog-2015/procedures/{activity_id}/external-procedures`

Success response

- HTTP `200 OK`
- Body model: `GatewayResponse`
- `result` shape: array of `ProcedureItem`

Success example

```
{
  "operationId": "op-01",
  "success": true,
  "result": [
    {
      "id": "external-procedure-id",
      "name": "Procedimento exemplo",
      "activityId": "82722c9b-cecc-4299-8a7b-ce5abeb8170b"
    }
  ]
}
```

Error response

- HTTP `500`, `502`, or propagated upstream status code

- Body model: `GatewayResponse`
- `result` shape: `ActivityError`

Notes

- The gateway maps each upstream external procedure `title` to response field `name`.
- If the upstream response contains no `content`, the endpoint returns an empty array.

19. GET `/documents/{document_id}`

Downloads a document from Gestiona. This is an absolute route and is not prefixed by `/processes`.

Route parameters

- `document_id` required

Query parameters

- `operationId` optional

Request body model

- none

Upstream calls

1. `GET /content/small/documentinstances/{document_id}`

Success response

- HTTP `200 OK`
- Body: raw binary document content
- Headers:
- `Content-Type`: document MIME type returned by Gestiona, or `application/octet-stream` as fallback
- `Content-Disposition: attachment; filename=...`
- `X-Operation-Id`: present when `operationId` is provided in the request
- `X-Storage-Extension`: present when the upstream document metadata includes a storage extension

Download filename resolution

The controller chooses the download filename in this order:

1. `document.fileName`
2. `document.documentId + "." + document.storageExtension`
3. `document.documentId`

Validation behavior

- If `document_id` is empty or whitespace, the endpoint returns HTTP `400`
- If Postman sends an unresolved variable such as `{{document_id}}`, the endpoint returns HTTP `400`

Error response

- HTTP `400`, `404`, `500`, or propagated upstream status code
- Body model: `GatewayResponse`
- `result` shape: `UploadDocumentError`

Error example

```
{
  "operationId": "op-123",
  "success": false,
  "result": {
    "code": 404,
    "name": "Not Found",
    "kind": "NotFound",
    "message": "Failed to download document from Gestiona: 12345."
  }
}
```

Notes

- Successful downloads do not return JSON
- Download errors reuse the same `GatewayResponse` envelope as upload errors
- When `operationId` is provided in the download request, it is echoed back:
- in the error JSON body on failure
- in the `X-Operation-Id` response header on success
- When the upstream response includes document storage extension metadata, it is exposed in the `X-Storage-Extension` response header

20. GET `/thirds?nif=<nif>`

Gets a third from Gestiona by resolving the third id from a NIF, then enriches it with the default address.

Route parameters

- none

Query parameters

- `nif` required
- `operationId` optional

Request body model

- none

Upstream calls

1. `GET /thirds` with body `{"nif":"nif"}` and `Content-Type: application/vnd.gestiona.filter.thirds+json`
2. `GET /thirds/{resolved_third_id}`
3. `GET /thirds/{resolved_third_id}/default-address`

Success response

- HTTP `200 OK`
- Body model: `GatewayResponse`
- `result` shape: `ThirdResult`

Success example

```
{
  "operationId": "op-01",
  "success": true,
  "result": {
    "full_name": "Luis Silva Fernandes",
    "first_name": "Luis",
    "second_surname": "Fernandes",
    "nif_country": "ESP",
    "id": "4b18954c-b66c-4e55-af6d-acf6a2c7aaa3",
    "nif": "196510880",
    "type": "PHISIC",
    "email": "luis.mcf.silva@gmail.com",
    "mobile": "913347827",
    "nif_type": "OWN",
    "address": "Rua das Cancelas",
    "number": "184",
    "block": "A",
    "stair": "1",
    "floor": "2",
    "door": "D",
    "extension": "Frente",
    "zip_code": "4440368",
    "province": "PORTO",
    "country": "Portugal",
    "type_of_road": "CL",
    "zone": "string | null",
    "parish_code": "string | null"
  }
}
```


Error response

- HTTP `400`, `404`, `500`, or propagated upstream status code
- Body model: `GatewayResponse`
- `result` shape: `ThirdError`

Notes

- The upstream NIF filter response must contain exactly one item in `content`
- The third id is extracted from the `id` field of that single item
- If `nif` is empty or whitespace, the endpoint returns HTTP `400`
- If Postman sends an unresolved variable such as `{{nif}}`, the endpoint returns HTTP `400`

21. GET `/thirds/{third_id}`

Gets a third from Gestiona and enriches it with the default address.

Route parameters

- `third_id` required

Query parameters

- `operationId` optional

Request body model

- none

Upstream calls

1. `GET /thirds/{third_id}`
2. `GET /thirds/{third_id}/default-address`

Success response

- HTTP `200 OK`
- Body model: `GatewayResponse`

- `result` shape: `ThirdResult`

Success example

```
{
  "operationId": "op-01",
  "success": true,
  "result": {
    "full_name": "Leonor Ranito Silva",
    "first_name": "Leonor",
    "second_surname": "Silva",
    "nif_country": "PT",
    "id": "3aeff9c7-a865-4f1a-9cd6-47993b423873",
    "nif": "211211211",
    "type": "PHISIC",
    "email": "leonor.silva@gmail.com",
    "mobile": "913344671",
    "nif_type": "OWN",
    "address": "Rua das Cancelas",
    "number": "184",
    "block": "A",
    "stair": "1",
    "floor": "2",
    "door": "D",
    "extension": "Frente",
    "zip_code": "4440368",
    "province": "PORTO",
    "country": "Portugal",
    "type_of_road": "CL",
    "zone": "string | null",
    "parish_code": "string | null"
  }
}
```

Error response

- HTTP `400`, `404`, `500`, or propagated upstream status code
- Body model: `GatewayResponse`
- `result` shape: `ThirdError`

Notes

- If `third_id` is empty or whitespace, the endpoint returns HTTP `400`
- If Postman sends an unresolved variable such as `{{third_id}}`, the endpoint returns HTTP `400`

22. GET `/queues/connectors/{connector_name}`

Gets queued messages from a Gestiona connector queue.

Before retrieving messages, the gateway verifies that the connector exists and that there is an active subscription for it. If no active subscription exists, the gateway subscribes to the connector queue and then retrieves queued messages.

Route parameters

- `connector_name` required

Query parameters

- `operationId` optional

Request body model

- none

Upstream calls

1. `GET /connectors`
- The gateway checks the upstream `content` array for an item where `code` equals `connector_name`.

- If no connector is found, the endpoint returns HTTP `404`.

2. `GET /queues/subscriptions`

- The gateway checks the upstream `content` array for an item where `name` equals `connectors#{connector_name}`.

3. `POST /queues/connectors/{connector_name}/subscription`

- Called only when no active subscription is found.
- If the upstream response body contains a `description` property, that value is used as the gateway error `result.message`.

4. `GET /queues/connectors/{connector_name}`

- Retrieves queued connector messages.

Access token behavior

This endpoint always uses the configured Gestiona access token from `Gestiona:AccessToken`. It does not use `X-User-Access-Token` from the request headers.

Success response

- HTTP `200 OK`
- Body model: `GatewayResponse`
- `result` shape: array of `QueueConnectorMessageResult`

Success example

```
{
  "operationId": "op-01",
  "success": true,
  "result": [
    {
      "message_id": "9376d53a-176e-4716-beaa-bd4486561bbd",
      "date_signed": "2026-09-03 10:07:09"
    }
  ]
}
```

Error response

- HTTP `400`, `404`, `500`, or propagated upstream status code
- Body model: `GatewayResponse`
- `result` shape: `QueueError`

Error example

```
{
  "operationId": "op-01",
  "success": false,
  "result": {
    "code": 412,
    "name": "Precondition Failed",
    "kind": "Upstream",
    "message": "already exists other consumer subscribed to queue"
  }
}
```

Notes

- If `connector_name` is empty or whitespace, the endpoint returns HTTP `400`.
- If Postman sends an unresolved variable such as `{{connector_name}}`, the endpoint returns HTTP `400`.
- The active subscription name must match `connectors#{connector_name}`.
- Each upstream queue message `payload.target` is returned as `message_id`.
- Each upstream queue message `entry` value is formatted with `DateTimeHelpers.FormatUnixTimestamp` and returned as `date_signed`.

23. GET `/queues/connectors/{connector_name}/{message_id}`

Gets a message from a Gestiona connector queue.

Before retrieving the message, the gateway verifies that the connector exists and that there is an active subscription for it. If no active subscription exists, the gateway subscribes to the connector queue and then retrieves the requested message.

Route parameters

- `connector_name` required
- `message_id` required

Query parameters

- `operationId` optional

Request body model

- none

Upstream calls

1. `GET /connectors`
- The gateway checks the upstream `content` array for an item where `code` equals `connector_name`.
- If no connector is found, the endpoint returns HTTP `404`.
2. `GET /queues/subscriptions`
- The gateway checks the upstream `content` array for an item where `name` equals `connectors#{connector_name}`.
3. `POST /queues/connectors/{connector_name}/subscription`
- Called only when no active subscription is found.
- If the upstream response body contains a `description` property, that value is used as the gateway error `result.message`.
4. `GET /queues/connectors/{connector_name}/{message_id}`
- `Accept: application/vnd.gestiona.queues.message`

Access token behavior

This endpoint always uses the configured Gestiona access token from `Gestiona:AccessToken`. It does not use `X-User-Access-Token` from the request headers.

Success response

- HTTP `200 OK`
- Body model: `GatewayResponse`
- `result` shape: `QueueConnectorMessageResult`

Success example

```
{
  "operationId": "op-01",
  "success": true,
  "result": {
    "message_id": "9376d53a-176e-4716-beaa-bd4486561bbd",
    "date_signed": "2026-09-03 10:07:09"
  }
}
```

Error response

- HTTP `400`, `404`, `500`, or propagated upstream status code
- Body model: `GatewayResponse`
- `result` shape: `QueueError`

Error example

```
{
  "operationId": "op-01",
  "success": false,
  "result": {
    "code": 412,
    "name": "Precondition Failed",
    "kind": "Upstream",
    "message": "already exists other consumer subscribed to queue"
  }
}
```

Notes

- If `connector_name` or `message_id` is empty or whitespace, the endpoint returns HTTP `400`.
- If Postman sends an unresolved variable such as `{{connector_name}}` or `{{message_id}}`, the endpoint returns HTTP `400`.
- The active subscription name must match `connectors#{connector_name}`.
- The upstream queue message `payload.target` is returned as `message_id`.
- The upstream queue message `entry` value is formatted with `DateTimeHelpers.FormatUnixTimestamp` and returned as `date_signed`.

24. POST `/queues/connectors/{connector_name}/{message_id}`

Sends a response for a Gestiona connector queue message.

Before sending the response, the gateway verifies that the connector exists and that there is an active subscription for it. If no active subscription exists, the gateway subscribes to the connector queue and then sends the response.

Route parameters

- `connector_name` required
- `message_id` required

Query parameters

- `operationId` optional

Request body model

- `SendQueueConnectorResponseRequest`

Request body example

```
{
  "result_success": "TRUE",
  "message": "Response message to the connector"
}
```

Upstream calls

1. `GET /connectors`
- The gateway checks the upstream `content` array for an item where `code` equals `connector_name`.
- If no connector is found, the endpoint returns HTTP `404`.
2. `GET /queues/subscriptions`
- The gateway checks the upstream `content` array for an item where `name` equals `connectors#{connector_name}`.
3. `POST /queues/connectors/{connector_name}/subscription`
- Called only when no active subscription is found.
- If the upstream response body contains a `description` property, that value is used as the gateway error `result.message`.
4. `POST /queues/connectors/{connector_name}/{message_id}`
- `Content-Type: application/vnd.gestiona.connector-response+json`
- Sends `result_success`.
- Sends `message` only when it is present.

Access token behavior

This endpoint always uses the configured Gestiona access token from `Gestiona:AccessToken`. It does not use `X-User-Access-Token` from the request headers.

Success response

- HTTP `200 OK`
- Body model: `GatewayResponse`
- `result` shape: `QueueConnectorResponseResult`

Success example

```
{
  "operationId": "op-01",
  "success": true,
  "result": {
    "connector_name": "sigma-medidata-file-docs",
    "message_id": "9376d53a-176e-4716-beaa-bd4486561bbd"
  }
}
```

Error response

- HTTP `400`, `404`, `500`, or propagated upstream status code
- Body model: `GatewayResponse`
- `result` shape: `QueueError`

Error example

```
{
  "operationId": "op-01",
  "success": false,
  "result": {
    "code": 412,
    "name": "Precondition Failed",
    "kind": "Upstream",
    "message": "already exists other consumer subscribed to queue"
  }
}
```

Notes

- The gateway accepts `Content-Type: application/json` and `Content-Type: application/vnd.gestiona.connector-response+json` for this endpoint.
- If `connector_name` or `message_id` is empty or whitespace, the endpoint returns HTTP `400`.
- If `result_success` is empty or whitespace, the endpoint returns HTTP `400`.
- If Postman sends an unresolved variable such as `{{connector_name}}` or `{{message_id}}`, the endpoint returns HTTP `400`.
- The active subscription name must match `connectors#{connector_name}`.

25. POST `/addon/authorizations`

Creates a Gestiona add-on authorization request.

Query parameters

- `operationId` optional

Request body model

- none

Upstream calls

1. `POST /addon/authorizations`

- Sends `X-Gestiona-Addon-Token` using `Gestiona:AddonToken`.
- Reads the authorization id from the last segment of the upstream `Location` header.

Success response

- HTTP `200 OK`
- Body model: `GatewayResponse`
- `result` shape: `AddOnAuthorizationResult`

```
{
  "operationId": "op-01",
  "success": true,
  "result": {
    "authId": "authorization-id"
  }
}
```

Error response

- HTTP `500`, `502`, or propagated upstream status code
- Missing configuration or an invalid/missing upstream `Location` header produces an error `GatewayResponse`.

26. GET `/addon/authorizations/{auth_id}`

Gets the current state of a Gestiona add-on authorization.

Route parameters

- `auth_id` required

Query parameters

- `operationId` optional

Request body model

- none

Upstream calls

1. `GET /addon/authorizations/{auth_id}`

- Sends `X-Gestiona-Addon-Token` using `Gestiona:AddonToken`.
- Upstream HTTP `401` is treated as an expected pending state; its `Location` header becomes `authorizeUrl`.
- Upstream HTTP `200` maps `user_id` and `access_token` into `authorizedInfo`.

Pending response

- HTTP `200 OK`

```
{
  "operationId": "op-01",
  "success": true,
  "result": {
    "authorized": false,
    "authorizeUrl": "https://gestiona.example/authorize/authorization-id"
  }
}
```

Authorized response

- HTTP `200 OK`

```
{
  "operationId": "op-01",
  "success": true,
  "result": {
    "authorized": true,
    "authorizedInfo": {
      "userId": "user-id",
      "accessToken": "access-token"
    }
  }
}
```

Error response

- HTTP `500`, `502`, or propagated upstream status code
- A pending response without `Location`, or an authorized response without `user_id` or `access_token`, produces HTTP `502`.

27. GET `/processes/{process_id}/procedure-data`

Gets all procedure-data definitions associated with a Gestiona process.

Route parameters

- `process_id` required

Query parameters

- `operationId` optional

Request body model

- none

Upstream calls

1. `GET /files/{process_id}/procedure-data`
- The gateway follows each top-level link where `rel` is `next` until no next page is returned.

Success response

- HTTP `200 OK`
- Body model: `GatewayResponse`
- `result` shape: array of procedure-data definitions

Success example

```
{
  "operationId": "op-01",
  "success": true,
  "result": [
    {
      "reference": "UrbanMorada",
      "caption": "Morada",
      "type": "ADDRESS"
    }
  ]
}
```

Error response

- HTTP `400`, `404`, `500`, `502`, or propagated upstream status code
- Body model: `GatewayResponse`
- `result` shape: `ProcessDocumentsError`

Notes

- `caption` is read from the `pt_PT` property inside the upstream `i18n_name` JSON string.
- If `process_id` is empty or contains the unresolved value `{{process_id}}`, the endpoint returns HTTP `400`.
- If the upstream response contains no procedure-data definitions, `result` is an empty array.

28. GET `/processes/{process_id}/procedure-data/{reference_id}`

Gets one procedure-data definition and its value from a Gestiona process.

Route parameters

- `process_id` required
- `reference_id` required

Query parameters

- `operationId` optional

Request body model

- none

Upstream calls

1. `GET /files/{process_id}/procedure-data/{reference_id}`

Success response

- HTTP `200 OK`
- Body model: `GatewayResponse`
- `result` contains `reference`, `caption`, `type`, and an always-present `value` property

Object value example

```
{
  "operationId": "op-01",
  "success": true,
  "result": {
    "reference": "UrbanMorada",
    "caption": "Morada",
    "type": "ADDRESS",
    "value": {
      "country": "PRT",
      "province": "PORTO",
      "town": "Vila Nova de Gaia",
      "town_code": "1317",
      "parish_code": "131727",
      "zip_code": "4400527",
      "type_of_road": "BL",
      "address": "Transparente",
      "number": "23",
      "block": "33",
      "stair": "44",
      "floor": "55",
      "door": "66",
      "extension": "77"
    }
  }
}
```

Simple value example

```
{
  "operationId": "op-01",
  "success": true,
  "result": {
    "reference": "decisao",
    "caption": "Decisão",
    "type": "TEXT",
    "value": "Deferido"
  }
}
```

DATE value example

```
{
  "operationId": "op-01",
  "success": true,
  "result": {
    "reference": "cabimento_data_emissao",
    "caption": "Data Emissao de Cabimento",
    "type": "DATE",
    "value": {
      "date": "2026-10-02"
    }
  }
}
```

Error response

- HTTP `400`, `404`, `500`, `502`, or propagated upstream status code
- Body model: `GatewayResponse`
- `result` shape: `ProcessDocumentsError`

Notes

- Gestiona may encode `value` as nested JSON strings. The gateway decodes these layers before returning the value.
- If the decoded value is an object, `value` is returned as that object. Simple strings, numbers, booleans, arrays, and null values retain their JSON type.
- If Gestiona omits `value` or returns an empty value, the gateway returns `"value": ""`.
- For type `DATE`, Unix timestamps are formatted as `yyyy-MM-dd`. A `date` property inside an object value is formatted in the same way.
- If either route parameter is empty, or contains the unresolved values `{{process_id}}` or `{{reference_id}}`, the endpoint returns HTTP `400`.