

Gestiona Upstream Calls Documentation

Versao 1.1.1

Index

Common behavior

- Base URL
- Authentication header

Upstream calls

- 1. GET /files
- 2. POST /uploads
- 3. PUT {upload_location}
- 4. POST /files/{file_id}/documents-and-folders
- 5. POST /files/{file_id}/documents-and-folders/{folder_id}
- 6. GET /content/small/documentinstances/{document_id}
- 7. GET /files/{file_id}/thirdparties
- 8. GET /thirds
- 9. GET /thirds/{third_id}
- 10. GET /thirds/{third_id}/default-address

Common behavior

Base URL

All relative upstream routes are sent to the configured Gestiona API base URL:

- Configuration key: `Gestiona:GestionaApiBaseUrl`
- The client normalizes the base URL by appending a trailing `/` when needed.

Authentication header

All Gestiona requests include:

- `X-Gestiona-Access-Token`

The token value is resolved by the gateway service layer:

1. Use the inbound API request header `X-User-Access-Token` when present and not blank.
2. Otherwise use the configured token from `Gestiona:AccessToken`.

Upstream calls

1. GET /files

Resolves a Gestion file from a process number/code.

Used by

- POST /processes/documents?process_number=<numero>
- POST /processes/documents/{folder_id}?process_number=<numero>
- GET /processes/thirds?process_number=<numero>

Request headers

- X-Gestion-Access-Token required
- Content-Type: application/vnd.gestion.filter.files

Request body model

```
{
  "exact_code": "string"
}
```

Request body example

```
{
  "exact_code": "PROC-2026-001"
}
```

Response data used

- content[0].id Used as the resolved Gestion file id.
- For the unused self-link helper only: content[].links[] where rel is self, then href.

Notes

- A 204 No Content response is treated as not found by the current process-code resolution flow.
- Other unsuccessful status codes are propagated as upstream failures by gateway services.

2. POST /uploads

Creates a temporary Gestion upload space before uploading DIGITAL document content.

Used by

- POST /processes/documents?process_number=<numero> when documentSourceType is DIGITAL
- POST /processes/{process_id}/documents when documentSourceType is DIGITAL
- POST /processes/documents/{folder_id}?process_number=<numero> when documentSourceType is DIGITAL
- POST /processes/{process_id}/documents/{folder_id} when documentSourceType is DIGITAL

Request headers

- X-Gestion-Access-Token required
- Content-Type: application/vnd.gestion.file-document+json; version=4

Request body model

- Empty byte array

Response data used

- Location response header Used as {upload_location} for the next upload step and as the source for the created document content link.

Response headers observed

- X-Gestiona-Deprecated Logged when Gestiona returns it for the application/vnd.gestiona.file-document+json; version=4 media type.

3. PUT {upload_location}

Uploads the binary content for a DIGITAL document to the temporary upload location returned by POST /uploads.

Used by

- POST /processes/documents?process_number=<numero> when documentSourceType is DIGITAL
- POST /processes/{process_id}/documents when documentSourceType is DIGITAL
- POST /processes/documents/{folder_id}?process_number=<numero> when documentSourceType is DIGITAL
- POST /processes/{process_id}/documents/{folder_id} when documentSourceType is DIGITAL

Request headers

- X-Gestiona-Access-Token required
- Content-Type: application/octet-stream

Route parameters

- upload_location required Can be an absolute URL returned by Gestiona or a relative URL resolved against Gestiona:GestionaApiBaseUrl.

Request body model

- Raw binary document bytes

Response data used

- Status code only.

4. POST /files/{file_id}/documents-and-folders

Creates a document or folder directly under a Gestiona file.

Used by

- POST /processes/documents?process_number=<numero>
- POST /processes/{process_id}/documents

Route parameters

- file_id required The Gestiona file id. It is either provided as process_id or resolved from process_number using GET /files.

Request headers

- X-Gestiona-Access-Token required
- Content-Type depends on the document source type:
 - application/vnd.gestiona.file-document+json; version=4 for DIGITAL and EXTERNAL_URL
 - application/vnd.gestiona.file-folder for FOLDER

DIGITAL request body model

```
{
  "name": "string",
  "type": "DIGITAL",
  "metadata_language": "ES",
  "trashed": "false",
  "version": "1",
  "links": [
    {
      "rel": "content",
      "href": "string"
    }
  ]
}
```

EXTERNAL_URL request body model

```
{
  "name": "string",
  "type": "EXTERNAL_URL",
  "metadata_language": "ES",
  "trashed": "false",
  "version": "1",
  "external_url": "string"
}
```

FOLDER request body model

```
{
  "name": "string",
  "line": "1"
}
```

Response data used

- Created entity response body is deserialized as `CreateDocumentAndFolderResponse`.
- `id` is used when present.
- If `id` is absent, the gateway resolves the created entity id from the last segment of the upstream `self` link.
- `creation_date` and `modification_date` are returned to gateway clients after Unix timestamp formatting.

Response headers observed

- `X-Gestiona-Deprecated` Logged for `DIGITAL` and `EXTERNAL_URL` document creation when Gestiona returns it for the file-document media type.

5. POST /files/{file_id}/documents-and-folders/{folder_id}

Creates a document or folder inside a Gestiona folder.

Used by

- `POST /processes/documents/{folder_id}?process_number=<numero>`
- `POST /processes/{process_id}/documents/{folder_id}`

Route parameters

- `file_id` required The Gestiona file id. It is either provided as `process_id` or resolved from `process_number` using `GET /files`.
- `folder_id` required The Gestiona folder id that receives the new document or child folder.

Request headers

- `X-Gestiona-Access-Token` required
- `Content-Type` depends on the document source type:
- `application/vnd.gestiona.file-document+json; version=4` for `DIGITAL` and `EXTERNAL_URL`
- `application/vnd.gestiona.file-folder` for `FOLDER`

Request body model

Uses the same `DIGITAL`, `EXTERNAL_URL`, and `FOLDER` request body models documented in call 4.

Response data used

- Created entity response body is deserialized as `CreateDocumentAndFolderResponse`.
- `id` is used when present.
- If `id` is absent, the gateway resolves the created entity id from the last segment of the upstream `self` link.
- `creation_date` and `modification_date` are returned to gateway clients after Unix timestamp formatting.

Response headers observed

- `X-Gestiona-Deprecated` Logged for `DIGITAL` and `EXTERNAL_URL` document creation when Gestiona returns it for the file-document media type.

6. GET /content/small/documentinstances/{document_id}

Downloads a document from Gestiona.

Used by

- GET `/documents/{document_id}`

Route parameters

- `document_id` required

Request headers

- `X-Gestiona-Access-Token` required

Request body model

- none

Response body used

- Raw binary document content.

Response headers used

- `Content-Disposition` Used to resolve the download file name.
- `Content-Type` Used as the gateway response content type.
- `X-Gestiona-Storage-Size`
- `X-Gestiona-Storage-Extension`
- `X-Gestiona-Storage-MIME-Type`
- `X-Gestiona-Storage-MD5`
- `X-Gestiona-Storage-SHA1`
- `X-Gestiona-Storage-SHA512`

7. GET /files/{file_id}/thirdparties

Gets third-party links associated with a Gestiona file.

Used by

- GET `/processes/thirds?process_number=<numero>`
- GET `/processes/{process_id}/thirds`

Route parameters

- `file_id` required The Gestiona file id. It is either provided as `process_id` or resolved from `process_number` using `GET /files`.

Request headers

- `X-Gestiona-Access-Token` required

Request body model

- none

Response data used

- `content[].links[]` entries where `rel` is `third`.
- The gateway extracts the third id from the last path segment of each matching `href`.
- The returned gateway value joins the extracted ids with `;`.

8. GET /thirds

Resolves a Gestiona third id from a NIF.

Used by

- `GET /thirds?nif=<nif>`

Request headers

- `X-Gestiona-Access-Token` required
- `Content-Type: application/vnd.gestiona.filter.thirds+json`

Request body model

```
{
  "nif": "string"
}
```

Request body example

```
{
  "nif": "196510880"
}
```

Response data used

- `content` Must contain exactly one item.
- `content[0].id` Used as the resolved Gestiona third id.

9. GET /thirds/{third_id}

Gets a third from Gestiona.

Used by

- `GET /thirds?nif=<nif>` after resolving the third id with `GET /thirds`
- `GET /thirds/{third_id}`

Route parameters

- `third_id` required

Request headers

- `X-Gestiona-Access-Token` required

Request body model

- none

Response data used

- The response body is deserialized as `Third`.
- Address fields are enriched by the next GET `/thirds/{third_id}/default-address` call.

10. GET /thirds/{third_id}/default-address

Gets the default address for a Gestion third.

Used by

- GET `/thirds?nif=<nif>` after resolving and retrieving the third
- GET `/thirds/{third_id}` after retrieving the third

Route parameters

- `third_id` required

Request headers

- `X-Gestion-Access-Token` required

Request body model

- none

Response data used

- The response body is deserialized as `ThirdDefaultAddress`.
- The gateway merges these address fields into the third result:
- `address`
- `number`
- `zip_code`
- `province`
- `country`
- `type_of_road`