

Gestiona Upstream Calls Documentation

Versao 1.9.0

Index

Common behavior

- Base URL
- Authentication header

Upstream calls

- 1. GET /files
- 2. POST /uploads
- 3. PUT {upload_location}
- 4. POST /files/{file_id}/documents-and-folders
- 5. POST /files/{file_id}/documents-and-folders/{folder_or_document_id}
- 6. GET /files/{file_id}/documents-and-folders
- 7. GET /files/{file_id}/documents-and-folders/{folder_or_document_id}
- 8. GET /content/small/documentinstances/{document_id}
- 9. GET /files/{file_id}/thirdparties
- 10. GET /thirds
- 11. GET /thirds/{third_id}
- 12. GET /thirds/{third_id}/default-address
- 13. POST
/catalog-2015/procedures/{activity_id}/external-procedures/{procedure_id}/create-file
- 14. GET /files/{file_id}/selectable-titles
- 15. POST {file_open_href}
- 16. POST /files/{file_id}/related-files
- 17. GET /files/{file_id}/related-files
- 18. DELETE /files/{file_id}/related-files/{related_file_id}
- 19. GET /catalog-2015/procedures
- 20. GET /catalog-2015/procedures/{activity_id}/external-procedures
- 21. GET /files/{file_id}/documents/{document_id}/signatures
- 22. GET {signer_user_href}
- 23. GET /files/assignees/users
- 24. GET /files/assignees/groups
- 25. GET /connectors
- 26. GET /queues/subscriptions
- 27. POST /queues/connectors/{connector_name}/subscription
- 28. POST /queues/connectors/{connector_name}?max-messages=100&hold-seconds=1
- 29. GET /queues/connectors/{connector_name}/{message_id}
- 30. POST /queues/connectors/{connector_name}/{message_id}
- 31. POST /addon/authorizations
- 32. GET /addon/authorizations/{auth_id}

Common behavior

Base URL

All relative upstream routes are sent to the configured Gestiona API base URL:

- Configuration key: `Gestiona:GestionaApiBaseUrl`
- The client normalizes the base URL by appending a trailing `/` when needed.

Authentication header

All Gestiona requests include:

- `X-Gestiona-Access-Token`

The token value is resolved by the gateway service layer:

1. Use the inbound API request header `X-User-Access-Token` when present and not blank.
2. Otherwise use the configured token from `Gestiona:AccessToken`.

Queue connector endpoints are an exception at the gateway-service level: they always use the configured token from `Gestiona:AccessToken`.

Add-on authorization calls use `X-Gestiona-Addon-Token` with the configured value from `Gestiona:AddonToken` instead of `X-Gestiona-Access-Token`.

Upstream calls

1. GET /files

Resolves a Gestiona file id or self link from a process number/code.

Used by

- GET /processes?process_number=<numero>
- POST /processes/documents?process_number=<numero>
- POST /processes/documents/{folder_id}?process_number=<numero>
- GET /processes/thirds?process_number=<numero>

Request headers

- X-Gestiona-Access-Token required
- Content-Type: application/vnd.gestiona.filter.files

Request body model

```
{
  "exact_code": "string"
}
```

Response data used

- content[0].id Used as the resolved Gestiona file id.
- content[0].links[] where rel is self Used when the service needs the upstream self href.

2. POST /uploads

Creates a temporary Gestiona upload space before uploading DIGITAL document content.

Used by

- POST /processes/documents?process_number=<numero> when documentSourceType is DIGITAL
- POST /processes/{process_id}/documents when documentSourceType is DIGITAL
- POST /processes/documents/{folder_id}?process_number=<numero> when documentSourceType is DIGITAL
- POST /processes/{process_id}/documents/{folder_id} when documentSourceType is DIGITAL

Request headers

- X-Gestiona-Access-Token required
- Content-Type: application/vnd.gestiona.file-document+json; version=4

Request body model

- Empty byte array

Response data used

- Location response header Used as {upload_location} for the next upload step and as the source for the created document content link.

3. PUT {upload_location}

Uploads binary content for a DIGITAL document to the temporary upload location returned by POST /uploads.

Used by

- DIGITAL document creation endpoints.

Request headers

- X-Gestiona-Access-Token required
- Content-Type: application/octet-stream

Route parameters

- upload_location required Can be an absolute URL returned by Gestiona or a relative URL resolved against Gestiona:GestionaApiBaseUrl.

Request body model

- Raw binary document bytes

Response data used

- Status code only.

4. POST /files/{file_id}/documents-and-folders

Creates a document or folder directly under a Gestiona file.

Used by

- POST /processes/documents?process_number=<numero>
- POST /processes/{process_id}/documents

Request headers

- X-Gestiona-Access-Token required
- Content-Type depends on the document source type:
- application/vnd.gestiona.file-document+json; version=4 for DIGITAL and EXTERNAL_URL
- application/vnd.gestiona.file-folder for FOLDER

Request body models

DIGITAL:

```
{
  "name": "string",
  "type": "DIGITAL",
  "metadata_language": "ES",
  "links": [
    {
      "rel": "content",
      "href": "string"
    }
  ]
}
```

EXTERNAL_URL:

```
{
  "name": "string",
  "type": "EXTERNAL_URL",
  "metadata_language": "ES",
  "external_url": "string"
}
```

FOLDER:

```
{
  "name": "string",
  "line": "1"
}
```

Response data used

- Created entity body deserialized as `CreateDocumentAndFolderResponse`.
- `id`, or the final path segment of the `self` link when `id` is absent.
- `creation_date` and `modification_date`.

5. POST

`/files/{file_id}/documents-and-folders/{folder_or_document_id}`

Creates a document or folder inside a Gestion folder.

Used by

- POST `/processes/documents/{folder_id}?process_number=<numero>`
- POST `/processes/{process_id}/documents/{folder_id}`

Request headers

- Same as call 4.

Request body model

- Same DIGITAL, EXTERNAL_URL, and FOLDER body models documented in call 4.

Response data used

- Same created entity fields documented in call 4.

6. GET `/files/{file_id}/documents-and-folders`

Lists documents and folders directly under a Gestion file.

Used by

- GET `/processes/{process_id}/documents`

Request headers

- X-Gestion-Access-Token required

Response data used

- `content[].type`
- `content[].links[]` The gateway maps the relevant link `rel` to `name` and the final `href` path segment to `id`.

7. GET

`/files/{file_id}/documents-and-folders/{folder_or_document_id}`

Lists documents and folders under a specific Gestion folder or document container.

Used by

- GET `/processes/{process_id}/documents/{document_id}`

Request headers

- X-Gestion-Access-Token required

Response data used

- Same document-list data documented in call 6.

8. GET /content/small/documentinstances/{document_id}

Downloads a document from Gestiona.

Used by

- GET /documents/{document_id}

Request headers

- X-Gestiona-Access-Token required

Response body used

- Raw binary document content.

Response headers used

- Content-Disposition
- Content-Type
- X-Gestiona-Storage-Size
- X-Gestiona-Storage-Extension
- X-Gestiona-Storage-MIME-Type
- X-Gestiona-Storage-MD5
- X-Gestiona-Storage-SHA1
- X-Gestiona-Storage-SHA512

9. GET /files/{file_id}/thirdparties

Gets third-party links associated with a Gestiona file.

Used by

- GET /processes/thirds?process_number=<numero>
- GET /processes/{process_id}/thirds

Request headers

- X-Gestiona-Access-Token required

Response data used

- content[].links[] entries where rel is third.
- The gateway extracts the third id from the last path segment of each matching href.
- The returned gateway value joins the extracted ids with ;.

10. GET /thirds

Resolves a Gestiona third id from a NIF.

Used by

- GET /thirds?nif=<nif>

Request headers

- X-Gestiona-Access-Token required
- Content-Type: application/vnd.gestiona.filter.thirds+json

Request body model

```
{
  "nif": "string"
}
```

Response data used

- content Must contain exactly one item.
- content[0].id Used as the resolved Gestiona third id.

11. GET /thirds/{third_id}

Gets a third from Gestiona.

Used by

- GET /thirds?nif=<nif> after resolving the third id with GET /thirds
- GET /thirds/{third_id}

Request headers

- X-Gestiona-Access-Token required

Response data used

- Response body deserialized as Third.
- Address fields are enriched by GET /thirds/{third_id}/default-address.

12. GET /thirds/{third_id}/default-address

Gets the default address for a Gestiona third.

Used by

- GET /thirds?nif=<nif>
- GET /thirds/{third_id}

Request headers

- X-Gestiona-Access-Token required

Response data used

- Response body deserialized as ThirdDefaultAddress.
- Address fields merged into the third result.
- The links entry where rel is parish; its final href segment maps to parish_code.

13. POST /catalog-2015/procedures/{activity_id}/external-procedures/{procedure_id}/create-file

Creates a Gestiona process file for a catalog activity and external procedure.

Used by

- POST /processes

Request headers

- X-Gestiona-Access-Token required

Request body model

- Empty byte array

Response data used

- `entry_date`
- Link where `rel` is `file-open` Used as `{file_open_href}` for call 15 and to extract the created file id for call 14.

14. GET /files/{file_id}/selectable-titles

Gets selectable titles for a created Gestion process file.

Used by

- POST /processes

Request headers

- X-Gestion-Access-Token required

Response data used

- `selectable_titles` The first non-blank value is sent as `selectable_title` in call 15.
- `required` Deserialized but not returned directly by the gateway.

15. POST {file_open_href}

Opens the created Gestion process file.

Used by

- POST /processes

Request headers

- X-Gestion-Access-Token required
- Content-Type: `application/vnd.gestion.file-opening+json; version=1`

Route parameters

- `file_open_href` required Can be an absolute URL returned by Gestion or a relative URL resolved against `Gestion:GestionApiBaseUrl`.

Request body model

```
{
  "entry_date": "string",
  "free_title": "string",
  "selectable_title": "string | null",
  "initial_assignment": [
    {
      "href": "string"
    }
  ],
  "links": [
    {
      "rel": "management-unit-group",
      "href": "string"
    }
  ]
}
```

Response data used

- `id`
- `code`

16. **POST** /files/{file_id}/related-files

Creates a related-file link from one Gestion file to another.

Used by

- POST /processes/related

Request headers

- X-Gestion-Access-Token required
- Content-Type: application/vnd.gestion.links+json

Request body model

```
{
  "links": [
    {
      "rel": "related-files",
      "href": "string"
    }
  ]
}
```

Response data used

- Status code only.

17. **GET** /files/{file_id}/related-files

Gets related Gestion files.

Used by

- GET /processes/{process_id}/related

Request headers

- X-Gestion-Access-Token required

Response data used

- content[].id
- content[].code

18. **DELETE** /files/{file_id}/related-files/{related_file_id}

Deletes a related-file link.

Used by

- DELETE /processes/{process_id}/related/{related_process_id}

Request headers

- X-Gestion-Access-Token required

Response data used

- Status code only.

19. **GET** /catalog-2015/procedures

Gets activities available in the Gestion catalog.

Used by

- GET /activities

Request headers

- X-Gestiona-Access-Token required

Response data used

- content[].id
- content[].name

20. GET /catalog-2015/procedures/{activity_id}/external-procedures

Gets external procedures for a Gestiona catalog activity.

Used by

- GET /activities/{activity_id}/procedures

Request headers

- X-Gestiona-Access-Token required

Response data used

- content[].id
- content[].title Returned by the gateway as name.

21. GET /files/{file_id}/documents/{document_id}/signatures

Gets signatures for a Gestiona document in a process file.

Used by

- GET /processes/{process_id}/documents/{document_id}/signatures

Request headers

- X-Gestiona-Access-Token required

Response data used

- content[].date
- content[].signature_state
- content[].links[] where rel is signed-user or signer-user The gateway follows this link with call 22.

22. GET {signer_user_href}

Gets a Gestiona user referenced by a document signature.

Used by

- GET /processes/{process_id}/documents/{document_id}/signatures

Request headers

- X-Gestiona-Access-Token required

Route parameters

- signer_user_href required Can be an absolute URL returned by Gestiona or a relative URL resolved against Gestiona:GestionaApiBaseUrl.

Response data used

- username
- name

23. GET /files/assignees/users

Gets the first Gestion assignee user matching a username.

Used by

- GET /processes/assignees/users

Request headers

- X-Gestion-Access-Token required
- Content-Type: application/vnd.gestion.filter.assignees+json

Request body model

```
{
  "username": "string"
}
```

Response data used

- First item in content.
- id
- username
- name

24. GET /files/assignees/groups

Gets Gestion assignee groups available for process assignment.

Used by

- GET /processes/assignees/groups

Request headers

- X-Gestion-Access-Token required

Response data used

- content[].id
- content[].name

25. GET /connectors

Gets Gestion queue connectors.

Used by

- GET /queues/connectors/{connector_name}
- GET /queues/connectors/{connector_name}/{message_id}
- POST /queues/connectors/{connector_name}/{message_id}

Request headers

- X-Gestion-Access-Token required

Response data used

- `content[].code` The gateway verifies that one connector code matches `{connector_name}`.

26. GET /queues/subscriptions

Gets active Gestion queue subscriptions.

Used by

- Queue connector message retrieval and response endpoints.

Request headers

- X-Gestion-Access-Token required

Response data used

- `content[].name` The gateway looks for `connectors#{connector_name}`.

27. POST /queues/connectors/{connector_name}/subscription

Subscribes the gateway to a Gestion connector queue when no active subscription exists.

Used by

- Queue connector message retrieval and response endpoints.

Request headers

- X-Gestion-Access-Token required

Request body model

- Empty byte array

Response data used

- Status code.
- Error response `description`, when present, is propagated as the gateway error message.

28. POST /queues/connectors/{connector_name}?max-messages=100&hold-seconds=1

Retrieves queued messages from a Gestion connector queue.

Used by

- GET /queues/connectors/{connector_name}

Request headers

- X-Gestion-Access-Token required

Response data used

- `content[].payload.target` Returned as `message_id`.
- `content[].entry` Formatted and returned as `date_signed`.

29. GET /queues/connectors/{connector_name}/{message_id}

Gets a single Gestion connector queue message.

Used by

- GET /queues/connectors/{connector_name}/{message_id}

Request headers

- X-Gestiona-Access-Token required
- Accept: application/vnd.gestiona.queues.message

Response data used

- payload.target Returned as message_id.
- entry Formatted and returned as date_signed.

30. POST /queues/connectors/{connector_name}/{message_id}

Sends a response for a Gestiona connector queue message.

Used by

- POST /queues/connectors/{connector_name}/{message_id}

Request headers

- X-Gestiona-Access-Token required
- Content-Type: application/vnd.gestiona.connector-response+json

Request body model

```
{
  "result_success": "string",
  "message": "string | null"
}
```

Response data used

- Status code.
- Error response description, when present, is propagated as the gateway error message.

31. POST /addon/authorizations

Creates an add-on authorization request.

Used by

- POST /addon/authorizations

Request headers

- X-Gestiona-Addon-Token required; value from Gestiona:AddonToken

Request body model

- Empty byte array

Response data used

- Location header. The final URL segment is returned by the gateway as authId.
- A missing or invalid Location header is treated as an upstream failure.

32. GET /addon/authorizations/{auth_id}

Checks whether an add-on authorization is pending or authorized.

Used by

- GET /addon/authorizations/{auth_id}

Request headers

- X-Gestiona-Addon-Token required; value from Gestiona:AddonToken

Response data used

- HTTP 401: the authorization is pending. The Location header is returned as authorizeUrl.
- HTTP 200: the authorization is complete. Body fields user_id and access_token are returned as authorizedInfo.userId and authorizedInfo.accessToken.
- Other non-success status codes are propagated as gateway errors.