Homework 6 - Class Question

Lilit Melkumyan - TSS: 200070809

Table of contents

Writing a reusable function 1
Intro 1
Creating Reusable Function 1
Testing the Function with Outputs 2
Conclusion 5

Writing a reusable function

Intro

The purpose of this assignment is to come up with a reusable R function that will help us analyze protein structures by using PDB data. To make the process more efficient so that we don't have to repeat the same code every time, the function will analyze the protein structure and generate an according plot. To test the function, I am using PDB Ids provided: 4AKE, 1AKE, 1E4Y

> Q6. Write your own function starting from the code above that analyzes protein drug interactions by reading in any protein PDB data and outputs a plot for the specified protein.

```
library(bio3d)
```

Creating Reusable Function

```
# Function: plot_protein
# Pdb_id is the PDB identifier for the protein structure.
# Default chain is "A" which specifies the protein chain we want to analyze
# We are trying to analyze protein B values from the PDB structure. As a result we are going


plot_protein <- function(pdb_id, chain = "A") {
  # reading the protein structure using its PDB ID
  protein<-read.pdb(pdb_id)

  # Selecting alpha carbon atoms from specified chain
  protein_ca<- trim.pdb(protein, chain = chain, elety="CA")

  # Taking out B-factor values from the specific atoms
  b_factors <-protein_ca$atom$b


  # Across all the proteins, plotting B-factor values
  plotb3(b_factors, sse = protein_ca, typ = "l",
         ylab="Bfactor")
}
```

Testing the Function with Outputs

```
# To test the function, I will still use the protein structures provided in the lab sheet. Tl


plot_protein("4AKE")
```

```
  Note: Accessing on-line PDB file
```





```
plot_protein("1AKE")
```

```
Note: Accessing on-line PDB file
 PDB has ALT records, taking A only, rm.alt=TRUE
```




```
plot_protein("1E4Y")
```

```
Note: Accessing on-line PDB file
```



Conclusion

The x-axis shows residue positions, while y-axis shows B-factor values. As an output we get a plot and not a table with data or numerical values. We can tell greater atonomic displacement by analyzing the higher B factor values.