

Trap, Forward, Resume: Capability Revocation as the Read Barrier of a Moving Garbage Collector on CHERI

XIAOHUI LUO*, Independent Researcher, China

Concurrent moving garbage collectors pay for relocation with a read barrier: a check on reference loads that redirects stale references to relocated objects. Production collectors implement the barrier in software—ZGC’s colored-pointer test, Shenandoah’s forwarding pointer—or, in one famous case, in custom silicon. CHERI capability hardware offers a commodity-adjacent alternative that has not been exploited: *capability revocation*, designed for C/C++ temporal memory safety, makes the load-store unit itself fault on any use of a revoked pointer. We repurpose this safety mechanism as a moving collector’s read barrier. Our collector, StoplessGC, relocates objects, revokes the capabilities to the old copies, and lets the hardware trap each surviving stale reference; a signal handler forwards the faulting register through a forwarding table and resumes the load. No check is executed on the hot path of reference loads—the barrier is the MMU’s tag check, which purecap code pays anyway.

We implement StoplessGC in the OpenJDK 17 template interpreter on Arm Morello (pure-capability CheriBSD) and measure it under QEMU system emulation. The relocation pause is bounded by the root-set size and is independent of heap size: with the root set held constant, the pause varies by 6% while the live heap grows 46×. The dominant cost is the whole-address-space revocation sweep, which is linear in memory size; because the sweep cost is independent of how many objects it revokes, batching relocations across collection cycles amortises the mean cycle pause by 11.9× without breaking our integrity tests. We also report the design points that capability hardware forces on a moving collector—most notably that forwarding metadata must not be stored as capabilities, since the revocation sweep destroys the collector’s own state—and a taxonomy of the pure-capability porting hazards we hit in HotSpot.

1 Introduction

A moving garbage collector must ensure that no mutator dereferences a stale reference to an object that has been relocated. Concurrent collectors enforce this with a *read barrier* [2]: extra work on reference loads that detects stale references and redirects them. The engineering history of low-latency Java collectors is largely a history of making this barrier cheap. Azul’s Pauseless collector put it in custom hardware [5]; C4 re-implemented it in software on x86 [13]; Shenandoah dereferences a per-object forwarding pointer [4, 8]; ZGC tests metadata bits embedded in the pointer itself [18]. In every case the mutator executes instructions on the hot path of reference loads that exist only for the collector’s benefit.

CHERI [16] and its Arm Morello implementation [9] change the substrate. In pure-capability (“purecap”) code, every pointer is a 128-bit capability with hardware-checked bounds, permissions, and an out-of-band validity tag; every load and store is checked by the load-store unit at no software cost. On top of this, CheriBSD provides *capability revocation* [6, 17]: mark an address range in a shadow bitmap, and a kernel sweep atomically invalidates every capability in the address space that points into the marked range. Subsequent use of a revoked capability traps. Revocation was designed to give C and C++ heaps temporal memory safety—to make use-after-free fail-stop—and its costs and mechanisms have been studied in that setting [6, 7, 17].

Our observation is that revocation is, almost verbatim, the read barrier of a moving collector. The difference is what happens at the trap. In the temporal-safety setting a revoked capability is

*The system and this manuscript were produced by Claude (Anthropic)—Opus 4.8 and Fable 5 models, via Claude Code—working autonomously under the direction and review of the human author, who takes full responsibility for the content. Current publisher and arXiv policies do not permit listing an AI system as an author; this note and the statement at the end of the paper are the prominent disclosure those policies require.

a use-after-free; the program is wrong and stops. In a moving collector a revoked capability is merely *stale*; the object lives on at a new address. If the trap handler can map the old address to the new object, it can repair the faulting register and resume the load. The hardware provides exact, per-capability staleness detection on every dereference; the collector only pays, lazily, for references that are actually used.

We built this collector. StoplessGC¹ relocates Java objects with a capability-preserving copy, records *from*→*to* in a forwarding table, revokes the old copies, and heals each trapped mutator access in a SIGPROT handler. To our knowledge it is the first garbage collector to use capability revocation as the read barrier of a moving collector—prior CHERI revocation work invalidates pointers but never forwards them, and prior Java-on-CHERI work ports only non-moving or stop-the-world-compacting collectors [14].

This paper makes the following contributions:

- **Mechanism** (§3): the trap-forward-resume protocol; an identity barrier for reference equality, the one operation that must observe relocation but does not dereference; and batched revocation, which exploits the fact that the sweep’s cost is independent of the number of objects revoked.
- **A capability-specific design law** (§3.2): the collector’s forwarding metadata must be stored as plain integers, not capabilities. The revocation sweep scans *all* memory—including the collector’s own tables—and will destroy forwarding entries that point into ranges revoked by a later cycle. We learned this from a corruption bug whose signature we describe so others can recognise it.
- **Implementation** (§4): StoplessGC in the OpenJDK 17 template interpreter on purecap CheriBSD/Morello, ~2.6 kLOC of new runtime plus interpreter patches, with a taxonomy of the purecap porting hazards that cost us the most time.
- **Measurement** (§5): with the root set held constant, the relocation pause varies 6% while the live heap grows 46× (3.6 → 163 MiB)—the pause is bound to roots, not heap. The revocation sweep is linear in memory size and dominates total cost; batching amortises the mean cycle pause 11.9× at batch size 32. Healing a trapped reference costs ~9 μs under emulation, and the identity barrier’s slow path executes only hundreds of times per run.

We are explicit about scope (§6): the evaluation runs under QEMU system emulation, so absolute times are inflated and only the *shapes*—flat versus linear, the amortisation ratio—are architectural claims; relocation is stop-the-world in the measured configuration (a concurrent collector thread is implemented and stable under light load); and execution is interpreter-only, as JIT compilation on Morello remains future work across the ecosystem.

2 Background

2.1 CHERI, Morello, and purecap execution

A CHERI capability is a 128-bit pointer carrying a 64-bit address, compressed bounds, permissions, and a 1-bit validity tag held out-of-band by the memory subsystem [16]. Capabilities can only be derived from other capabilities by monotonic restriction (narrow the bounds, drop permissions); any attempt to forge or widen one clears the tag, and dereferencing an untagged capability traps. In purecap code every pointer—every Java object reference included—is a capability, and ordinary loads and stores are capability-checked by hardware. Morello [9] is Arm’s experimental implementation; CheriBSD [15] is the FreeBSD-derived OS that runs purecap userspace.

¹The name is an homage to, not a claim of lineage from, the Stopless real-time collector of Pizlo et al. [12], which addresses lock-free concurrent compaction on conventional hardware.




Fig. 1. The trap-forward-resume protocol. The mutator’s fast path contains no barrier code: staleness detection is the capability tag check the load-store unit performs on every purecap access anyway.

2.2 Capability revocation

Revocation gives CHERI heaps temporal safety. CHERIvoke [17] established the sweeping-revocation design: quarantine freed memory, mark it in a shadow bitmap, then sweep memory and clear the tag of (or strip the permissions of, depending on kernel build) every capability pointing into marked ranges. Cornucopia [6] implemented this in CheriBSD with kernel support, and Cornucopia Reloaded [7] nearly eliminated its stop-the-world pauses using Morello’s per-page capability-load generation barrier. CheriBSD exposes the mechanism to userspace as a shadow bitmap plus a `cheri_revoke` system call. Throughout this line of work the post-revocation trap is a *verdict*—the access is a temporal-safety violation. No forwarding is needed because freed objects have no successor.

2.3 Read barriers in moving collectors

Baker’s incremental collector [2] introduced the read barrier; Brooks [4] made it an unconditional indirection through a forwarding pointer. Appel, Ellis, and Li [1] moved the check into hardware a generation early, using virtual-memory page protection: protect from-space pages and let the fault handler evacuate. Its granularity problem—one page-sized fault stalls every object on the page, and protection changes require TLB shootdowns—foreshadows our per-capability contrast. Azul’s Pauseless collector [5] added a dedicated read-barrier instruction to the Vega processor; C4 [13] brought the same loaded-value-barrier design to x86 in software. ZGC encodes GC state in unused high bits of the 64-bit pointer (“colored pointers”) and tests them on load, using multiple virtual mappings of the heap to make the colored address dereferenceable [18]. Shenandoah [8] stores a forwarding pointer in the object header.

2.4 Java on CHERI, and why ZGC’s encoding does not transfer

The MOJO project ported OpenJDK 17 to purecap CheriBSD/Morello, including the Epsilon, Serial, and G1 collectors [14]; the concurrent moving collectors (ZGC, Shenandoah) were not ported. This is not an accident of effort: ZGC’s two structural optimisations are specifically hostile to capabilities. Colored pointers require unused, software-controlled address bits, but a capability’s address must stay within its bounds and cannot carry out-of-band metadata—and the pointer is 128 bits with a hardware-owned tag, so “just use the high bits” forges an invalid capability. Multi-mapping requires the same physical object to be reachable at several virtual addresses, but a capability is bound to the address range it was derived for; dereferencing the same object through a differently-colored alias requires re-deriving capabilities at every color flip. A capability-native moving collector needs a different barrier mechanism, which is what this paper supplies.

3 Design

3.1 Overview

StoplessGC manages a single contiguous arena. Allocation derives a tight-bounds capability for each object from the arena’s root capability (csetbounds to the object’s exact size, software permissions stripped). A collection cycle (Figure 1):

- (1) **Relocate.** At a safepoint, scan the strong roots (thread stacks, OopStorage, class-loader data). Each root’s referent is copied to a fresh arena slot with a capability-preserving copy (the copy must use capability loads/stores, or every reference field in the object loses its tag), the pair (*from*, *to*) is recorded in the forwarding table, and the root slot is updated.
- (2) **Revoke.** The old object ranges are marked in the CheriBSD revocation shadow bitmap and a `cheri_revoke` sweep is issued. After the sweep, every surviving capability to an old copy—heap fields, VM-internal slots, registers—is invalid.
- (3) **Heal lazily.** When a mutator dereferences a stale reference, the access traps (SIGPROT). The handler extracts the faulting capability from the saved register file, looks up its *base address* in the forwarding table, rebuilds a valid capability to the new copy, writes it back to the faulting register, and returns; the instruction retries and succeeds. References that are never used are never healed and cost nothing.

The protocol is self-correcting in the same sense as ZGC’s self-healing barrier: each stale reference traps at most a handful of times (once per register copy) before the healed value propagates.

3.2 The forwarding table must not contain capabilities

The single most consequential design point is what the forwarding table stores. The obvious representation—map `from_addr` to a capability for the new object—is wrong, and fails in a way specific to capability hardware.

The revocation sweep scans *all* of memory, including the collector’s own metadata. Suppose object *A* is moved to *A'* in cycle *i* (table entry $A \rightarrow \text{cap}(A')$), and *A'* is itself moved in a later cycle *j* and its range revoked. The sweep finds the capability `cap(A')` *inside the forwarding table* and clears its tag. A mutator that still holds a stale reference to *A* then traps, the handler looks up *A*—and hands back an untagged capability. The mutator faults again, this time unforwardably. The failure is non-deterministic (it needs an object to move twice with a live stale reference across both moves) and presents as inexplicable corruption at the start of unrelated cycles; disabling revocation makes it vanish, which falsely implicates the sweep itself.

The fix follows from the diagnosis: store plain integers—destination address and length—which the sweep cannot touch, and rebuild the capability at lookup time from the arena’s root capability: `csetbounds(csetaddr(arena_root, addr), len)`, with software permissions stripped. Two details are load-bearing. First, the arena root carries CheriBSD’s `SW_VMEM` software permission, which exempts it from revocation, so the rebuild source survives every sweep. Second, the rebuilt capability must reproduce the allocator’s *exact tight bounds*: both the interior-pointer heal and the identity barrier (below) key their lookups on `cheri_base(c)`, the object’s base address. An early version that rebuilt arena-wide capabilities broke reference identity in `java.lang.invoke`’s identity-keyed caches, far from the collector. The general law: *on revocation-based systems, GC metadata that must survive revocation must be integers, with capabilities re-derived on demand from a revocation-exempt root.*

Forwarding entries persist across cycles, so a reference that is multiple relocations stale heals through a chain of faults, one per generation.

3.3 The heal handler

The handler receives the kernel’s capability-fault signal and must decide: stale (forward it) or genuinely bad (a real bug; re-raise). The forwarding table itself is the oracle—only addresses the collector relocated are in it. Three mechanics matter:

- **Register identification.** CheriBSD delivers the faulting PC, not the faulting capability. The handler scans the saved capability register file for registers that are untagged (or permission-stripped—CheriBSD kernels represent revocation either way, and the handler must accept both) and whose address forwards.
- **Interior pointers.** A faulting capability may address a field or array element. Because allocation bounds are tight, the object’s base is `cheri_base` of the faulting capability; the handler looks up the base and re-applies the offset to the rebuilt capability.
- **Coexistence with expected faults.** HotSpot deliberately takes faults (the `SafeFetch` probes); on purecap these arrive as capability faults too, and every handler in the chain—including crash dumpers—must replay that redirect before treating a fault as fatal, and must itself attempt the heal path.

3.4 The identity barrier

Reference equality (`if_acmpeq/ne, ==`) is the one operation that observes addresses without dereferencing, so the hardware barrier never fires: comparing a stale capability to a healed one yields *false* for the same object. ZGC solves this in the load barrier (references are healed before comparison); we must solve it at the comparison. The interpreter’s compare becomes three-tier: (1) equal addresses $\Rightarrow$ equal (no relocation can make two objects share an address); (2) both capabilities tagged $\Rightarrow$ plain comparison is correct (neither is stale, because revocation untags); (3) otherwise, call a runtime that normalises both operands through the forwarding table and compares the results. The fast paths add two `gctag` instructions and a branch to one bytecode; the slow path is rare (§5.5).

3.5 Batched revocation

The revocation sweep visits all mapped memory regardless of how many objects are marked: revoking one object costs the same as revoking a thousand. The shadow bitmap accumulates marks, and forwarding entries already persist and chain across cycles. So the collector can relocate every cycle but sweep every N th cycle, amortising the dominant cost by up to N . The trade-off is a longer window in which old copies remain dereferenceable: a not-yet-healed reference can read a stale copy after the object has moved, which is correct only while relocation is stop-the-world or objects are immutable in the window. A production design would close the window with Morello’s per-page capability-load generation barrier, exactly as Cornucopia Reloaded [7] does for free-reuse windows; we measure the amortisation (§5.4) and leave the load-barrier integration as future work.

4 Implementation

StoplessGC is implemented against OpenJDK 17 (`jdk17u`) on purecap CheriBSD 15 (`aarch64c`). The collector proper is a CHERI-side runtime library (~1.6 kLOC of C: forwarding table, revocation glue, signal handler) plus a HotSpot `CollectedHeap` implementation (~1 kLOC of C++: arena, root-scan closures, the collection `VM_Operation`, an optional concurrent collector thread). Around 170 further patches against HotSpot make the template interpreter and runtime capability-clean; they are mechanical but load-bearing, and their failure modes are instructive. The classes that cost the most time:

A64/C64 interworking. Morello executes in two instruction-set modes; purecap code runs in C64. An indirect call through an *integer* register (`blr xn` rather than `blr cn`) does not switch mode, and—the trap within the trap—setting the link address’s low bit does *not* set `PSTATE.C64`: the callee then decodes C64 prologue bytes as A64 garbage. Every interpreter codelet that calls into the VM through a raw function address had to be routed through capability branches.

Capability-blind code generation. Patterns that are correct on aarch64 silently strip tags on Morello: a conditional select (`csel`) on what is actually a capability value, integer compare-and-move on 16-byte object headers, an integer store overwriting half a capability. The 16-byte mark word also forces the header lock CAS to be a capability-sized CAS.

DDC-relative assembly. In purecap CheriBSD the default data capability is null; handwritten `.S` code that addresses memory as `[x0]` (DDC-relative) faults even though the “pointer” is valid. HotSpot’s `SafeFetch` stubs were the prominent case.

Signal-handler composition. The GC trap handler, HotSpot’s expected-fault machinery, and any diagnostic crash handler all receive the same signal; each must try *all* the others’ redirects (`SafeFetch` continuation, heal path) before declaring a fault fatal. Getting this wrong turns a healable stale-reference trap into a VM abort that looks like GC corruption.

VM-internal raw references. HotSpot’s C++ code caches object addresses in places the root scan does not cover (interned handles, scratch fields). These never fault when merely *copied* as values—only dereferences trap—so a stale cached reference can be compared, hashed, or stored long before the barrier can intervene. We bisected aggressive-relocation boot failures to this class (§6); it is the purecap analogue of the classic “unreported root” GC bug, made subtler because reads-as-values escape the hardware check.

The collection cycle itself runs as a safepoint `VM_Operation`; an optional concurrent thread triggers cycles on a timer and is stable under light load (§6). Relocation volume per cycle is capped by a tunable move limit; integrity tests also run with the limit effectively removed (every reachable root referent relocated, 1,016 objects in our largest configuration) to validate whole-heap movement with correct reference identity.

5 Evaluation

5.1 Setup and method

All measurements run on purecap CheriBSD 15.0-CURRENT (GENERIC-MORELLO-PURECAP, aarch64c) under QEMU system-mode emulation of Morello, with the OpenJDK 17 template interpreter (`-Xint`), compressed oops and compressed class pointers disabled, and the concurrent collector triggering cycles every 50 ms with a per-cycle move limit of 8 objects unless stated. Phase timings are taken inside the safepoint operation with the VM’s nanosecond clock, so the reported windows are exactly the mutator pause; barrier-side counters (heal faults, heal time, identity slow-path executions) are accumulated in the signal handler with a monotonic clock and reported at VM exit.

What emulation does and does not invalidate. QEMU inflates all absolute times and does not model Morello’s microarchitecture, so we make no absolute-latency claims. The claims we do make are structural: *which* costs scale with *what* (heap size, root count, batch size), and those relationships are properties of the algorithm and the revocation mechanism, not of the emulator. Workloads are purpose-built: an allocation-heavy benchmark whose live set grows continuously (StoplessBench), a linked-structure integrity test that relocates every object and then verifies structure and reference identity (IntegrityGC), and a string-concatenation workload that exercises `invokedynamic`, `MethodHandle` bootstraps, and identity-keyed caches (`ConcatTest`). They are




Fig. 2. StoplessBench, root set constant at 894 after warm-up, live heap growing 3.6 $\rightarrow$ 163 MiB (46 $\times$); 40 collection cycles, 8 objects relocated per cycle. (a) The mutator-visible relocation phase (root scan + copy + root fixup) stays at 13–15 ms. (b) The `cheri_revoke` sweep grows linearly with mapped memory, 0.83 $\rightarrow$ 5.95 s. Absolute times are QEMU-inflated; the claim is the contrast in shape.

Table 1. Measured costs of the three mechanisms (QEMU-emulated; relative magnitudes are the claim). Heal statistics from IntegrityGC and ConcatTest under the concurrent collector.

mechanism	cost	scales with	frequency
relocation pause	13–15 ms	roots + moved objects	per cycle
revocation sweep	0.83–5.95 s	mapped memory	per cycle (or batch)
heal trap	7–9 μ s	—	per <i>used</i> stale ref
identity slow path	2 table lookups	—	218 / run (ConcatTest)

microbenchmarks, not DaCapo; running standard suites requires JIT and library coverage beyond any current purecap JVM, including ours.

5.2 The relocation pause is independent of heap size

Figure 2 is the central result. StoplessBench grows its live heap continuously while its root-set size stabilises, isolating heap size as the variable. Over a 46 $\times$ heap range at a constant 894 roots, the relocation pause moves from 13.7 ms to 14.6 ms (+6%, within cycle-to-cycle noise), because the pause does work proportional to roots scanned plus objects moved—never to heap size. There is no marking phase, no per-object liveness traversal, and no card or remembered-set scan in the pause: unreferenced old copies are simply never healed, and their reclamation is the (off-pause) revocation sweep. By contrast the sweep itself, panel (b), is linear in mapped memory—0.83 s at 3.6 MiB to 5.95 s at 163 MiB—confirming that sweeping, exactly as in the C/C++ revocation literature [7, 17], is the cost to engineer around, and motivating §5.4.

5.3 Cost of the barrier mechanisms

Table 1 summarises. Healing a trapped stale reference—signal delivery, register-file scan, forwarding lookup, capability rebuild, return-and-retry—averages 8.7 μ s over 805 heals in IntegrityGC and 7.0 μ s over 903 heals in ConcatTest; signal delivery dominates under emulation. Aggregate heal time is $\sim$ 7 ms per run—three orders of magnitude below a single sweep—supporting the design’s




Fig. 3. Batched revocation, IntegrityGC under the concurrent collector. (a) Per-cycle pause, log scale: with batching most cycles pause only for relocation ($\sim 15\text{--}25$ ms); the sweep cost concentrates in every N th cycle. (b) Mean pause per cycle falls from 0.84 s to 0.07 s ($11.9\times$) at batch size 32. The integrity test passes at every batch size.

bet that lazy, per-used-reference healing is cheap. The mutator’s load fast path, to restate, contains no added instructions at all.

5.4 Batched revocation amortises the dominant cost

Because the sweep visits all memory regardless of marks, sweeping every N th cycle divides its amortised cost by N while relocation continues every cycle. Figure 3: mean pause per cycle falls $0.843 \rightarrow 0.149 \rightarrow 0.071$ s for batch sizes 1, 8, 32—a $11.9\times$ reduction, tracking the sweep-count reduction ($62/23/4$ sweeps over the respective runs)—and the structure-and-identity verification passes at every batch size. The per-cycle trace shows the expected shape: a floor at the heap-independent relocation pause, with the sweep concentrated in periodic spikes whose amplitude is unchanged (the sweep is no more expensive for being batched—that is the point). The consistency caveat of §3.5 applies: our integrity tests do not mutate relocated objects inside the batch window, and closing that window in general requires the per-page load-barrier integration.

5.5 The identity barrier is nearly free

Over a full ConcatTest run—chosen because `java.lang.invoke.bootstrap` is dense with identity-keyed caching—the identity barrier’s slow path executed 218 times, against 903 heal faults and on the order of 10^6 executed branches of the fast path. Two extra tag-check instructions on a taken `if_acmp` bytecode, with table lookups only when an untagged capability actually reaches a comparison, leaves reference equality effectively unburdened.

6 Discussion and limitations

Emulation. We re-emphasise: all absolutes are QEMU-scaled. On hardware, signal delivery, memory bandwidth (the sweep is bandwidth-bound [17]), and the relocation copy all shrink by different factors; the flat-versus-linear contrast and the batching arithmetic are preserved because they are counting arguments, not timings. Reproducing Figure 2 on a Morello board is the natural next step.

Stop-the-world relocation. The measured configuration relocates at safepoints; concurrency in StoplessGC currently means the *collector schedule* (a background thread triggering cycles, the

mutator running between them, healing on demand). True concurrent relocation—mutators running *during* the copy—needs an object-granularity copy protocol; the hardware trap handles the post-move window already, and revocation’s atomic global cut-over is precisely the property that makes the post-copy side tractable.

Coverage of VM-internal references. Our root scan covers the standard strong-root sets. HotSpot additionally caches raw object addresses in VM-internal C++ state that is invisible to the root scan and—because capability *reads* do not trap, only dereferences—can launder a stale reference back into circulation. We hit this as boot-time failures under aggressive relocation and bisected it to specific unscanned caches. The fix is the classic one (enumerate or eliminate the caches); we flag it because the hardware barrier’s guarantee is easily over-read: it covers *dereference*, not *data flow*.

Interpreter only. Like all current purecap JVM work to our knowledge [10, 14], we run interpreted. Template-interpreter bytecodes are exactly where our barrier costs sit (the *acmp* tiers), so JIT changes the constant factors, not the structure.

Memory overhead. Old copies occupy arena space until swept, so batching trades pause time for float, bounded by (moved bytes per cycle) $\times N$; the forwarding table is three machine words per relocated object per generation.

7 Related work

CHERI revocation. CHERIvoke [17], Cornucopia [6], and Cornucopia Reloaded [7] build and optimise sweeping revocation for C/C++ temporal safety; revoked references are use-after-free errors, terminal by design. We inherit their mechanism (quarantine, shadow bitmap, sweep) and invert the trap’s meaning, from verdict to redirect. Cornucopia Reloaded’s per-page load barrier is also the missing piece for closing our batching window, a reunion of the two lines we find pleasing.

Hardware-assisted read barriers. Appel–Ellis–Li [1] used page protection as the barrier; its page granularity caused multi-object stalls and its protection flips are TLB-expensive. Capability revocation gives *per-object* (indeed *per-capability*) granularity with one global cut-over. Azul Vega [5] put the barrier in a custom instruction, achieving per-reference granularity at the price of bespoke silicon; CHERI offers the trap-on-stale primitive in a general-purpose, security-motivated architecture.

Software barriers in production JVMs. ZGC [11, 18] and Shenandoah [8] demonstrate that software self-healing barriers can reach sub-millisecond pauses on commodity hardware, at a per-load instruction cost and, for ZGC, a pointer encoding that purecap disallows outright (§2.4). C4 [13] likewise relies on address-space tricks (virtual-memory remapping) that capability bounds constrain. Our contribution is not to outperform these collectors but to show the barrier they implement in software is already present, exact, and free-per-load in capability hardware.

Java on CHERI. MOJO [14] ports OpenJDK 17’s Epsilon, Serial, and G1 to CheriBSD/Morello; Lowther et al. [10] optimise a MicroPython interpreter on Morello. Neither moves objects under a hardware barrier. Bramley et al. [3] study CHERI *malloc* implementations, the non-moving end of the same design space.

8 Conclusion

Capability revocation was built to make dangling pointers trap. A moving garbage collector needs exactly that trap—plus a forwarding table on the other side of it. StoplessGC demonstrates the combination end to end in OpenJDK on Morello: relocation pauses bound by roots rather than heap (+6% pause across a 46 $\times$ heap), lazy per-use healing measured in microseconds, an identity

barrier that almost never takes its slow path, and a sweep cost that batches away $11.9\times$ because revoking n objects costs the same as revoking one. The capability-specific lessons—integer-only GC metadata rebuilt from revocation-exempt roots, identity as the one barrier hardware cannot give you, reads-as-values as the residual coverage gap—are, we believe, durable properties of building moving collectors on this class of hardware, and the remaining engineering (per-page load barriers for the batch window, concurrent copy, JIT) has known designs waiting on the same substrate.

AI contribution statement. The design, implementation, debugging, measurement, and manuscript of this work were produced by Claude (Anthropic)—Opus 4.8 and Fable 5 models, operating via Claude Code—under the direction, constraint setting, and review of the human author. The division of labour is recorded in the project repository’s development log. Per current arXiv and publisher policies, AI systems are not listed as authors because authorship carries accountability; the human author assumes that accountability and verified the empirical results and every citation.

References

- [1] Andrew W. Appel, John R. Ellis, and Kai Li. 1988. Real-Time Concurrent Collection on Stock Multiprocessors. In *Proceedings of the ACM SIGPLAN Conference on Programming Language Design and Implementation (PLDI)*. doi:10.1145/53990.54005
- [2] Henry G. Baker. 1978. List Processing in Real Time on a Serial Computer. *Commun. ACM* 21, 4 (1978), 280–294. doi:10.1145/359460.359470
- [3] Jacob Bramley, Dejece Jacob, Andrei Lascu, Jeremy Singer, and Laurence Tratt. 2023. Picking a ChERI Allocator: Security and Performance Considerations. In *Proceedings of the 2023 ACM SIGPLAN International Symposium on Memory Management (ISMM)*. doi:10.1145/3591195.3595278
- [4] Rodney A. Brooks. 1984. Trading Data Space for Reduced Time and Code Space in Real-Time Garbage Collection on Stock Hardware. In *Proceedings of the ACM Symposium on LISP and Functional Programming (LFP)*. doi:10.1145/800055.802042
- [5] Cliff Click, Gil Tene, and Michael Wolf. 2005. The Pauseless GC Algorithm. In *Proceedings of the 1st ACM/USENIX International Conference on Virtual Execution Environments (VEE)*. doi:10.1145/1064979.1064988
- [6] Nathaniel Wesley Filardo, Brett F. Gutstein, Jonathan Woodruff, Sam Ainsworth, Lucian Paul-Trifu, Brooks Davis, Hongyan Xia, Edward Tomasz Napierala, Alexander Richardson, John Baldwin, David Chisnall, Jessica Clarke, Khilan Gudka, Alexandre Joannou, A. Theodore Markettos, Alfredo Mazinghi, Robert M. Norton, Michael Roe, Peter Sewell, Stacey Son, Timothy M. Jones, Simon W. Moore, Peter G. Neumann, and Robert N. M. Watson. 2020. Cornucopia: Temporal Safety for ChERI Heaps. In *IEEE Symposium on Security and Privacy (S&P)*. doi:10.1109/SP40000.2020.00098
- [7] Nathaniel Wesley Filardo, Brett F. Gutstein, Jonathan Woodruff, Jessica Clarke, Peter Rugg, Brooks Davis, Mark Johnston, Robert Norton, David Chisnall, Simon W. Moore, Peter G. Neumann, and Robert N. M. Watson. 2024. Cornucopia Reloaded: Load Barriers for ChERI Heap Temporal Safety. In *Proceedings of the 29th ACM International Conference on Architectural Support for Programming Languages and Operating Systems (ASPLOS), Volume 2*. doi:10.1145/3620665.3640416
- [8] Christine H. Flood, Roman Kennke, Andrew Dinn, Andrew Haley, and Roland Westrelin. 2016. Shenandoah: An Open-Source Concurrent Compacting Garbage Collector for OpenJDK. In *Proceedings of the 13th International Conference on Principles and Practices of Programming on the Java Platform: Virtual Machines, Languages, and Tools (PPPJ)*. doi:10.1145/2972206.2972210
- [9] Richard Grisenthwaite, Graeme Barnes, Robert N. M. Watson, Simon W. Moore, Peter Sewell, and Jonathan Woodruff. 2023. The Arm Morello Evaluation Platform—Validating ChERI-Based Security in a High-Performance System. *IEEE Micro* 43, 3 (2023), 50–57. doi:10.1109/MM.2023.3264676
- [10] Duncan Lowther, Dejece Jacob, and Jeremy Singer. 2023. ChERI Performance Enhancement for a Bytecode Interpreter. *arXiv preprint arXiv:2308.05076* (2023).
- [11] OpenJDK Project. 2023. JEP 439: Generational ZGC. <https://openjdk.org/jeps/439>.
- [12] Filip Pizlo, Daniel Frampton, Erez Petrank, and Bjarne Steensgaard. 2007. Stopless: A Real-Time Garbage Collector for Multiprocessors. In *Proceedings of the 6th International Symposium on Memory Management (ISMM)*. doi:10.1145/1296907.1296927
- [13] Gil Tene, Balaji Iyengar, and Michael Wolf. 2011. C4: The Continuously Concurrent Compacting Collector. In *Proceedings of the International Symposium on Memory Management (ISMM)*. doi:10.1145/1993478.1993491
- [14] THG and University of Manchester. 2024. MOJO: Porting OpenJDK 17 and its Garbage Collectors to CheriBSD on Morello. Project site: <https://www.mojo-jvm.org>. Ported collectors: Epsilon, Serial, G1.

- [15] University of Cambridge and SRI International. 2026. CheriBSD: A Capability-Adapted Version of FreeBSD. <https://www.cheribsd.org>.
- [16] Robert N. M. Watson, Peter G. Neumann, Jonathan Woodruff, Michael Roe, Hesham Almatary, Jonathan Anderson, John Baldwin, Graeme Barnes, David Chisnall, Jessica Clarke, et al. 2023. *Capability Hardware Enhanced RISC Instructions: CHERI Instruction-Set Architecture (Version 9)*. Technical Report UCAM-CL-TR-987. University of Cambridge, Computer Laboratory.
- [17] Hongyan Xia, Jonathan Woodruff, Sam Ainsworth, Nathaniel W. Filardo, Michael Roe, Alexander Richardson, Peter Rugg, Peter G. Neumann, Simon W. Moore, Robert N. M. Watson, and Timothy M. Jones. 2019. CHERivoke: Characterising Pointer Revocation Using CHERI Capabilities for Temporal Memory Safety. In *Proceedings of the 52nd Annual IEEE/ACM International Symposium on Microarchitecture (MICRO)*. doi:10.1145/3352460.3358288
- [18] Albert Mingkun Yang and Tobias Wrigstad. 2022. Deep Dive into ZGC: A Modern Garbage Collector in OpenJDK. *ACM Transactions on Programming Languages and Systems* 44, 4 (2022), 22:1–22:34. doi:10.1145/3538532