

Software Architecture

- The outlet, using a bare-metal Raspberry Pi Pico 2
- The hub, using a Raspberry Pi Zero 2W running Debian 13
- The user device, running any mainstream OS
- The relay server, running Debian 13

1. allows the user to control their outlets remotely,
2. reports power consumption data to the user,
3. respects the user's privacy, and
4. can be progressively rolled out in the user's home without regard for wireless connectivity.

- [1] P. Goyal, "Design of Power-Line Communication System (PLC) Using a PIC Microcontroller," International Conference on Information & Communication Technology (IICT), DIT University, India, July 2007
- [2] C. Lien, Y. Bai, and M. Lin, "Remote-Controllable Power Outlet System for Home Power Management", IEEE Transactions on Consumer Electronics, vol.53, no. 4, pp. 1634-1641, Nov. 2007, doi: 10.1109/TCE.2007.4429263.
- [3] A.S. Musleh, M. Debozza, M. Farook, "Design and implementation of smart plug: An Internet of Things (IoT) approach," IEEE, Jan. 2018, doi: 10.1109/ICCECTA.2017.8252033
- [4] "PCB Trace Width Calculator." Digikey, <https://www.digikey.ca/en/resources/conversion-calculators/conversion-calculator-pcb-trace-width> (Accessed July 26, 2026)