

BestPracticesSTBiocBook

Table of contents

Welcome	4
Docker image	5
RStudio Server	6
Session info	7
I Introduction	10
1 Introduction	11
1.1 Overview	11
1.2 Contents	11
1.3 Scope and who this book is for	11
1.4 Bioconductor	12
1.5 Additional resources	12
1.6 Contributions	13
References	13
2 Spatial transcriptomics	14
2.1 Overview	14
2.2 Sequencing-based platforms	14
2.2.1 10x Genomics Visium	15
2.2.2 10x Genomics Visium HD	16
2.2.3 Curio Seeker	16
2.3 Molecule-based platforms	16
2.3.1 10x Genomics Xenium	16
2.3.2 Vizgen MERSCOPE	17
2.3.3 NanoString CosMx	17
References	17
3 Bioconductor data classes	18
3.1 Overview	18
3.2 SpatialExperiment class	18

3.3	Molecule-based data	19
3.3.1	MoleculeExperiment	19
3.3.2	SpatialFeatureExperiment	19
	References	20
II	Analysis steps	21
4	Analysis steps	22
4.1	Save data objects for re-use in later chapters	22
4.1.1	Human DLPFC dataset	22
	References	24
5	Load data	25
5.1	Overview	25
5.2	Dataset	25
5.3	Load data	25
5.4	SpatialExperiment object	26
5.5	Build object	28
5.6	Molecule-based data	29
	References	29
6	Quality control	30
6.1	Overview	30
6.2	Load data from previous steps	31
6.3	Plot data	31
6.4	Calculate QC metrics	32
6.5	Selecting thresholds	33
6.5.1	Library size	33
6.5.2	Number of expressed features	38
6.5.3	Proportion of mitochondrial reads	42
6.5.4	Number of cells per spot	46
6.5.5	Remove low-quality spots	49
6.6	Zero-cell and single-cell spots	50
6.7	Quality control at gene level	51
	References	51

Welcome

Package: BestPracticesSTBiocBook **Authors:** First Last [aut, cre] **Compiled:** 2024-09-26
Package version: 0.98.0 **R version:** R version 4.4.1 (2024-06-14) **BioC version:** 3.20
License: MIT + file LICENSE

This is the website for the online book ‘**Best Practices for Spatial Transcriptomics Analysis with Bioconductor**’.

This book provides discussion and interactive examples on best practices for computational analysis workflows for spatial transcriptomics data, using the [Bioconductor](#) framework within R. The chapters contain details on individual analysis steps as well as complete example workflows, with interactive example datasets and R code.

The book is organized into several parts, including introductory materials, analysis steps, and example workflows.

Additional details on analysis workflows for non-spatial single-cell data as well as further introductory materials on R and Bioconductor can be found in the related book [Orchestrating Single-Cell Analysis with Bioconductor \(OSCA\)](#).

Docker image

A Docker image built from this repository is available here:

ghcr.io/lmweber/bestpracticesstbiocbook

Get started now

You can get access to all the packages used in this book in < 1 minute, using this command in a terminal:

Listing 0.1 bash

```
docker run -it ghcr.io/lmweber/bestpracticesstbiocbook:devel R
```

RStudio Server

An RStudio Server instance can be initiated from the **Docker** image as follows:

Listing 0.2 bash

```
docker run \  
  --volume <local_folder>:<destination_folder> \  
  -e PASSWORD=OHCA \  
  -p 8787:8787 \  
  ghcr.io/lmweber/bestpracticesstbiocbook:devel
```

The initiated RStudio Server instance will be available at <https://localhost:8787>.

Session info

 Click to expand

Part I

Introduction

1 Introduction

1.1 Overview

Bioconductor

1.2 Contents

-
-
-
-

1.3 Scope and who this book is for

Preprocessing

Visium Data

1.4 Bioconductor

[Bioconductor](#)

1.5 Additional resources

- [Orchestrating Single-Cell Analysis with Bioconductor \(OSCA\)](#)
- [R for Data Science](#)
- [Data Carpentry](#) [Software Carpentry](#)

- [detailed guide](#)
[YouTube videos](#)
- [Visium Data Preprocessing](#)

1.6 Contributions

[GitHub issues](#)

References

2 Spatial transcriptomics

2.1 Overview

of the Year 2020

Method

2.2 Sequencing-based platforms

2.2.1 10x Genomics Visium

10x Genomics Visium




Figure 2.1: Schematic illustrating the 10x Genomics Visium platform. Source: [10x Genomics Visium](#)

2.2.2 10x Genomics Visium HD

[10x Genomics Visium HD](#)

2.2.3 Curio Seeker

[Curio Seeker](#)

2.3 Molecule-based platforms

2.3.1 10x Genomics Xenium

[10x Genomics](#)

2.3.2 Vizgen MERSCOPE

Vizgen

2.3.3 NanoString CosMx

NanoString

References

3 Bioconductor data classes

3.1 Overview

3.2 SpatialExperiment class

[SpatialExperiment](#)

[SingleCellExperiment](#)

[Bioconductor vignette](#)




Figure 3.1: Overview of the **SpatialExperiment** data class for storing and manipulating spatial transcriptomics datasets within the Bioconductor framework.

3.3 Molecule-based data

3.3.1 MoleculeExperiment

[Bioconductor package](#)

3.3.2 SpatialFeatureExperiment

[Bioconductor package](#)

References

Part II

Analysis steps

4 Analysis steps

3

4.1 Save data objects for re-use in later chapters

4.1.1 Human DLPFC dataset

```
# LOAD DATA

library(SpatialExperiment)
library(STexampleData)
spe <- Visium_humanDLPFC()

# save object
library(here)
# if (!dir.exists(here("outputs"))) dir.create(here("outputs"))
# saveRDS(spe, file = here("outputs/spe_load.rds"))
saveRDS(spe, file = "spe_load.rds")
```

```

# QUALITY CONTROL (QC)

library(scater)
# subset to keep only spots over tissue
spe <- spe[, colData(spe)$in_tissue == 1]
# identify mitochondrial genes
is_mito <- grepl("(^MT-)|(^mt-)", rowData(spe)$gene_name)
# calculate per-spot QC metrics
spe <- addPerCellQC(spe, subsets = list(mito = is_mito))
# select QC thresholds
qc_lib_size <- colData(spe)$sum < 600
qc_detected <- colData(spe)$detected < 400
qc_mito <- colData(spe)$subsets_mito_percent > 28
qc_cell_count <- colData(spe)$cell_count > 10
# combined set of discarded spots
discard <- qc_lib_size | qc_detected | qc_mito | qc_cell_count
colData(spe)$discard <- discard
# filter low-quality spots
spe <- spe[, !colData(spe)$discard]

# save object
# saveRDS(spe, file = here("outputs/spe_qc.rds"))
saveRDS(spe, file = "spe_qc.rds")

```

```

# NORMALIZATION

library(scraper)
# calculate logcounts using library size factors
spe <- logNormCounts(spe)

# save object
# saveRDS(spe, file = here("outputs/spe_logcounts.rds"))
saveRDS(spe, file = "spe_logcounts.rds")

```

```

# FEATURE SELECTION

# remove mitochondrial genes
spe <- spe[!is_mito, ]
# fit mean-variance relationship
dec <- modelGeneVar(spe)
# select top HVGs
top_hvgs <- getTopHVGs(dec, prop = 0.1)

```

```
# save object
# saveRDS(spe, file = here("outputs/spe_hvgs.rds"))
# saveRDS(top_hvgs, file = here("outputs/top_hvgs.rds"))
saveRDS(spe, file = "spe_hvgs.rds")
saveRDS(top_hvgs, file = "top_hvgs.rds")
```

DIMENSIONALITY REDUCTION

```
# compute PCA
set.seed(123)
spe <- runPCA(spe, subset_row = top_hvgs)
# compute UMAP on top 50 PCs
set.seed(123)
spe <- runUMAP(spe, dimred = "PCA")
# update column names
colnames(reducedDim(spe, "UMAP")) <- paste0("UMAP", 1:2)

# save object
# saveRDS(spe, file = here("outputs/spe_reduceddims.rds"))
saveRDS(spe, file = "spe_reduceddims.rds")
```

CLUSTERING

```
# graph-based clustering
set.seed(123)
k <- 10
g <- buildSNNGraph(spe, k = k, use.dimred = "PCA")
g_walk <- igraph::cluster_walktrap(g)
clus <- g_walk$membership
colLabels(spe) <- factor(clus)

# save object
# saveRDS(spe, file = here("outputs/spe_cluster.rds"))
saveRDS(spe, file = "spe_cluster.rds")
```

References

5 Load data

5.1 Overview

3

Preprocessing

Visium Data

STexampleData

5.2 Dataset

5.3 Load data

STexampleData

```
library(SpatialExperiment)
library(STexampleData)

# load object
spe <- Visium_humanDLPFC()
```

5.4 SpatialExperiment object

3

```
# check object
spe
## class: SpatialExperiment
## dim: 33538 4992
## metadata(0):
## assays(1): counts
## rownames(33538): ENSG00000243485 ENSG00000237613 ... ENSG00000277475
##      ENSG00000268674
## rowData names(3): gene_id gene_name feature_type
## colnames(4992): AAACAACGAATAGTTC-1 AAACAAGTATCTCCCA-1 ...
##      TTGTTTGTATTACACG-1 TTGTTTGTGTAAATTC-1
## colData names(8): barcode_id sample_id ... reference cell_count
## reducedDimNames(0):
## mainExpName: NULL
## altExpNames(0):
## spatialCoords names(2) : pxl_col_in_fullres pxl_row_in_fullres
## imgData names(4): sample_id image_id data scaleFactor

# number of genes (rows) and spots (columns)
dim(spe)
## [1] 33538 4992

# names of 'assays'
assayNames(spe)
## [1] "counts"

# row (gene) data
head(rowData(spe))
## DataFrame with 6 rows and 3 columns
```

```
##           gene_id   gene_name   feature_type
##           <character> <character>   <character>
## ENSG00000243485 ENSG00000243485 MIR1302-2HG Gene Expression
## ENSG00000237613 ENSG00000237613   FAM138A Gene Expression
## ENSG00000186092 ENSG00000186092   OR4F5  Gene Expression
## ENSG00000238009 ENSG00000238009 AL627309.1 Gene Expression
## ENSG00000239945 ENSG00000239945 AL627309.3 Gene Expression
## ENSG00000239906 ENSG00000239906 AL627309.2 Gene Expression

# column (spot) data
head(colData(spe))
## DataFrame with 6 rows and 8 columns
##           barcode_id   sample_id in_tissue array_row
##           <character>   <character> <integer> <integer>
## AAACAACGAATAGTTC-1 AAACAACGAATAGTTC-1 sample_151673      0      0
## AAACAAGTATCTCCCA-1 AAACAAGTATCTCCCA-1 sample_151673      1     50
## AAACAATCTACTAGCA-1 AAACAATCTACTAGCA-1 sample_151673      1      3
## AAACACCAATAACTGC-1 AAACACCAATAACTGC-1 sample_151673      1     59
## AAACAGAGCGACTCCT-1 AAACAGAGCGACTCCT-1 sample_151673      1     14
## AAACAGCTTTCAGAAG-1 AAACAGCTTTCAGAAG-1 sample_151673      1     43
##           array_col ground_truth   reference cell_count
##           <integer>   <character> <character>   <integer>
## AAACAACGAATAGTTC-1      16         NA         NA         NA
## AAACAAGTATCTCCCA-1     102      Layer3      Layer3         6
## AAACAATCTACTAGCA-1      43      Layer1      Layer1        16
## AAACACCAATAACTGC-1      19         WM         WM         5
## AAACAGAGCGACTCCT-1      94      Layer3      Layer3         2
## AAACAGCTTTCAGAAG-1       9      Layer5      Layer5         4

# spatial coordinates
head(spatialCoords(spe))
##           pxl_col_in_fullres pxl_row_in_fullres
## AAACAACGAATAGTTC-1          3913          2435
## AAACAAGTATCTCCCA-1          9791          8468
## AAACAATCTACTAGCA-1          5769          2807
## AAACACCAATAACTGC-1          4068          9505
## AAACAGAGCGACTCCT-1          9271          4151
## AAACAGCTTTCAGAAG-1          3393          7583

# image data
imgData(spe)
## DataFrame with 2 rows and 4 columns
```

```
##      sample_id  image_id  data scaleFactor
##      <character> <character> <list>  <numeric>
##  1 sample_151673    lowres  #####  0.0450045
##  2 sample_151673    hires   #####  0.1500150
```

5.5 Build object

SpatialExperiment

```
# create data
n_genes <- 200
n_spots <- 100

counts <- matrix(0, nrow = n_genes, ncol = n_spots)

row_data <- DataFrame(
  gene_name = paste0("gene", sprintf("%03d", seq_len(n_genes)))
)

col_data <- DataFrame(
  sample_id = rep("sample01", n_spots)
)

spatial_coords <- matrix(0, nrow = n_spots, ncol = 2)
colnames(spatial_coords) <- c("x", "y")

# create SpatialExperiment object
spe <- SpatialExperiment(
  assays = list(counts = counts),
  colData = col_data,
  rowData = row_data,
  spatialCoords = spatial_coords
)
```

5.6 Molecule-based data

3

References

6 Quality control

6.1 Overview

-
-
-
-

6.2 Load data from previous steps

4


```
library(SpatialExperiment)
library(here)
# spe <- readRDS(here("outputs/spe_load.rds"))
spe <- readRDS("spe_load.rds")
```

6.3 Plot data

ggspavis

```
library(ggspavis)
```

```
# plot spatial coordinates (spots)
plotSpots(spe)
```



6.4 Calculate QC metrics

```
library(scater)
```

```
# subset to keep only spots over tissue
spe <- spe[, colData(spe)$in_tissue == 1]
dim(spe)
## [1] 33538 3639
```

```
# identify mitochondrial genes
is_mito <- grepl("(^MT-)|(^mt-)", rowData(spe)$gene_name)
table(is_mito)
## is_mito
## FALSE TRUE
## 33525 13
rowData(spe)$gene_name[is_mito]
## [1] "MT-ND1" "MT-ND2" "MT-CO1" "MT-CO2" "MT-ATP8" "MT-ATP6" "MT-CO3"
## [8] "MT-ND3" "MT-ND4L" "MT-ND4" "MT-ND5" "MT-ND6" "MT-CYB"
```


```
# calculate per-spot QC metrics and store in colData
spe <- addPerCellQC(spe, subsets = list(mito = is_mito))
head(colData(spe))
## DataFrame with 6 rows and 14 columns
##           barcode_id      sample_id in_tissue array_row
##           <character>    <character> <integer> <integer>
## AAACAAGTATCTCCCA-1 AAACAAGTATCTCCCA-1 sample_151673      1      50
## AAACAATCTACTAGCA-1 AAACAATCTACTAGCA-1 sample_151673      1       3
## AAACACCAATAACTGC-1 AAACACCAATAACTGC-1 sample_151673      1      59
## AAACAGAGCGACTCCT-1 AAACAGAGCGACTCCT-1 sample_151673      1      14
## AAACAGCTTTCAGAAG-1 AAACAGCTTTCAGAAG-1 sample_151673      1      43
## AAACAGGGTCTATATT-1 AAACAGGGTCTATATT-1 sample_151673      1      47
##           array_col ground_truth  reference cell_count      sum
```


##		<integer>	<character>	<character>	<integer>	<numeric>
##	AAACAAGTATCTCCCA-1	102	Layer3	Layer3	6	8458
##	AAACAATCTACTAGCA-1	43	Layer1	Layer1	16	1667
##	AAACACCAATAACTGC-1	19	WM	WM	5	3769
##	AAACAGAGCGACTCCT-1	94	Layer3	Layer3	2	5433
##	AAACAGCTTTCAGAAG-1	9	Layer5	Layer5	4	4278
##	AAACAGGGTCTATATT-1	13	Layer6	Layer6	6	4004
##		detected	subsets_mito_sum	subsets_mito_detected		
##		<numeric>	<numeric>	<numeric>		
##	AAACAAGTATCTCCCA-1	3586	1407	13		
##	AAACAATCTACTAGCA-1	1150	204	11		
##	AAACACCAATAACTGC-1	1960	430	13		
##	AAACAGAGCGACTCCT-1	2424	1316	13		
##	AAACAGCTTTCAGAAG-1	2264	651	12		
##	AAACAGGGTCTATATT-1	2178	621	13		
##		subsets_mito_percent	total			
##		<numeric>	<numeric>			
##	AAACAAGTATCTCCCA-1	16.6351	8458			
##	AAACAATCTACTAGCA-1	12.2376	1667			
##	AAACACCAATAACTGC-1	11.4089	3769			
##	AAACAGAGCGACTCCT-1	24.2223	5433			
##	AAACAGCTTTCAGAAG-1	15.2174	4278			
##	AAACAGGGTCTATATT-1	15.5095	4004			


6.5 Selecting thresholds

6.5.1 Library size

```
# histogram of library sizes
hist(colData(spe)$sum, breaks = 20)
```




```
# plot library size vs. number of cells per spot
plotSpotQC(spe, plot_type = "scatter",
            x_metric = "cell_count", y_metric = "sum",
            y_threshold = 600)
## `geom_smooth()` using formula = 'y ~ x'
## `stat_xsidebin()` using `bins = 30`. Pick better value with `binwidth`.
## `stat_ysidebin()` using `bins = 30`. Pick better value with `binwidth`.
```




```
# select QC threshold for library size
qc_lib_size <- colData(spe)$sum < 600
table(qc_lib_size)
## qc_lib_size
## FALSE TRUE
## 3631 8

colData(spe)$qc_lib_size <- qc_lib_size
```


```
# check spatial pattern of discarded spots
plotSpotQC(spe, plot_type = "spot",
            annotate = "qc_lib_size")
```



```
# check spatial pattern of discarded spots if threshold is too high
qc_lib_size_2000 <- colData(spe)$sum < 2000
colData(spe)$qc_lib_size_2000 <- qc_lib_size_2000
plotSpotQC(spe, plot_type = "spot",
            annotate = "qc_lib_size_2000")
```




```
# plot ground truth (manually annotated) layers
plotSpots(spe, annotate = "ground_truth",
          pal = "libd_layer_colors")
```




6.5.2 Number of expressed features

```
# histogram of numbers of expressed genes
hist(colData(spe)$detected, breaks = 20)
```

Histogram of colData(spe)\$detected




```
# plot number of expressed genes vs. number of cells per spot
plotSpotQC(spe, plot_type = "scatter",
            x_metric = "cell_count", y_metric = "detected",
            y_threshold = 400)
## `geom_smooth()` using formula = 'y ~ x'
## `stat_xsidebin()` using `bins = 30`. Pick better value with `binwidth`.
## `stat_ysidebin()` using `bins = 30`. Pick better value with `binwidth`.
```




```
# select QC threshold for number of expressed genes
qc_detected <- colData(spe)$detected < 400
table(qc_detected)
## qc_detected
## FALSE TRUE
## 3632 7

colData(spe)$qc_detected <- qc_detected
```

```
# check spatial pattern of discarded spots
plotSpotQC(spe, plot_type = "spot",
            annotate = "qc_detected")
```


```
# check spatial pattern of discarded spots if threshold is too high
qc_detected_1000 <- colData(spe)$detected < 1000
colData(spe)$qc_detected_1000 <- qc_detected_1000
plotSpotQC(spe, plot_type = "spot",
            annotate = "qc_detected_1000")
```




6.5.3 Proportion of mitochondrial reads

```
# histogram of mitochondrial read proportions  
hist(colData(spe)$subsets_mito_percent, breaks = 20)
```

Histogram of colData(spe)\$subsets_mito_percent




```
# plot mitochondrial read proportion vs. number of cells per spot
plotSpotQC(spe, plot_type = "scatter",
            x_metric = "cell_count", y_metric = "subsets_mito_percent",
            y_threshold = 28)
## `geom_smooth()` using formula = 'y ~ x'
## `stat_xsidebin()` using `bins = 30`. Pick better value with `binwidth`.
## `stat_ysidebin()` using `bins = 30`. Pick better value with `binwidth`.
```




```
# select QC threshold for mitochondrial read proportion
qc_mito <- colData(spe)$subsets_mito_percent > 28
table(qc_mito)
## qc_mito
## FALSE TRUE
## 3622 17

colData(spe)$qc_mito <- qc_mito
```

```
# check spatial pattern of discarded spots
plotSpotQC(spe, plot_type = "spot",
            annotate = "qc_mito")
```




```
# check spatial pattern of discarded spots if threshold is too high
qc_mito_25 <- colData(spe)$subsets_mito_percent > 25
colData(spe)$qc_mito_25 <- qc_mito_25
plotSpotQC(spe, plot_type = "spot",
            annotate = "qc_mito_25")
```



6.5.4 Number of cells per spot


```
# histogram of cell counts  
hist(colData(spe)$cell_count, breaks = 20)
```

Histogram of colData(spe)\$cell_count



```
# distribution of cells per spot
tbl_cells_per_spot <- table(colData(spe)$cell_count)
```


```
# plot number of expressed genes vs. number of cells per spot
plotSpotQC(spe, plot_type = "scatter",
            x_metric = "cell_count", y_metric = "detected",
            x_threshold = 10)
## `geom_smooth()` using formula = 'y ~ x'
## `stat_xsidebin()` using `bins = 30`. Pick better value with `binwidth`.
## `stat_ysidebin()` using `bins = 30`. Pick better value with `binwidth`.
```



```
# select QC threshold for number of cells per spot
qc_cell_count <- colData(spe)$cell_count > 10
table(qc_cell_count)
##   qc_cell_count
##   FALSE  TRUE
##   3549    90

colData(spe)$qc_cell_count <- qc_cell_count
```

```
# check spatial pattern of discarded spots
plotSpotQC(spe, plot_type = "spot",
            annotate = "qc_cell_count")
```

6.5.5 Remove low-quality spots


```
# number of discarded spots for each metric
apply(cbind(qc_lib_size, qc_detected, qc_mito, qc_cell_count), 2, sum)
##      qc_lib_size  qc_detected      qc_mito qc_cell_count
##              8           7          17           90

# combined set of discarded spots
discard <- qc_lib_size | qc_detected | qc_mito | qc_cell_count
table(discard)
## discard
```

```
## FALSE TRUE
## 3524 115

# store in object
colData(spe)$discard <- discard
```

```
# check spatial pattern of combined set of discarded spots
plotSpotQC(spe, plot_type = "spot",
  annotate = "discard")
```



```
# remove combined set of low-quality spots
spe <- spe[, !colData(spe)$discard]
dim(spe)
## [1] 33538 3524
```

6.6 Zero-cell and single-cell spots

```

# distribution of cells per spot
tbl_cells_per_spot[1:13]
##
##      0      1      2      3      4      5      6      7      8      9     10     11     12
##    84 211 483 623 617 541 421 287 140  92  50  25  18

# as proportions
prop_cells_per_spot <- round(tbl_cells_per_spot / sum(tbl_cells_per_spot), 2)
prop_cells_per_spot[1:13]
##
##      0      1      2      3      4      5      6      7      8      9     10     11     12
##  0.02 0.06 0.13 0.17 0.17 0.15 0.12 0.08 0.04 0.03 0.01 0.01 0.00

```

6.7 Quality control at gene level

References