

Full Rank is an Illusion: Weight Matrices in Large Language Models are Composites of Low-Dimensional Sub-Manifolds

Jin Yanyan (corresponding author), Zhao Lei

Abstract

Large language model (LLM) weight matrices often appear nearly full-rank under spectral measures, while local intrinsic-dimension estimators such as TwoNN report dimensions one to two orders of magnitude smaller. Previous work interpreted this eRank/TwoNN gap as evidence of strongly curved weight manifolds. We show that this interpretation is misleading: the ratio is primarily a proxy for the number of low-dimensional sub-manifolds concatenated into a single architectural matrix. Splitting weight matrices along known functional boundaries (attention heads, Q/K/V segments, and expert matrices) reduces the ratio by 1–2 orders of magnitude. Across Qwen3.6-27B and DeepSeek V4 Flash 280B, per-head query ratios converge to a narrow 3–9x band despite a 10x difference in parameter count, suggesting that individual attention heads have a bounded architectural complexity while scale primarily increases the number and organization of subspaces. We further identify a mid-layer head-orthogonalization window in Qwen3.6, show that deep DeltaNet value-ratio growth is better explained by increasing inter-head separation than by intra-head complexity, and observe strong geometric differentiation among deep MoE experts. These results suggest that LLM scale is organized less as a single increasingly complex manifold and more as a partitioned system of low-complexity subspaces.

1. Introduction

Recent empirical work has documented a striking discrepancy in the geometry of weight matrices in large language models (LLMs): the effective rank (eRank) of a weight matrix routinely exceeds its intrinsic dimension estimated by the Two-Nearest-Neighbor (TwoNN) method by one to two orders of magnitude. A natural interpretation of this gap is that the weight manifold has high curvature — that the rows of the matrix live on a surface that bends so aggressively that local neighborhood statistics undercount the true dimensionality. This paper argues that the curvature interpretation is wrong, or at best misleading, and proposes a simpler, empirically falsifiable alternative.

Our claim is that the eRank/TwoNN ratio is not primarily a curvature indicator. It is a proxy for the number of geometrically distinct low-dimensional sub-manifolds that have been concatenated into a single weight matrix by the architecture. When a weight matrix is split along its known functional boundaries

— attention heads, query/key/value segments — the ratio drops by one to two orders of magnitude, and the per-component ratios converge to a narrow band (3–9x) that is stable across models of vastly different size and architecture.

This reinterpretation matters because it changes what the ratio tells us about the model. A high ratio does not necessarily mean the weight geometry is complex in the differential-geometric sense. It often means the matrix is doing multiple jobs at once. Each job, examined in isolation, has much simpler geometry. The dominant complexity is organizational.

We demonstrate this through systematic splitting experiments on two architecturally distinct models: Qwen3.6-27B (27 billion parameters, dense architecture with DeltaNet/GQA hybrid attention) and DeepSeek V4 Flash (280 billion parameters, Mixture-of-Experts with 256 routed experts). Across both models, splitting weight matrices along functional boundaries consistently collapses the ratio from the 50–400x range to the 3–9x range. We further show that value projections in DeltaNet linear attention layers have per-head ratios of approximately 2x — far less complex than the composite matrix suggests — and that expert feed-forward weights in deeper layers develop internal sub-manifold structure absent in shallow layers.

2. Background

2.1 Effective Rank (eRank)

The effective rank of a matrix, introduced by Roy and Vetterli (2007), measures the “spread” of its singular value spectrum. Given a matrix $W \in \mathbb{R}^{m \times n}$ with singular values $\sigma_1 \geq \sigma_2 \geq \dots \geq \sigma_r > 0$, define the normalized distribution:

$$p_i = \frac{\sigma_i}{\sum_{j=1}^r \sigma_j}$$

The effective rank is the exponential of the Shannon entropy of this distribution:

$$\text{eRank}(W) = \exp \left(- \sum_{i=1}^r p_i \ln p_i \right)$$

When all singular values are equal, $\text{eRank}(W) = r$ (the matrix has “full” effective rank). When one singular value dominates, $\text{eRank}(W) \approx 1$. For a typical LLM weight matrix, eRank falls between these extremes and reflects how many spectral directions carry significant energy.

Crucially, eRank is a global, spectral property. It sees the matrix as a whole and is blind to whether the rows cluster into groups with different local structure.

2.2 TwoNN Intrinsic Dimension

The TwoNN estimator, introduced by Facco et al. (2017), estimates the intrinsic dimension of a point cloud from the ratio of distances to each point’s first and second nearest neighbors. For a point x_i with nearest neighbor at distance r_1 and second nearest neighbor at distance r_2 , define $\mu_i = r_2/r_1$. Under the assumption that the data lie on a d -dimensional manifold and are locally uniformly distributed, the cumulative distribution of μ follows:

$$P(\mu \leq t) = 1 - t^{-d}$$

The intrinsic dimension d is estimated by maximum likelihood from the empirical distribution of μ values across all points.

TwoNN is a local estimator. It measures geometric complexity in the immediate neighborhood of each point. If the data lie on a single smooth manifold, TwoNN recovers the manifold dimension regardless of how that manifold is embedded in ambient space. But if the data are a union of multiple manifolds with different local structure, TwoNN reports a dimension reflecting the local geometry of whichever manifold each point sits on, averaged across all points.

This paper measures the local geometry of weight-matrix row vectors, which is distinct from the intrinsic dimensionality of fine-tuning studied by Aghajanyan et al. (2021). The two notions are not numerically interchangeable, but both point to the same broad fact: the effective operational geometry of large models can be far lower-dimensional than the raw parameter space.

2.3 Why Their Ratio Does Not Measure Curvature

Consider a matrix W whose rows lie on a single smooth d -dimensional manifold. In this case, TwoNN estimates d , eRank reflects the spectral spread of the embedding, and their ratio depends on how the manifold’s principal axes distribute energy across the spectrum. High curvature could, in principle, cause TwoNN to underestimate d if neighborhoods bend enough to distort distance ratios. Under this reading, a high eRank/TwoNN ratio signals curvature.

But there is a simpler explanation for a high ratio that does not invoke curvature at all. Suppose W is constructed by vertically concatenating k blocks, each of which is a separate low-dimensional manifold with its own orientation in ambient space. TwoNN, being local, estimates the average intrinsic dimension of the individual blocks. eRank, being global, sees a matrix whose singular values reflect the superposition of k differently-oriented subspaces, yielding a much higher effective rank. The ratio scales with k — the number of sub-manifolds — not with the curvature of any one of them.

This is exactly the situation in LLM weight matrices. A query projection matrix W_Q in a multi-head attention layer is the vertical concatenation of H independent head projections. Each head maps the residual stream into its own

query subspace. These subspaces have different orientations, are trained under different gradient signals, and develop different spectral profiles. The weight matrix is not one manifold with high curvature. It is H manifolds stitched together.

The key prediction of this interpretation is falsifiable: if the ratio measures sub-manifold count, then splitting the matrix along its functional boundaries should dramatically reduce the ratio. If the ratio only measures curvature of a single continuous manifold, splitting should not systematically help — the curvature of each piece should be comparable to the curvature of the whole.

3. Experimental Setup

3.1 Models

We study two models chosen for architectural diversity:

Qwen3.6-27B is a 27-billion-parameter dense model with 64 transformer layers. It uses a hybrid attention design: layers 0, 1, and 2 use Gated DeltaNet linear attention (Yang et al., 2025), while the remaining layers use standard grouped-query attention (GQA) with 48 query heads and 8 key-value heads, each with dimension 256. In the DeltaNet layers, Q, K, and V projections are fused into a single `in_proj_qkv` matrix of shape [10240, 5120], where the first 2048 rows encode Q, the next 2048 encode K, and the final 6144 encode V (48 heads $\times$ 128 dimensions). The DeltaNet layers also contain small gating matrices `in_proj_a` (α decay gate) and `in_proj_b` (β write gate), each of shape [48, 5120].

DeepSeek V4 Flash is a 280-billion-parameter Mixture-of-Experts model with 43 transformer layers. Its attention uses Multi-head Latent Attention (MLA) with low-rank factorization: the query path factors through W_{q_a} [1024, 4096] and W_{q_b} [32768, 1024], where W_{q_b} projects into 128 heads of dimension 256. The 43 layers alternate in attention type: L00/L01 are standard MLA, even-numbered layers use CSA (compression ratio 4), and odd-numbered layers use HCA (compression ratio 128). In MLA, all heads share a low-rank representation through a 1024-dimensional bottleneck, so whole-ratio-divided-by-head-count analysis does not apply. Each MoE layer contains 256 routed experts, with individual expert feed-forward weight matrices of shape [2048, 4096] (up-projection) and [4096, 2048] (down-projection). The routing gate matrix has shape [256, 4096].

3.2 Splitting Strategy

We apply two types of splits, both following known architectural boundaries:

Head-boundary splitting. For multi-head projection matrices, we partition the row dimension into segments of size equal to the per-head dimension. For Qwen3.6 `q_proj` [12288, 5120], this yields 48 blocks of [256, 5120]. For DeepSeek

V4 `wq_b` [32768, 1024], this yields 128 blocks of [256, 1024]. For Qwen3.6 DeltaNet V segments [6144, 5120], this yields 48 blocks of [128, 5120].

Functional-segment splitting. For fused projection matrices, we split along the Q/K/V functional boundary. For Qwen3.6 DeltaNet `in_proj_qkv` [10240, 5120], this yields Q [2048, 5120], K [2048, 5120], and V [6144, 5120].

These splits are not arbitrary partitions. They follow the exact boundaries that the model’s forward pass uses to route information. Each block, after splitting, corresponds to a functionally independent computation.

3.3 Metrics

For each matrix (whole or split), we compute:

- **eRank**: effective rank from the singular value distribution.
- **TwoNN**: intrinsic dimension estimated from nearest-neighbor distance ratios, treating each row of the weight matrix as a point in the column-dimensional ambient space.
- **Ratio**: eRank / TwoNN.

3.4 Hardware

All experiments were conducted on an NVIDIA DGX Spark system with 128 GB of unified CPU-GPU memory. Code and data are open-sourced.

4. Results

4.1 Qwen3.6-27B: Query Projection Head Splitting

We selected six GQA layers spanning the full depth of the network: L03, L07, L11, L31, L47, and L63. Table 1 reports the whole-matrix ratio and the per-head statistics after splitting into 48 heads of dimension 256.

Table 1. Qwen3.6-27B `q_proj` [12288, 5120]: whole-matrix vs. per-head (48 heads, 256 dim each).

Layer	Whole	Per-Head Ratio		Orthogonality	Reduction
	Ratio	Ratio/48	(mean)	Ratio	Factor
L03	120.3x	2.5	5.5x	2.2x	22.0x
L07	442.0x	9.2	8.9x	1.0x	49.9x
L11	54.4x	1.1	6.0x	5.3x	9.1x
L31	88.8x	1.9	5.9x	3.2x	15.1x
L47	93.3x	1.9	6.1x	3.1x	15.4x
L63	96.7x	2.0	4.7x	2.3x	20.7x

Here Ratio/48 divides the whole ratio by the head count, and Orthogonality Ratio = Per-Head Ratio / (Ratio/48). We use this quantity as a coarse proxy for inter-head subspace overlap: values near 1.0 suggest nearly separated head subspaces, while higher values suggest more overlap. A strict orthogonality claim would require direct head-subspace similarity, principal-angle, or cosine-matrix analysis.

The whole-matrix ratio ranges from 54x to 442x. After splitting, the per-head mean ratio collapses to 4.7x – 8.9x. The reduction factor ranges from 9x to 50x. Despite large variation in the whole-matrix ratio across layers, the per-head ratios converge to a narrow band. Notably, L07 has an orthogonality ratio of 1.0x, suggesting nearly separated 48 head subspaces — the lowest inter-head overlap observed across all measured layers.

4.2 Qwen3.6-27B: DeltaNet in_proj_qkv Functional Splitting

The first three layers (L00, L01, L02) use DeltaNet linear attention with a fused Q/K/V projection matrix. Table 2 reports the results of splitting by functional segment and further splitting V into per-head blocks.

Table 2. Qwen3.6-27B DeltaNet in_proj_qkv [10240, 5120]: functional and head splitting.

Layer	Whole Ratio	Q Ratio (2048 rows)	K Ratio (2048 rows)	V Ratio (6144 rows)	V Per-Head Mean (48 heads, 128 dim)
L00	30.7x	14.6x	38.4x	55.7x	2.41
L01	81.6x	173.9x	94.3x	40.8x	2.17
L02	56.8x	20.6x	16.9x	44.0x	1.76

Table 2b. V-segment per-head analysis across all depths (48 heads, 128 dim each).

Layer	V eRank	V TwoNN	V Ratio	Ratio/48	Per-Head Ratio	Orthogonality Ratio
L00	4018	72	55.7x	1.16	2.41x	2.1x
L01	3902	96	40.8x	0.85	2.17x	2.6x
L02	4062	92	44.0x	0.92	1.76x	1.9x
L09	4162	97	43.0x	0.90	2.15x	2.4x
L20	4221	95	44.2x	0.92	2.08x	2.3x
L30	4074	65	62.8x	1.31	2.37x	1.8x
L46	4178	52	80.5x	1.68	2.30x	1.4x
L62	4248	42	101.7x	2.12	2.57x	1.2x

Several findings stand out. First, the whole-matrix ratios range from 31x to 82x. Second, splitting by Q/K/V functional segment reduces the ratio

substantially in most cases but does not always bring it below 20x, indicating that Q and K segments themselves contain internal sub-structure from multiple heads (particularly L01 Q at 173.9x, which contains 16 K heads with different orientations). Third, the V segment, when further split into 48 heads of 128 dimensions each, reaches per-head ratio means of 1.76x – 2.57x.

The extended depth analysis in Table 2b reveals a key pattern: per-head ratio remains stable at 2.1x – 2.6x across all depths, while whole V ratio increases from 41x to 102x in deeper layers. The conservative interpretation is that this increase is mainly driven by growing inter-head separation (orthogonality ratio drops from 2.1x to 1.2x), not by increased intra-head complexity.

4.3 DeepSeek V4 Flash: `wq_b` Head Splitting

The query projection in V4 Flash factors through a low-rank bottleneck. We analyze W_{q_b} [32768, 1024], which fans out from the bottleneck into 128 heads of 256 dimensions each. Table 3 reports results across ten layers spanning all three attention types.

Table 3. DeepSeek V4 Flash `wq_b` [32768, 1024]: whole-matrix vs. per-head (128 heads, 256 dim each).

Layer	Type	Whole eRank	Whole TwoNN	Whole Ratio	Per-Head Ratio (mean)
L00	MLA	1015	53	19.3x	5.56
L01	MLA	1004	34	29.9x	4.13
L10	CSA	1018	51	19.9x	4.60
L11	HCA	1017	81	12.6x	2.79
L20	CSA	1017	30	34.1x	6.60
L21	HCA	1017	23	45.2x	6.20
L30	CSA	1017	40	25.7x	4.51
L31	HCA	1016	56	18.0x	3.48
L41	HCA	1017	59	17.3x	2.96
L42	CSA	1016	207	4.9x	4.43

V4 Flash’s 43 layers alternate: L00/L01 are standard MLA, even layers use CSA (compression ratio 4), odd layers use HCA (compression ratio 128). Because MLA shares a low-rank representation (1024-dim bottleneck) across all heads, whole-ratio-divided-by-head-count analysis does not apply — the whole ratio reflects structure within the bottleneck space, not inter-head concatenation effects.

The per-head ratios across all attention types (MLA, CSA, HCA) range from 2.8x to 6.6x, in the same order of magnitude as the Qwen3.6 query head ratios (4.7x – 8.9x), despite the models differing by an order of magnitude in parameter count and using fundamentally different architectures. Note that Q and V

head dimensions differ (256 vs. 128), so their per-head ratios cannot be directly compared to infer differences in functional complexity.

4.4 DeepSeek V4 Flash: Expert Weight Layer-Wise Differentiation

We sampled four experts per layer across five layers and computed the eRank/TwoNN ratio for their feed-forward weight matrices (w_1 , w_2 , w_3). Table 4 reports per-layer summary statistics.

Table 4. DeepSeek V4 Flash expert FFN weight ratio statistics (4 experts $\times$ 3 matrices per layer).

Layer	Expert Ratio Mean	Expert Ratio Min	Expert Ratio Max	Expert Ratio Std
L00	14.6	7.8	21.5	4.0
L10	16.2	7.7	45.7	10.7
L20	26.7	12.2	61.4	17.1
L30	55.4	16.6	120.8	40.9
L42	34.2	9.3	113.4	30.4

Shallow layers (L00, L10) have relatively low and uniform expert ratios (mean 14.6 and 16.2, standard deviation 4.0 and 10.7). Deep layers (L30, L42) exhibit dramatically higher means (55.4, 34.2) and extreme individual values reaching 120.8 and 113.4. The standard deviation increases by a factor of 3–10 from shallow to deep layers.

4.5 Background Data: Small Functional Matrices

For completeness, we report eRank/TwoNN ratios for small functional matrices measured in prior experiments:

- **Qwen3.6 in_proj_a** (α decay gate, [48, 5120]): ratio 2.4x
- **Qwen3.6 in_proj_b** (β write gate, [48, 5120]): ratio 1.5x – 2.2x
- **DeepSeek V4 Flash gate** (MoE router, [256, 4096]): ratio 5.3x – 11.1x

The gating matrices have ratios in the low single digits (1.5x – 2.4x). However, these matrices have shape [48, 5120] — only 48 rows, i.e., 48 data points. Estimating manifold dimension from 48 points is at the measurement limit, so the near-1x ratios may reflect a measurement scale effect rather than evidence that gating is functionally simpler than content encoding. The MoE router, which must distinguish among 256 experts, has a somewhat higher ratio, consistent with the sub-manifold interpretation: each row of the router corresponds to one expert’s selection boundary.

5. Discussion

5.1 The Ratio is a Sub-Manifold Count Proxy, Not a Curvature Indicator

The central result of this paper is negative: the eRank/TwoNN ratio does not measure curvature of the weight manifold. The evidence is straightforward. If the ratio reflected curvature, splitting a matrix into pieces should not systematically reduce it, because curvature is a local property that does not vanish upon partitioning. But splitting along functional boundaries reduces the ratio by 1–2 orders of magnitude (Tables 1–3).

The ratio is better understood as a proxy for the number of geometrically distinct sub-manifolds packed into a single matrix. eRank, as a global spectral measure, grows when multiple differently-oriented subspaces contribute to the singular value distribution. TwoNN, as a local measure, reports the average local dimension, which does not grow with the number of subspaces as long as each subspace is individually low-dimensional. The gap between them therefore scales with the number of distinct subspaces — that is, with the number of functional components concatenated in the matrix.

This interpretation aligns with what we know about how these matrices are used. A query projection matrix in a 48-head attention layer is, in a precise computational sense, 48 independent linear maps stacked vertically. The architecture defines the sub-manifolds. Training shapes their internal geometry but does not erase the boundaries between them.

For standard multi-head concatenation (e.g., Qwen q_proj), comparing the whole ratio divided by head count with the per-head ratio gives a coarse proxy for inter-head overlap (Table 1). The orthogonality ratio (per-head ratio / (whole ratio / 48)) should not be treated as a direct orthogonality measurement; direct validation requires head-subspace similarity, principal-angle, or cosine-matrix analysis. Still, L07 achieves an orthogonality ratio of 1.0x, suggesting its 48 heads occupy nearly separated subspaces. Supplementary L08–L10 measurements show a small mid-layer orthogonalization window: L07, L09, and L10 exhibit large whole ratios while their per-head ratios remain normal, whereas L08 is weaker and likely transitional. This suggests that high ratio in this region reflects heads being pulled apart rather than individual heads becoming more complex. This analysis does not apply to MLA architectures (e.g., V4 Flash), where heads share a bottleneck representation by design.

5.2 Residual Complexity Per Head: An Architectural Constant

A striking empirical regularity emerges from Tables 1 and 3. After splitting, per-head ratios converge to approximately 3x – 9x across both models, despite differences in:

- Total parameter count (27B vs. 280B)
- Architecture type (dense vs. MoE)

- Attention mechanism (standard GQA vs. low-rank factored)
- Head dimension (256 in both cases, but with different input dimensions: 5120 vs. 1024)
- Training data, training recipe, and model family

This convergence suggests that the per-head ratio of 3–9x reflects a residual geometric complexity that is intrinsic to what an attention head does, rather than an artifact of any particular training run. Each head, regardless of context, develops a weight geometry that is far less complex than the composite matrix suggests, but not perfectly flat (ratio $\neq 1x$; a per-head ratio of 3–9x still indicates meaningful internal structure).

One plausible interpretation is that each head’s weight rows trace out a low-dimensional surface with a small number of internal modes — perhaps reflecting the fact that each head must encode multiple types of positional or semantic relationships within a single linear map. The ratio of 3–9x may represent an architectural “complexity budget” for a single attention head: enough structure to support several distinct functions, but far less than the full rank of the ambient space. We emphasize that this analysis demonstrates concatenation as the dominant effect; it does not prove individual sub-manifolds are flat. If this band persists across more model families, it would support a broader scaling picture: increasing scale primarily adds sub-manifolds and organizes their topology, rather than making individual heads arbitrarily more complex.

5.3 Value Heads: Concatenation is the Dominant Effect

The DeltaNet V-segment results (Tables 2 and 2b) reveal an instructive case: after splitting V into 48 heads of 128 dimensions, the per-head ratio drops to 1.76x – 2.57x. The extended depth analysis in Table 2b shows that per-head ratio remains stable at 2.1x – 2.6x across all depths, while the whole V ratio increases from 41x to 102x in deeper layers. This increase is best explained by growing inter-head separation (orthogonality ratio drops from 2.1x to 1.2x), not by increased intra-head complexity.

This finding is consistent with the computational role of value projections in linear attention. In Gated DeltaNet, the value projection produces the content that will be written into the recurrent state. Unlike query and key projections, which must encode complex relational patterns (positional encodings, attention patterns), value projections perform a relatively straightforward linear mixing of input features into a per-head value space.

However, a per-head ratio of 2x does not mean “flat.” A ratio of 1x would indicate a perfectly linear subspace; 2x still indicates some nonlinear structure within each head. What we can conclude is that concatenation is the dominant source of the whole V matrix’s high ratio, and that individual V heads are far less complex than the composite matrix suggests. Note also that Q heads have dimension 256 while V heads have dimension 128, so their per-head ratios cannot be directly compared to infer differences in functional complexity.

This also provides a geometric hypothesis for linear attention. DeltaNet uses a fixed-size recurrent state, so deeper and more abstract representations must be written into a limited per-head space. The observed pattern suggests that the model responds to this pressure by increasing separation between heads, reducing write-interference, rather than by making each value head internally more complex.

5.4 Deep Expert Sub-Manifold Differentiation

The key signal in Table 4 is not the change in mean ratio but the change in **standard deviation**. The standard deviation increases from 4.0 at L00 to 40.9 at L30 — an order of magnitude increase. This means deep-layer experts are far more heterogeneous than shallow-layer experts: some develop ratios exceeding 120x while others remain near 10x within the same layer.

From the sub-manifold concatenation perspective, deep experts with high ratios have developed multiple internal geometric partitions — they have differentiated into multiple functional sub-components within a single expert. This structural differentiation parallels the functional specialization that prior work has documented in deep MoE layers: deep experts tend to specialize for specific token types, linguistic constructions, or knowledge domains. Our results suggest that this functional specialization has a geometric signature: the weight matrix of a specialized expert literally contains multiple sub-manifolds.

The high variance across experts in the same deep layer is equally informative. Not all experts differentiate equally. Some remain geometrically simple (ratio $\approx 10x$), while others become highly structured (ratio $> 100x$). This heterogeneity is consistent with the known skew in expert utilization: a small fraction of experts handle disproportionately diverse inputs and must develop correspondingly richer internal geometry.

5.5 Implications for Fine-Tuning and Knowledge Localization

If weight matrices are composites of functionally distinct sub-manifolds, and if these sub-manifolds correspond to identifiable computational units (heads, experts, functional segments), then model editing and fine-tuning operations could in principle operate at the sub-manifold level rather than at the level of whole weight matrices.

Current parameter-efficient fine-tuning methods such as LoRA (Hu et al., 2022) apply low-rank updates to entire weight matrices. Our results suggest that this is geometrically coarse: a rank- r update to a matrix containing 48 sub-manifolds distributes its capacity across all 48, rather than concentrating on the sub-manifolds relevant to the target task. A sub-manifold-aware fine-tuning strategy would identify which heads or functional segments need modification and apply updates selectively.

Similarly, knowledge localization research has sought to identify where in a model

specific facts or capabilities reside. Our analysis suggests a more granular unit of analysis: not “which layer” or “which weight matrix,” but “which sub-manifold within which weight matrix.” The low complexity of individual value heads (ratio $\approx 2x$) suggests that value projections may be easier targets for direct knowledge editing, though their internal structure is not trivially flat.

6. Conclusion

The eRank/TwoNN ratio in LLM weight matrices does not measure what it was thought to measure. It is not primarily a curvature indicator. It is a sub-manifold count proxy — a measure of how many geometrically distinct functional components have been concatenated into a single matrix by the architecture.

This paper established this reinterpretation through splitting experiments on two models spanning an order of magnitude in parameter count. The results are consistent: splitting along architectural boundaries reduces the ratio by 1–2 orders of magnitude, and per-head ratios converge to a model-independent band of 3–9x. Value heads in linear attention have ratios of approximately 2x — far less complex than the composite matrix suggests — and the increase in whole V ratio across depth is mainly attributable to growing inter-head separation, not increased intra-head complexity. Deep experts develop internal sub-manifold structure that shallow experts lack, with standard deviation increasing by an order of magnitude from shallow to deep layers.

The apparent full rank of LLM weight matrices is an illusion produced by concatenation. Each functional component, examined individually, is a low-dimensional object with modest complexity. The engineering implication is that the matrix is not the right unit of analysis for understanding weight geometry. The sub-manifold — the head, the expert, the functional segment — is. At a higher level, LLM scale appears less like a single manifold becoming ever more complex and more like a partitioned system of low-complexity subspaces: heads provide orthogonalized partitions, experts provide functional differentiation, and intelligence emerges from their organization.

References

- Aghajanyan, A., Gupta, S., & Zettlemoyer, L. (2021). Intrinsic dimensionality explains the effectiveness of language model fine-tuning. *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics (ACL)*.
- Ansuini, A., Laio, A., Macke, J. H., & Zoccolan, D. (2019). Intrinsic dimension of data representations in deep neural networks. *Advances in Neural Information Processing Systems (NeurIPS)*, 32.

- Facco, E., d’Errico, M., Rodriguez, A., & Laio, A. (2017). Estimating the intrinsic dimension of datasets by a minimal neighborhood information. *Scientific Reports*, 7(1), 12140.
- Hu, E. J., Shen, Y., Wallis, P., Allen-Zhu, Z., Li, Y., Wang, S., Wang, L., & Chen, W. (2022). LoRA: Low-rank adaptation of large language models. *Proceedings of the International Conference on Learning Representations (ICLR)*.
- Roy, O., & Vetterli, M. (2007). The effective rank: A measure of effective dimensionality. *15th European Signal Processing Conference (EUSIPCO)*, 606–610.
- Yang, S., Wang, B., Shen, Y., Panda, R., & Kim, Y. (2025). Gated Delta Networks: Improving mamba-2 with delta rule. *Proceedings of the International Conference on Learning Representations (ICLR)*.