


BQF-038

BOOSTER MAGNET REPORT

Results	
Date	05/04/2016
Hour	14:04:41
Temperature [°C]	21.2
Number of Measurements	17
Main Coil Current [A]	(130.0097 ± 0.0005)
Trim Coil Current [A]	
Integrated Gradient [T]	(-4.82289 ± 0.00001)
Magnet Center Offset X [μm] - (< ±160.0)	(6.96 ± 0.04)
Magnet Center Offset Y [μm] - (< ±160.0)	(-33.88 ± 0.06)
Roll [mrad] - (< ±0.8)	(-3.64 ± 0.02) x E-1
Electric Parameters	
Indutance [mH]	8.237
Voltage [V]	0.481
Resistance [m Ω]	48.10
Main Coil Number of Turns	26.25



	Normalized Normal	Normalized Skew	
n	Multipoles x=17.5 mm	Multipoles	
		x=17.5 mm	
	[T.m ⁽²⁻ⁿ⁾]	[T.m ⁽²⁻ⁿ⁾]	
1 (dipole)	(3.98 ± 0.02) x E-4	(-1.936 ± 0.003) x E-3	
2 (quadrupole)	(1.000000 ± 0.000002)	(-7.28 ± 0.01) x E-4	
3 (sextupole)	(1.7 ± 0.3) x E-5	(-6.73 ± 0.03) x E-4	
4	(-3.53 ± 0.02) x E-4	(1.16 ± 0.04) x E-4	
5	(-3.3 ± 0.2) x E-5	(3.6 ± 0.2) x E-5	
6	(-1.190 ± 0.003) x E-3	(-2.0 ± 0.4) x E-5	
7	(2.6 ± 0.2) x E-5	(-2.0 ± 0.3) x E-5	
8	(1.2 ± 0.3) x E-5	(-5.5 ± 0.3) x E-5	
9	(-2 ± 3) x E-6	(1.7 ± 0.3) x E-5	
10	(1.106 ± 0.004) x E-3	(8 ± 4) x E-6	
11	(-1.5 ± 0.4) x E-5	(-2.9 ± 0.4) x E-5	
12	(-4 ± 4) x E-6	(-1.3 ± 0.3) x E-5	
13	(1.6 ± 0.6) x E-5	(1.4 ± 0.4) x E-5	
14	(-8.8 ± 0.5) x E-5	(3 ± 5) x E-6	
15	(-2.0 ± 0.4) x E-5	(-3.2 ± 50.9) x E-7	

