


BQF-018

BOOSTER MAGNET REPORT

Results		
Date	30/03/2016	
Hour	12:28:38	
Temperature [°C]	21.2	
Number of Measurements	17	
Main Coil Current [A]	(130.0175 ± 0.0003)	
Trim Coil Current [A]	(0 ± 0)	
Integrated Gradient [T]	(-4.823961 ± 0.000009)	
Magnet Center Offset X [μm] - (< ±160.0)	(-12.76 ± 0.03)	
Magnet Center Offset Y [μm] - (< ±160.0)	(-32.76 ± 0.06)	
Roll [mrad] - (< ±0.8)	(-5.75 ± 0.03) x E-1	
Electric Parameters		
Indutance [mH]	8.26	
Voltage [V]	0.487	
Resistance [m Ω]	48.70	
Main Coil Number of Turns	26.25	



n	Normalized Normal Multipoles x=17.5 mm [T.m ⁽²⁻ⁿ⁾]	Normalized Skew Multipoles x=17.5 mm [T.m ⁽²⁻ⁿ⁾]
1 (dipole)	(-7.29 ± 0.02) x E-4	(-1.872 ± 0.004) x E-3
2 (quadrupole)	(1.000000 ± 0.000002)	(-1.150 ± 0.002) x E-3
3 (sextupole)	(-8.4 ± 0.4) x E-5	(-5.95 ± 0.04) x E-4
4	(-1.5 ± 0.3) x E-5	(8.0 ± 0.4) x E-5
5	(-4.0 ± 0.3) x E-5	(-3.2 ± 0.3) x E-5
6	(-1.138 ± 0.003) x E-3	(-7 ± 3) x E-6
7	(7.1 ± 0.3) x E-5	(1.0 ± 0.4) x E-5
8	(-2.1 ± 0.3) x E-5	(-1.9 ± 0.4) x E-5
9	(-3.7 ± 0.4) x E-5	(-1.4 ± 0.6) x E-5
10	(1.135 ± 0.003) x E-3	(-2.5 ± 0.3) x E-5
11	(2.5 ± 0.5) x E-5	(-6 ± 4) x E-6
12	(-6 ± 6) x E-6	(1.6 ± 0.7) x E-5
13	(-2.8 ± 0.5) x E-5	(3 ± 4) x E-6
14	(-8.8 ± 0.4) x E-5	(-2.8 ± 0.4) x E-5
15	(9 ± 5) x E-6	(-10 ± 4) x E-6

