


BQF-014

BOOSTER MAGNET REPORT

Results		
Date	07/04/2016	
Hour	10:45:49	
Temperature [°C]	21.4	
Number of Measurements	17	
Main Coil Current [A]	(130.0035 ± 0.0005)	
Trim Coil Current [A]	(0 ± 0)	
Integrated Gradient [T]	(-4.81621 ± 0.00001)	
Magnet Center Offset X [μm] - (< ±160.0)	(3.70 ± 0.03)	
Magnet Center Offset Y [μm] - (< ±160.0)	(-17.12 ± 0.08)	
Roll [mrad] - (< ±0.8)	(-4.18 ± 0.03) x E-1	
Electric Parameters		
Indutance [mH]	8.304	
Voltage [V]	0.489	
Resistance [m Ω]	48.90	
Main Coil Number of Turns	26.25	



n	Normalized Normal Multipoles x=17.5 mm [T.m ⁽²⁻ⁿ⁾]	Normalized Skew Multipoles x=17.5 mm [T.m ⁽²⁻ⁿ⁾]	
1 (dipole)	(2.12 ± 0.02) x E-4	(-9.78 ± 0.04) x E-4	
2 (quadrupole)	(1.000000 ± 0.000003)	(-8.35 ± 0.02) x E-4	
3 (sextupole)	(-4.14 ± 0.03) x E-4	(-7.80 ± 0.04) x E-4	
4	(3.1 ± 0.2) x E-5	(7.6 ± 0.4) x E-5	
5	(-9.1 ± 0.3) x E-5	(6.3 ± 0.4) x E-5	
6	(-1.203 ± 0.004) x E-3	(4.53 ± 405.85) x E-8	
7	(6.0 ± 0.4) x E-5	(3.9 ± 42.5) x E-7	
8	(-1.8 ± 0.4) x E-5	(-2.1 ± 0.5) x E-5	
9	(-2.6 ± 0.3) x E-5	(1.4 ± 0.2) x E-5	
10	(1.104 ± 0.003) x E-3	(-1.3 ± 0.5) x E-5	
11	(8 ± 5) x E-6	(-1.2 ± 0.6) x E-5	
12	(1.7 ± 0.5) x E-5	(1.4 ± 0.4) x E-5	
13	(-1.9 ± 0.4) x E-5	(3.1 ± 0.1) x E-5	
14	(-1.14 ± 0.04) x E-4	(-1.2 ± 0.3) x E-5	
15	(-7 ± 4) x E-6	(-1.1 ± 0.3) x E-5	

