

Package ‘gEcon’

October 27, 2014

Type Package

Title General Equilibrium Economic Modelling Language and Solution Framework (gEcon)

Version 0.7.0

Date 2014-10-27

Author Grzegorz Klima, Karol Podemski, Kaja Retkiewicz-Wijtiwiak

Copyright Chancellery of the Prime Minister of the Republic of Poland

Maintainer Grzegorz Klima <gklima@users.sourceforge.net>

Description Package for developing and solving dynamic general equilibrium models

Depends R(>= 3.0.0)

Imports methods, MASS, Matrix, nleqslv, Rcpp

License_restricts_use yes

License file LICENCE

Archs i386, x64

R topics documented:

gecon-package	2
check_bk	3
compute_corr	4
compute_irf	6
find_calibr_eq	7
find_eq	8
gecon_model	8
gecon_model-class	10
gecon_parameter_info-class	12
gecon_shock_info-class	14
gecon_simulation	15
gecon_simulation-class	16
gecon_var_info-class	17
get_moments	19
get_names	20

get_parameter_vals	21
get_pert_solution	22
get_residuals	23
get_simulation_results	24
get_ss_values	25
initval_calibr_par	26
initval_var	27
load_model	27
make_model	28
parameter_info	29
plot_simulation	30
print-methods	31
random_path	32
set_free_par	33
set_shocks	34
set_shock_distr_par	35
shock_info	36
show-methods	37
simulate_model	37
solve_pert	39
steady_state	40
summary-methods	42
var_info	42

Index	45
--------------	-----------

gecon-package	<i>General Equilibrium Economic Modelling Language and Solution Framework (gEcon)</i>
---------------	---

Description

Package for developing and solving dynamic general equilibrium models.

Details

gEcon is a framework for developing and solving large scale dynamic (stochastic) & static general equilibrium models. It consists of model description language and an interface with a set of solvers in R. It was developed at the Department for Strategic Analyses at the Chancellery of the Prime Minister of the Republic of Poland as a part of a project aiming at construction of large scale DSGE & CGE models of Polish economy.

Publicly available toolboxes/toolkits used in RBC/DSGE modelling require users to derive the first order conditions and linearisation equations by pen & pencil (e.g. Uhlig's toolkit) or at least require manual derivation of the FOCs (e.g. Dynare). Derivation of FOCs is also required by GAMS and GEMPACK - probably the two most popular frameworks used in CGE modelling. Owing to the development and implementation of an algorithm for automatic derivation of first order conditions, gEcon allows users to describe their models in terms of optimisation problems of agents. To authors' best knowledge there is no other publicly available framework for writing and solving DSGE & CGE models in this natural way. Writing models in terms of optimisation problems instead of the FOCs is far more natural to an economist, takes off the burden of tedious differentiation and reduces the risk of making a mistake. gEcon allows users to focus on economic aspects of the

model and makes it possible to design large-scale (100+ variables) models. Additionally, gEcon can automatically produce a draft of LaTeX documentation for a model.

The model description language is simple and intuitive. Given optimisation problems, constraints and identities, computer derives the FOCs, steady state equations, and linearisation matrices automatically. Numerical solvers can then be employed to determine steady state and approximate equilibrium laws of motion around it.

Author(s)

Grzegorz Klima <gklima@users.sourceforge.net>
 Karol Podemski <karol.podemski@gmail.com>,
 Kaja Retkiewicz-Wijtiwiak <kaja.retkiewicz@gmail.com>
 Maintainer: Grzegorz Klima <gklima@users.sourceforge.net>

References

Cf. gEcon manual distributed with the package.

Examples

```
# copy the example model to current working directory
file.copy(from = file.path(system.file("examples", package='gEcon'),
  'rbc.gcn'), to = getwd())

# make and load model
rbc <- make_model('rbc.gcn')

# solve model
rbc <- steady_state(rbc)
rbc <- solve_pert(rbc)

# compute and print correlations
rbc <- set_shocks(rbc, shock_matrix = matrix(0.01, 1, 1), shock_order = 'epsilon_Z')
rbc <- compute_corr(rbc, ref_var = 'Y')
get_moments(rbc, moments=TRUE, correlations=TRUE,
  autocorrelations=TRUE, var_dec=TRUE)
irf_rbc <- compute_irf(rbc)
plot_simulation(irf_rbc)
summary(rbc)
```

check_bk

Blanchard Kahn conditions and eigenvalues

Description

Checks Blanchard Kahn conditions and prints information about eigenvalues.

Usage

```
check_bk(model)
```

Arguments

model an object of the gecon_model class.

Details

Eigenvalues are computed when gEcon attempts to solve the perturbation (solver uses the Lapack zgges function to compute eigenvalues). `solve_pert` must be called before the eigenvalues can be retrieved.

Author(s)

Karol Podemski <karol.podemski@gmail.com>,
Kaja Retkiewicz-Wijtiwiak <kaja.retkiewicz@gmail.com>

References

Blanchard, O., Kahn C. M. (1980), "The Solution of Linear Difference Models under Rational Expectations", *Econometrica*

Examples

```
# copy model to current working directory
file.copy(from = file.path(system.file("examples", package='gEcon'),
  'rbc.gcn'), to = getwd())
rbc <- make_model('rbc.gcn')
rbc <- steady_state(rbc)

# solve in loglinearized form
rbc <- solve_pert(rbc)
# check eigenvalues
check_bk(rbc)
```

compute_corr

Computation of correlations

Description

This function computes the statistics of the model by using spectral and simulation methods.

Usage

```
compute_corr(model, ngrid = (64 * 16), filter = TRUE,
  sim = FALSE, nrun = 1e+05, lambda = 1600,
  ref_var = NULL, n_leadlags = 6)
```

Arguments

model an object of gecon_model class.

ngrid density of grid used by the Fourier transform. It has to be a multiplicity of 8.

filter logical. If TRUE, the statistics are computed for the HP-filtered series, otherwise non-filtered series are used for the statistics computation.

sim	logical. If TRUE, simulation methods are used for correlations computations, otherwise spectral methods are used.
nrun	the number of MC simulation runs.
lambda	the lambda parameter for the HP filter.
ref_var	the name or the number of a variable in relation to which correlations are computed. When not specified, the first variable in variables list is treated as the reference value.
n_leadlags	the number of leads/lags for computing correlation tables.

Details

Cf. gEcon manual, chapter "Model analysis".

Value

An object of `gecon_model` class representing a model. Generic functions such as `print` and `summary` allow to show model elements. The `get_moments` function returns various statistics of the model (both absolute and relative).

Note

The grid has to be large enough (at least $64 * 8$) for spectral methods to converge to simulation means.

Author(s)

Karol Podemski <karol.podemski@gmail.com>,
Kaja Retkiewicz-Wijtiwiak <kaja.retkiewicz@gmail.com>

References

Hamilton. J.D. (1994), "Time Series Analysis", *Princeton University Press*

Examples

```
# copy model to current working directory
file.copy(from = file.path(system.file("examples", package='gEcon'),
  'rbc.gcn'), to = getwd())

# make and load model
rbc <- make_model('rbc.gcn')

# solve model
rbc <- steady_state(rbc)
rbc <- solve_pert(rbc)

# compute and print correlations
rbc <- set_shocks(rbc, shock_matrix = matrix(0.01, 1, 1), shock_order = 'epsilon_Z')
rbc <- compute_corr(rbc, ref_var = 'Y')
get_moments(rbc, moments=TRUE, correlations=TRUE,
  autocorrelations=TRUE, var_dec=TRUE)
```

compute_irf

*Compute impulse response functions (IRFs)***Description**

The `compute_irf` function computes the impulse response functions for the specified set of variables and shocks and returns an object of the `gecon_simulation` class.

Usage

```
compute_irf(model, shock_list = NULL, var_list = NULL,
            path_length = 40, cholesky = TRUE)
```

Arguments

<code>model</code>	an object of the <code>gecon_model</code> class.
<code>shock_list</code>	a list of shocks for which the IRFs are to be computed. If this argument is missing, the IRFs are computed for all the shocks in the model. By default, the impulse response functions are created for all the shocks in the model.
<code>var_list</code>	a list of variables, for which the impact of shocks has to be computed. By default, the impulse response functions are created for the state variables only.
<code>path_length</code>	the number of periods for which IRFs are to be computed.
<code>cholesky</code>	logical. If this option is set to <code>FALSE</code> , the function computes the IRFs based on uncorrelated shocks, otherwise the variance-covariance matrix is orthogonalized by using the Cholesky decomposition and the IRFs are computed by using this matrix.

Details

Cf. `gEcon` manual, chapter "Model analysis".

Value

The function returns an object of `gecon_simulation` class. Generic functions such as `print` and `summary` provide information about the impulse response functions. The `plot_simulation` function allows to visualize the IRFs.

Author(s)

Karol Podemski <karol.podemski@gmail.com>,
Kaja Retkiewicz-Wijtiwiak <kaja.retkiewicz@gmail.com>

Examples

```
# copy model to current working directory
file.copy(from = file.path(system.file("examples", package='gEcon'),
                                     'rbc.gcn'), to = getwd())

# make and load model
rbc <- make_model('rbc.gcn')
```

```
# solve model
rbc <- steady_state(rbc)
rbc <- solve_pert(rbc)

# compute and print correlations
rbc <- set_shocks(rbc, shock_matrix = matrix(0.01, 1, 1), shock_order = 'epsilon_Z')
irf_rbc <- compute_irf(rbc, cholesky = TRUE,
                      var_list = c('K_s', 'C', 'Z', 'I', 'Y'))

summary(irf_rbc)
plot_simulation(irf_rbc)
```

find_calibr_eq	<i>Find a calibrated equation</i>
----------------	-----------------------------------

Description

The `find_calibr_eq` function finds calibrated equations with the specified indices.

Usage

```
find_calibr_eq(model, no_eq = NULL)
```

Arguments

<code>model</code>	an object of the <code>gecon_model</code> class.
<code>no_eq</code>	a numeric variable, specifies the indices of requested equations.

Value

A character vector of requested equations.

Author(s)

Karol Podemski <karol.podemski@gmail.com>,
Kaja Retkiewicz-Wijtiwiak <kaja.retkiewicz@gmail.com>

Examples

```
# copy model to current working directory
file.copy(from = file.path(system.file("examples", package='gEcon'),
                                     'rbc.gcn'), to = getwd())

# make and load model
rbc <- make_model('rbc.gcn')
find_calibr_eq(rbc, c(1))
```

find_eq	<i>Find an equation</i>
---------	-------------------------

Description

The find_eq function finds equations with the specified indices.

Usage

```
find_eq(model, no_eq = NULL)
```

Arguments

model	an object of the gecon_model class.
no_eq	a numeric variable, specifies the indices of requested equations.

Value

A character vector of requested equations.

Author(s)

Karol Podemski <karol.podemski@gmail.com>,
Kaja Retkiewicz-Wijtiwiak <kaja.retkiewicz@gmail.com>

Examples

```
# copy model to current working directory
file.copy(from = file.path(system.file("examples", package='gEcon'),
  'rbc.gcn'), to = getwd())

# make and load model
rbc <- make_model('rbc.gcn')
find_eq(rbc, c(3, 5))
```

gecon_model	<i>Constructor of "gecon_model" class</i>
-------------	---

Description

The gecon_model function is a constructor of gecon_model class objects.

Usage

```
gecon_model(model_info, map_var, map_shocks, map_params, map_params_free,
  map_params_free_val, map_equations, map_calibr_equations,
  var_eq_map, shock_eq_map, var_ceq_map, cpar_eq_map,
  cpar_ceq_map, fpar_eq_map, fpar_ceq_map, ss_function,
  calibr_function, ss_calibr_function_jac, pert)
```


Arguments

<code>model_info</code>	a character vector of length 3, containing information about the model: the input file name, the input file path and the date of creation.
<code>map_var</code>	a character vector with the list of all the variable names.
<code>map_shocks</code>	a character vector with the list of all the shock names.
<code>map_params</code>	a character vector with the list of all the parameter names.
<code>map_params_free</code>	a character vector with the list of all the free parameter names.
<code>map_params_free_val</code>	a numeric vector with the values of the free parameter names.
<code>map_equations</code>	a character vector with model equations.
<code>map_calibr_equations</code>	a character vector with model calibrating equations.
<code>var_eq_map</code>	a sparse matrix (a <code>Matrix</code> class object) with the mapping of variables into equations.
<code>shock_eq_map</code>	a sparse matrix (a <code>Matrix</code> class object) with the mapping of shocks into equations.
<code>var_ceq_map</code>	a sparse matrix (a <code>Matrix</code> class object) with the mapping of variables into calibrating equations.
<code>cpar_eq_map</code>	a sparse matrix (a <code>Matrix</code> class object) with the mapping of calibrated parameters into equations.
<code>cpar_ceq_map</code>	a sparse matrix (a <code>Matrix</code> class object) with the mapping of calibrated parameters into calibrating equations.
<code>fpar_eq_map</code>	a sparse matrix (a <code>Matrix</code> class object) with the mapping of free parameters into equations.
<code>fpar_ceq_map</code>	a sparse matrix (a <code>Matrix</code> class object) with the mapping of free parameters into calibrating equations.
<code>ss_function</code>	a function defining the steady state (equilibrium for the static models).
<code>calibr_function</code>	a function used for the calibration of parameters.
<code>ss_calibr_function_jac</code>	a function returning a Jacobian of functions defining the steady state (equilibrium for steady state models) and calibration equations.
<code>pert</code>	a function returning a list with the matrices representing canonical form of the model.

Value

An object of the `gecon_model` class.

Note

The `gecon_model` constructor is used in R files created by `gEcon`.

Author(s)

Karol Podemski <karol.podemski@gmail.com>,
Kaja Retkiewicz-Wijtiwiak <kaja.retkiewicz@gmail.com>

gecon_model-class	Class "gecon_model"
-------------------	---------------------

Description

The class for storing models.

Objects from the Class

Objects can be created by calling `new("gecon_model", ...)` or preferably using [gecon_model](#) constructor.

Slots

model_info: a character vector of length 3, containing information about the model: the input file name, the input file path and the date of creation.

map_params: a character vector with the list of all parameter names.

map_params_free: a character vector with the list of free parameter names.

map_free_into_params: a numeric vector with the mapping of free parameters into parameters indices.

map_params_free_mod_flag: a logical vector with flags denoting if particular free parameter has been modified with respect to the .gcn file calibration

map_params_calibr: a character vector with the names of calibrated parameters.

map_params_calibr_mod_flag: a logical vector with the flags denoting if any non-default value has been given for the calibrated parameter.

map_calibr_into_params: a numeric vector with the mapping of free parameters into parameters indices.

map_var: a character vector with the names of variables.

map_shocks: a character vector with the names of shocks.

map_equations: a character vector with the names of equations.

map_calibr_equations: a character vector with the names of calibrating equations.

var_eq_map: a sparse matrix (a *Matrix* class object) with the mapping of variables into equations.

shock_eq_map: a sparse matrix (a *Matrix* class object) with the mapping of shocks into equations.

var_ceq_map: a sparse matrix (a *Matrix* class object) with the mapping of variables into calibrating equations.

cpar_eq_map: a sparse matrix (a *Matrix* class object) with the mapping of calibrated parameters into equations.

cpar_ceq_map: a sparse matrix (a *Matrix* class object) with the mapping of calibrated parameters into calibrating equations.

fpar_eq_map: a sparse matrix (a *Matrix* class object) with the mapping of free parameters into equations.

fpar_ceq_map: a sparse matrix (a *Matrix* class object) with the mapping of free parameters into calibrating equations.

init_calib_pars_supplied: logical. It informs if calibrated parameters values have been supplied.

init_vals_supplied: logical. It informs if values of variables have been supplied.
loglin: logical. It informs if the model has to be loglinearized. The default value is TRUE.
loglin_var: logical. Flags are set to TRUE for loglinearized variables.
re_solved: logical. It is set to TRUE if the model has been solved. The default value is FALSE.
corr_computed: logical. If TRUE, indicates that the correlations and other statistics of variables have been computed. The default value is FALSE.
is_stochastic: logical. If TRUE, the model has stochastic shocks.
is_dynamic: logical. If TRUE, the model has any lead or lagged variables.
is_calibrated: logical. If TRUE, the model takes into account calibrating equations when solving for the steady state for a dynamic model (equilibrium in case of static model).
map_params_free_init_val: a vector of free parameters values which have been declared in .gcn file.
map_params_free_val: a vector of current free parameter values.
map_params_calibr_val: a vector of current values of calibrated parameters.
params: a vector of the model parameters.
steady: a vector of the steady state values of variables for dynamic models or equilibrium for static models.
ss_function: a function defining the steady state (equilibrium for static models).
ss_function_jac: a function computing the Jacobian of steady state function (equilibrium for static models).
ss_calibr_function_jac: a function computing the Jacobian of both steady state (equilibrium) and calibrating functions.
calibr_function: calibrating functions
init_residual_vector: a numeric vector of residuals of the steady state (equilibrium) function computed for initial values and calibrating parameters.
residual_vector: a numeric vector of residuals of the steady state (equilibrium) function computed for the values of variables and calibrating parameters after the nonlinear solver has exited.
solver_status: a character describing the steady state (equilibrium) solver status.
ss_solved: logical. If TRUE, steady state (equilibrium for static models) has been found.
pert: functions defining perturbation of first order (returning a list of matrices).
eig_vals: a matrix of system eigenvalues.
solution: a list with elements P, Q, R, S storing solution of the model.
state_var_indices: a numeric vector containing the indices of state variables.
solver_exit_info: a character containing information about perturbation solver exit information.
solution_resid: residuals of checking equations, verifying if the model has been solved.
active_shocks: a logical vector with the length equal to the number of shocks. If entry is set to FALSE, the shock is not taken into account while performing stochastic simulations of the model.
shock_mat: a variance-covariance matrix of model shocks.
shock_mat_flag: logical. Set to TRUE when the user defines non-default entries in variance-covariance matrix for shocks.
corr_mat: a matrix of the model variables correlations.

autocorr_mat: a matrix of the model variables autocorrelations.

corr_variable_mat: a matrix of correlations of variables with the reference variable lead and lagged values.

var_position: a numeric value indicating position of reference variable for the computation of statistics.

var_dec: a matrix of variance decomposition of shocks.

sdev: a vector of standard deviations of variables.

Methods

print signature(x = "gecon_model"): prints information about the model solution status.

show signature(object = "gecon_model"): prints short information about the model solution status.

summary signature(object = "gecon_model"): prints detailed results of the model.

Author(s)

Karol Podemski <karol.podemski@gmail.com>,
Kaja Retkiewicz-Wijtiwiak <kaja.retkiewicz@gmail.com>

Examples

```
# copy model to current working directory
file.copy(from = file.path(system.file("examples", package='gEcon'),
  'rbc.gcn'), to = getwd())

# make and load model
rbc <- make_model('rbc.gcn')
print(rbc)
class(rbc)
```

```
gecon_parameter_info-class
```

```
Class "gecon_parameter_info"
```

Description

The class storing information about specified parameters.

Objects from the Class

Objects of this class are created when calling the [parameter_info](#) function.

Slots

model_info: a character vector of length 3, containing information about the model: the input file name, the input file path and the date of creation.

model_variable_name: a character denoting the name of variable storing model for which the information about parameters has been created.

par_names: a character vector of the parameter names.

gcn_values: a numeric vector with the values of free parameters specified in the .gcn file.

current_values: a numeric vector with the most recent values of the parameters.

calibr_flag: a logical vector with the length equal to the number of the parameters. The TRUE entries denote that a corresponding parameter is a calibrated parameter.

incid_mat: a Matrix object with the mapping of parameters into equations and calibrating equations.

Methods

print signature(x = "gecon_parameter_info"): Prints all the available information (short listing, values, type, incidence) about the parameters, retrieved from the model when creating a gecon_parameter_info-class object.

show signature(object = "gecon_parameter_info"): Prints information about parameters' types, values, and the incidence matrix.

summary signature(object = "gecon_parameter_info"): Prints all the available information (short listing, values, type, incidence) about the parameters, retrieved from the model when creating a gecon_parameter_info-class object.

Author(s)

Karol Podemski <karol.podemski@gmail.com>,
Kaja Retkiewicz-Wijtiwiak <kaja.retkiewicz@gmail.com>

See Also

[parameter_info](#) to create a gecon_parameter_info object. The analogous classes for information about shocks and variables are [gecon_shock_info-class](#) and [gecon_var_info-class](#).

Examples

```
# copy model to current working directory
file.copy(from = file.path(system.file("examples", package='gEcon'),
  'rbc.gcn'), to = getwd())

# make and load model
rbc <- make_model('rbc.gcn')

# compute steady state and calibrate alpha
rbc <- steady_state(rbc)
rbc <- solve_pert(rbc)
rbc <- set_shocks(rbc, shock_matrix = matrix(0.01, 1, 1), shock_order = 'epsilon_Z')
rbc <- compute_corr(rbc, ref_var='Y')
rbc_par_info <- parameter_info(rbc, all_parameters = TRUE)
print(rbc_par_info)
summary(rbc_par_info)
show(rbc_par_info)
```

gecon_shock_info-class

Class "gecon_shock_info"

Description

The class storing information about specified shocks of a relevant model.

Objects from the Class

Objects of this class are created when calling the [shock_info](#) function.

Slots

model_info: a character vector of length 3, containing information about the relevant model: the input file name, the input file path and the date of creation.

model_variable_name: a character denoting the name of variable storing model for which the simulations have been created.

shock_names: a character vector of the shock names.

shock_matrix: a matrix object with a variance-covariance matrix of specified shocks and all the model shocks.

shock_matrix_flag: logical. Set to TRUE when the user defines non-default entries in variance-covariance matrix for shocks.

incid_mat: a Matrix object with the mapping of shocks into equations.

Methods

print signature(x = "gecon_shock_info"): Prints all the available information (the incidence matrix, the variance-covariance matrix) about the shocks.

show signature(object = "gecon_shock_info"): Prints the incidence matrix and the variance-covariance matrix of shocks specified when creating a gecon_shock_info object.

summary signature(object = "gecon_shock_info"): Prints all the available information (the incidence matrix, the variance-covariance matrix) about the shocks.

Author(s)

Karol Podemski <karol.podemski@gmail.com>,
Kaja Retkiewicz-Wijtiwiak <kaja.retkiewicz@gmail.com>

See Also

[shock_info](#) to create a gecon_shock_info object. The analogous classes for information about variables and parameters are [gecon_var_info-class](#) and [gecon_parameter_info-class](#).

Examples

```
# copy model to current working directory
file.copy(from = file.path(system.file("examples", package='gEcon'),
  'rbc.gcn'), to = getwd())

# make and load model
rbc <- make_model('rbc.gcn')

# compute steady state and calibrate alpha
rbc <- steady_state(rbc)
rbc <- solve_pert(rbc)
rbc <- set_shocks(rbc, shock_matrix = matrix(0.01, 1, 1), shock_order = 'epsilon_Z')
rbc <- compute_corr(rbc, ref_var='Y')

# display info about the shocks
rbc_shock_info <- shock_info(rbc, all_shocks = TRUE)
print(rbc_shock_info)
summary(rbc_shock_info)
show(rbc_shock_info)
```

gecon_simulation

*Constructor for "gecon_simulation" class object***Description**

This function creates an object of gecon_simulation class.

Usage

```
gecon_simulation(sim, shock_list, var_list, sim_type, time_n, model_info, model_variable_name)
```

Arguments

sim	the array of simulation results (three dimensional when the impulse response functions have been computed for more than one shock).
shock_list	a list of shocks for which the simulations have been computed.
var_list	a list of variables used.
sim_type	a type of simulation.
time_n	the number of periods for which the simulation has been performed.
model_info	a character vector of length 3, containing information about the model: the input file name, the input file path, and the date of creation.
model_variable_name	a string denoting the name of the model for which the simulation has been performed.

Value

An object of the gecon_simulation class.

Author(s)

Karol Podemski <karol.podemski@gmail.com>,
Kaja Retkiewicz-Wijtiwiak <kaja.retkiewicz@gmail.com>

```
gecon_simulation-class
      Class "gecon_simulation"
```

Description

The class storing simulation results.

Objects from the Class

Objects can be created by calling the `new("gecon_simulation", ...)` form or (preferably) using `gecon_simulation` constructor.

Slots

sim: a three-dimensional array with impulse response functions (the dimensions are variables, time, shocks) or two-dimensional array when storing the results of user defined path of shocks or random path of shocks.

shock_list: a vector of shocks for which simulations have been computed.

var_list: a vector of names of simulated variables.

sim_type: a type of simulation.

time_n: the number of simulation periods.

model_info: a character vector of length 3, containing information about the model: the input file name, the input file path and the date of creation.

model_variable_name: a character denoting the name of variable storing model for which the simulations have been created.

Methods

print signature(`x = "gecon_simulation"`): prints diagnostic information about the simulation performed.

show signature(`object = "gecon_simulation"`): prints short information about the simulation.

summary signature(`object = "gecon_simulation"`): prints and returns the simulation results in the form of list.

Author(s)

Karol Podemski <karol.podemski@gmail.com>,
Kaja Retkiewicz-Wijtiwiak <kaja.retkiewicz@gmail.com>

See Also

`get_simulation_results` to retrieve the simulated series from `sim` slot.

Examples

```
# copy model to current working directory
file.copy(from = file.path(system.file("examples", package='gEcon'),
  'rbc.gcn'), to = getwd())

# make and load model
rbc <- make_model('rbc.gcn')

# solve model
rbc <- steady_state(rbc)
rbc <- solve_pert(rbc)

# compute and print correlations
rbc <- set_shocks(rbc, shock_matrix = matrix(0.01, 1, 1), shock_order = 'epsilon_Z')
irf_rbc <- compute_irf(rbc)
summary(irf_rbc)
class(irf_rbc)
```

```
gecon_var_info-class  Class "gecon_var_info"
```

Description

The class storing information about specified variables of a relevant model.

Objects from the Class

Objects of this class are created when calling the `var_info` function.

Slots

model_info: a character vector of length 3, containing information about the model: the input file name, the input file path and the date of creation.

model_variable_name: a character denoting the name of variable storing model for which the simulations have been created.

var_names: a character vector of the variable names.

is_stochastic: logical. If TRUE, the model, based on which the info was generated, has stochastic shocks.

is_dynamic: logical. If TRUE, the model, based on which the info was generated, has any lead or lagged variables.

ss_solved: logical. If TRUE, steady state for the variables (equilibrium for static models) has been found.

re_solved: logical. It is set to TRUE if the model, based on which the info was generated, has been solved. The default value is FALSE.

corr_computed: logical. If TRUE, indicates that the correlations and other statistics of variables have been computed. The default value is FALSE.

ss_val: a vector of the steady state values of variables for dynamic models or equilibrium for static models. If the steady state has not been computed when the object was generated, this slot contains initial values of variables.

state: logical. IF TRUE, indicates that the corresponding variable is a state variable.

imp_s: a matrix with the impact of state variables values in the previous period on the specified variable values.

imp_exo: a matrix with the impact of exogenous shock values on the variables values.

std_dev_val: a numeric vector of standard deviations of variables.

loglin_flag: a logical vector with the length equal to the number of the variables. The TRUE entries denote that a corresponding variable has been loglinearised before solving the model.

cr: a matrix with correlations of the variables with all the model variables.

incid_mat: a Matrix object with the mapping of variables into equations and calibrating equations.

Methods

print signature(x = "gecon_var_info"): Prints all the available information (short listing, values, statistics, incidence) about the variables, retrived from the model when creating a gecon_var_info-class object.

show signature(object = "gecon_var_info"): Prints information about variables incidence and the results already obtained for the variables.

summary signature(object = "gecon_var_info"): Prints all the available information (short listing, values, statistics, incidence) about the variables, retrived from the model when creating a gecon_var_info-class object.

Author(s)

Karol Podemski <karol.podemski@gmail.com>,
Kaja Retkiewicz-Wijtiwiak <kaja.retkiewicz@gmail.com>

See Also

[var_info](#) to create a gecon_var_info object. The analogous classes for information about shocks and parameters are [gecon_shock_info-class](#) and [gecon_parameter_info-class](#).

Examples

```
# copy model to current working directory
file.copy(from = file.path(system.file("examples", package='gEcon'),
  'rbc.gcn'), to = getwd())

# make and load model
rbc <- make_model('rbc.gcn')

# compute steady state and calibrate alpha
rbc <- steady_state(rbc)
rbc <- solve_pert(rbc)
rbc <- set_shocks(rbc, shock_matrix = matrix(0.01, 1, 1), shock_order = 'epsilon_Z')
rbc <- compute_corr(rbc, ref_var='Y')
rbc_var_info <- var_info(rbc, all_variables = TRUE)
print(rbc_var_info)
summary(rbc_var_info)
show(rbc_var_info)
```

get_moments	<i>The statistics of model</i>
-------------	--------------------------------

Description

The `get_moments` function prints and returns the statistics of the model (absolute and relative to the reference variable).

Usage

```
get_moments(model, var_names, relative_to = FALSE, moments = TRUE,
             correlations = TRUE, autocorrelations = TRUE, var_dec = TRUE,
             to_tex = FALSE)
```

Arguments

<code>model</code>	an object of the <code>gecon_model</code> class.
<code>var_names</code>	the names of the variables of interest.
<code>relative_to</code>	logical. The default value is <code>FALSE</code> . If <code>TRUE</code> , the function returns moments relative to one of the variables in accordance with relevant options chosen in the compute_corr (then only 'moments' and 'correlations' are active options).
<code>moments</code>	logical. If <code>TRUE</code> , the moments of variables: steady state values, standard deviations and variances are returned with the information about which variables have been loglinearized. If 'relative_to' is set to <code>TRUE</code> then the moments and steady state values relative to the reference variable are returned.
<code>correlations</code>	logical. The default value is <code>TRUE</code> . If <code>TRUE</code> , a correlation matrix is returned. If <code>relative_to</code> is set to <code>TRUE</code> , then the correlations of variables with lagged and leading values of a chosen variable are returned.
<code>autocorrelations</code>	logical. The default value is <code>TRUE</code> . If <code>TRUE</code> then the autocorrelations of variables are returned. If the <code>relative_to</code> is set to <code>TRUE</code> , this option is inactive.
<code>var_dec</code>	logical. The default value is <code>TRUE</code> . If <code>TRUE</code> then the variance decomposition (of shocks) is returned. If the <code>relative_to</code> is set to <code>TRUE</code> , the option is inactive.
<code>to_tex</code>	logical. The default value is <code>FALSE</code> . If <code>TRUE</code> , the output is written to a .tex file.

Value

The function returns a list of absolute or relative moments of variables depending on the value of the `relative_to` argument.

When the `relative_to` is set to `FALSE`, the list may consist of the following elements:

- `moments` - means, standard deviations, and variances of variables,
- `correlation_matrix` - a matrix of correlation of variables,
- `autocorrelations` - a matrix of correlation of variables with their own lagged values (autocorrelations),
- `variance_decomposition` - the variance decomposition, describing the amount of variable variability that can be ascribed to each of shocks.

When the `relative_to` is set to `TRUE`, the list may consist of two elements:

- `relative_moments` - means, standard deviations and variance of variables with respect to reference variable specified in the `compute_corr` function,
- `correlations_variable` - a matrix of correlation of variables with lead and lagged values of a reference variable (usually GDP).

Author(s)

Karol Podemski <karol.podemski@gmail.com>,
Kaja Retkiewicz-Wijtiwiak <kaja.retkiewicz@gmail.com>

See Also

the `compute_corr` function to see how the statistics are computed.

Examples

```
# copy model to current working directory
file.copy(from = file.path(system.file("examples", package='gEcon'),
  'rbc.gcn'), to = getwd())

# make and load model
rbc <- make_model('rbc.gcn')

# compute steady state and calibrate alpha
rbc <- steady_state(rbc)
rbc <- solve_pert(rbc)
rbc <- set_shocks(rbc, shock_matrix = matrix(0.01, 1, 1), shock_order = 'epsilon_Z')
rbc <- compute_corr(rbc, ref_var='Y')
get_moments(model = rbc, relative_to = FALSE, moments = TRUE, correlations = TRUE,
  autocorrelations = TRUE, var_dec = TRUE)
get_moments(model = rbc, relative_to = TRUE, moments = TRUE, correlations = TRUE)
```

get_names

Accessing names used by gecon_model class objects

Description

The `get_free_parameter_names`, `get_shock_names`, and `get_var_names` functions allow to retrieve names of free parameters, shocks, and variables from `gecon_model` class objects.

Usage

```
get_free_parameter_names(model)

get_shock_names(model)

get_var_names(model)
```

Arguments

`model` an object of class `gecon_model`

Value

Each of these function returns vector of characters respectively with: free parameter, shock, and variable names used in the specified object of `gecon_model` class.

Examples

```
file.copy(from = file.path(system.file("examples", package='gEcon'),
  'rbc.gcn'), to = getwd())

# make and load model
rbc <- make_model('rbc.gcn')

# names of free parameters
get_free_parameter_names(rbc)
# names of shocks
get_shock_names(rbc)
# names of variables
get_var_names(rbc)
```

get_parameter_vals	<i>Parameters of the model</i>
--------------------	--------------------------------

Description

The `get_parameter_vals` function prints and returns the values of parameters.

Usage

```
get_parameter_vals(model, var_names, to_tex)
```

Arguments

<code>model</code>	an object of the <code>gecon_model</code> class.
<code>var_names</code>	a list of requested parameters names.
<code>to_tex</code>	logical. The default value is FALSE. If TRUE, the output is written to a .tex file.

Value

This function returns both free and calibrated parameter values.

Author(s)

Karol Podemski <karol.podemski@gmail.com>,
Kaja Retkiewicz-Wijtiwiak <kaja.retkiewicz@gmail.com>

Examples

```
# copy model to current working directory
file.copy(from = file.path(system.file("examples", package='gEcon'),
  'rbc.gcn'), to = getwd())

# make and load model
rbc <- make_model('rbc.gcn')

# solve model
rbc <- steady_state(rbc)
get_parameter_vals(rbc)
```

get_pert_solution	<i>Recursive laws of motion for the model variables</i>
-------------------	---

Description

The `get_pert_solution` function prints and returns the recursive laws of motion for the model's variables.

Usage

```
# getting recursive laws of motion
get_pert_solution(model, to_tex = FALSE)
```

Arguments

<code>model</code>	an object of the <code>gecon_model</code> class.
<code>to_tex</code>	logical. The default value is <code>FALSE</code> . If <code>TRUE</code> , the output is written to a <code>.tex</code> file.

Value

A list with P, Q, R, S elements. P and Q matrices denote the impact of lagged state variables and current values of shocks variables on current values of state variables. R and S matrices denote the impact of lagged state variables and current values of shocks variables on current values of non-state variables.

Author(s)

Karol Podemski <karol.podemski@gmail.com>,
Kaja Retkiewicz-Wijtiwiak <kaja.retkiewicz@gmail.com>

See Also

[solve_pert](#) for the description of solution procedure and description of output.

Examples

```
# prepare perturbation
file.copy(from = file.path(system.file("examples", package='gEcon'),
    'rbc.gcn'), to = getwd())
rbc <- make_model('rbc.gcn')
rbc <- steady_state(rbc)

# solve in loglinearized form
rbc <- solve_pert(rbc)
get_pert_solution(rbc)
```

get_residuals

*Retriving residuals***Description**

The `get_residuals` function allows to check the residuals of the steady state equations (equations characterizing equilibrium in case of static models) and identify equations with the highest errors. This information may help to assign better initial values to variables when the solver cannot find the steady state (equilibrium).

Usage

```
get_residuals(model, highest = 5)
```

Arguments

<code>model</code>	an object of the <code>gecon</code> class.
<code>highest</code>	the number of equations with the highest error to be printed.

Value

This function returns a list with the `initial` and `final` elements. The initial residuals are residuals computed using the initial values. The final residuals are residuals computed after the solver has exited. The function prints the indices of equations with the highest initial and final errors. The equations can be investigated by using the [find_eq](#) function.

Author(s)

Karol Podemski <karol.podemski@gmail.com>,
Kaja Retkiewicz-Wijtiwiak <kaja.retkiewicz@gmail.com>

Examples

```
file.copy(from = file.path(system.file("examples", package='gEcon'),
    'rbc.gcn'), to = getwd())
rbc <- make_model('rbc.gcn')
# we deliberately give an initial value extremely far from the solution
rbc <- initval_var(rbc, list(Y=10000))
rbc <- steady_state(rbc, use_jac=TRUE,
    options_list=list(method='Newton',
        global='gline',
```

```

max_iter = 300,
tol = 1e-7))

get_residuals(rbc)
# residuals are much closer to zero then during initial evaluation.
# One can infer that to solve model with this starting value more iterations
# or change of global search strategy are necessary.
# One can also change starting value of variables in equations 4, 11 and 13.
rbc <- initval_var(rbc, list(Y=1000))
rbc <- steady_state(rbc, use_jac=TRUE,
                    options_list=list(method='Newton',
                                      global='qline',
                                      max_iter = 500,
                                      tol = 1e-7))

get_residuals(rbc)

```

get_simulation_results

Retrive series of simulated variables

Description

The `get_simulation_results` function retrives the series of simulated variables from an object of the `gecon_simulation` class.

Usage

```
get_simulation_results(sim_obj)
```

Arguments

`sim_obj` An object of the `gecon_simulation` class.

Value

The results are returned as one element list when the simulation has been invoked by the `random_path` or `simulate_model` functions or a list of more elements corresponding to the number of shocks when the simulation has been performed with the `compute_irf` function.

Author(s)

Karol Podemski <karol.podemski@gmail.com>,
Kaja Retkiewicz-Wijtiwiak <kaja.retkiewicz@gmail.com>

Examples

```

# copy model to current working directory
file.copy(from = file.path(system.file("examples", package='gEcon'),
                                     'rbc.gcn'), to = getwd())

# make and load model
rbc <- make_model('rbc.gcn')

# solve model
rbc <- steady_state(rbc)

```



```

rbc <- solve_pert(rbc)

# compute and print correlations
rbc <- set_shocks(rbc, shock_matrix = matrix(0.01, 1, 1), shock_order = 'epsilon_Z')
irf_rbc <- compute_irf(rbc, cholesky = TRUE,
                      var_list = c('K_s', 'C', 'Z', 'I', 'Y'))
get_simulation_results(irf_rbc)

```

get_ss_values	<i>Return steady state (equilibrium) values</i>
---------------	---

Description

The `get_ss_values` function returns (and prints) the steady state of the model for dynamic models (equilibrium for static models).

Usage

```
get_ss_values(model, var_names, to_tex = FALSE)
```

Arguments

<code>model</code>	an object of the <code>gecon_model</code> class.
<code>var_names</code>	the names or the indices of the variables, whose steady state values (equilibrium values) are to be returned. The default option is a vector containing all the variable names.
<code>to_tex</code>	logical. The default value is <code>FALSE</code> . If <code>TRUE</code> , the output is written to a <code>.tex</code> file.

Value

A numeric vector with the steady state (equilibrium for static models).

Author(s)

Karol Podemski <karol.podemski@gmail.com>,
Kaja Retkiewicz-Wijtiwiak <kaja.retkiewicz@gmail.com>

Examples

```

# copy model to current working directory
file.copy(from = file.path(system.file("examples", package='gEcon'),
                                     'rbc.gcn'), to = getwd())

# make and load model
rbc <- make_model('rbc.gcn')

# solve model
rbc <- steady_state(rbc)
get_ss_values(rbc)
get_ss_values(rbc, var_names=c('K_s', 'L_s'))

```

initval_calibr_par	<i>Setting initial values of calibrated parameters</i>
--------------------	--

Description

This function enables setting the initial values of calibrated parameters for the nonlinear solver searching for the steady state of dynamic models (equilibrium for static models) and the values of calibrated parameters. If not set by this function, the default values of parameters are assumed to be 0.5.

Usage

```
initval_calibr_par(model, calibr_par)
```

Arguments

model	an object of the <code>gecon_model</code> class.
calibr_par	a named list or a vector of parameters.

Details

The values of parameters passed to the `gecon_model` are treated as initial values for the steady state solver when the user specifies calibrating equations in a `.gcn` file and requests that `steady_state` function shall use it. If the calibration is omitted, the initial values of calibrated parameters are treated as their final values, so one has to specify the right set of calibrated parameters values when decides to omit the calibrating equations.

Value

An object of the `gecon_model` class representing the model. Generic functions such as `print` and `summary` allow to show the model's elements. The `get_parameter_vals` function return parameter values.

Author(s)

Karol Podemski <karol.podemski@gmail.com>,
Kaja Retkiewicz-Wijtiwiak <kaja.retkiewicz@gmail.com>

Examples

```
file.copy(from = file.path(system.file("examples", package='gEcon'),
  'rbc.gcn'), to = getwd())

# make and load model
rbc <- make_model('rbc.gcn')
rbc <- initval_calibr_par(rbc, calibr_par=list(alpha = 0.4))
rbc <- steady_state(rbc, use_jac=TRUE,
  options_list=list(method='Broyden', global='gline',
    max_iter = 300, tol = 1e-7))

get_parameter_vals(rbc, c('alpha'))
```

initval_var	<i>Setting initial values of variables.</i>
-------------	---

Description

The `initval_var` function sets the initial values of the model's variables to values specified by the user. The initial values close to solution will help the nonlinear equations solver to find the solution.

Usage

```
initval_var(model, init_var)
```

Arguments

<code>model</code>	an object of the <code>gecon_model</code> class.
<code>init_var</code>	a named list or vector of the initial values of variables.

Value

An object of the `gecon_model` class representing the model. Generic functions such as `print` and `summary` allow to show model elements. The [get_ss_values](#) function returns the steady state (equilibrium) values of the model variables.

Author(s)

Karol Podemski <karol.podemski@gmail.com>,
Kaja Retkiewicz-Wijtiwiak <kaja.retkiewicz@gmail.com>

Examples

```
file.copy(from = file.path(system.file("examples", package='gEcon'),
  'rbc.gcn'), to = getwd())
rbc <- make_model('rbc.gcn')
rbc <- initval_var(rbc, list(K_s = 10, C = 2, I = 0.5, Y = 2.5))
rbc <- initval_var(rbc, c(pi=0))
```

load_model	<i>Load model from R file</i>
------------	-------------------------------

Description

The `load_model` function loads the already generated R file with the model and creates an object of the `gecon_model` class.

Usage

```
load_model(model_file)
```

Arguments

`model_file` the name of the .R file containing the model's functions and variables. It can be a name of file or a name of file ending with a .model.R extension.

Details

The R file with the model specification has to be created first. It can be done by using the `make_model` command and the `gcn` file model specification or manually.

Value

An object of the `gecon_model` class representing the model. Generic functions such as `print` and `summary` allow to show the model's elements.

Author(s)

Karol Podemski <karol.podemski@gmail.com>,
Kaja Retkiewicz-Wijtiwiak <kaja.retkiewicz@gmail.com>

See Also

the [make_model](#) function in order to create an R file with the model elements based on the model specification.

Examples

```
# copy model to current working directory
file.copy(from = file.path(system.file("examples", package='gEcon'),
  'rbc.gcn'), to = getwd())

# make and load model
rbc <- make_model('rbc.gcn')
rbc2 <- load_model('rbc.model.R')
print(rbc2)
```

make_model

Make model from .gcn file

Description

This function calls the dynamic library, parses the .gcn model file, generates an R file, and loads it into a `gecon_model` class object.

Usage

```
make_model(model_file)
```

Arguments

`model_file` the name of the .gcn file containing model formulation. It must be ended with a .gcn extension.

Details

Cf. gEcon manual, chapters "Model description language" and "Derivation of First Order Conditions".

Value

An object of the `gecon_model` class representing the model. Generic functions such as `print` and `summary` allow to show the model elements.

Note

When the function is called, an R file with the same name as the `.gcn` file is created in the `.gcn` file directory. Additional files such as a Latex documentation or a log may be created when such an option is set to `TRUE` in the `.gcn` file.

Author(s)

Grzegorz Klima <gklima@users.sourceforge.net>
 Karol Podemski <karol.podemski@gmail.com>
 Kaja Retkiewicz-Wijtiwiak <kaja.retkiewicz@gmail.com>

See Also

the [load_model](#) function to load already created R file with model.

Examples

```
# copy model to current working directory
file.copy(from = file.path(system.file("examples", package='gEcon'),
  'rbc.gcn'), to = getwd())

# make and load model
rbc <- make_model('rbc.gcn')
print(rbc)
```

parameter_info

Information about parameters

Description

The `parameter_info` function allows to create an object of class `gecon_parameter_info`, containing information about the specified parameters of the chosen model. It allows to check type and value of a given set of parameters, and in which equation these parameters appear.

Usage

```
parameter_info(model, par_names = NULL, all_parameters = FALSE)
```

Arguments

`model` an object of the `gecon_model` class.

`par_names` the names of the parameters of interest.

`all_parameters` the logical value. If set to `TRUE`, the `par_names` argument is overwritten with a vector of all parameters appearing in the model. The default value is `FALSE`.

Details

If the function result is not assigned to any variable, the information about the requested parameters is printed in the console.

Value

An object of `gecon_parameter_info-class` class.

Author(s)

Karol Podemski <karol.podemski@gmail.com>,
Kaja Retkiewicz-Wijtiwiak <kaja.retkiewicz@gmail.com>

See Also

[shock_info](#) for information about the shocks and [var_info](#) for information about the variables.

Examples

```
# copy model to current working directory
file.copy(from = file.path(system.file("examples", package='gEcon'),
  'rbc.gcn'), to = getwd())

# make and load model
rbc <- make_model('rbc.gcn')

# solve model
rbc <- steady_state(rbc)
rbc <- solve_pert(rbc)

# get information about parameters
parameter_info(rbc, all_parameters = TRUE)
```

plot_simulation

Plot a gecon_simulation object

Description

The function plots the simulations or saves them as `.eps` files in the model's subdirectory `/plots`.

Usage

```
plot_simulation(sim_obj, to_tex = NULL, to_eps = NULL)
```

Arguments

<code>sim_obj</code>	an object of the <code>gecon_simulation</code> class.
<code>to_tex</code>	logical. If TRUE, the plots are added to a .tex file.
<code>to_eps</code>	logical. if TRUE, plot(s) shall be saved as .eps file(s) in the model's subdirectory /plots.

Value

If the number of variables of interest is greater than five, more than one plots for each impulse are created (max. 5 variables on each plot). Separate plots are created for all the impulses, if the `compute_irf` function has been used for generating simulations.

Author(s)

Karol Podemski <karol.podemski@gmail.com>,
Kaja Retkiewicz-Wijtiwiak <kaja.retkiewicz@gmail.com>

Examples

```
# copy model to current working directory
file.copy(from = file.path(system.file("examples", package='gEcon'),
  'rbc.gcn'), to = getwd())

# make and load model
rbc <- make_model('rbc.gcn')

# solve model
rbc <- steady_state(rbc)
rbc <- solve_pert(rbc)

# compute and print correlations
rbc <- set_shocks(rbc, shock_matrix = matrix(0.01, 1, 1), shock_order = 'epsilon_Z')
irf_rbc <- compute_irf(rbc)
plot_simulation(irf_rbc)
```

print-methods

Methods for Function print in gEcon package

Description

Prints information about objects of the `gecon_simulation`, `gecon_model`, `gecon_var_info`, `gecon_shock_info`, and `gecon_parameter_info` classes.

Methods

`signature(x = "gecon_simulation")` Prints the name of the model for which the simulations have been generated, information about the time span, shock, and variables used.

`signature(x = "gecon_model")` Shows the type of the model, the date of creation, the solving status, and more detailed information about the number of variables and parameters than the `show generic`.

`signature(x = "gecon_var_info")` Prints all the available information (a short listing, the incidence matrix, the statistics) about the variables, retrived from the model when creating a `gecon_var_info`-class object.

`signature(x = "gecon_shock_info")` Prints all the available information (a short listing, the incidence matrix, the variance-covariance matrix) about the shocks, retrived from the model when creating a `gecon_shock_info`-class object.

`signature(x = "gecon_parameter_info")` Prints all the available information (a short listing, the values, the type, and the incidence) about the parameters, retrived from the model when creating a `gecon_parameter_info`-class object.

random_path

Simulation of the model using a random path of shocks

Description

This function draws random shocks from distribution with user specified covariance matrix and then simulates the behaviour of the system.

Usage

```
random_path(model, shock_list = NULL, var_list = NULL, path_length = 100)
```

Arguments

<code>model</code>	an object of the <code>gecon_model</code> class.
<code>shock_list</code>	a list of shock names that should be taken into account. If not specified the system of all the shocks is simulated.
<code>var_list</code>	a list of variables on which the impact of shocks is to be computed. By default, the impact of random path is evaluated for the state variables only.
<code>path_length</code>	the length of stochastic path, default value = 100.

Details

Cf. gEcon manual, chapter "Model analysis".

Value

An object of the `gecon_simulation` class with simulated paths of variables.

Author(s)

Karol Podemski <karol.podemski@gmail.com>,
Kaja Retkiewicz-Wijtiwiak <kaja.retkiewicz@gmail.com>

See Also

the `simulate_model` function enables user to specify her own path of shocks and simulate the impact. The function returns an object of the `gecon_simulation` class. Generic functions such as `print` and `summary` provide information about the simulations. The `plot_simulation` function allows to visualize the impact on variables.

Examples

```
# copy model to current working directory
file.copy(from = file.path(system.file("examples", package='gEcon'),
  'rbc.gcn'), to = getwd())

# make and load model
rbc <- make_model('rbc.gcn')

# solve model
rbc <- steady_state(rbc)
rbc <- solve_pert(rbc)

# compute and print correlations
rbc <- set_shocks(rbc, shock_matrix = matrix(0.01, 1, 1), shock_order = 'epsilon_Z')
irf_rbc <- random_path(rbc, path_length = 100,
  var_list = c('K_s', 'C', 'Z', 'I', 'Y'))
plot_simulation(irf_rbc)
```

set_free_par

Setting free parameters of model

Description

The set_free_par function defines parameters of a gecon_model class object.

Usage

```
set_free_par(model, free_par, reset = FALSE)
```

Arguments

model	an object of class gecon_model.
free_par	a named list or a vector of parameters.
reset	logical value. If TRUE, allows to reset the free parameters to values specified in the .gcn file.

Value

An object of the gecon_model class representing the model. If the reset option has been set to TRUE, the model's parameters will be set back to values from .gcn file. Generic functions such as print and summary allow to show model elements. The [get_parameter_vals](#) function returns parameter values currently in use.

Author(s)

Karol Podemski <karol.podemski@gmail.com>,
Kaja Retkiewicz-Wijtiwiak <kaja.retkiewicz@gmail.com>

Examples

```
# copy model to current working directory
file.copy(from = file.path(system.file("examples", package='gEcon'),
  'rbc.gcn'), to = getwd())

# make and load model
rbc <- make_model('rbc.gcn')

# set free parameters to different values than in .gcn file
rbc <- set_free_par(rbc, free_par = list(beta = 0.98, delta = 0.01))
rbc <- steady_state(rbc, options=list(method='Broyden', global='gline'))
get_ss_values(rbc)

# reset values to .gcn file values
rbc <- set_free_par(rbc, reset = TRUE)
rbc <- steady_state(rbc)
get_ss_values(rbc)
```

set_shocks

Setting a variance-covariance matrix of stochastic shocks.

Description

The set_shocks function allows to set a variance-covariance matrix for the model shocks.

Usage

```
set_shocks(model, shock_matrix, shock_order = NULL)
```

Arguments

model	an object of the gecon_model class.
shock_matrix	a positive definite matrix with the dimensions (n * n), where n is the number of shocks in the model.
shock_order	a character vector declaring the ordering of shocks in the shock_matrix. If not specified, it is assumed that the ordering is in accordance with the internal ordering of model. The default ordering can be displayed by using the shock_info function with the all_shocks argument set to TRUE.

Details

The rows and columns of shock matrix must agree with the order of shocks stored in a gecon_class object if the shock_order argument is not supplied. This order can be checked by using the [shock_info](#) function and the generic function print.

Value

An object of the gecon_model class, which is representing the model. Generic functions such as print and summary allow to show the model elements. The [shock_info](#) function returns names of shocks, information about which equations they appear in and the current variance-covariance matrix.

Author(s)

Karol Podemski <karol.podemski@gmail.com>,
 Kaja Retkiewicz-Wijtiwiak <kaja.retkiewicz@gmail.com>

Examples

```
# copy model to current working directory
file.copy(from = file.path(system.file("examples", package='gEcon'),
  'rbc.gcn'), to = getwd())

# make and load model
rbc <- make_model('rbc.gcn')
shock_info(rbc, all_shocks = TRUE)

# set the shocks
rbc <- set_shocks(rbc, shock_matrix = matrix(0.01, 1, 1), shock_order = 'epsilon_Z')
shock_info(rbc, all_shocks = TRUE)
```

set_shock_distr_par *Setting distribution parameters of model shocks*

Description

The set_shock_distr_par assigns distribution parameters (standard deviations, correlations of shocks etc) to a gecon_model object

Usage

```
set_shock_distr_par(model, distr_par = NULL)
```

Arguments

model	an object of class gecon_model.
distr_par	a list or vector of distribution parameters

Details

By default, gEcon uses identity matrix as a variance-covariance matrix for shocks. Valid parameter names should match any of the following patterns:

```
"sd( SHOCK_NAME )"
```

```
"var( SHOCK_NAME )"
```

```
"cov( SHOCK_NAME_1, SHOCK_NAME_2 )"
```

```
"cor( SHOCK_NAME_1, SHOCK_NAME_2 )"
```

There are two issues which the user should be careful about while using the set_shock_distr_par function. First, in contrast to other parameters, shock distribution parameters require quotation marks to be assigned properly. If quotation marks are omitted, R parser treats elements of the distr_par list or vector as functions and attempts to evaluate them, producing errors. Second, parameters passed to the distr_par argument should not be specified twice.

Value

An object of the `gecon_model` class representing the model.

Author(s)

Karol Podemski <karol.podemski@gmail.com>,
Kaja Retkiewicz-Wijtiwiak <kaja.retkiewicz@gmail.com>

Examples

```
# copy model to current working directory
file.copy(from = file.path(system.file("examples", package='gEcon'),
  'home_production.gcn'), to = getwd())

# make and load model
home_production <- make_model('home_production.gcn')
shock_info(home_production, all_shocks = TRUE)

# set the shocks
home_production <- set_shock_distr_par(home_production,
  distr_par = list('sd(epsilon_h)' = 0.7,
    'var(epsilon_m)' = 0.49,
    'cor(epsilon_m,
      epsilon_h)' = 2/3))

shock_info(home_production, all_shocks = TRUE)
```

shock_info

Information about shocks

Description

The `shock_info` function allows to create an object of the `gecon_shock_info` class, which contains the information about the model's shocks (occurrence in equations and the variance-covariance matrix)

Usage

```
shock_info(model, shock_names = NULL, all_shocks = FALSE)
```

Arguments

<code>model</code>	an object of the <code>gecon_model</code> class.
<code>shock_names</code>	the names of shocks of interest.
<code>all_shocks</code>	the logical value. If set to <code>TRUE</code> , the <code>shock_names</code> argument is overwritten with the vector of all shocks appearing in the model. The default value is <code>FALSE</code> .

Value

An object of the `gecon_shock_info-class` class.

Author(s)

Karol Podemski <karol.podemski@gmail.com>,
 Kaja Retkiewicz-Wijtiwiak <kaja.retkiewicz@gmail.com>

Examples

```
# copy model to current working directory
file.copy(from = file.path(system.file("examples", package='gEcon'),
  'rbc.gcn'), to = getwd())

# make and load model
rbc <- make_model('rbc.gcn')
rbc <- set_shocks(rbc, shock_matrix = matrix(0.01, 1, 1), shock_order = 'epsilon_Z')

# getting information about shocks
shock_info(rbc, all_shocks = TRUE)
```

show-methods

Methods for show Function in gEcon package

Description

This method shows objects of the `gecon_simulation`, `gecon_model`, `gecon_var_info`, `gecon_shock_info`, and `gecon_parameter_info` classes.

Methods

`signature(object = "gecon_simulation")` Shows the name of the model for which the simulations have been created, information about time span, shocks, and variables used.

`signature(object = "gecon_model")` Shows the type of the model, the date of creation, the solving status, and the information about number of variables and parameters.

`signature(object = "gecon_var_info")` Prints information about variables' incidence and the results that have been already obtained for the variables.

`signature(object = "gecon_shock_info")` Prints the incidence matrix and the variance-covariance matrix of shocks, retrieved from the model when creating `gecon_shock_info` object.

`signature(object = "gecon_parameter_info")` Prints information about parameters' type, value, and the incidence matrix.

simulate_model

Simulation of the model

Description

The `simulate_model` function simulates model based on user defined realisations of shock values. In particular enables to compute the impact of negative shocks.

Usage

```
simulate_model(model, shock_list = NULL, var_list = NULL, shock_m = NULL,
               periods = NULL, path_length = 40,
               sim_type = NULL, model_name = NULL)
```

Arguments

<code>model</code>	an object of the <code>gecon_model</code> class.
<code>shock_list</code>	the shock names for the rows of <code>shock_m</code> specified by the user. The default names are the names of the first shocks from the list of shocks up to the number of <code>shock_m</code> matrix rows.
<code>var_list</code>	the list of variables for which the impact has to be computed. By default, the impact of shocks is evaluated for the state variables only.
<code>shock_m</code>	a matrix or vector of user defined shocks. Values for different shocks should be stored in rows and values for periods in columns.
<code>periods</code>	the number of periods for which, shocks in the <code>shock_m</code> function have been specified. The default values are from 1 to the number of columns of the shock matrix.
<code>path_length</code>	the number of periods for which the model is simulated. The default number is 40.
<code>sim_type</code>	the type of simulation performed on model. It does not have to be specified when user invokes this function directly.
<code>model_name</code>	the name of the <code>gecon_class</code> object based on which simulations are created. The user does not have to specify the name explicitly (by default, the variable is deparsed and name is retrieved automatically). It does not have to be specified when user invokes this function directly.

Details

The `random_path` and `compute_irf` functions are wrappers for this function. They generate a path of shock(s) values and pass it on to `simulate_model` function, which performs computations and returns relevant results.

Value

An object of the `gecon_simulation` class with simulated paths of variables.

Author(s)

Karol Podemski <karol.podemski@gmail.com>,
Kaja Retkiewicz-Wijtiwiak <kaja.retkiewicz@gmail.com>

See Also

the `random_path` function to use random path of shocks for the simulation of the model. The function returns an object of the `gecon_simulation` class. Generic functions such as `print` and `summary` provide information about the simulations. The `plot_simulation` function allows to visualize the impact on variables.

Examples

```
# copy model to current working directory
file.copy(from = file.path(system.file("examples", package='gEcon'),
  'rbc.gcn'), to = getwd())

# make and load model
rbc <- make_model('rbc.gcn')

# solve model
rbc <- steady_state(rbc)
rbc <- solve_pert(rbc)

# compute and print correlations
rbc <- set_shocks(rbc, shock_matrix = matrix(0.01, 1, 1), shock_order = 'epsilon_Z')
irf_rbc <- simulate_model(rbc, shock_m = matrix(c(-0.05, -0.05), 1, 2),
  periods=c(1, 4), var_list = c('K_s', 'C', 'Z', 'I', 'Y'))

plot_simulation(irf_rbc)
```

solve_pert

Solve the model in a linearised form (1st order perturbation)

Description

This function solves the model in a linearised form using Christopher Sims' gensys solver.

Usage

```
solve_pert(model, loglin = TRUE, not_loglin_var = NULL,
  norm_tol = 1e-08, solver = "sims_solver")
```

Arguments

model	an object of the <code>gecon_model</code> class.
loglin	an option to log-linearise the perturbation. If FALSE then model is linearised only.
not_loglin_var	a vector of variables that will not be log-linearised.
norm_tol	the tolerance for residuals of model(default 1e-08).
solver	the name linear RE solver. The default solver is Christopher Sims' solver. Currently no other solvers are available.

Details

Cf. gEcon manual, chapter "Solving model in linearised form".

Value

an object of the `gecon_model` class representing the model. Generic functions such as `print` and `summary` allow to show the model elements. The `get_pert_solution` function returns computed recursive laws of motion for the model's variables. The `check_bk` function displays the eigenvalues of the system and checks the Blanchard-Kahn conditions.

Author(s)

Karol Podemski <karol.podemski@gmail.com>,
 Kaja Retkiewicz-Wijtiwiak <kaja.retkiewicz@gmail.com>

References

Sims, Ch. A. (2002), "Solving Linear Rational Expectations Models.", *Computational Economics*

Examples

```
# create model object and find steady state
file.copy(from = file.path(system.file("examples", package='gEcon'),
  'rbc.gcn'), to = getwd())
rbc <- make_model('rbc.gcn')
rbc <- steady_state(rbc)

# solve in loglinearized form
rbc <- solve_pert(rbc)
get_pert_solution(rbc)

# solve in linearized form
rbc <- solve_pert(rbc, loglin = FALSE)
get_pert_solution(rbc)

# solve with all variables except L_s loglinearized
rbc <- solve_pert(rbc, not_loglin_var=c('L_s'))
get_pert_solution(rbc)
```

steady_state

Compute the steady state (equilibrium) of the dynamic (static) model

Description

This function solves for the steady state of a dynamic model (equilibrium for static model) and calibrates the chosen parameters using a set of solvers from the nleqslv package.

Usage

```
steady_state(model, solver = "slv1_nleqslv", use_jac = TRUE,
  calibration = TRUE, options_list = NULL, solver_status = FALSE)
```

Arguments

model	an object of the gecon_model class.
solver	the name of nonlinear equations solver. In the current version only an interface to slv1_nleqslv function has been implemented.
use_jac	the option to use the Jacobian generated by the symbolic library. If FALSE, numerical derivatives are computed.
calibration	if FALSE, calibrating equations will not be taken into account in the computation of the steady state (equilibrium in case of static model). The initial values of calibrated parameters will be then treated as their values.

- `options_list` a list containing one or more of the following fields:
- `method` a character, can be set to "Newton" or "Broyden", the default option is "Newton".
 - `global` a character, search strategy can be set to "dbldog", "pwldog", "qline", "gline", "none". The default option is "qline".
 - `xscalm` a character, a method of scaling x. It can be set to "fixed", "auto". The default option is "fixed".
 - `max_iter` a numeric value denoting max. number of iterations. The default value is 150.
 - `tol` a numeric value setting the numeric tolerance for a solution. The default value is 1e-6.
- `solver_status` the information about the solver exit code.

Details

Cf. gEcon Manual, chapter "Deterministic steady state".

Value

An object of the `gecon_model` class representing the model. Generic functions such as `print` and `summary` allow to show model elements. The `get_ss_values` and `get_parameter_vals` functions return steady state (equilibrium) and parameter values respectively.

Author(s)

Karol Podemski <karol.podemski@gmail.com>,
Kaja Retkiewicz-Wijtiwiak <kaja.retkiewicz@gmail.com>

See Also

[nleqslv](#) for the detailed description of the `nleqslv` solver capabilities.

Examples

```
# copy model to current working directory
file.copy(from = file.path(system.file("examples", package='gEcon'),
  'rbc.gcn'), to = getwd())

# make and load model
rbc <- make_model('rbc.gcn')

# compute steady state and calibrate alpha
rbc <- initval_calibr_par(rbc, list(alpha = 0.33))
rbc <- steady_state(rbc, use_jac=TRUE,
  options_list=list(method='Broyden', global='gline',
    max_iter = 300, tol = 1e-7))

get_ss_values(rbc)

# compute steady state not taking alpha calibration into account
rbc <- initval_calibr_par(rbc, list(alpha = 0.4))
rbc <- steady_state(rbc, calibration=FALSE, use_jac=FALSE,
  options_list=list(method='Newton', global='gline',
    max_iter = 100, tol = 1e-5))

get_ss_values(rbc)
```

summary-methods

*Summary Method for gecon_model objects in gEcon package***Description**

This method summarizes the objects of the `gecon_simulation`, `gecon_model`, `gecon_var_info`, `gecon_shock_info`, and `gecon_parameter_info` classes.

Methods

`signature(object = "gecon_simulation")` Prints a summary of a `gecon_simulation` class object consisting of a shock matrix and the simulation for each shock.

`signature(object = "gecon_model")` Prints a summary of a `gecon_model` class object consisting of all the computed statistics and values.

`signature(object = "gecon_var_info")` Prints all the available information (short listing, the incidence matrix, the statistics) about the variables, retrieved from the model when creating a `gecon_var_info`-class object.

`signature(object = "gecon_shock_info")` Prints all the available information (short listing, the incidence matrix, the variance-covariance matrix) about the shocks, retrieved from the model when creating a `gecon_shock_info`-class object.

`signature(object = "gecon_parameter_info")` Prints all the available information (short listing, the values, the type, and the incidence) about the parameters, retrieved from the model when creating a `gecon_parameter_info`-class object.

var_info

*Information about variables***Description**

The `var_info` function allows to create an object of `gecon_var_info` class, which contains information about the specified variables. It allows to check which equations a given set of variables appear in. In addition, this function prints the already computed statistics of the given set of variables.

Usage

```
var_info(model, var_names = NULL, all_variables = FALSE)
```

Arguments

`model` an object of the `gecon_model` class.

`var_names` the names of the variables of interest.

`all_variables` the logical value. If set to `TRUE`, the `var_names` argument is overwritten with a vector of all variables appearing in the model. The default value is `FALSE`.

Details

The function may be useful in debugging model and quick retrieval of information when the model is large. If the object returned by the function is not assigned to any variable, the information about the requested parameters is printed to the console. One or more of the following elements may be printed:

- incidence information,
- steady state (equilibrium) values,
- variables info (which ones are loglinearized and which are state variables),
- state variables impact on the chosen variables,
- shocks impact on the chosen variables,
- moments,
- correlations,

depending on which operations have been performed on `gecon_model` class object.

Value

An object of `gecon_var_info-class` class.

Note

The function only displays the already set and computed elements of a model, eg. if the model has been solved but the statistics have not been computed, the correlations will not be passed to the `gecon_var_info` class.

Author(s)

Karol Podemski <karol.podemski@gmail.com>,
Kaja Retkiewicz-Wijtiwiak <kaja.retkiewicz@gmail.com>

See Also

[shock_info](#) for information about the shocks.
[get_ss_values](#), [get_pert_solution](#), [get_moments](#) to extract directly the steady state (equilibrium) values, the solution of model, various moments and statistics of the model.

Examples

```
# copy model to current working directory
file.copy(from = file.path(system.file("examples", package='gEcon'),
  'rbc.gcn'), to = getwd())

# make and load model
rbc <- make_model('rbc.gcn')

# solve model
rbc <- steady_state(rbc)
rbc <- solve_pert(rbc)

# get information about variables
rbc_var_info <- var_info(rbc, var_names = c('K_s'))
print(rbc_var_info)
```

```
show(rbc_var_info)
summary(rbc_var_info)
```

Index

*Topic **methods**

print-methods, [31](#)
show-methods, [37](#)
summary-methods, [42](#)

*Topic **package**

gecon-package, [2](#)

check_bk, [3](#), [39](#)

compute_corr, [4](#), [19](#), [20](#)

compute_irf, [6](#), [38](#)

find_calibr_eq, [7](#)

find_eq, [8](#), [23](#)

gecon (gecon-package), [2](#)

gecon-package, [2](#)

gecon_model, [8](#), [10](#)

gecon_model-class, [10](#)

gecon_parameter_info-class, [12](#)

gecon_shock_info-class, [14](#)

gecon_simulation, [15](#), [16](#), [32](#), [38](#)

gecon_simulation-class, [16](#)

gecon_var_info-class, [17](#)

get_free_parameter_names (get_names), [20](#)

get_moments, [5](#), [19](#), [43](#)

get_names, [20](#)

get_parameter_vals, [21](#), [26](#), [33](#), [41](#)

get_pert_solution, [22](#), [39](#), [43](#)

get_residuals, [23](#)

get_shock_names (get_names), [20](#)

get_simulation_results, [16](#), [24](#)

get_ss_values, [25](#), [27](#), [41](#), [43](#)

get_var_names (get_names), [20](#)

initval_calibr_par, [26](#)

initval_var, [27](#)

load_model, [27](#), [29](#)

make_model, [28](#), [28](#)

nleqslv, [41](#)

parameter_info, [12](#), [13](#), [29](#)

plot_simulation, [30](#)

print,gecon_model-method

(print-methods), [31](#)

print,gecon_parameter_info-method

(print-methods), [31](#)

print,gecon_shock_info-method

(print-methods), [31](#)

print,gecon_simulation-method

(print-methods), [31](#)

print,gecon_var_info-method

(print-methods), [31](#)

print-methods, [31](#)

random_path, [32](#), [38](#)

set_free_par, [33](#)

set_shock_distr_par, [35](#)

set_shocks, [34](#)

shock_info, [14](#), [30](#), [34](#), [36](#), [43](#)

show,gecon_model-method (show-methods),
[37](#)

show,gecon_parameter_info-method
(show-methods), [37](#)

show,gecon_shock_info-method
(show-methods), [37](#)

show,gecon_simulation-method
(show-methods), [37](#)

show,gecon_var_info-method
(show-methods), [37](#)

show-methods, [37](#)

simulate_model, [32](#), [37](#)

solve_pert, [4](#), [22](#), [39](#)

steady_state, [40](#)

summary,gecon_model-method
(summary-methods), [42](#)

summary,gecon_parameter_info-method
(summary-methods), [42](#)

summary,gecon_shock_info-method
(summary-methods), [42](#)

summary,gecon_simulation-method
(summary-methods), [42](#)

summary,gecon_var_info-method
(summary-methods), [42](#)

summary-methods, [42](#)

var_info, [17](#), [18](#), [30](#), [42](#)