

SUPRASEC 5025 (A Polymeric Isocyanate)

Version	Revision Date:	SDS Number:	Date of last issue: 19.08.2019
0.0	-	SDS086	Date of first issue: 10.03.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Trade name	: SUPRASEC® 5025 (A Polymeric Isocyanate)
Substance name	: Polymethylene polyphenylene isocyanate
CAS-No.	: 9016-87-9
EC-No.	: Polymer

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture	: Component of a Polyurethane System.
------------------------------	---------------------------------------

Recommended restrictions on use	: For industrial use only.
---------------------------------	----------------------------

1.3 Details of the supplier of the safety data sheet

Company	: HUNTSMAN UAE FZE
Address	: Huntsman (UAE) FZE, P.O Box 16942 Jebel Ali Trade Zone, Dubai UAE
Telephone	: +97148813800
Telefax	: +97148813060
E-mail address of person responsible for the SDS	: Global_Product_EHS_HPU@huntsman.com

1.4 Emergency telephone number

Emergency telephone number	: EUROPE: +32 35 75 1234 USA: +1 800 424 9300 ASIA: +65 6542 9595 China: +86 20 39377888 +86 532 83889090 India: + 91 22 42 87 5333 Australia: 1 800 786 152 New Zealand: 0 800 767 437
----------------------------	--

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification T.R. SEA No 28848**

Acute toxicity, Category 4	H332: Harmful if inhaled.
----------------------------	---------------------------

Skin irritation, Category 2	H315: Causes skin irritation.
-----------------------------	-------------------------------

SUPRASEC 5025 (A Polymeric Isocyanate)

Version	Revision Date:	SDS Number:	Date of last issue: 19.08.2019
0.0	-	SDS086	Date of first issue: 10.03.2019

Eye irritation, Category 2	H319: Causes serious eye irritation.
Respiratory sensitisation, Category 1	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Carcinogenicity, Category 2	H351: Suspected of causing cancer.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.

2.2 Label elements**Labelling T.R. SEA No 28848**

Hazard pictograms :



Signal word : Danger

Hazard statements	:	H315	Causes skin irritation.
		H317	May cause an allergic skin reaction.
		H319	Causes serious eye irritation.
		H332	Harmful if inhaled.
		H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
		H335	May cause respiratory irritation.
		H351	Suspected of causing cancer.
		H373	May cause damage to organs through prolonged or repeated exposure.

Precautionary statements	:	Prevention:	
		P201	Obtain special instructions before use.
		P260	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
		P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
		P284	Wear respiratory protection.
		Response:	
		P304 + P340 + P312	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
		P308 + P313	IF exposed or concerned: Get medical advice/ attention.

SUPRASEC 5025 (A Polymeric Isocyanate)

Version	Revision Date:	SDS Number:	Date of last issue: 19.08.2019
0.0	-	SDS086	Date of first issue: 10.03.2019

Additional Labelling:

EUH204 Contains isocyanates. May produce an allergic reaction.

2.3 Other hazards

None known.

SECTION 3: Composition/information on ingredients**3.1 Substances**

Substance name	: Polymer
CAS-No.	: 9016-87-9

Hazardous components

Chemical name	CAS-No. EC-No.	Concentration (% w/w)
Isocyanic acid, polymethylenepolyphenylene ester	9016-87-9 Polymer	>= 90 - <= 100

SECTION 4: First aid measures**4.1 Description of first aid measures**

General advice	: Move out of dangerous area. Do not leave the victim unattended. Get medical attention immediately if symptoms occur. Show this safety data sheet to the doctor in attendance.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If potential for exposure exists refer to Section 8 for specific personal protective equipment. First Aid responders should pay attention to self-protection and use the recommended protective clothing

SUPRASEC 5025 (A Polymeric Isocyanate)

Version	Revision Date:	SDS Number:	Date of last issue: 19.08.2019
0.0	-	SDS086	Date of first issue: 10.03.2019

- | | |
|-------------------------|--|
| If inhaled | : If breathed in, move person into fresh air.
Call a physician or poison control centre immediately.
Keep patient warm and at rest.
Keep respiratory tract clear.
If breathing is difficult, give oxygen.
If breathing is irregular or stopped, administer artificial respiration.
If unconscious, place in recovery position and seek medical advice.
Consult a physician immediately if symptoms such as shortness of breath or asthma are observed.
A hyper-reactive response to even minimal concentrations of diisocyanates may develop in sensitised persons.
The exposed person may need to be kept under medical surveillance for 48 hours.
LC50 (rat) : ca. 490 mg/m ³ (4 hours) : using experimentally produced respirable aerosol having aerodynamic diameter <5microns. |
| In case of skin contact | : In case of contact, immediately flush skin with soap and plenty of water.
Take off contaminated clothing and shoes immediately.
Wash contaminated clothing before reuse.
Thoroughly clean shoes before reuse.
Call a physician if irritation develops or persists.
An MDI study has demonstrated that a polyglycol-based skin cleanser (such as D-Tam TM , PEG-400) or corn oil may be more effective than soap and water. |
| In case of eye contact | : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist. |
| If swallowed | : Gently wipe or rinse the inside of the mouth with water.
DO NOT induce vomiting unless directed to do so by a physician or poison control center.
Keep respiratory tract clear.
Keep at rest.
If a person vomits when lying on his back, place him in the recovery position.
Never give anything by mouth to an unconscious person.
Take victim immediately to hospital.
If symptoms persist, call a physician. |

4.2 Most important symptoms and effects, both acute and delayed

- | | |
|----------|---|
| Symptoms | : Severe allergic skin reactions, bronchospasm and anaphylactic shock |
|----------|---|

SUPRASEC 5025 (A Polymeric Isocyanate)

Version	Revision Date:	SDS Number:	Date of last issue: 19.08.2019
0.0	-	SDS086	Date of first issue: 10.03.2019

Risks	: This product is a respiratory irritant and potential respiratory sensitiser: repeated inhalation of vapour or aerosol at levels above the occupational exposure limit could cause respiratory sensitisation. Symptoms may include irritation to the eyes, nose, throat and lungs, possibly combined with dryness of the throat, tightness of chest and difficulty in breathing. The onset of the respiratory symptoms may be delayed for several hours after exposure. A hyper-reactive response to even minimal concentrations of MDI may develop in sensitised persons.
-------	--

4.3 Indication of any immediate medical attention and special treatment needed

Treatment	: Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours. The first aid procedure should be established in consultation with the doctor responsible for industrial medicine.
-----------	--

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing media	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Foam Carbon dioxide (CO ₂) Dry powder
Unsuitable extinguishing media	: Water may be used if no other available and then in copious quantities. Reaction between water and hot isocyanate may be vigorous.

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses. The pressure in sealed containers can increase under the influence of heat. Exposure to decomposition products may be a hazard to health.
Hazardous combustion products	: Combustion products may include: carbon monoxide, carbon dioxide, nitrogen oxides, hydrocarbons and HCN. In the event of extreme heat (>500 degrees C), aniline is suspected of being formed.

5.3 Advice for firefighters

Special protective equipment for firefighters	: Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.
Specific extinguishing methods	: Cool containers/tanks with water spray.

SUPRASEC 5025 (A Polymeric Isocyanate)

Version	Revision Date:	SDS Number:	Date of last issue: 19.08.2019
0.0	-	SDS086	Date of first issue: 10.03.2019

Further information : Standard procedure for chemical fires. Due to reaction with water producing CO₂-gas, a hazardous build-up of pressure could result if contaminated containers are re-sealed. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Prevent fire extinguishing water from contaminating surface water or the ground water system. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Immediately evacuate personnel to safe areas.

Use personal protective equipment.
If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.
Ensure adequate ventilation.
Keep people away from and upwind of spill/leak.
Only qualified personnel equipped with suitable protective equipment may intervene.
For additional precautions and advice on safe handling, see section 7.
Never return spills in original containers for re-use.
Make sure that there is a sufficient amount of neutralizing/absorbent material near the storage area.
The danger areas must be delimited and identified using relevant warning and safety signs.
Treat recovered material as described in the section "Disposal considerations".
For disposal considerations see section 13.

6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.
Do not allow material to contaminate ground water system.
Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
Local authorities should be advised if significant spillages cannot be contained.
If the product contaminates rivers and lakes or drains inform respective authorities.

SUPRASEC 5025 (A Polymeric Isocyanate)

Version	Revision Date:	SDS Number:	Date of last issue: 19.08.2019
0.0	-	SDS086	Date of first issue: 10.03.2019

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Clean-up methods - small spillage
Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).
Clean contaminated surface thoroughly.
Sweep up or vacuum up spillage and collect in suitable container for disposal.
Neutralize small spillages with decontaminant.
The compositions of liquid decontaminants are given in Section 16.
Remove and dispose of residues.
Clean-up methods - large spillage
If the product is in its solid form:
Spilled MDI flakes should be picked up carefully.
The area should be vacuum cleaned to remove remaining dust particles completely.
If the product is in its liquid form:
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Leave to react for at least 30 minutes.
Shovel into open-top drums for further decontamination.
Wash the spillage area with water.

Test atmosphere for MDI vapour.
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8., For disposal considerations see section 13., The compositions of liquid decontaminants are given in Section 16.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Technical measures	: Ensure that eyewash stations and safety showers are close to the workstation location.
Local/Total ventilation	: Use only with adequate ventilation.

SUPRASEC 5025 (A Polymeric Isocyanate)

Version	Revision Date:	SDS Number:	Date of last issue: 19.08.2019
0.0	-	SDS086	Date of first issue: 10.03.2019

Advice on safe handling : For personal protection see section 8.
 Avoid formation of aerosol.
 Do not breathe vapours or spray mist.
 Do not breathe vapours/dust.
 Do not swallow.
 Do not get in eyes or mouth or on skin.
 Do not get on skin or clothing.
 Avoid exposure - obtain special instructions before use.
 Smoking, eating and drinking should be prohibited in the application area.
 Provide sufficient air exchange and/or exhaust in work rooms.
 Keep container closed when not in use.
 Open drum carefully as content may be under pressure.
 Dispose of rinse water in accordance with local and national regulations.
 Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Wash face, hands and any exposed skin thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. When using do not eat, drink or smoke. Contaminated work clothing should not be allowed out of the workplace. Wash hands before breaks and immediately after handling the product. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep containers tightly closed in a dry, cool and well-ventilated place. Keep in properly labelled containers. Observe label precautions. Protect from moisture. Electrical installations / working materials must comply with the technological safety standards. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Advice on common storage : Acids
 Amines
 Bases
 Metals
 water

Recommended storage temperature : 20 - 25 °C

Further information on storage stability : Stable under recommended storage conditions.

7.3 Specific end use(s)

Specific use(s) : No data available

SUPRASEC 5025 (A Polymeric Isocyanate)

Version	Revision Date:	SDS Number:	Date of last issue: 19.08.2019
0.0	-	SDS086	Date of first issue: 10.03.2019

SECTION 8: Exposure controls/personal protection
8.1 Control parameters
Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Polymethylene polyphenylene isocyanate	Workers	Dermal	Systemic effects, Short-term exposure	50 mg/kg bw/day
	Workers	Inhalation	Systemic effects, Short-term exposure	0,1 mg/m3
	Workers	Dermal	Local effects, Short-term exposure	27,8 mg/kg bw/day
	Workers	Inhalation	Local effects, Short-term exposure	0,1 mg/m3
	Workers	Inhalation	Long-term systemic effects	0,05 mg/m3
	Workers	Inhalation	Long-term local effects	0,05 mg/m3
	Consumers	Dermal	Systemic effects, Short-term exposure	25 mg/kg bw/day
	Consumers	Inhalation	Systemic effects, Short-term exposure	0,05 mg/m3
	Consumers	Oral	Systemic effects, Short-term exposure	20 mg/kg bw/day
	Consumers	Dermal	Local effects, Short-term exposure	17,2 mg/cm2
	Consumers	Inhalation	Local effects, Short-term exposure	0,05 mg/m3
	Consumers	Inhalation	Long-term systemic effects	0,025 mg/m3
	Consumers	Inhalation	Long-term local effects	0,025 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Polymethylene polyphenylene isocyanate	Fresh water	1 mg/l
Remarks:	Assessment Factors	
	Marine water	0,1 mg/l
	Assessment Factors	
	Soil	1 mg/kg
	Assessment Factors	
	Sewage treatment plant	1 mg/l
	Assessment Factors	
	Freshwater - intermittent	10 mg/l

SUPRASEC 5025 (A Polymeric Isocyanate)

Version	Revision Date:	SDS Number:	Date of last issue: 19.08.2019
0.0	-	SDS086	Date of first issue: 10.03.2019

8.2 Exposure controls
Personal protective equipment

Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.
Chemical splash goggles.
Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.
Please follow all applicable local/national requirements when selecting protective measures for a specific workplace.
Ensure that eyewash stations and safety showers are close to the workstation location.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Protective gloves should be worn when handling freshly made polyurethane products to avoid contact with trace residual materials which may be hazardous in contact with skin.

Use chemical resistant gloves classified under Standard EN374: protective gloves against chemicals and microorganisms. Examples of glove materials that might provide suitable protection include: Butyl rubber, Chlorinated polyethylene, Polyethylene, Ethyl vinyl alcohol copolymers laminated ("EVAL"), Polychloroprene (Neoprene*), Nitrile/butadiene rubber ("nitrile" or "NBR"), Polyvinyl chloride ("PVC" or "vinyl"), Fluoroelastomer (Viton*).

When prolonged or frequently repeated contact may occur, a glove with protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN374) is recommended.

When only brief contact is expected, a glove with protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN374) is recommended.
Contaminated gloves should be decontaminated and disposed of.

Notice: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all requisite workplace factors such as, but not limited to : other chemicals that may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), as well as instructions/specifications provided by the glove supplier.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Recommended:
Overall (preferably heavy cotton) or Tyvek-Pro Tech 'C' , Tyvek Pro 'F' disposable coverall.

SUPRASEC 5025 (A Polymeric Isocyanate)

Version	Revision Date:	SDS Number:	Date of last issue: 19.08.2019
0.0	-	SDS086	Date of first issue: 10.03.2019

- | | |
|------------------------|---|
| Respiratory protection | : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
In emergency, non-routine and unknown exposure situations, including confined space entries, a NIOSH-certified full facepiece pressure demand self-contained breathing apparatus (SCBA) or a full facepiece pressure demand supplied air respirator (SAR) with auxiliary self-contained air supply, should be used. |
| Protective measures | : Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing
The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Ensure that eye flushing systems and safety showers are located close to the working place. |

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

- | | |
|--|---|
| Appearance | : liquid |
| Colour | : brown, clear |
| Odour | : slight, musty |
| Odour Threshold | : No data is available on the product itself. |
| pH | : No data is available on the product itself. |
| Freezing point | : No data is available on the product itself. |
| Melting point | : No data is available on the product itself. |
| Boiling point | : No data is available on the product itself. |
| Flash point | : > 150 °C
Method: closed cup |
| Evaporation rate | : No data is available on the product itself. |
| Flammability (solid, gas) | : No data is available on the product itself. |
| Burning rate | : No data is available on the product itself. |
| Upper explosion limit / Upper flammability limit | : No data is available on the product itself. |
| Lower explosion limit / Lower flammability limit | : No data is available on the product itself. |

SUPRASEC 5025 (A Polymeric Isocyanate)

Version	Revision Date:	SDS Number:	Date of last issue: 19.08.2019
0.0	-	SDS086	Date of first issue: 10.03.2019

Vapour pressure	: < 0,00001 hPa (20 °C)
Relative vapour density	: No data is available on the product itself.
Relative density	: 1,23
Density	: 1,23 g/cm ³ (20 °C) Method: estimated
Solubility(ies)	
Water solubility	: Decomposes in contact with water. (20 °C) Method: Information given is based on data obtained from similar substances.
Solubility in other solvents	: No data is available on the product itself.
Partition coefficient: n-octanol/water	: No data is available on the product itself.
Auto-ignition temperature	: No data is available on the product itself.
Decomposition temperature	: No data is available on the product itself.
Viscosity	
Viscosity, dynamic	: 200 mPa.s (25 °C)
Explosive properties	: No data is available on the product itself.
Oxidizing properties	: No data is available on the product itself.

9.2 Other information

No data available

SECTION 10: Stability and reactivity**10.1 Reactivity**

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

SUPRASEC 5025 (A Polymeric Isocyanate)

Version	Revision Date:	SDS Number:	Date of last issue: 19.08.2019
0.0	-	SDS086	Date of first issue: 10.03.2019

10.3 Possibility of hazardous reactions

Hazardous reactions : Reaction with water (moisture) produces CO₂-gas.
Exothermic reaction with materials containing active hydrogen groups.
The reaction becomes progressively more vigorous and can be violent at higher temperatures if the miscibility of the reaction partners is good or is supported by stirring or by the presence of solvents.
MDI is insoluble with, and heavier than water and sinks to the bottom but reacts slowly at the interface.
A solid water-insoluble layer of polyurea is formed at the interface by liberating carbon dioxide gas.

10.4 Conditions to avoid

Conditions to avoid : Extremes of temperature and direct sunlight.
Exposure to air or moisture over prolonged periods.

10.5 Incompatible materials

Materials to avoid : Acids
Amines
Bases
Metals
water

10.6 Hazardous decomposition products

Combustion products may include: carbon monoxide, carbon dioxide, nitrogen oxides, hydrocarbons and HCN. In the event of extreme heat (>500 degrees C), aniline is suspected of being formed.

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity**

Acute oral toxicity - Product : LD₅₀ (Rat, male): > 10 000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity - Product : LC₅₀ (Rat, male and female): 0,49 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity - Product : LD₅₀ (Rabbit, male and female): > 9 400 mg/kg
Method: OECD Test Guideline 402

Acute toxicity (other routes of administration) : No data available

SUPRASEC 5025 (A Polymeric Isocyanate)

Version	Revision Date:	SDS Number:	Date of last issue: 19.08.2019
0.0	-	SDS086	Date of first issue: 10.03.2019

Skin corrosion/irritation**Product:**

Species: Rabbit
Assessment: Irritating to skin.
Method: OECD Test Guideline 404
Result: Skin irritation

Serious eye damage/eye irritation**Product:**

Species: Rabbit
Assessment: Mild eye irritant
Method: OECD Test Guideline 405
Result: Irritation to eyes, reversing within 7 days

Respiratory or skin sensitisation**Product:**

Exposure routes: Skin
Species: Guinea pig
Method: OECD Test Guideline 406
Result: May cause sensitisation by skin contact.

Exposure routes: Respiratory Tract
Species: Rat
Result: May cause sensitisation by inhalation.

Assessment: May cause an allergic skin reaction., May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity**Product:**

Genotoxicity in vitro : Concentration: 200 ug/plate
Metabolic activation: with and without metabolic activation
Method: Directive 67/548/EEC, Annex, B.13/14
Result: negative

Product:

Genotoxicity in vivo : Application Route: Inhalation
Result: Not classified due to inconclusive data.

Application Route: Inhalation
Exposure time: 3 Weeks
Dose: 113 mg/m³
Method: OECD Test Guideline 474
Result: negative

Product:

Germ cell mutagenicity-
Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

SUPRASEC 5025 (A Polymeric Isocyanate)

Version	Revision Date:	SDS Number:	Date of last issue: 19.08.2019
0.0	-	SDS086	Date of first issue: 10.03.2019

Carcinogenicity**Product:**

Remarks: Rats have been exposed for two years to a respirable aerosol of polymeric MDI which resulted in a chronic pulmonary irritation at high concentrations. Only at the top level (6 mg/m³), there was a significant incidence of a benign tumour of the lung (adenoma) and one malignant tumour (adenocarcinoma). There were no lung tumours at 1 mg/m³ and no effects at 0.2 mg/m³. Overall, the tumour incidence, both benign and malignant, and the number of animals with the tumours were not different from controls. The increased incidence of lung tumours is associated with prolonged respiratory irritation and the concurrent accumulation of yellow material in the lung, which occurred throughout the study. In the absence of prolonged exposure to high concentrations leading to chronic irritation and lung damage, it is highly unlikely that tumour formation will occur.

Species: Rat, male and female
Application Route: Inhalation
Exposure time: 24 month(s)
Dose: 1 mg/m³
Frequency of Treatment: 5 daily
Method: OECD Test Guideline 453
Result: positive

Species: Rat, male and female
Application Route: Inhalation
Exposure time: 24 month(s)
Dose: 1 mg/m³
Frequency of Treatment: 5 daily
Method: OECD Test Guideline 453
Result: positive

Components:

Isocyanic acid, polymethylenepolyphenylene ester:
Carcinogenicity - : Suspected human carcinogens
Assessment

Reproductive toxicity**Product:**

Effects on fertility : Species: Rat, male and female
Application Route: Inhalation
Method: OECD Test Guideline 414
Remarks: No significant adverse effects were reported

Product:

Effects on foetal development : Species: Rat, male and female
Application Route: Inhalation
General Toxicity Maternal: 4 mg/m³
Method: OECD Test Guideline 414
Result: No teratogenic effects

Product:

Reproductive toxicity - : No toxicity to reproduction
Assessment : No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.

SUPRASEC 5025 (A Polymeric Isocyanate)

Version	Revision Date:	SDS Number:	Date of last issue: 19.08.2019
0.0	-	SDS086	Date of first issue: 10.03.2019

STOT - single exposure**Product:**

Exposure routes: Inhalation

Target Organs: Respiratory Tract

Assessment: May cause respiratory irritation.

STOT - repeated exposure**Product:**

Exposure routes: Inhalation

Target Organs: Respiratory Tract

Assessment: May cause damage to organs through prolonged or repeated exposure.

Repeated dose toxicity**Product:**

Species: Rat, male and female

: 0,2

Exposure time: 2 yrNumber of exposures: 5 d

Method: OECD Test Guideline 453

Repeated dose toxicity - : No data available
Assessment

Aspiration toxicity

No data available

Experience with human exposure

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

SUPRASEC 5025 (A Polymeric Isocyanate)

Version	Revision Date:	SDS Number:	Date of last issue: 19.08.2019
0.0	-	SDS086	Date of first issue: 10.03.2019

Further information

Ingestion: No data available

SECTION 12: Ecological information**12.1 Toxicity****Product:**

Toxicity to fish	: LC50 (Brachydanio rerio (zebrafish)): > 1 000 mg/l Exposure time: 96 h Test Type: static test Test substance: Fresh water Method: OECD Test Guideline 203 LC0 : > 1 000 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 1 000 mg/l Exposure time: 24 h Test Type: static test Test substance: Fresh water Method: OECD Test Guideline 202
Toxicity to algae	: EC50 (Desmodesmus subspicatus (green algae)): > 1 640 mg/l Exposure time: 72 h Test Type: static test Test substance: Fresh water Method: OECD Test Guideline 201
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC: >= 10 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Test Type: semi-static test Test substance: Fresh water Method: OECD Test Guideline 211
Toxicity to microorganisms	: EC50 (activated sludge): > 100 mg/l Exposure time: 3 h Test Type: static test Test substance: Fresh water Method: OECD Test Guideline 209
Toxicity to soil dwelling organisms	: EC50: > 1 000 mg/kg Exposure time: 336 h Species: Eisenia fetida (earthworms) Method: OECD Test Guideline 207

SUPRASEC 5025 (A Polymeric Isocyanate)

Version	Revision Date:	SDS Number:	Date of last issue: 19.08.2019
0.0	-	SDS086	Date of first issue: 10.03.2019

Components:

Isocyanic acid, polymethylenepolyphenylene ester:

- | | |
|--|--|
| Toxicity to fish | : LC50 (Brachydanio rerio (zebrafish)): > 1 000 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 203

LC0 : > 1 000 mg/l
Exposure time: 96 h |
| Toxicity to daphnia and other aquatic invertebrates | : EC50 (Daphnia magna (Water flea)): > 1 000 mg/l
Exposure time: 24 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202 |
| Toxicity to algae | : EC50 (Desmodesmus subspicatus (green algae)): > 1 640 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 201 |
| Toxicity to microorganisms | : EC50 (activated sludge): > 100 mg/l
Exposure time: 3 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 209 |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : NOEC: >= 10 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 211 |
| Toxicity to soil dwelling organisms | : EC50: > 1 000 mg/kg
Exposure time: 336 h
Species: Eisenia fetida (earthworms)
Method: OECD Test Guideline 207 |

12.2 Persistence and degradability.**Product:**

- | | |
|------------------|--|
| Biodegradability | : Inoculum: Domestic sewage
Concentration: 30 mg/l
Result: Not biodegradable
Biodegradation: 0 %
Exposure time: 28 d
Method: Inherent Biodegradability: Modified MITI Test (II) |
|------------------|--|

Components:

Isocyanic acid, polymethylenepolyphenylene ester:

SUPRASEC 5025 (A Polymeric Isocyanate)

Version	Revision Date:	SDS Number:	Date of last issue: 19.08.2019
0.0	-	SDS086	Date of first issue: 10.03.2019

Biodegradability : Inoculum: Domestic sewage
Concentration: 30 mg/l
Result: Not biodegradable
Biodegradation: 0 %
Exposure time: 28 d
Method: Inherent Biodegradability: Modified MITI Test (II)

Stability in water : Degradation half life (DT50): 0,8 d (25 °C)
Method: No information available.
Remarks: Fresh water

12.3 Bioaccumulative potential**Product:**

Bioaccumulation : Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): 200
Remarks: Bioaccumulation is unlikely.

Components:

Isocyanic acid, polymethylenepolyphenylene ester:

Bioaccumulation : Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): 200

Remarks: Bioaccumulation is unlikely.

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SUPRASEC 5025 (A Polymeric Isocyanate)

Version	Revision Date:	SDS Number:	Date of last issue: 19.08.2019
0.0	-	SDS086	Date of first issue: 10.03.2019

SECTION 14: Transport information**IATA**

Not regulated as dangerous goods

IMDG

Not regulated as dangerous goods

ADR

Not regulated as dangerous goods

RID

Not regulated as dangerous goods

Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Other regulations:

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures".
Regulation on Classification, Labelling and Packaging of Substances and Mixtures. Dated 11 December 2013, Numbered 28848 (Bis) Ministry of Environment and Forestry.

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

SUPRASEC 5025 (A Polymeric Isocyanate)

Version	Revision Date:	SDS Number:	Date of last issue: 19.08.2019
0.0	-	SDS086	Date of first issue: 10.03.2019

TSCA : On the inventory, or in compliance with the inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), ENCS (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States of America (USA))

SECTION 16: Other information**Further information**

Other information : Liquid decontaminants (percentages by weight or volume) :
Decontaminant 1 : *- sodium carbonate : 5 - 10 % *- liquid detergent : 0.2 - 2 % *- water : to make up to 100 %

Decontaminant 2 : *- concentrated ammonia solution : 3 - 8 %
*- liquid detergent : 0.2 - 2 % *- water : to make up to 100 %
Decontaminant 1 reacts slower with diisocyanates but is more environmentally friendly than decontaminant 2.
Decontaminant 2 contains ammonia. Ammonia presents health hazards. (See supplier safety information.)

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.

HUNTSMAN UAE FZE. based in DUBAI, UAE is a fully owned subsidiary of Huntsman.