

MATERIAL SAFETY DATA SHEET

1. PRODUCT : ROB RED OXIDE PRIMER

2. COMPOSITION/INFORMATION OF INGREDIENTS

Contains aromatic hydrocarbons, polyols, ketones, Alkyd resin,
Red oxide pigments.

CAS NO ; Alkyd resin binder : 64742-82-1

3. HAZARDS IDENTIFICATION OF THE PREPARATION

Highly inflammable.
Harmful by inhalation and in contact with skin.
Irritating to skin.
Irritating to respiratory system.

4. FIRST AID AND MEASURES

General:

In all cases of doubt, or when symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.

Inhalation:

Remove to fresh air, keep patient warm and at rest, if breathing is irregular or stopped, administer artificial respiration. Give nothing by mouth. If unconscious, place in recovery position and seek medical advice.

Eye contact:

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.

Skin contact:

Remove contaminated clothing. Wash skin thoroughly with soap and water or use Recognized skin cleanser. Do **NOT** use solvents or thinners.

Ingestion:

If accidentally swallowed obtain immediate medical attention. Keep at rest.
Do **NOT** induce vomiting.

5. FIRE-FIGHTING MEASURES

Extinguishing media :

Recommended : alcohol resistant foam, CO2, powers, water spray
Not to be used : water jet.

Recommendations :

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

6 .ACCIDENTAL RELEASE MEASURES

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in section 7 and 8. Contain and collect spillage with non- combustible adsorbent materials, e. g. sand, earth, vermiculate, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Do not allow to enter drains or water courses. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

7 .HANDLING AND STORAGE

Handling:

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentration higher than the occupational limits.

Additionally, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard

Preparation may charge electro statically : always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and floors should be of the conducting type.

Keep container tightly closed. Isolate from sources of heat, sparks and open

flame. No sparking tools should be used

Avoid skin and eye contact. Avoid inhalation of vapor and spray mist.

Smoking, eating and drinking should be prohibited in application area.

For personnel protection see Section 8.

Never use pressure to empty : container is not a pressure vessel.

Always keep in containers of same material as the original one.

Comply with the health and safety at work laws.

Storage:

Store in accordance with local rules and legislation.

Observe label precautions.

Store in a dry, well ventilated place away from sources of ignition. Keep away from oxidizing agents, from strongly alkaline and strongly acid materials. No smoking. Prevent unauthorized access, Containers, which are opened must be carefully resealed and kept to prevent leakage.

8. EXPOSURE CONTROLS/PERSONNEL PROTECTION

Engineering Measures:

Provide adequate ventilation. Where reasonably practicable this should be achieved by use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapor below the OEL, suitable respiratory protection must be worn.

9. PHYSICAL AND CHEMICAL PROPERTIES

As per Product Data Sheet

10. STABILITY AND REACTIVITY

Stable under recommended storage and handling conditions (see section 7).

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

11. DISPOSAL CONSIDERATIONS

Do not allow into drains or water courses.

Waste and emptied containers should be disposed of according to the local rules and legislations.

12. REGULATORY INFORMATION

In accordance with the Dangerous Preparations Directive 88/379/Eec the product is labeled as follows:

F Highly Inflammable

Xn Harmful

Prepared on 08/02/2006 by Quality Control Sect.NPF-QATAR

