

Câu 1:

```
class Ngusoi {  
    protected String hoten;  
    protected String ngay Sinh;  
  
    public void nhap(Scanner sc) {  
        hoten = sc.nextLine();  
        ngay Sinh = sc.nextLine();  
    }  
  
    public void xuat() {  
        System.out.print(hoten + "-" + ngay Sinh);  
    }  
}
```

Câu 2:

```
class SinhVien extends Ngusoi {  
    private String maSV;  
    private double diemTB;
```

@ override

```
    public void nhap(Scanner sc) {  
        super.nhap(sc);  
        maSV = sc.nextLine();  
        diemTB = Double.parseDouble(sc.nextLine());  
    }
```


@Override

```
public void xuat() {
```

```
    super.xuat();
```

```
    System.out.println(" - " + MaSV + " - " + Diem (SV
```

```
});
```

```
public double get Diem () {
```

```
    return diem + B;
```

```
};
```

```
public String get ten () {
```

```
    return ten;
```

```
};
```

Ans:

```
public class Main {
```

```
    public static void main (String [] args) {
```

```
        Scanner sc = new Scanner (System.in);
```

```
        int n = Integer.parseInt (sc.nextLine());
```

```
        ArrayList < Sinh Vien > ds = new ArrayList <> (n);
```

```
        for (int i = 0; i < n; i++) {
```

```
            Sinh Vien sv = new Sinh Vien ();
```

```
            sv.nhap (sc);
```



```
ds.add(SV);
```

```
collections.sort(ds, (a, b) -> a.getTen().compareTo(b.getTen()));
```

```
for (sinh vien sv: ds) {  
    sv.xuat();
```

```
double max = 0;
```

```
for (sinh vien sv: ds) {
```

```
    if (sv.getDiem() > max) max = sv.getDiem();
```

```
System.out.println("SV diem Cao nhất:");
```

```
for (sinh vien sv: ds) {
```

```
    if (sv.getDiem() == max) {
```

```
        sv.xuat();
```