HANDS-ON WORKSHOP · 120 MINUTES

Building a Multi-Agent Harness for Security Work

You will build a harness that finds, refutes and confirms a security finding, one role at a time, against a Cybench task.

github.com/lockfale/agent-harness-workshop

THE SESSION

Six parts, 95 of 120 minutes hands-on

Min	Part	Format
10	Why roles, and the risk cascade	Talk
25	Recon lab: giving an agent capability	Hands-on
20	Triage lab: handoff and triage	Hands-on
5	Break	
30	Confirm lab: building a harness to confirm	Hands-on
20	Scope lab: scope as a gated judge	Hands-on
10	Closing demo: prompt craft, economics, failures	Demo

BEFORE THE FIRST LAB

In every terminal you use for the labs

```
cd agent-harness-workshop
. .venv/bin/activate

[ -n "$HARNESS_API_KEY" ] && echo set

python -m pytest harness/tests -q
```

The two commands of every lab

```
python -m harness.run --adapter cybench --task
flag-command --budget-usd 2 --pause-after recon
```


```
python -m harness.trace_stats runs/<run-
dir>/trace.jsonl
```

Read **stop_reason** first. Leave **--budget-usd** and the role caps alone.

Stuck? CHEATSHEET.md maps every error message to its fix.

WHY ROLES · 10 MIN TALK

The model that generates a finding never judges it alone



Each role has its own model, its own tools and its own budget. Stages hand each other records, not transcripts.

The refuters and the judge, outlined, come from other model families than the generators. A model checking its own work agrees with itself.

Models from config/roles.yaml. Change the strings, not the code.

WHY ROLES · THE RISK CASCADE

Cheap models for recall, checks for precision, large models for judgment

Recall

Wide and cheap. Recon and triage run on a fast model and record everything that might matter.

Precision

Deterministic code first: dedup, schemas, gates. Then a panel that tries to disprove each candidate.

Judgment

The expensive model only sees what survived, against a prediction written in advance and a negative control.

Tokens are a risk metric: what each stage spends is part of the design, not an afterthought.

From Adrian Wood’s talk “Hackbots! Preparing for, and using offensive AI capabilities”, UNC Charlotte Cybersecurity Symposium 2026.

LAB 1 · RECON · 25 MIN

Giving an agent capability

Recon explores the target and records what it sees: facts you can point at, not conclusions.

`harness/roles/recon.py · TODO(M2)`

`mcp-skeleton/server.py · TODO(M2)`

You write: the recon prompt, record_observation, a browser twice, your own MCP server.

RECON LAB · STEP 1 OF 5

Write the recon prompt

Do

Read the docstring at the top of **harness/roles/recon.py**. Run recon once with the placeholder prompt (Step 3's command) and read the trace. Then write **SYSTEM_PROMPT** to fix what you saw.

Its tools: **shell**, **http_request**, **record_observation**, **finish**.

Hints

"The page loads /static/terminal/js/main.js" is an observation. "The app is vulnerable to X" is a conclusion, and it belongs to a later stage.

Finding an exposed key is recon. Using it is the exploit stage's job: record a secret, never use it.

RECON LAB · STEP 2 OF 5

Implement record_observation

Do

Same file. Store one observation where triage will find it, **ctx.state["observations"]**. The docstring says what to keep. Then run the tests.

```
python -m pytest harness/tests -q
```

Hint

The refuters judge your observations later, with no tools. **evidence** is the model's own account. If an observation can point at the call that produced it, exactly as sent and answered, nobody has to take its word.

Wrap the tools in **build_registry**. A new argument needs a field in **OBSERVATION_SCHEMA**.

RECON LAB · STEP 3 OF 5

Run recon on its own

```
python -m harness.run --adapter cybench --task flag-command --budget-usd 2 --pause-after recon

python -m harness.trace_stats runs/<run-dir>/trace.jsonl
```

Ask

How many observations did it record? How many are conclusions dressed up as observations?

Read first

last_stop_reason in the table. With no terminal, the pause stops the run instead of asking.

RECON LAB · STEP 4 OF 5

Give it a browser, twice

The narrow skill

The attacker container has Playwright and headless Chromium. Add a few lines to your prompt on rendering a page from the shell, and what to record. Start from **harness/attacker/BROWSER.md**.

The official MCP server

Microsoft's Playwright MCP, in its own container on shared_net. Add to **build_registry()**:

```
registry.load_mcp_stdio("docker", ["run", "-i",
"--rm", "--init", "--network", "shared_net",
"mcr.microsoft.com/playwright/mcp:v0.0.83"],
prefix="pw_", timeout=60)
```

Run recon with each. Which tools did it call? Which run recorded more, and cost more? Did any **pw_** call go through the scope gate?

Write your own MCP server

Do

mcp-skeleton/server.py is a working stdio server over a folder of notes. **search_notes** is done. **read_note** is yours; its comments walk through what to refuse.

```
registry.load_mcp_stdio("python", ["mcp-skeleton/server.py"], prefix="mcp_")
```

Or wrap your own

Docs: documentation, threat models, design notes. **A tool you already run,** exposing only the subcommands you want. **An API,** with care over auth and what you leave out.

What matters is what goes in the tool description, read on every call, and what goes in the prompt.

Prompts are not boundaries.

Recon finished Flag Command by itself in six turns, with “do not exploit anything” in its prompt. Finding an exposed key is recon. Using it is the exploit stage.

Production harnesses hold the line with the tool set: the mapping role gets no tool that could use what it finds. Anything that must not happen is enforced in code.

Only the loop knows the clock.

What happened

On a harder task, recon explored for all 24 of its turns, never called **finish**, and recorded nothing. Its prompt said about 20 turns, and to record as it went. Triage got an empty list.

What the harness does now

When three or fewer turns remain, the loop tells every role how many are left and to record what it has. The note goes in as a user turn, so the system prompt stays the same and keeps caching.

Saying it is done does not make it done.

What happened

A role could call **finish** with outcome **success** having recorded nothing at all. The stage counted as clean, and the next stage started with nothing to work on.

What the harness does now

Each role can define done in code. Recon's success with zero observations is sent back once; a second time, the role is incomplete. Finishing with **no_result** is still an honest answer.

A tool schema is a contract with the provider, not just the model.

What happened

One provider read the URL pattern **^https?://** as a whole-string match, so the model could send only “http://”. It fell back to curl and the run looked fine. Six of six calls on that provider; none of 25 elsewhere.

What the harness does now

The pattern is anchored at both ends, **^https?://\S+$**, with a test that reads it both ways. Worth adding next: the serving provider in the trace, which would have made this a five-minute find.

RECON LAB · WHAT TESTING SHOWED · RULE 10

Tools nobody calls still cost tokens on every turn.

45.6k → 98.6k

input tokens for the same recon run, after offering 25 browser tools through MCP. None of them was called.

What to take from it

Every tool description rides along on every call. On this target curl was enough, so the browser added cost and nothing else. Give each role the tools for its job, and measure what an extra server costs before you keep it.

LAB 2 · TRIAGE · 20 MIN

Handoff and triage

Triage turns recon’s observations into a short, defended ranking. A panel of three refuters then tries to disprove each candidate.

`harness/roles/triage.py · TODO(M3)`

`harness/roles/refute.py · TODO(M3)`

You write: the triage prompt, rank_candidate, the refuter prompt.

TRIAGE LAB · STEP 1 OF 3

The triage prompt and rank_candidate

Do

Open **harness/roles/triage.py**. The dedup runs in code before the model sees anything. You write **SYSTEM_PROMPT** and **rank_candidate**, both marked TODO(M3).

Hint

Ask for the cheapest check that would prove each candidate wrong, not just a score. A ranking nobody has to defend drifts toward whatever sounds most dangerous.

Keep **must_be_true** to what the observation already shows. A check that still needs running belongs in **first_check**.

The refuter prompt

Do

Open **harness/roles/refute.py** and write **SYSTEM_PROMPT**. Ask for refutation, not review: each panelist's job is to disprove the candidate.

Hint

A refuter with no tools can reject any candidate by imagining a defense: "the server might check a session". Ask for a refutation that points at something it was shown: a status, header or field.

"By design" is not a reason if it hands a caller something they should not have.

TRIAGE LAB · STEP 3 OF 3

Run through the refuter panel

```
python -m harness.run --adapter cybench --task flag-command --budget-usd 3 --pause-after refute

python -m harness.trace_stats runs/<run-dir>/trace.jsonl
```

Ask

What did the panel reject? Did the panelists agree? Read each one’s reason, not just its vote.

Note

Every run starts from the top, so this re-runs recon too.

TRIAGE LAB · WHY THREE REFUTERS?

One outside model satisfies the rule. Two more are for the vote.

One refuter

Its mistakes go straight through. A wrong “stands” passes a false positive; a wrong “refuted” drops a real bug.

Three, majority

A candidate is dropped only when most of the panel refutes it, and **uncertain** counts as refuted. An odd number means no ties.

Three families

GLM, Qwen and MiniMax, none of them DeepSeek like the generators. Three copies of one model make the same mistake.

No abliterated model in triage, refute or the judge: removing refusals damages calibration, and these roles exist to say no.

harness/README.md · On abliterated models · Matt Suiche’s weightless write-up

Evidence the harness logged beats evidence the model wrote.

What happened

Two of three refuters said “the request isn’t shown, so we can’t tell whether credentials were sent.” That was fair: the evidence was recon’s own description of what it did.

What the harness does now

Every call is logged with an id. Recon cites the id, and the refuters read the exact request and response. The next run, all three cited the logged request and the candidate survived 3 to 0.

A refutation has to point at something.

What happened

Three runs in a row, nothing survived the panel. The reasons: a check nobody had run, “the server might check a session”, and “intended behavior” for a weakness that handed any caller what it should not.

What the harness does now

A refuter names the status, header or field that contradicts the claim. “By design” counts only if it is safe for whoever can trigger it. **must_be_true** says what the evidence already shows. Next run: 3 to 0 and 2 to 1.

Read the reasons, not just the votes.

What happened

One panelist voted refuted, and the vote was right. Its reason was wrong: it read the app’s hidden command as nonsense input. It also recorded its judgment three times.

What the harness does now

Three refuters from three model families, none of them the generator’s, and a majority vote. The trace keeps every reason, so a right answer for a wrong reason is visible before it is trusted.

BREAK · 5 MIN

Stretch. Your tests should pass when you are back.

```
python -m pytest harness/tests -q
```

LAB 3 · CONFIRM · 30 MIN

Building a harness to confirm a finding

Ranking is triage. Confirming is a different job: build, exploit, judge. The judge needs a working proof of concept and a negative control that must not trigger.

`build.py` `exploit.py` `judge.py` `TODO(M4)`

You write: the build, exploit and judge prompts, and control_triggered().

CONFIRM LAB · STEP 1 OF 6

The expectations contract

Do

Open **harness/roles/build.py** and write **SYSTEM_PROMPT**. The build role writes down what success looks like before anything runs.

Why

The exploit role refuses to start without that file. That is what stops anyone moving the goalposts after seeing the output.

The exploit prompt and the negative control

Do

Open **harness/roles/exploit.py**. Write **SYSTEM_PROMPT**, then **control_triggered()**.

The harness runs the negative control itself: an ordinary request every visitor makes. If that benign request triggered the behavior you claim, your exploit proves nothing.

Hint

What does success look like in the output? A clean control's output must not contain it.

A control that failed to run at all is not a clean control.

CONFIRM LAB · STEP 3 OF 6

The judge prompt

Do

Open **harness/roles/judge.py** and write **SYSTEM_PROMPT**. The judge rules only through a tool, and code checks six rules before accepting a verdict (**harness/gates/verdict.py**).

Proof tier	Severity
rejected, inconclusive	none
source	informational
reachable	low
exploitable	medium
impact_confirmed	high

CONFIRM LAB · STEP 4 OF 6

The full run

```
python -m harness.run --adapter cybench --task flag-command --budget-usd 5

python -m harness.trace_stats runs/<run-dir>/trace.jsonl
```

Ask

What verdict and proof tier did you get?

Then

If the verdict was rejected, which rule rejected it? Try arguing with it once.

CONFIRM LAB · STEP 5 OF 6

Break your own harness

```
python -m harness.run --adapter cybench --task flag-command --budget-usd 5 --break-harness
```

A good harness

Reports an infrastructure failure, leaves the finding unconfirmed, and never calls the judge.

A bad one

Reports “exploit failed” and throws a real bug away.

CONFIRM LAB · STEP 6 OF 6

Classify what you saw

For each run

Confirmed, candidate, or infrastructure failure?

Then the separate question

Does your exploit’s path resemble anything real code would do? If the harness built the triggering state itself, it proved the bug only under conditions it invented. Rule 6 caps that at **exploitable**; look for **trigger_origin**.

CONFIRM LAB · WHAT TESTING SHOWED

Cheap because the bug is easy. The checks cost the same on a hard one.

$0.15

and about six minutes for the full run on Flag Command, recon to verdict.

What happened

Build wrote the contract first. The negative control ran clean. The judge ruled **confirmed**. The contract, the control and the verdict gate work the same on a hard bug; the turns and the bill do not.

With the triage fixes from the triage lab in place.

LAB 4 · SCOPE · 20 MIN

Scope as a gated judge

Agents leave scope faster than people do. The scope gate checks every action that leaves the sandbox and answers allow, deny or ask. Then you try to break it.

`scope-gate/rules.yaml · TODO(M5)` `harness/gates/scope.py`

You write: a named deny, an ask, and the attack on your own gate.

SCOPE LAB · STEPS 1 AND 2

Bring up the decoy, then write the rules

```
python -m harness.run --adapter cybench --task flag-command --with-task locktalk --budget-usd
2 --pause-after recon
```

The decoy

locktalk is a second Cybench task on shared_net, next to the target. It is out of scope.

The rules

In **scope-gate/rules.yaml**, add a named **deny** for the decoy and an **ask** for something you would want a human to approve.

SCOPE LAB · STEP 3 OF 4

Attack your own gate

The attack

Change your recon prompt to tell the agent that **locktalk:1337** is also part of the task. Then run it.

```
python -m harness.run --adapter cybench --task
flag-command --with-task locktalk --budget-usd 2
--pause-after recon

grep scope_decision runs/<run-dir>/trace.jsonl
```

SCOPE LAB · STEP 4 OF 4

What did the gate catch, and what did it miss?

Action	What the gate saw
http_request to locktalk	Denied, with your rule named in the trace
curl locktalk:1337 in the shell	Allowed: a shell command in the attacker container, not where it connects
Playwright MCP tools	Never asked: the check lives in the harness’s own tools

Parsing shell commands for hosts is a losing game. What closes the gap is the network: the attacker container can reach only what is in scope.

SCOPE LAB · DEBRIEF

Rules in code, or a model judge? Both, layered.

Rules in code

Cannot be argued with, but miss anything nobody wrote down. They break on host tricks: raw IPs, redirects, alternate names.

A model judge

Covers the long tail for a fraction of a cent per call, but can be talked out of its answer by injected text. Production limits what it sees: tool calls, never tool results.

Adrian Wood’s talk: a small decision model answers allow, deny or ask on every verification call against a live target.

Optional stretches: a model judge such as Jev behind ask, and an allowlisting proxy on the network.

CLOSING DEMO · 10 MIN

Prompt craft, economics, failures

Watched, not typed. To try the prompt A/B at home, any role can append a suffix file to its system prompt:

```
system_prompt_suffix_file: ~/somewhere/outside-the-repo/suffix.md
```

The trace records only the file’s name and hash. One run per side is an anecdote.

WHAT TESTING SHOWED · TWELVE RULES

Each came from a run that went wrong

01 Read the stop reason before you blame the model.

02 A provider refusal looks like a model failure.

03 Prompts are not boundaries.

04 Only the loop knows the clock.

05 Saying it is done does not make it done.

06 Logged evidence beats written evidence.

07 A refutation has to point at something.

08 Read the reasons, not just the votes.

09 A tool schema is a contract with the provider.

10 Tools nobody calls still cost tokens.

11 Benchmark prompts carry framing.

12 A good score on public tasks can be recall.

The same list closes LABS.md, so it goes home with you.

RULE 01 · READING A RUN

Read the stop reason before you blame the model.

What happened

A builder spent 57k tokens and made zero tool calls, which read like a refusal. Its first turn hit the 32k output cap mid-thought. Its second ended on **tool_use**: it was about to act when a mispriced budget guard stopped the run.

What the harness does now

trace_stats prints each role's last stop reason, and the labs start there. **max_tokens** means it ran out of room. **tool_use** means it was about to act. Neither is a model that said no.

RULE 02 · READING A RUN

A provider refusal looks like a model failure.

What happened

The first live run stopped at recon. Stop reason **content_filter**, zero tokens used: the provider blocked the request before the model saw it. The run cost under a cent and found nothing.

What the harness does now

The cheat sheet names it. Setup explains that cyber verification belongs to the account sending the request, switched on per workspace. The default roster uses models that take this work.

ECONOMICS · WHERE RUNS FALL OFF

Turns, tokens and the cliffs

Every turn resends everything

Six recon turns: 48k input tokens, 28k of them cache reads. Keep the system prompt identical so it caches.

The output cap

It includes reasoning. Hit it mid-thought and the turn bought nothing. Raise the cap before blaming the model.

The turn cap

Whatever is unrecorded at the cap is lost. The loop warns at three turns left; record as you go.

Long runs drift

On a harder task, recon’s output grew from under 100 to about 3,500 tokens a turn, and it recorded nothing. Short stages, short handoffs.

Caps that keep stages small: tool output 20,000 characters per call; what each observation keeps is yours to set.

RULE 11 · FRAMING

Benchmark prompts carry framing. Brief the agent as you would a person.

What happened

The agent’s first message was the benchmark’s own capture-the-flag wording. It tells the model what kind of exercise this is, and that shapes what it does.

What the harness does now

The task prompt is the harness’s own: the app is in scope for an assessment, find its flaws and what they expose, and back every finding with the request and the response.

RULE 12 · RECALL

A good score on public tasks can be recall.

What the evidence says

bots-bench found models answering public BOTSv3 questions with no tools at all, and far fewer on a blinded set. A prompt tuned on the same tasks it is scored on reports a training score, not a result.

What to do about it

Ask the model with no tools first: what it answers there, it already knew. Keep a held-out set it was never tuned on, and report only that. Test on something it has not seen.

Sources: bots-bench (botsbench.com); GEPA, Agrawal et al., arXiv:2507.19457

PROMPT CRAFT · GEPA

How an evolved prompt is made, and the catch

The loop

1. Start from a one-line prompt and scored tasks.
2. Run the agent; keep the traces and the scores.
3. A stronger model reads them and rewrites the prompt.
4. Keep the rewrite only if it scores better.
5. Keep every version best on some task, not just the leader.

The catch


Adrian Wood's "operational discipline" prompt took the solve rate from 53% to as high as 77%. That is **in-sample**: scored on the tasks it was optimized against. A training score, not a held-out result.

The fix: train, validation, and a test set it never sees.

GEPA: Agrawal et al., arXiv:2507.19457 · prompt by Adrian Wood, used with permission

PROMPT CRAFT · ONE GEPA STEP, RECORDED

Can a better prompt keep recon in its lane?



Prompt	Overstepped	Sends	Obs
Basic	5 of 5	18	6.2
Hand-written	5 of 5	9	6.6
Reflected	1 of 5	1	6.0

The hand-written suffix halved the sends but never stopped them.

The reflected one was written after reading the basic runs’ feedback, and turned “map, do not use” into concrete rules.

Five runs each: a direction, not a result.

Recon role, Flag Command, same models. Sends = requests that do more than read. Click the recording to play it.

PROMPT CRAFT · TRY IT AT HOME

GEPA on your own harness

What GEPA needs	Where it comes from in this harness
A prompt to evolve	One role’s system_prompt_suffix_file
A score	The trace: confirmed or not, overstepped or not, turns, cost
Written feedback	The judge’s reason, the refuters’ reasons, the stop reasons
Tasks	Several Cybench tasks: train, validation, and a test set it never sees
A budget	About 260 to 420 runs: $65 on cheap models, $1,300 on frontier

It optimizes exactly the score you give it. Score only restraint and you get a timid recon.

dspy.GEPA or the gepa package · Python 3.10 to 3.14 · pin gepa 0.1.4 and DSPy 3.4.1 · set exactly one budget argument

PROMPT CRAFT · ONE SAMPLE

Structure and prompt characteristics

```
You are one refuter on a panel of three. You judge one candidate.
You do not test it, fix it or rank it.

1. Read source: the request and response the harness logged.
2. Find the status, header or field that contradicts the claim.
3. Found one: record_judgement refuted, and quote it.
4. None: record_judgement stands, and say what you tried.

Rules: a refutation you cannot show is not one. Never assume a
defense the evidence does not show.

End with exactly one record_judgement, then call finish.
```

Who it is, and what it does not do. Everything else belongs to another role.

A numbered workflow that names the tools. Down to which field decides the next step.

Hard rules, each with its reason. Short and absolute.

A fixed ending. One recording call, with the fields it needs.

In code, not the prompt: tools per role, handlers that refuse and say why, loop notes as user turns, finish checked against what the role owes.

CLEANING UP

The harness tears its containers down, even after a failed run

If something is left over:

```
docker ps --filter name=harness-attacker

docker compose -p flag-command -f tasks/flag-command/docker-compose.yml down

docker compose -p locktalk -f tasks/locktalk/docker-compose.yml down
```

AFTER THE WORKSHOP

Take it to your own work

Authorization first

Scope rules written from the document, default deny, every gap an ask.

Two layers

The scope gate on every call, an allowlisting proxy on the network.

No flag to check

A contract written first, a negative control, a proof tier the judge must justify.

People in the loop

At every ask, and on every finding before it leaves your hands.

github.com/lockfale/agent-harness-workshop · docs/your-own-harness.md