

# LAAWS Configuration Service API

API of Configuration Service for LAAWS

[Contact the developer](#)

[Modified BSD License](#)

## aus

**GET****/aus**

Get the configuration of all AUs

### Implementation Notes

Get the configuration of all AUs

### Response Class (Status 200)

The configuration of all AUs

Model | Example Value

```
{
  "props": {}
}
```

Response Content Type

### Response Messages

HTTP Status Code	Reason	Response Model	Headers
401	Unauthorized request	Model   Example Value	
		<pre>{   "props": {} }</pre>	
403	Forbidden		
404	Not Found		
500	Internal server error	Model   Example Value	
		<pre>{   "props": {} }</pre>	
503	Some or all of the system is not available	Model   Example Value	
		<pre>{   "props": {} }</pre>	

Try it out!

DELETE

/aus/{auid}

Delete the configuration of an AU

### Implementation Notes

Delete the configuration of an AU given the AU identifier

### Response Class (Status 200)

The deleted configuration of the specified AU

Model | Example Value

```
{
  "props": {}
}
```

Response Content Type application/json ▼

### Parameters

Parameter	Value	Description	Parameter Type	Data Type
<b>auid</b>	<span>(required)</span>	<b>auid</b>	path	string

### Response Messages

HTTP Status Code	Reason	Response Model	Headers
204	No Content		
400	Bad Request	Model   Example Value <pre>{   "props": {} }</pre>	
401	Unauthorized request	Model   Example Value <pre>{   "props": {} }</pre>	
403	Forbidden request	Model   Example Value <pre>{   "props": {} }</pre>	

HTTP Status Code	Reason	Response Model		Headers
500	Internal server error	Model	Example Value	
		<pre>{   "props": {} }</pre>		
503	Some or all of the system is not available	Model	Example Value	
		<pre>{   "props": {} }</pre>		

Try it out!

GET

/aus/{auid}

Get the configuration of an AU

Implementation Notes

Get the configuration of an AU given the AU identifier

Response Class (Status 200)

The configuration of the specified AU

Model

Example Value

```
{
  "props": {}
}
```

Response Content Type

application/json ▼

Parameters

Parameter	Value	Description	Parameter Type	Data Type
auid	(required)	auid	path	string

Response Messages

HTTP Status Code	Reason	Response Model	Headers
400	Bad Request	<div><div>Model</div><div>Example Value</div><div><pre>{   "props": {} }</pre></div></div>	

HTTP Status Code	Reason	Response Model		Headers
401	Unauthorized request	Model	Example Value	
<pre>{   "props": {} }</pre>				
403	Forbidden			
404	Not Found			
500	Internal server error	Model	Example Value	
<pre>{   "props": {} }</pre>				
503	Some or all of the system is not available	Model	Example Value	
<pre>{   "props": {} }</pre>				

Try it out!

PUT

/aus/{auid}

Store the configuration of an AU

Implementation Notes

Store the configuration of an AU given the AU identifier

Response Class (Status 200)

The configuration of the specified AU

Model

Example Value

```
{
  "props": {}
}
```

Response Content Type

application/json ▼

Parameters

Parameter	Value	Description	Parameter Type	Data Type
auid	(required)	auid	path	string

Parameter	Value	Description	Parameter Type	Data Type
<b>configExchange</b>	(required) 	<b>configExchange</b>	body	Model   Example Value <pre>{   "props": {} }</pre>
Parameter content type: application/json ▼				

## Response Messages

HTTP Status Code	Reason	Response Model	Headers
201	Created		
400	Bad Request	Model   Example Value <pre>{   "props": {} }</pre>	
401	Unauthorized request	Model   Example Value <pre>{   "props": {} }</pre>	
403	Forbidden request	Model   Example Value <pre>{   "props": {} }</pre>	
404	Not Found		
500	Internal server error	Model   Example Value <pre>{   "props": {} }</pre>	
503	Some or all of the system is not available	Model   Example Value <pre>{   "props": {} }</pre>	

[Try it out!](#)

## config

GET /config/lastupdatetime Get the timestamp when the configuration was last updated

## Implementation Notes

Get the timestamp when the configuration was last updated

## Response Class (Status 200)

date-time

Response Content Type application/json ▼

## Response Messages

HTTP Status Code	Reason	Response Model	Headers
401	Unauthorized request	date-time	
403	Forbidden		
404	Not Found		
500	Internal server error	date-time	
503	Some or all of the system is not available	date-time	

Try it out!

GET /config/loadedurls Get the URLs from which the configuration was loaded

## Implementation Notes

Get the URLs from which the configuration was actually loaded, reflecting any failover to local copies

## Response Class (Status 200)

The URLs from which the configuration was loaded

Model | Example Value

```
[
  "string"
]
```

Response Content Type application/json ▼

## Response Messages

HTTP Status Code	Reason	Response Model	Headers
401	Unauthorized request	Array[string]	

HTTP Status Code	Reason	Response Model	Headers
403	Forbidden		
404	Not Found		
500	Internal server error	Array[string]	
503	Some or all of the system is not available	Array[string]	

Try it out!

PUT

/config/reload

Request a configuration reload

Implementation Notes

Request that the stored configuration is reloaded

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	OK		
201	Created		
401	Unauthorized request		
403	Forbidden request		
404	Not Found		
500	Internal server error		
503	Some or all of the system is not available		

Try it out!

DELETE

/config/{sectionName}

Delete the named configuration

Implementation Notes

Delete the configuration for a given name

Response Class (Status 200)

The named configuration that has been deleted

Model

Example Value

```
{
  "props": {}
}
```

Response Content Type application/json ▼

Parameters

Parameter	Value	Description	Parameter Type	Data Type
sectionName	<input type="text" value="(required)"/>	sectionName	path	string

Response Messages

HTTP Status Code	Reason	Response Model	Headers
204	No Content		
400	Bad request	<div>Model   Example Value</div> <div><pre>{   "props": {} }</pre></div>	
401	Unauthorized request	<div>Model   Example Value</div> <div><pre>{   "props": {} }</pre></div>	
403	Forbidden request	<div>Model   Example Value</div> <div><pre>{   "props": {} }</pre></div>	
500	Internal server error	<div>Model   Example Value</div> <div><pre>{   "props": {} }</pre></div>	
503	Some or all of the system is not available	<div>Model   Example Value</div> <div><pre>{   "props": {} }</pre></div>	

Try it out!

GET

/config/{sectionName}

Get the named configuration

Implementation Notes

Get the configuration items stored for a given name



## Response Class (Status 200)

The named configuration

Model | Example Value

```
{
  "props": {}
}
```

Response Content Type application/json ▼

## Parameters

Parameter	Value	Description	Parameter Type	Data Type
<b>sectionName</b>	<input type="text" value="(required)"/>	<b>sectionName</b>	path	string

## Response Messages

HTTP Status Code	Reason	Response Model	Headers
400	Bad request	Model   Example Value <pre>{   "props": {} }</pre>	
401	Unauthorized request	Model   Example Value <pre>{   "props": {} }</pre>	
403	Forbidden		
404	Not Found		
500	Internal server error	Model   Example Value <pre>{   "props": {} }</pre>	
503	Some or all of the system is not available	Model   Example Value <pre>{   "props": {} }</pre>	

Try it out!

PUT

/config/{sectionName}

Modify the named configuration

## Implementation Notes

Modify the configuration properties for a given name

## Response Class (Status 200)

The named configuration after it's modified

Model | Example Value

```
{
  "props": {}
}
```

Response Content Type application/json ▼

## Parameters

Parameter	Value	Description	Parameter Type	Data Type
<b>sectionName</b>	<input type="text" value="(required)"/>	<b>sectionName</b>	path	string
<b>configModSpec</b>	<div><div>(required)</div><div></div></div>	<b>configModSpec</b>	body	<div>Model   Example Value</div> <div><pre>{   "deletes": [     "string"   ],   "header": "string",   "updates": {} }</pre></div>

Parameter content type:  
application/json ▼

## Response Messages

HTTP Status Code	Reason	Response Model	Headers
201	Created		
400	Bad request	<div>Model   Example Value</div> <div><pre>{   "props": {} }</pre></div>	
401	Unauthorized request	<div>Model   Example Value</div> <div><pre>{   "props": {} }</pre></div>	

HTTP Status Code	Reason	Response Model		Headers
403	Forbidden request	Model	Example Value	
		<pre>{   "props": {} }</pre>		
404	Not Found			
500	Internal server error	Model	Example Value	
		<pre>{   "props": {} }</pre>		
503	Some or all of the system is not available	Model	Example Value	
		<pre>{   "props": {} }</pre>		

Try it out!

[ BASE URL: / , API VERSION: 1.0.0 ]