

# PRJ301-Thân Thị Ngọc ...

Search courses


[Home](#) [Dashboard](#) [Events](#) [My courses](#) [This course](#) [Instructions](#) [Courses](#) [Mobile App](#)
[Hide blocks](#) [Standard view](#)
[Home](#) > [My courses](#) > [PRJ301\\_VanTTN](#) > [General](#) > [Progress test 1](#)
**Question 1**Answer saved  
Marked out of 1.00

Flag question

Consider the code:

&lt;jsp:useBean id="b" class="vantrn.dto.Book" scope="session" /&gt;

What option is similar to the above code?

- a. <%  
    b= new vantrn.dto.Book();  
    pageContext.setAttribute("b", b);  
%>
- b. <% vantrn.dto.Book b= (vantrn.dto.Book) pageContext.getAttribute("b");  
    if (b== null) {  
        b= new vantrn.dto.Book();  
        pageContext.setAttribute("b", b);  
    }%>
- c. <% Book b= pageContext.getAttribute("b");  
    if (b== null) {  
        b= new Book();  
        pageContext.setAttribute("b", b);  
    }  
%>
- d. <%    b= new vantrn.dto.Book();  
    pageContext.setAttribute("b", b);  
%>

[Clear my choice](#)**Quiz navigation**

1	2	3	4	5	6	7	8	9
10	11	12	13	14	15	16	17	18
19	20	21	22	23	24	25	26	27
28	29	30	31	32	33	34	35	36
37	38	39	40	41	42	43	44	45
46	47	48	49					

[Finish attempt ...](#)

Time left 0:19:37

**Question 2**Answer saved  
Marked out of 1.00

Flag question

Which structure of war file does?

- a. WEB-INF directory, and META-INF directory
- b. WEB-INF directory, all directory putting outside WEB-INF directory that is shown in IDE tool, lib directory with jar files that are added, and/or META-INF directory
- c. WEB-INF directory, resources that browser can access depending permission putting outside WEB-INF directory, and/or META-INF directory
- d. None of the others

[Clear my choice](#)**Question 3**Answer saved  
Marked out of 1.00

Flag question

Which definition is used to map dynamic database connection?

- a. Data-source
- b. Java Database Connection
- c. None of the others
- d. Resource

[Clear my choice](#)**Question 4**Answer saved  
Marked out of 1.00

Flag question

Assume that the web app is deployed and named "MyAPP", use the server name "localhost", port: 8080.

Consider the code in the filter

...

```
public void doFilter(ServletRequest request,ServletResponse response, FilterChain chain) throws ServletException, IOException {
    HttpServletRequest req = (HttpServletRequest)request;
    System.out.println("tried to access " + req.getRequestURL() + " on " + new Date() + ".");
    chain.doFilter(request,response);
}
```

and this filter is applied to the servlet1

What is the output when client send a request to the servlet1 on "Tue Mar 08 15:26:33 ICT 2022."?

- a. display the text: tried to access http://localhost:8080/MyApp on Tue Mar 08 15:26:33 ICT 2022.
- b. display the text: tried to access http://localhost:8080/MyApp/servlet1 on Tue Mar 08 15:26:33 ICT 2022.
- c. display the text: tried to access /servlet1 on Tue Mar 08 15:26:33 ICT 2022.
- d. display the text: tried to access /MyApp/servlet1 on Tue Mar 08 15:26:33 ICT 2022.

[Clear my choice](#)**Question 5**

Answer saved

Consider the table structure:

Accounts(accid:int primary key, fullname:varchar(20), role:int foreign key, email:varchar(20))

Marked out of  
1.00  
 Flag question

Role(id, roleid, name, description) (20) Given the following Java code (20),

Roles(roleid: int, description: varchar(50))

What query can be used to check the account id=1 that exists in the Accounts table?

- a. all of the others
- b. select \* from Accounts where accid=1
- c. select count(accid) from Accounts where accid=1
- d. select accid from Accounts where accid=1

[Clear my choice](#)

Question 6  
Answer saved  
Marked out of  
1.00  
 Flag question

Which symbol is used to get or call get method of object in EL?

- a. Semi Colon Symbol
- b. Double quote
- c. Dot Symbol
- d. None of the others

[Clear my choice](#)

Question 7  
Answer saved  
Marked out of  
1.00  
 Flag question

Given tld fragment

```
<tag>
  <name>test</name>
  <tag-class>sample.custag.Test</tag-class>
  <body-content>EMPTY</body-content>
  <attribute>
    <name>a</name>
    <required>false</required>
    <rtpvalue>true</rtpvalue>
  </attribute>
</tag>
```

Which following tag is NOT correct when it is applied above configuration? Assume that the prefix of tag is test in used.

- a. <test:test>abc</test:test>
- b. None of the others
- c. <test:test a = "\${2 + 2}"/>
- d. <test:test a = "5"/>

[Clear my choice](#)

Question 8  
Answer saved  
Marked out of  
1.00  
 Flag question

What Java API is used in your code to access data that is stored in RDBMS?

- a. java.sql.\* and javax.sql.\*
- b. javax.query.\*
- c. java.query.\*
- d. java.sql.\* and java.query.\*

[Clear my choice](#)

Question 9  
Answer saved  
Marked out of  
1.00  
 Flag question

Which mission of JSP Engine does?

- a. Parse JSP File, Generate Servlet Code, Compile Servlet, and Instantize Servlet
- b. None of the others
- c. Compile JSP into Java Class, Generate Mapping into Web Deployment Descriptor (web.xml), Generate Request and Response Object, Forward to Resource
- d. Generate Servlet Code, Compile Servlet, Generate Mapping into Web Deployment Descriptor (web.xml), and Instantize Servlet

[Clear my choice](#)

Question 10  
Answer saved  
Marked out of  
1.00  
 Flag question

Consider the code in the file web.xml:

```
...
<context-param>
  <param-name>count</param-name>
  <param-value>5</param-value>
</context-param>

and in the servlet "testServlet.java"
public class testServlet extends HttpServlet{
  ...
  protected void processRequest(HttpServletRequest request, HttpServletResponse response) throws ServletException, IOException {
    //MISSING
  }
}
```

Choose the right option to get initial context parameter at [MISSING]

- a. ServletContext sc=getServletContext();
 int result=sc.getInitParameter("count");
- b. ServletConfig scf=getServletConfig();
 String result2=scf.getInitParameter("count");
- c. ServletContext sc=getServletContext();
 String result=sc.getInitParameter("count");

d. 

```
ServletConfig scf=getServletConfig();
int result2=scf.getInitParameter("count");
```

[Clear my choice](#)

[Next page](#)

« PREVIOUS ACTIVITY  
supporting materials

NEXT ACTIVITY »  
Progress test 2

Jump to...

FPT University HCM Campus

Contact: [it.hcm@fpt.edu.vn](mailto:it.hcm@fpt.edu.vn)

IT Support: 0914 291 596

[Get the mobile app](#)

# PRJ301-Thân Thị Ngọc ...

Search courses 
[Home](#) [Dashboard](#) [Events](#) [My courses](#) [This course](#) [Instructions](#) [Courses](#) [Mobile App](#)
[Hide blocks](#) [Standard view](#)
[Home](#) > [My courses](#) > PRJ301\_VanTTN > General > Progress test 1
**Question 11**

Answer saved

Marked out of

1.00

 Flag question

Which following function in core library taglib of JSTL is used to make the urlrewriting technique?

- a. import and/or param
- b. url and/or param
- c. None of the others
- d. set and/or param

[Clear my choice](#)**Question 12**

Answer saved

Marked out of

1.00

 Flag question

Which method does container generate code with scriptlets and expression?

- a. \_jspForward
- b. None of the others
- c. service
- d. \_jspService

[Clear my choice](#)**Question 13**

Answer saved

Marked out of

1.00

 Flag question

What is the meaning of param keyword in EL?

- a. param is a briefcase of Request Parameter
- b. None of the others
- c. param is a briefcase of Parameters of Context Scope, Config, and Request Scope
- d. param is a briefcase of request.getParameter

[Clear my choice](#)**Question 14**

Answer saved

Marked out of

1.00

 Flag question

Who initializes the Response Object?

- a. None of the others
- b. Container
- c. Tomcat Server
- d. Servlet

[Clear my choice](#)**Question 15**

Answer saved

Marked out of

1.00

 Flag question

Consider the code:

```
...
String myvalue=request.getParameter("txtname");
Select * From Registration Where uName = ?
```

What can be used to set the myvalue variable to "?"?

- a. Using Connection
- b. using Statement
- c. Using ResultSet
- d. using the PreparedStatement

[Clear my choice](#)**Question 16**

Answer saved

Marked out of

1.00

 Flag question

How does remain the Request Object's life longer?

- a. None of the others
- b. Using Attribute of Request Object
- c. Using UrlRewriting combining sendRedirect method of Response Object
- d. Using Request Dispatcher

[Clear my choice](#)**Question 17**

Answer saved

Marked out of

1.00

 Flag question

What is Interceptor in Struts 2 Framework?

- a. None of the others
- b. It is another Filter that receive information from Main Filter (Dispatch Filter)
- c. It is a Filter that applied to application when the user uses browser send request to container

[Clear my choice](#)**Quiz navigation**

1	2	3	4	5	6	7	8	9
10	11	12	13	14	15	16	17	18
19	20	21	22	23	24	25	26	27
28	29	30	31	32	33	34	35	36
37	38	39	40	41	42	43	44	45
46	47	48	49					

[Finish attempt ...](#)Time left **0:18:58**

**Question 18**

Answer saved

Marked out of

1.00

Flag

question

assume that all library files are imported, consider the code in the files:

```
processingServlet.java
...
ArrayList<Book> list=new ArrayList();
list.add( new Book("b1","test1"));
list.add( new Book("b2","test2"));
list.add( new Book("b3","test3"));
request.setAttribute("data", list);
response.sendRedirect("index.jsp");
...
```

**index.jsp**

```
...
<c:foreach var="b" items="${requestScope.data} >
<p>${b.id} ${b.title}</p>
</c:foreach>
...
```

What is the output when processingServlet.java runs?

- a. display three paragraphs that contain id and title of the books
- b. None of the others
- c. display three paragraphs that are null
- d. display three paragraphs that are empty string

[Clear my choice](#)

**Question 19**

Answer saved

Marked out of

1.00

Flag

question

What is data-source?

- a. None of the others
- b. Logical name binds to database server address with its authentication and connection drivers
- c. Logical name binds to context path that is in the context.xml file and container read it at deploy time
- d. Logical name is get from database's name

[Clear my choice](#)

**Question 20**

Answer saved

Marked out of

1.00

Flag

question

Choose the right option about "servlet" in java

- a. Servlets are Java classes that dynamically process HTTP requests and construct responses
- b. All of the others
- c. There is only a single instance of Servlet created on the Web server.
- d. The Web server creates multiple threads for the same Servlet instance to service multiple client's requests

[Clear my choice](#)

[Previous page](#)

[Next page](#)



PREVIOUS ACTIVITY  
supporting materials

NEXT ACTIVITY  
Progress test 2



Jump to...



# PRJ301-Thân Thị Ngọc ...

Search courses

[Home](#) [Dashboard](#) [Events](#) [My courses](#) [This course](#) [Instructions](#) [Courses](#) [Mobile App](#)
[Hide blocks](#) [Standard view](#)
[Home](#) > [My courses](#) > [PRJ301\\_VanTTN](#) > [General](#) > [Progress test 1](#)
**Question 21**

Answer saved

Marked out of

1.00

Flag question

What memory scope is used to store data that exists until the web container is stopped?

- a. page scope
- b. request scope
- c. application/context scope
- d. session scope

[Clear my choice](#)**Question 22**

Answer saved

Marked out of

1.00

Flag question

How does output of Servlet Object present into browser?

- a. None of the others
- b. The servlet's output should be put into Scope then Request Dispatcher will be forwarded to browser
- c. The servlet's output should be put into Response Object
- d. The servlet's output is automatically sent to user's browser

[Clear my choice](#)**Question 23**

Answer saved

Marked out of

1.00

Flag question

Which of following feature does indicate "Servlet should NOT use as dynamic page"?

- a. Low lever HTML format
- b. Getting auto refresh on receiving a request time
- c. None of the others
- d. Initialize only once at deploy time

[Clear my choice](#)**Question 24**

Answer saved

Marked out of

1.00

Flag question

consider the code:

```
<form action="/targetServlet">....</form>
```

Choose the right option.

- a. The browser will assume that "targetServlet" resides in the same place the default page as index.jsp or index.html
- b. The browser will assume that "targetServlet" resides in the Lib folder
- c. The browser will assume that "targetServlet" resides in the WEB\_INF folder
- d. The browser will assume the path at the root location for specified host (http://host:port).

[Clear my choice](#)**Question 25**

Answer saved

Marked out of

1.00

Flag question

Consider the code:

.....

```
String sql="select ORDERID,ORDERDATE,STATUS from ORDERS where STATUS=?"
PreparedStatement pst=cn.prepareStatement(sql);
//MISSING
ResultSet rs=pst.executeQuery();
```

...

What statement is used insert to [MISSING] to get orders that is processing?

- a. pst.setString(1,"processing");
- b. pst.setString("processing");
- c. pst.setInt(1,"processing");
- d. pst.getString("STATUS");

[Clear my choice](#)**Question 26**

Answer saved

Marked out of

1.00

Flag question

What way is used to transfer data from the resource ( jsp or servlet) to the other resource?

- a. response.sendRedirect(url);
- b. request.dispatcher(url).send();
- c. request.sendRedirect(url);
- d. request.getRequestDispatcher(url).forward(request,response);

[Clear my choice](#)**Question 27**

Answer saved

Consider some statements:

F11 - Dynamically generates a document from the code given in the document.

**Quiz navigation**

1	2	3	4	5	6	7	8	9
10	11	12	13	14	15	16	17	18
19	20	21	22	23	24	25	26	27
28	29	30	31	32	33	34	35	36
37	38	39	40	41	42	43	44	45
46	47	48	49					

[Finish attempt ...](#)

Time left 0:18:41

Marked out of  
1.00

Flag  
question

- [1] Dynamically access incoming requests from the user before the servlet processes the request  
[2] Access the outgoing response from the web resources before it reaches the user  
[3] Intercept the requests and response that flow between a client and a Servlet/JSP  
[4] Was introduced as a Web component in Java servlet specification version 2.3

What these statements are saying about?

- a. web server
- b. container
- c. back end services
- d. filter

[Clear my choice](#)

Question 28

Answer saved

Marked out of  
1.00

Flag  
question

What is difference about resource response mission between Request Dispatcher and Filter?

- a. The first resource that is forwarded information will response in Request Dispatcher mechanism. The last resources that is applied filter will be response in Filter
- b. The first resource that is forwarded information will response in Request Dispatcher mechanism. The last Filter that is apply to resources will be response in Filter
- c. The last resource that is forwarded information will response in Request Dispatcher. The first Filter that is apply to resources will be response in Filter
- d. None of the others

[Clear my choice](#)

Question 29

Answer saved

Marked out of  
1.00

Flag  
question

Consider the code:

```
<form action="target" method="post">
<input type="text" value="testing" name="txt"/>
<input type="submit" name="btn" value="search"/>
</form>
```

What value will be sent to the resource "target" after submitting?

- a. nothing is sent
- b. Both "testing" and "search" are sent
- c. The text "testing" is sent
- d. The text "search" is sent

[Clear my choice](#)

Question 30

Answer saved

Marked out of  
1.00

Flag  
question

The method="GET" Is the method commonly used to request a resource/get information from the server. What this method is triggered by ?

- a. Clicking on a link in a web page
- b. Pressing the submit button in an HTML form with GET method
- c. All of the others
- d. Typing into the address line of the browser and pressing GO

[Clear my choice](#)

[Previous page](#)

[Next page](#)



[PREVIOUS ACTIVITY](#)  
supporting materials

NEXT ACTIVITY  
[Progress test 2](#)



Jump to...



# PRJ301-Thân Thị Ngọc ...

Search courses 
[Home](#) [Dashboard](#) [Events](#) [My courses](#) [This course](#) [Instructions](#) [Courses](#) [Mobile App](#)
[Hide blocks](#) [Standard view](#)
[Home](#) > [My courses](#) > [PRJ301\\_VanTTN](#) > [General](#) > [Progress test 1](#)
**Question 31**

Answer saved

Marked out of

1.00

 Flag question

Which mechanism does forEach function of core taglib library of JSTL executes?

- a. Loop depends the container reading the size of collection
- b. Loop depends on event on tag when the collection's item is existed
- c. Loop depends the while control structure when collection's item is existed
- d. None of the others

[Clear my choice](#)**Question 32**

Answer saved

Marked out of

1.00

 Flag question

What memory scope is used to store data that exists until the session is closed, session is time out, or server is crashed?

- a. Session scope
- b. Request scope
- c. page scope
- d. Context scope

[Clear my choice](#)**Question 33**

Answer saved

Marked out of

1.00

 Flag question

Consider the code in the file "index.jsp":

```
...
<form method="post">
    <input type="text" name="txt1" value="" placeholder="input email" />
    <input type="password" name="txt2" value="" placeholder="input password"/>
    <input type="submit" name="btn" value="submit" />
</form>
```

What statement is used to assign again the inputted value in the text control "txt1" after submitting?

- a. At the value property of the control "txt1", type: \${requestScope.txt1}
- b. At the value property of the control "txt1", type: \${param.txt1}
- c. All of the others
- d. At the value property of the control "txt1", type: <%= request.getParameter("txt1") %>

[Clear my choice](#)**Question 34**

Answer saved

Marked out of

1.00

 Flag question

Consider the code in the file "web.xml":

```
<web-app>
    ...
    <filter>
        <filter-name>myfilter</filter-name>
        <filter-class>vanttn.filter.myfilter</filter-class>
    </filter>
    <filter-mapping>
        <filter-name>myfilter</filter-name>
        <url-pattern>/servlet1</url-pattern>
    </filter-mapping>
    ...
</web-app>
```

Choose the right statement.

- [1] Intercept the requests and response that flow between a client and the servlet "servlet1".
- [2] Supports dynamic modification of requests between a client and the servlet "servlet1"
- [3] only apply the filter "myfilter" to all servlets in the web app exception the servlet "servlet1"
- [4] can not apply the filter "myfilter" by using "web.xml"

- a. 3
- b. 1
- c. 2
- d. 4

[Clear my choice](#)**Question 35**

Answer saved

Marked out of

1.00

 Flag question

What statement is used to display data from the session scope in the page(jsp)?

- a. <%= session.getAttribute(name) %>
- b. All of the others
- c. \${sessionScope.name}
- d. \${name}

**Quiz navigation**

1	2	3	4	5	6	7	8	9
10	11	12	13	14	15	16	17	18
19	20	21	22	23	24	25	26	27
28	29	30	31	32	33	34	35	36
37	38	39	40	41	42	43	44	45
46	47	48	49					

[Finish attempt ...](#)

Time left 0:18:23

[Clear my choice](#)

**Question 36**

Answer saved

Marked out of

1.00

Flag

question

Consider some steps:

- [1] Check available DB connection
- [2] Create SQL String using DML
- [3] Connect DB using method that you are built
- [4] Create Statement/PrepareStatement/CallableStatement
- [5] Execute Query to get ResultSet
- [6] Process the ResultSet

Choose the right sequence to access the DB using JDBC API?

- a. 3,1,2,4,5,6
- b. 1,2,3,4,5,6
- c. 1,3,2,4,5,6
- d. 3,4,5,6,1,2

[Clear my choice](#)

**Question 37**

Answer saved

Marked out of

1.00

Flag

question

What different points between Java Bean and Java class?

- a. Using <jsp:useBean /> to locate or instantiate the Bean.
- b. Java Bean class must be implemented from Serializable
- c. All of the others
- d. Java Bean class must have a public no-argument constructor

[Clear my choice](#)

**Question 38**

Answer saved

Marked out of

1.00

Flag

question

Which mechanism does Struts 2 can be used some components in any projects or libraries?

- a. Using Action Context to contain information
- b. Using xml to configure
- c. None of the others
- d. Using JavaBeans

[Clear my choice](#)

**Question 39**

Answer saved

Marked out of

1.00

Flag

question

What method commonly used for passing user input/ sending information to the server. These request parameters are passed in the body of the request?

- a. POST
- b. PASS
- c. GET
- d. SENT

[Clear my choice](#)

**Question 40**

Answer saved

Marked out of

1.00

Flag

question

**Consider the code in the filter**

```
public void doFilter(ServletRequest request, ServletResponse response,
    FilterChain chain) throws IOException, ServletException {
    try {
        chain.doFilter(request, response);
        request.setAttribute("id", "SE12345");
    } catch (Throwable t) {}
}
```

**And the code in the servlet1**

```
...
String s=(String)request.getAttribute("id");
out.println("id:" +s);
...
```

**Apply this filter to the servlet1**

What is displayed in the browser?

- a. the null value is displayed in the browser
- b. the empty string is displayed in the browser.
- c. the text "SE12345" is displayed in the browser.
- d. None of the others

[Clear my choice](#)

[Previous page](#)

[Next page](#)



PREVIOUS ACTIVITY  
supporting materials

NEXT ACTIVITY  
Progress test 2



Jump to...

[Get the mobile app](#)

FPT University HCM Campus

Contact: [it.hcm@fpt.edu.vn](mailto:it.hcm@fpt.edu.vn)

IT Support: 0914 291 596

# PRJ301-Thân Thị Ngọc ...

Search courses 
[Home](#) [Dashboard](#) [Events](#) [My courses](#) [This course](#) [Instructions](#) [Courses](#) [Mobile App](#)
[Hide blocks](#) [Standard view](#)

 > Home > My courses > PRJ301\_VanTTN > General > Progress test 1

**Question 41**

Answer saved

Marked out of

1.00

 Flag question

Which structure of Status Line in Response Message is?

- a. [HTTP Version] [Response Code] [Http Method]
- b. [HTTP Version] [Response Code] [Status]
- c. [HTTP Method] [Protocol Version] [Requested Resource forming URI]
- d. None of the others

[Clear my choice](#)**Question 42**

Answer saved

Marked out of

1.00

 Flag question

choose the right option to insert data as: name="testing" to the request scope in the servlet.

- a. request.setAttribute("name","testing");
- b. this.setAttribute("name","testing");
- c. RequestScope.setAttribute("name","testing");
- d. Request.setAttribute("name","testing");

[Clear my choice](#)**Question 43**

Answer saved

Marked out of

1.00

 Flag question

What attribute presents value that contains some target resource in the web application (e.g. Servlet or JSP)?

- a. action
- b. encryption
- c. multidata
- d. method

[Clear my choice](#)**Question 44**

Answer saved

Marked out of

1.00

 Flag question

Assume that all library files are imported and there is a data as user="testing" in the session scope .

Consider the code in the file "index.jsp"

```
...<h1>welcome [MISSING]</h1>...
```

What statement is used to display "testing" at [MISSING]?

- [1] \${sessionScope.testing}
- [2] \${sessionScope.user}
- [3] \${session.getAttribute("testing")}
- [4] \${"testing"}

- a. 3
- b. 4
- c. 1
- d. 2

[Clear my choice](#)**Question 45**

Answer saved

Marked out of

1.00

 Flag question

What is the url-pattern tag in filter-mapping tag for?

- a. Define the mechanism to resource accessing the Filter
- b. None of the others
- c. Determining the resource is applied by configuring Filter
- d. Determining the access path to access the Filter from the browser

[Clear my choice](#)**Question 46**

Answer saved

Marked out of

1.00

 Flag question

What does the prefix in TLD file means?

- a. It is an address to access tag class
- b. None of the others
- c. It is an alias name to avoid the conflict name of tag in this tld to others
- d. It is a name that the users must be used and fill when they import taglib on JSP Page

[Clear my choice](#)**Question 47**

Answer saved

Marked out of

1.00

Assume that all library files are imported, the page is run on the localhost, port:8080, the web name is "MyWeb"

consider the code in the file "index.jsp"

**Quiz navigation**

1	2	3	4	5	6	7	8	9
10	11	12	13	14	15	16	17	18
19	20	21	22	23	24	25	26	27
28	29	30	31	32	33	34	35	36
37	38	39	40	41	42	43	44	45
46	47	48	49					

[Finish attempt ...](#)

Time left 0:18:03

1.00

Flag question

```
<c:url var="test" value="search.jsp">
  <c:param name="key" value="plant"/>
</c:url>

<a href="${test}"> click here</a>
...
What will be displayed when the user clicks the hot pot "click here"?
[1] "http://localhost/MyWeb/search.jsp?key=plant"
[2] "http://localhost:8080/MyWeb/search.jsp&key=plant"
[3] "http://localhost/MyWeb/search.jsp?key=plant"
[4] "http://localhost:8080/MyWeb/search.jsp?key=plant"
```

- a. 1
- b. 2
- c. 3
- d. 4

[Clear my choice](#)**Question 48**Answer saved  
Marked out of 1.00

Flag question

Consider the table structure:  
**Accounts**( accid: int primary key, fullname: varchar(20), role: int foreign key, email: varchar(20)).  
**Roles**(roleid: int, rolename: varchar(50))

What query can be used to get full name and role name of the account?

- a. select fullname, rolename from Accounts, Roles
- b. select fullname, rolename from Accounts, Roles where role=roleid
- c. select \* from Accounts , Roles
- d. None of the others

[Clear my choice](#)**Question 49**Answer saved  
Marked out of 1.00

Flag question

Assume that path is valid, consider the code in two servlets:

```
firstServlet.java
protected void processRequest(HttpServletRequest request, HttpServletResponse response) throws ServletException, IOException {
    request.setAttribute("us","Testing");
    request.getRequestDispatcher("secondServlet").forward(request,response);
}

secondServlet.java
protected void processRequest(HttpServletRequest request, HttpServletResponse response) throws ServletException, IOException {
    try (PrintWriter out = response.getWriter()) {
        String data=request.getParameter("us");
        out.println(data);
    }
}
```

What is the result when the first Servlet runs?

- a. None of the others
- b. display "null" in the browser.
- c. display "" in the browser.
- d. display "Testing" in the browser.

[Clear my choice](#)[Previous page](#)[Finish attempt ...](#)

« PREVIOUS ACTIVITY  
supporting materials

NEXT ACTIVITY »  
Progress test 2

[Jump to...](#)