

JSON-NTV Format

Presentation

10/02/2023

Environmental Sensing



TABLE OF CONTENTS

1. Abstract	1
2 Conventions used	2
3 Terminology	2
4 Introduction	3
5 NTV structure	5
5.1 NTV entities	5
5.2 NTVtype	5
5.3 NTVvalue	6
6 JSON-NTV representation	7
6.1 JsonNTVtype	7
6.2 JsonName	7
6.3 JsonValue	7
6.4 JSON-NTV format	8
7 Examples	9
8 Parsing a JSON-value	10
8.1 NTVtype	10
8.2 NTV entity	10
Appendix : Global NTVtype	12
Datation	12
Duration	13
Location	13
Tabular data	14
Normalized String	14
Appendix : Global NTVtype namespace	15
Country	15
Catalog	15

1. ABSTRACT

This document describes a set of simple rules for unambiguously and concisely encoding data-names and data-types into JSON Data Interchange Format (RFC 8259).

These rules and framework, called JSON-NTV (JSON with Named and Typed Values), relies on the rules defined in the JSON-ND project (<https://github.com/glenkleidon/JSON-ND>).

2 CONVENTIONS USED

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP14 [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

The grammatical rules in this document are to be interpreted as described in [RFC5234].

3 TERMINOLOGY

The terms

JSON-type, JSON-text, JSON-name, JSON-value, JSON-object,
JSON-member, JSON-element, JSON-array, JSON-number, JSON-string,
JSON-false, JSON-null, JSON-true

are defined as

type, text, name, value, object, member, element, array, number, string,
false, null, true

in the JSON grammar.

The JSON-primitive term represents a JSON-number, JSON-string, JSON-false, JSON-true or JSON-null

The JSON-unnamed term represent a JSON-object without single member

The JSON-named term represent a JSON-object with a single member

4 INTRODUCTION

The JSON grammar is based on simple entities: array, object, number, string, true, false, null.

JSON-NTV proposes to increase the semantic level of the entities by adding two OPTIONAL pieces of information to a JSON entity :

- name: interpretation of the value in human language or detailed information (e.g., "beginning of the observation") or link to external information(e.g., "<https://github.com/loco-philippe/Environmental-Sensing/tree/main>"),
- type: interpretation of the value in a data standard (e.g. GeoJSON, datetime) or in a data catalog or in a software language.

The NTV entity is thus a triplet with a mandatory element (value) and two OPTIONAL elements (name, type).

For example, Paris location can be represented by :

- a name : "paris",
- a type : geoJSON Point coordinates,
- a value : [2.3522, 48.8566]

The simplest way to add those informations is to use a JSON-object with a single member where:

- JSON-ND syntax is used for the member name
- JSON representation of the value is used for the member value.

The JSON value of the previous example is:

```
{ "paris:point" : [2.3522, 48.8566] }
```

With this approach, three NTV entities are defined :

- one primitive entity not composed of other entities
- two structured entities: an unordered collection of NTV entities and an ordered sequence of NTV entities.

and two JSON formats depending on the presence of the OPTIONAL elements :

- simple format where name and type are not present
- named format where a name or a type is present

Example (entity composed with two primitive entities):

```
{ "cities::point": [[2.3522, 48.8566], [4.8357, 45.7640]] }
```

```
{ "cities::point": { "paris": [2.3522, 48.8566], "lyon": [4.8357, 45.7640] } }
```

A JSON-NTV generator produces a JSON-value from a NTV entity and vice versa
a JSON-NTV parser transforms a JSON-value into a NTV entity.

The conversion between NTV entity and software object is not the subject of this note.

5 NTV STRUCTURE

5.1 NTV ENTITIES

The NTV entity is a triplet (NTVvalue, NTVtype, NTVname):

- the NTVvalue is the JSON representation of the NTV entity
- the NTVtype defines the conversion rules between entity and NTVvalue
- the NTVname is a string

The triplet contains all the data needed to reconstruct the NTV entity.

NTVtype and NTVname are OPTIONAL and have None as default value.

Three categories of entities (one primitive and two structured) are defined:

- NTV-single for the primitive entity,
- NTV-set for an unordered collection of NTV entities
- NTV-list for an ordered sequence of NTV entities

5.2 NTVTYPE

The NTVtype is defined in a Namespace. Namespaces may be nested.

A Namespace is represented by a string followed by a point.

The global Namespace is represented by an empty string.

The Namespace representations are added to have an absolute representation of an NTVtype.

Example for a representation of an NTVtype defined in two nested Namespace :
"ns1.ns2.type"

where:

*ns1. is a Namespace defined in the global Namespace,
 ns2. is a Namespace defined in the ns1. Namespace,
 type is a NTVtype defined in the ns2. Namespace*

Example for a NTVtype defined in the global Namespace :

"type"

where:

type is a NTVtype defined in the global Namespace

The NTVtype for NTV-single entities defines the type of entity and the conversion rules between the NTV entity and the NTVvalue.

The NTVtype for structured entities is the Namespace or default NTVtype to apply to the NTV entities included.

Three categories of NTVtype are defined (None, Simple, Generic).

- If NTVtype is None, the conversion rules are the JSON conversion rules.

- If NTVtype is Simple, the rules associated with the NTVtype are used for the conversion between an entity and a NTVvalue.
- The Generic NTVtype is available only for structured entities. Generic NTVtype avoids having to include a type in the JSON representation of the included NTV entities.

5.3 NTVVALUE

The NTVvalue for an NTV-single entity is the JSON-value of the NTV entity.

The NTVvalue for an NTV-list or an NTV-set entity is the list of included NTV entities.

6 JSON-NTV REPRESENTATION

6.1 JsonNTVtype

The JsonNTVtype is identical to the NTVtype for the NTV entities not included in another entity.

For NTV entities included in another entity, the JsonNTVtype MAY be set to :

- absolut NTVtype,
- None if the NTVtype of the structured NTV entity is identical (Simple type) or associated (Generic type) to the NTVtype of the NTV entity,
- relative NTVtype if the NTVtype of the structured NTV entity is a Namespace shared with the NTVtype of the NTV entity.

6.2 JsonName

For NTV-single, JsonName is :

- NTVname:JsonNTVtype *(if NTVname and JsonNTVtype are present),*
- NTVname *(if JsonNTVtype is None),*
- :JsonNTVtype *(if NTVname is None),*

For NTV-set or NTV-list, JsonName is :

- NTVname::JsonNTVtype *(if NTVname and JsonNTVtype are present),*
- NTVname *(if JsonNTVtype is None),*
- ::JsonNTVtype *(if NTVname is None),*

If the JsonName contains one colon, the entity is a NTV-single.

If the JsonName contains two adjacent colons, the entity is an NTV-set or an NTV-list.

6.3 JsonValue

For an NTV-single, the JsonValue is the NTVvalue.

For an NTV-list, the JsonValue is a JSON-array where JSON-elements are the JSON-NTV formats of included NTV entities.

For an NTV-set, the JsonValue is a JSON-object where the JSON-members are the JSON-members of the JSON-NTV formats of included NTV entities.

Note:

A JsonValue MUST NOT be a JSON-object with a single member.

NTV entities included in an NTV-set MUST have a JsonName and all the JsonName MUST be different (e.g. `{"point" : [2.3522, 48.8566], "point" : [4.8357, 45.7640]}` is not a valid JSON-value)

6.4 JSON-NTV FORMAT

The JSON-NTV format is the JSON representation of an NTV entity. The JSON-NTV format is built with the NTVname, NTVvalue and the JsonNTVtype.

Two JSON-NTV formats are defined:

- named format (*if NTVname or JsonNTVtype are present*):
 - { JsonName : JsonValue }
- simple format (*if NTVname and JsonNTVtype are None*):
 - JsonValue

where:

- JsonName is a string representing a combination of JsonNTVtype and NTVname
- JsonValue is the NTVvalue.

7 EXAMPLES

simple JSON-NTV format of a NTV-single entity :

```
"lyon"
52.5
{ }
```

named JSON-NTV format of a NTV-single entity:

```
{ "paris:point" : [2.3522, 48.8566] }
{ ":point" : [4.8357, 45.7640] }
{ "city" : "paris" }
```

simple JSON-NTV format of a NTV-list entity :

```
[ [2.3522, 48.8566], {"lyon" : [4.8357, 45.7640]} ]
[ { ":point" : [2.3522, 48.8566]}, {":point" : [4.8357, 45.7640]} ]
[4, 45]
["paris"]
[]
```

named JSON-NTV format of a NTV-list entity :

```
{ "cities::point" : [[2.3522, 48.8566], {"lyon": [4.8357, 45.7640]}] }
{ "::point" : [ [2.3522, 48.8566], {"lyon" : [4.8357, 45.7640]} ] }
{ "simple list" : [4, 45.7] }
{ "generic date::dat" : [ "2022-01-28T18-23-54Z", "2022-01-28", 1234.78 ] }
```

simple JSON-NTV format of a NTV-set entity :

```
{ "name": "white", "firstname": "walter", "surname": "heisenberg" }
{ "paris:point" : [2.3522, 48.8566] , "lyon" : "france"}
{ "paris" : [2.3522, 48.8566], "" : [4.8357, 45.7640]}
```

named JSON-NTV format of a NTV-set entity :

```
{ "cities::point": { "paris": [2.352, 48.856], "lyon": [4.835, 45.764]} }
{ "cities" : { "paris:point" : [2.3522, 48.8566] , "lyon" : "france"} }
{ "city" : { "paris" : [2.3522, 48.8566] } }
```

8 PARSING A JSON-VALUE

8.1 NTVTYPE

The NTVtype is identical to the JsonNTVtype for the NTV entities not included in another entity.

For NTV entities included in another entity, the NTVtype is set to :

- the JsonNTVtype if it is an absolute NTVtype and the entity is a NTV-single,
- the concatenation of the NTVtype of the structured NTV entity and the JsonNTVtype if it is a relative NTVtype,
- the NTVtype of the structured NTV entity if the JsonNTVtype is None.

If the resulting NTVtype is Generic, the NTVtype is set to the Simple NTVtype consistent with the JSON-value.

If the resulting NTVtype is inconsistent, the NTVtype is set to None.

Example :

If a JSON-value is { "::

If JSON-value is { "::

8.2 NTV ENTITY

An NTV entity is deduced from the JSON-value according to its JSON-type, JsonName (if present) and JsonValue (if different).

The table below shows the conversion rules.

JSON-value			NTV entity	
JSON-type	JsonName	JsonValue	NTV category	JSON-NTV format
JSON-primitive	None	JSON-value	NTV-single	simple
JSON-unnamed	None	JSON-value	NTV-set	simple
JSON-array	None	JSON-value	NTV-list	simple

JSON-NTV FORMAT

JSON-named	without colon	JSON-primitive	NTV-single	named
JSON-named	without colon	JSON-object	NTV-set	named
JSON-named	without colon	JSON-array	NTV-list	named
JSON-named	with one colon	JSON-value	NTV-single	named
JSON-named	with two adjacent colon	JSON-object	NTV-set	named
JSON-named	with two adjacent colon	JSON-array	NTV-list	named
JSON-named	with two adjacent colon	JSON-primitive	None	None

The NTVvalue of NTV-single is the JsonValue.

The NTVname is deduced from the JsonName.

The NTVtype is deduced from the JsonName or if None from the inherited NTVtype of the "parent" NTV entity (if exists).

APPENDIX : GLOBAL NTVTYPE

A Global NTVtype is a NTVtype defined in the Global Namespace.

NTVtype and the rules to code or decode NTVvalues MUST be understood by data producers and data consumers.

So Global NTVtype and rules associated have to be defined in a specification shared by a large community.

The Global NTVtype are listed below (to be completed).

DATATION

Datation has a generic Type : datation (or dat)

NTVtype (generic)	NTVvalue	example NTVvalue
year	Json-Number (Year - ISO8601)	1998
month	Json-Number (Month - ISO8601)	10
day	Json-Number (Day - ISO8601)	21
week	Json-Number (Week - ISO8601)	38
hour	Json-Number (Hour - ISO8601)	20
minute	Json-Number (Minute - ISO8601)	18
second	Json-Number (Second - ISO8601)	54
timeposix (dat)	Json-Number	123456.78
date (dat)	Json-string (Calendar date, extended format - ISO8601)	"2022-01-28"
time (dat)	Json-string (time of day, extended format - ISO8601)	"T18:23:54", "18:23", "T18"
datetime (dat)	Json-string (date and time of day, extended format - ISO8601)	"2022-01-28T18-23-54Z" "2022-01-28T18-23-54+0400"
timearray (dat)	Json-Array	[date1, date2] date1, date2 are date, datetime or timeposix
timeslot (dat)	Json-Array	[array1, array2] array1, array2 are timearray

DURATION

Duration has a generic type : duration (or dur)

NTVtype (generic)	NTVvalue	example NTVvalue
timeinterval (dur)	Json-string (Time interval with start and end, extended format-ISO8601)	"2007-03-01T13:00:00Z/2008-05-11T15:30:00Z"
durationiso (dur)	Json-string (Time interval by alternative format duration and context, extended format - ISO8601)	"P0002-10- 15T10:30:20"
durposix (dur)	Json-Number	123456.78

LOCATION

Location has a generic type : location (or loc)

The CRS (Coordinate Reference Systems) is geographic, using the World Geodetic System 1984 (WGS 84) datum, with longitude and latitude units of decimal degrees (EPSG:4326).

NTVtype (generic)	NTVvalue	example NTVvalue
point (loc)	Json-Array (Point coordinates - RFC7946)	[5.12, 45.256] (<i>lon, lat</i>)
line (loc)	Json-Array (LineString coordinates - RFC7946)	[point1, point2, point3] pointxx is point
ring	Json-Array (linear ring coordinates - RFC7946)	[point1, point2, point3] pointxx is point
multiline	Json-Array (MultiLineString coordinates - RFC7946)	[line1, line2, line3] linexx is line
polygon (loc)	Json-Array (Polygon coordinates - RFC7946)	[ring1, ring2, ring3] ringxx is ring
multipolygon (loc)	Json-Array (MultiPolygon coordinates - RFC7946)	[poly1, poly2, poly3] polyxx is polygon
bbox (loc)	Json-Array (bbox coordinates - RFC7946)	[-10.0, -10.0, 10.0, 10.0]

JSON-NTV FORMAT

geojson (loc)	Json-Object (geoJSON object - RFC7946)	{"type": "point", "coordinates": [40.0, 0.0] }
codeolc (loc)	Json-string (Open Location Code)	"8FW4V75V+8F6"

TABULAR DATA

Several types can be defined following the "Model for Tabular Data and Metadata on the Web - W3C Recommendation 17 December 2015"

NTVtype	NTVvalue
row	JSON-array of JSON-NTV
field	JSON-array of NTVvalue (following JSON-TAB format)
table	JSON-array of NTVvalue of fields with the same length

NORMALIZED STRING

Normalized String doesn't have a generic Type.

NTV type	NTVvalue	example NTVvalue
uri	Json-string (URI - RFC3986)	" https://www.ietf.org/rfc/rfc3986.txt " " https://gallica.bnf.fr/ark:/12148/bpt6k107371t " "urn:uuid:f81d4fae-7dec-11d0-a765-00a0c91e6bf6" "ni:///sha-256;UyaQV-Ev4rdLoHyJJWCi11OHfrYv9E1aGQ ALMO2X_-Q" "geo:13.4125,103.86673" (RFC5870) "info:eu-repo/dai/nl/12345" " mailto:John.Doe@example.com " "news:comp.infosystems. www.servers.unix " "urn:oasis:names:specification:docbook:dtd:xml:4.1.2"

(to be completed)

APPENDIX : GLOBAL NTVTYPE NAMESPACE

COUNTRY

The ISO 3166-1 alpha-2 codes are Namespace defined in the Global Namespace.

Example :

"fr." is the Namespace defined in the Global Namespace for France country NTVtypes.

CATALOG

NTVtype	example JSON-NTV
schemaorg.	{ ":schemaorg.propertyID": "NO2" } { ":schemaorg.unitText": "µg/m3" }
darwincore.	{ ":darwincore.acceptedNameUsage": "Tamias minimus" }

(to be completed)