Events

Last updated by | LINCKENS Rob (ENGIE Energie Nederland NV) | Mar 31, 2026 at 9:24 AM GMT+2

- We sturen overal het gehele bericht mee in de envelop. Mocht dat tot performance problemen leiden, dan wordt op dat moment het claim-check pattern toegepast: het bericht wordt opgeslagen in een aparte store en in de envelop wordt een bericht ID opgenomen.

EnTEM bericht definitie (envelop)

Name	Mandatory	Type	Description	Example
specversion	x	string	Version of the event specs	
id	x	string	Unique Id of the event	UUID
type	x	string	<context>.<resource>.<action>	mma.msg.new
creationtime	x	timestamp	Creation timestamp of the event in UTC (Conform ISO 8601 and formatted as yyyy-mm-ddThh:mm:ss.ffffffZ)	
source	x	string	Source application where the event was created	MKC
msgsender	o	String.ean13	Ean code of the message sender	8712423009196
msgsenderrole	o	string	Role of the message sender (conactTypeIdentifier)	DDK
msgreciever	o	String.ean13	Ean code of the message receiver	8719189100006
msgreceiverrole	o	string	Role of the message receiver	DDM
msgtype	o	string	It references to the msgType For resource message it is mandatory	AllocationSeriesNo
msgsubtype	o	string	Can be used to categorize extra level under msgtype (e.g. for Tennet messages processtype)	N101

Name	Mandatory	Type	Description	Example
msgid	o	string	it references to the msgID of the message. This should be used to retrieve the Payload. For resource message it is mandatory	UUID
msgcorrelationid	o	string	If message in this event has a correlation with another msg in another event then this has to be the msgid which has been used in the other event. For resource message and if message has a correlation	UUID
msgcreationtime	o	timestamp	Creation timestamp of the message in UTC (Conform ISO 8601 and formatted as yyyy-mm-ddThh:mm:ss.ffffffZ) For resource message it is mandatory	
msgversion	o	string	Version of the message definition structure For resource message it is mandatory	
msgcontenttype	o	string	Contenttpye of th message For message it is mandatory	application/xml
msgpayload	o	string	Bevat altijd xml payload	

Name	Mandatory	Type	Description	Example
entemsendtooutput	x	boolean	Message will be send to output handler	
entemsendacknowledgement	x	boolean	Acknowledgement will be generated	
entemvalidationresult	o	Array of object { code <string> , text <string> }	Validation result	
entemtimestamp	x	timestamp	Receive timestamp of the message in EnTem in UTC (Conform ISO 8601 and formatted as yyyy-mm-ddThh:mm:ss.ffffffZ) For resource message it is mandatory	

Voorbeeld van binnenkomend EnTem message in json formaat


```
{
  "id": "d9d4a01c-0df2-427d-b3d9-0caec6a2c32a",
  "type": "mma.msg.new",
  "creationtime": "2026-03-26T08:15:42.123456Z",
  "source": "MKC",
  "msgsender": "8716867999990",
  "msgsenderrole": "DDM",
  "msgreceiver": "8712423009196",
  "msgreceiverrole": "DDK",
  "msgtype": "AllocationSeriesNotification",
  "msgsubtype": "N101"
  "msgid": "7aa1c9b3-5d24-4a9b-88c2-abcdef123456",
  "msgcorrelationid": ""
  "msgcreationtime": "2026-03-26T08:15:41.999999Z",
  "msgversion": "1.2",
  "msgpayloadid": "9dd95e4c-c95a-4764-be95-af343c616e77",
  "msgcontenttype": "application/xml",
  "msgpayload": {""}
  "entemsendacknowledgement  ": true,
  "entemsendtooutput": true,
  "entemvalidationresult": [{}],
  "entemtimestamp": "2026-03-26T08:15:41.999999Z",
}
```

Voorbeeld van uitgaand EnTem message in json formaat


```
{
  "id": "d9d4a01c-0df2-427d-b3d9-0caec6a2c32a",
  "type": "mma.msg.new",
  "creationtime": "2026-03-26T08:15:42.123456Z",
  "source": "EnTEM",
  "msgsender": "8712423009196", // msg receiver of the original message
  "msgsenderrole": "DDK", // msg receiverrol of the original message
  "msgreceiver": "8716867999990", // msg sender of the original message
  "msgreceiverrole": "DDM", // msg senderrole of the original message
  "msgtype": "AllocationSeriesNotification",
  "msgsubtype": "N101"
  "msgid": "7aa1c9b3-5d24-4a9b-88c2-abcdef123456",
  "msgcorrelationid": "7aa1c9b3-5d24-4a9b-88c2-abcdef123456" // msgid of the original message
  "msgcreationtime": "2026-03-26T08:15:41.999999Z",
  "msgversion": "1.2",
  "msgpayloadid": "9dd95e4c-c95a-4764-be95-af343c616e77",
  "msgcontenttype": "application/xml",
  "msgpayload": {""}
  "entemsendacknowledgement  ": true,
  "entemsendtooutput": true,
  "entemvalidationresult": [
   {
      "code" : "683",
      "text" : "The combination of origin indication, validation status and repair method is not a vali
   }],
  "entemtimestamp": "2026-03-26T08:15:41.999999Z",
}
```


TODO

- Lijst met alle MessageTypes
- Lijst met alle ContentType
- Entem validation result nog aanvullen